

•

Install Learn

- Introduction
 - New to TensorFlow?
- TensorFlow
 - The core open source ML library
- For JavaScript
 - TensorFlow.js for ML using JavaScript
- For Mobile & IoT
- TensorFlow Lite for mobile and embedded devices
- For Production
 - TensorFlow Extended for end-to-end ML components
- Swift for TensorFlow (in beta)

API

- API
- <u>r2.0</u>
- (stable)
- API r1
- <u>r1.15</u>
- More...

Resources

- Models & datasets
 - Pre-trained models and datasets built by Google and the community
- Tools
 - Ecosystem of tools to help you use TensorFlow
- <u>Libraries & extensions</u>
 - Libraries and extensions built on TensorFlow
- <u>Learn ML</u>
 - Educational resources to learn the fundamentals of ML with TensorFlow

Community Why TensorFlow

- About
- Case studies
- Trusted Partner Program



- Language
- English
- 中文 简体

Language

- Language
- English
- 中文 简体

GitHub

• TensorFlow Core r1.15

Overview Python JavaScript C++ Java



- •
- Install
- Learn
- More
- <u>API</u>
 - More
 - o Overview
 - Python
 - o JavaScript
 - <u>C++</u>
 - o Java
- Resources
 - More
- Community
- Why TensorFlow
 - More
- GitHub
- Python r1.15
- tf
- o <u>Overview</u>
- o add check numerics ops
- o add to collection
- o add to collections
- AggregationMethod
- o all variables
- o <u>argsort</u>
- o arg max
- o arg min
- o assert variables initialized
- o <u>assign</u>
- o assign add
- o assign sub
- AttrValue
- AttrValue.ListValue
- o batch gather
- o batch scatter update
- o batch to space
- o batch to space nd
- bitcast
- o boolean mask
- o broadcast dynamic shape
- o broadcast static shape
- o broadcast to
- o case
- o cast
- o clip by average norm
- o clip by global norm
- o clip by norm
- o clip by value
- o colocate with
- o concat

- o cond
- Conditional Accumulator
- ConditionalAccumulatorBase
- ConfigProto
- ConfigProto.DeviceCountEntry
- ConfigProto.Experimental
- o constant
- container
- o control dependencies
- o control flow v2 enabled
- o convert to tensor
- o convert to tensor or indexed slices
- o convert to tensor or sparse tensor
- count up to
- o create partitioned variables
- CriticalSection
- o <u>custom gradient</u>
- o decode raw
- delete session tensor
- device
- <u>DeviceSpec</u>
- Dimension
- disable control flow v2
- o disable eager execution
- o disable resource variables
- disable tensor equality
- o disable v2 behavior
- disable v2 tensorshape
- o div
- o dynamic partition
- o dynamic stitch
- o edit distance
- o einsum
- enable control flow v2
- o enable eager execution
- enable resource variables
- enable tensor equality
- enable v2 behavior
- o enable v2 tensorshape
- o ensure shape
- o Event
- executing eagerly
- expand dims
- o extract volume patches
- o <u>eye</u>
- <u>fill</u>
- <u>fingerprint</u>
- FixedLengthRecordReader
- o <u>fixed size partitioner</u>
- o <u>floor div</u>
- o foldl
- foldr
- <u>function</u>
- o gather
- o gather nd
- o get collection
- o get collection ref
- o get default graph
- get default session
- o get local variable

- o get logger
- o get session handle
- o get session tensor
- o get static value
- o get variable
- o get variable scope
- o global variables
- o glorot normal initializer
- glorot uniform initializer
- GPUOptions
- GPUOptions.Experimental
- GPUOptions.Experimental.VirtualDevices
- o gradients
- GradientTape
- o grad pass through
- Graph
- GraphDef
- GraphKeys
- GraphOptions
- o <u>group</u>
- o guarantee const
- hessians
- HistogramProto
- histogram fixed width
- histogram fixed width bins
- identity
- <u>IdentityReader</u>
- o identity n
- IndexedSlices
- <u>IndexedSlicesSpec</u>
- o initialize all tables
- o <u>initialize</u> all variables
- initialize local variables
- o <u>initialize variables</u>
- o init scope
- InteractiveSession
- is tensor
- is variable initialized
- <u>linspace</u>
- LMDBReader
- o load file system library
- load library
- load op library
- local variables
- <u>LogMessage</u>
- o make ndarray
- o make template
- o make tensor proto
- o map fn
- o meshgrid
- MetaGraphDef
- MetaGraphDef.CollectionDefEntry
- MetaGraphDef.MetaInfoDef
- MetaGraphDef.SignatureDefEntry
- o min max variable partitioner
- o model variables
- Module
- o moving average variables
- NameAttrList
- NameAttrList.AttrEntry

- o <u>name scope</u>
- NodeDef
- NodeDef.AttrEntry
- NodeDef.ExperimentalDebugInfo
- o nondifferentiable batch function
- o norm
- o no gradient
- o <u>no op</u>
- o no regularizer
- numpy function
- o ones
- o ones like
- o one hot
- o Operation
- OptimizerOptions
- OptionalSpec
- o op scope
- o pad
- parallel stack
- o placeholder
- o placeholder with default
- Print
- o print
- o py func
- o py function
- o quantize v2
- RaggedTensor
- RaggedTensorSpec
- o random normal initializer
- o random uniform initializer
- o <u>range</u>
- o rank
- ReaderBase
- o <u>realdiv</u>
- o recompute grad
- RegisterGradient
- o register tensor conversion function
- o <u>repeat</u>
- report uninitialized variables
- o required space to batch paddings
- o reset_default_graph
- o <u>reshape</u>
- o resource variables enabled
- <u>reverse</u>
- o <u>reverse sequence</u>
- o <u>rol</u>
- RunMetadata
- RunMetadata.FunctionGraphs
- RunOptions
- RunOptions.Experimental
- o scan
- scatter add
- o scatter div
- o scatter max
- o scatter min
- scatter mul
- o scatter nd
- o scatter nd add
- scatter nd sub
- o scatter nd update

- o scatter sub
- o scatter update
- searchsorted
- sequence mask
- <u>Session</u>
- SessionLog
- o setdiff1d
- o shape
- o <u>shape n</u>
- o size
- slice
- o sort
- space to batch nd
- <u>SparseTensorSpec</u>
- <u>SparseTensorValue</u>
- sparse matmul
- o sparse to dense
- o split
- o <u>squeeze</u>
- o stack
- o stop gradient
- o strided slice
- string split
- o <u>substr</u>
- Summary
- <u>SummaryMetadata</u>
- SummaryMetadata.PluginData
- switch case
- <u>Tensor</u>
- TensorArray
- <u>TensorArraySpec</u>
- tensordot
- TensorInfo
- TensorInfo.CompositeTensor
- <u>TensorInfo.CooSparse</u>
- <u>TensorShape</u>
- <u>TensorSpec</u>
- o tensor scatter nd add
- o tensor scatter nd sub
- o tensor scatter nd update
- <u>TextLineReader</u>
- TFRecordReader
- o <u>tile</u>
- <u>timestamp</u>
- to bfloat16
- o to complex 128
- o to complex64
- o to double
- o to float
- o to int32
- <u>to int64</u>
- o trainable variables
- o <u>transpose</u>
- o truncatediv
- o truncatemod
- <u>tuple</u>
- <u>TypeSpec</u>
- <u>UnconnectedGradients</u>
- <u>unique</u>
- o unique with counts

- o <u>unravel_index</u>
- unstack
- Variable
- <u>Variable.SaveSliceInfo</u>
- <u>VariableAggregation</u>
- <u>VariableScope</u>
- <u>VariableSynchronization</u>
- o variable axis size partitioner
- o variable creator scope
- variable op scope
- o variable scope
- vectorized map
- o where
- where v2
- while loop
- WholeFileReader
- o wrap function
- o <u>zeros</u>
- o zeros initializer
- o zeros like
- tf.app
 - o <u>Overview</u>
 - o <u>run</u>
- tf.audio
 - Overview
 - o decode way
 - o encode way
- tf.autograph
 - o <u>Overview</u>
 - set verbosity
 - to code
 - o to graph
 - o <u>trace</u>
 - experimental
 - Overview
 - do not_convert
 - Feature
- tf.bitwise
 - Overview
 - o bitwise and
 - o bitwise or
 - o bitwise xor
 - o <u>invert</u>
 - left shift
 - o right shift
- tf.compat
 - o Overview
 - o as bytes
 - o as str any
 - o as text
 - o dimension at index
 - o dimension value
 - o forward compatibility horizon
 - o forward compatible
 - o path to str
 - o v1
- Overview
- app
 - Overview
- audio

- Overview
- autograph
 - Overview
 - experimental
 - Overview
- bitwise
 - Overview
- compat
 - Overview
- config
 - Overview
 - experimental
 - Overview
 - optimizer
 - Overview
 - threading
 - Overview
- data
 - Overview
 - experimental
 - Overview
- debugging
 - Overview
- distribute
 - Overview
 - cluster resolver
 - Overview
 - experimental
 - Overview
- distributions
 - Overview
- dtypes
 - Overview
- errors
 - Overview
- experimental
 - Overview
- feature_column
 - Overview
- gfile
 - Overview
- graph_util
 - Overview
- image
 - Overview
- initializers
 - Overview
- io
- Overview
- gfile
 - Overview
- layers
 - Overview
 - experimental
 - Overview
- linalg
 - Overview
- lite
 - Overview
 - constants

- Overview
- experimental
 - Overview
 - nn
- Overview
- logging
 - Overview
- lookup
 - Overview
 - experimental
 - Overview
- losses
 - Overview
- manip
 - Overview
- math
 - Overview
- metrics
 - Overview
- nest
 - Overview
- nn
- Overview
- rnn_cell
 - Overview
- profiler
 - Overview
- python_io
 - Overview
- quantization
 - Overview
- queue
 - Overview
- ragged
 - Overview
- random
 - Overview
 - experimental
 - Overview
- raw_ops
 - Overview
- resource_loader
 - Overview
- saved_model
 - Overview
 - builder
 - Overview
 - constants
 - Overview
 - experimental
 - Overview
 - loader
 - Overview
 - main op
 - Overview
 - signature_constants
 - Overview
 - signature_def_utils
 - Overview
 - tag_constants

- Overview
- utils
 - Overview
- sets
 - Overview
- signal
 - Overview
- sparse
 - Overview
- spectral
 - Overview
- strings
 - Overview
- summary
 - Overview
- sysconfig
 - Overview
- test
 - Overview
- tpu
 - Overview
 - experimental
 - Overview
- train
 - Overview
 - experimental
 - Overview
 - queue_runner
 - Overview
- user_ops
 - Overview
- version
 - Overview
- xla
 - Overview
 - experimental
 - Overview
- o v2
- Overview
- argmax
- argmin
- assert equal
- assert_greater
- assert less
- assert rank
- batch to space
- boolean mask
- case
- cond
- constant
- convert to tensor
- device
- DeviceSpec
- expand dims
- gather
- gather nd
- gradients
- hessians
- <u>name scope</u>
- <u>norm</u>

- ones like
- pad
- reduce all
- reduce any
- reduce logsumexp
- reduce max
- reduce mean
- reduce min
- reduce prod
- reduce sum
- reverse sequence
- scalar mul
- shape
- size
- space to batch
- squeeze
- <u>transpose</u>
- <u>tuple</u>
- Variable
- VariableAggregation
- variable creator scope
- while loop
- zeros like
- audio
 - Overview
- autograph
 - Overview
 - to code
 - to graph
 - experimental
 - Overview
- bitwise
 - Overview
- compat
 - Overview
- config
 - Overview
 - experimental
 - Overview
 - optimizer
 - Overview
 - threading
 - Overview
- data
 - Overview
 - Dataset
 - FixedLengthRecordDataset
 - <u>TextLineDataset</u>
 - TFRecordDataset
 - experimental
 - Overview
 - choose from datasets
 - Counter
 - CsvDataset
 - make batched features dataset
 - make csv dataset
 - RandomDataset
 - sample from datasets
 - <u>SqlDataset</u>
 - <u>StatsAggregator</u>

- debugging
 - Overview
 - assert all finite
 - <u>assert greater equal</u>
 - <u>assert integer</u>
 - assert_less_equal
 - assert near
 - assert negative
 - assert none equal
 - assert non negative
 - assert non positive
 - assert positive
 - assert rank at least
 - assert rank in
 - <u>assert_scalar</u>
 - assert shapes
 - <u>assert type</u>
- distribute
 - Overview
 - MirroredStrategy
 - OneDeviceStrategy
 - Strategy
 - StrategyExtended
 - cluster_resolver
 - Overview
 - experimental
 - Overview
 - CentralStorageStrategy
 - MultiWorkerMirroredStrategy
 - ParameterServerStrategy
 - <u>TPUStrategy</u>
- dtypes
 - Overview
- errors
 - Overview
- estimator
 - Overview
 - BaselineClassifier
 - BaselineEstimator
 - BaselineRegressor
 - classifier parse example spec
 - DNNClassifier
 - **DNNEstimator**
 - DNNLinearCombinedClassifier
 - DNNLinearCombinedEstimator
 - <u>DNNLinearCombinedRegressor</u>
 - DNNRegressor
 - Estimator
 - LinearClassifier
 - <u>LinearEstimator</u>
 - LinearRegressor
 - regressor parse example spec
 - experimental
 - Overview
 - RNNClassifier
 - RNNEstimator
 - export
 - Overview
- experimental
 - Overview

- feature_column
 - Overview
 - categorical column with vocabulary file
 - make parse example spec
 - shared embeddings
- graph_util
 - Overview
- image
 - Overview
 - crop and resize
 - draw bounding boxes
 - extract glimpse
 - resize
 - ResizeMethod
 - resize with pad
 - sample distorted bounding box
- io
- Overview
- decode csv
- decode raw
- parse example
- parse single example
- serialize many sparse
- <u>serialize sparse</u>
- gfile
 - Overview
- keras
 - Overview
 - activations
 - Overview
 - applications
 - ipplications
 - Overviewdensenet
 - Overview
 - imagenet_utils
 - Overview
 - inception_resnet_v2
 - Overview
 - inception_v3
 - Overview
 - mobilenet
 - Overview
 - mobilenet_v2
 - Overview
 - nasnet
 - Overview
 - resnet
 - Overview
 - resnet50
 - Overview
 - resnet v2
 - Overview
 - vgg16
 - Overview
 - vgg19
 - Overview
 - xception
 - Overview
 - backend
 - Overview

- name_scope
- callbacks
 - Overview
 - TensorBoard
- constraints
 - Overview
- datasets
 - Overview
 - boston_housing
 - Overview
 - cifar10
 - Overview
 - cifar100
 - Overview
 - fashion_mnist
 - Overview
 - imdb
 - Overview
 - mnist
 - Overview
 - reuters
 - Overview
- estimator
 - Overview
 - model to estimator
- experimental
 - Overview
- initializers
 - Overview
 - Constant
 - GlorotNormal
 - GlorotUniform
 - he normal
 - he_uniform
 - Identity
 - Initializer
 - lecun normal
 - <u>lecun uniform</u>
 - Ones
 - Orthogonal
 - RandomNormal
 - RandomUniform
 - TruncatedNormal
 - VarianceScaling
 - Zeros
- layers
 - Overview
 - BatchNormalization
 - DenseFeatures
 - <u>GRU</u>
 - GRUCell
 - LSTM
 - LSTMCell
- losses
 - Overview
 - Reduction
- metrics
 - Overview
- mixed_precision
 - Overview

- experimental
 - Overview
- models
 - Overview
- optimizers
 - Overview
 - schedules
 - Overview
- preprocessing
 - Overview
 - image
 - Overview
 - sequence
 - Overview
 - text
 - Overview
- regularizers
 - Overview
- utils
 - Overview
- wrappers
 - Overview
 - scikit_learn
 - Overview
- linalg
 - Overview
 - <u>12 normalize</u>
- lite
 - Overview
 - <u>TFLiteConverter</u>
 - experimental
 - Overview
- lookup
 - Overview
 - StaticHashTable
 - <u>StaticVocabularyTable</u>
 - experimental
 - Overview
- math
 - Overview
 - bincount
 - confusion matrix
 - count nonzero
 - in top k
 - <u>log_softmax</u>
 - <u>softmax</u>
- nest
 - Overview
- nn
- Overview
- avg_pool2d
- batch norm with global normalization
- conv1d
- conv2d
- conv2d transpose
- conv3d
- conv3d_transpose
- convolution
- crelu
- depthwise conv2d

- depth to space
- dilation2d
- dropout
- embedding lookup
- embedding lookup sparse
- erosion2d
- fractional avg_pool
- fractional max pool
- max pool with argmax
- moments
- <u>nce loss</u>
- pool
- RNNCellDeviceWrapper
- <u>RNNCellDropoutWrapper</u>
- RNNCellResidualWrapper
- safe embedding lookup sparse
- <u>sampled softmax loss</u>
- separable conv2d
- sigmoid cross entropy with logits
- softmax cross entropy with logits
- space to depth
- sparse softmax cross entropy with logits
- sufficient statistics
- weighted cross entropy with logits
- weighted moments
- quantization
 - Overview
- queue
 - Overview
- ragged
 - Overview
- random
 - Overview
 - poisson
 - set seed
 - experimental
 - Overview
- raw_ops
 - Overview
- saved_model
 - Overview
 - contains saved model
- sets
 - Overview
- signal
 - Overview
- sparse
 - Overview
 - <u>add</u>
 - concat
 - reduce max
 - reduce sum
 - <u>segment mean</u>
 - segment sqrt nsegment sum
 - <u>split</u>
- strings
 - Overview
 - <u>length</u>
 - reduce join

- <u>split</u>
- substr
- to hash bucket
- to number
- summary
 - Overview
 - audio
 - create file writer
 - create noop writer
 - flush
 - histogram
 - <u>image</u>
 - record if
 - scalar
 - SummaryWriter
 - text
 - trace export
 - trace off
 - trace on
 - write
 - experimental
 - Overview
 - get step
 - <u>set step</u>
 - <u>summary scope</u>
 - write raw pb
- sysconfig
 - Overview
- test
 - Overview
 - assert equal graph def
 - compute gradient
- tpu
 - Overview
 - experimental
 - Overview
- train
 - Overview
 - Checkpoint
 - experimental
 - Overview
 - disable mixed precision graph rewrite
 - enable mixed precision graph rewrite
- version
 - Overview
- xla
 - Overview
 - experimental
 - Overview
- tf.config
 - o <u>Overview</u>
 - o experimental connect to cluster
 - o experimental connect to host
 - o experimental list devices
 - experimental run functions eagerly
 - o get soft device placement
 - o set soft device placement
 - o experimental
 - Overview
 - get device policy

- get memory growth
- get synchronous execution
- get virtual device configuration
- get visible devices
- list logical devices
- <u>list physical devices</u>
- set device policy
- <u>set_memory_growth</u>
- set synchronous execution
- set virtual device configuration
- set visible devices
- VirtualDeviceConfiguration
- o optimizer
 - Overview
 - get experimental options
 - get jit
 - set experimental options
 - <u>set jit</u>
- threading
 - Overview
 - get inter op parallelism threads
 - get intra op parallelism threads
 - set inter op parallelism threads
 - set intra op parallelism threads
- tf.contrib
 - o Overview
 - autograph
 - Overview
 - AutoGraphError
 - ConversionOptions
 - convert
 - converted call
 - set element type
 - stack
 - StackTraceMapper
 - batching
 - Overview
 - bayesflow
 - Overview
 - monte_carlo
 - Overview
 - <u>expectation</u>
 - expectation importance sampler
 - expectation importance sampler logspace
 - o checkpoint
 - Overview
 - capture dependencies
 - Checkpointable
 - CheckpointableBase
 - CheckpointableObjectGraph
 - CheckpointableObjectGraph.TrackableObject
 - <u>CheckpointableObjectGraph.TrackableObject.ObjectReference</u>
 - <u>CheckpointableObjectGraph.TrackableObject.SerializedTensor</u>
 - CheckpointableObjectGraph.TrackableObject.SlotVariableReference
 - dot graph from checkpoint
 - List
 - <u>list_objects</u>
 - Mapping
 - NoDependency
 - NumpyState

- <u>object_metadata</u>
- split dependency
- UniqueNameTracker
- o cloud
 - Overview
 - <u>BigQueryReader</u>
 - BigtableClient
 - BigtableTable
 - BlockCacheParams
 - ConfigureGcsHook
 - configure colab session
 - configure gcs
- o cluster resolver
 - Overview
- compiler
 - Overview
- constrained_optimization
 - Overview
 - AdditiveExternalRegretOptimizer
 - AdditiveSwapRegretOptimizer
 - ConstrainedMinimizationProblem
 - ConstrainedOptimizer
 - find best candidate distribution
 - find best candidate index
 - MultiplicativeSwapRegretOptimizer
- copy_graph
 - Overview
 - copy op to graph
 - copy variable to graph
 - get copied op
- o crf
 - Overview
 - CrfDecodeBackwardRnnCell
 - CrfDecodeForwardRnnCell
 - CrfForwardRnnCell
 - crf binary score
 - crf decode
 - crf log likelihood
 - crf log norm
 - crf multitag sequence score
 - crf sequence score
 - crf unary score
 - viterbi decode
- o cudnn_rnn
 - Overview
 - <u>CudnnCompatibleGRUCell</u>
 - <u>CudnnCompatibleLSTMCell</u>
 - CudnnGRU
 - CudnnGRUSaveable
 - CudnnLSTM
 - CudnnLSTMSaveable
 - CudnnParamsFormatConverterGRU
 - CudnnParamsFormatConverterLSTM
 - CudnnParamsFormatConverterRelu
 - CudnnParamsFormatConverterTanh
 - CudnnRNNRelu
 - <u>CudnnRNNReluSaveable</u>
 - CudnnRNNTanh
 - <u>CudnnRNNTanhSaveable</u>
- data

- Overview
- assert element shape
- batch and drop remainder
- bucket by sequence length
- CheckpointInputPipelineHook
- choose from datasets
- copy to device
- Counter
- CsvDataset
- dense to sparse batch
- enumerate dataset
- get single element
- group by reducer
- group by window
- ignore errors
- LMDBDataset
- make batched features dataset
- make csv dataset
- make saveable from iterator
- map and batch
- padded batch and drop remainder
- parallel interleave
- parse example dataset
- prefetch to device
- RandomDataset
- read batch features
- Reducer
- reduce dataset
- rejection_resample
- <u>sample from datasets</u>
- scan
- shuffle and repeat
- sliding window batch
- sloppy_interleave
- SqlDataset
- TFRecordWriter
- unbatch
- unique
- deprecated
 - Overview
 - audio summary
 - histogram summary
 - image summary
 - merge all summaries
 - merge summary
 - scalar summary
- o distribute
 - Overview
 - AllReduceCrossDeviceOps
 - <u>CollectiveAllReduceStrategy</u>
 - DistributeConfig
 - get cross replica context
 - MirroredStrategy
 - Monitor
 - MultiWorkerAllReduce
 - ParameterServerStrategy
 - require replica context
 - run standard tensorflow server
 - <u>StandardInputStep</u>
 - StandardSingleLossStep

- <u>Step</u>
- UpdateContext
- distributions
 - Overview
 - assign log moving mean exp
 - assign moving mean variance
 - Autoregressive
 - auto correlation
 - BatchReshape
 - BetaWithSoftplusConcentration
 - Binomial
 - Cauchy
 - Chi2
 - Chi2WithAbsDf
 - ConditionalDistribution
 - ConditionalTransformedDistribution
 - Deterministic
 - estimator head distribution regression
 - ExponentialWithSoftplusRate
 - ExpRelaxedOneHotCategorical
 - fill triangular
 - fill triangular inverse
 - GammaWithSoftplusConcentrationRate
 - Geometric
 - HalfNormal
 - Independent
 - InverseGamma
 - <u>InverseGammaWithSoftplusConcentrationRate</u>
 - Kumaraswamy
 - LaplaceWithSoftplusScale
 - Logistic
 - matrix diag transform
 - Mixture
 - MixtureSameFamily
 - moving mean variance
 - MultivariateNormalDiag
 - MultivariateNormalDiagPlusLowRank
 - MultivariateNormalDiagWithSoftplusScale
 - MultivariateNormalFullCovariance
 - MultivariateNormalTriL
 - NegativeBinomial
 - NormalWithSoftplusScale
 - normal conjugates known scale posterior
 - normal conjugates known scale predictive
 - OneHotCategorical
 - percentile
 - Poisson
 - PoissonLogNormalQuadratureCompound
 - quadrature scheme lognormal gauss hermite
 - quadrature_scheme_lognormal_quantiles
 - quadrature scheme softmaxnormal gauss hermite
 - quadrature scheme softmaxnormal quantiles
 - QuantizedDistribution
 - reduce weighted logsumexp
 - RelaxedBernoulli
 - RelaxedOneHotCategorical
 - SeedStream
 - SinhArcsinh
 - softplus inverse
 - <u>StudentTWithAbsDfSoftplusScale</u>

- TransformedDistribution
- tridiag
- VectorDeterministic
- VectorDiffeomixture
- <u>VectorExponentialDiag</u>
- VectorLaplaceDiag
- VectorSinhArcsinhDiag
- WishartCholesky
- WishartFull
- bijectors
 - Overview
 - AbsoluteValue
 - Affine
 - AffineLinearOperator
 - AffineScalar
 - BatchNormalization
 - Bijector
 - Chain
 - CholeskyOuterProduct
 - ConditionalBijector
 - **■ Exp**
 - FillTriangular
 - Gumbel
 - Identity
 - Inline
 - Invert
 - <u>Kumaraswamy</u>
 - MaskedAutoregressiveFlow
 - masked autoregressive default template
 - masked dense
 - MatrixInverseTriL
 - Ordered
 - Permute
 - PowerTransform
 - RealNVP
 - real nvp default template
 - Reshape
 - ScaleTriL
 - Sigmoid
 - SinhArcsinh
 - SoftmaxCentered
 - Softplus
 - <u>Softsign</u>
 - Square
 - TransformDiagonal

o eager

- Overview
- add execution callback
- async clear error
- async_wait
- clear execution callbacks
- <u>defun</u>
- <u>EagerVariableStore</u>
- enable remote eager execution
- errstate
- ExecutionCallback
- execution mode
- get optimizer variables
- gradients function
- <u>implicit gradients</u>

- implicit value and gradients
- inf callback
- inf nan callback
- Iterator
- make template
- nan callback
- Network
- num_gpus
- restore network checkpoint
- restore variables on create
- riin
- run all tests in graph and eager modes
- run test in graph and eager modes
- Saver
- save network checkpoint
- Sequential
- seterr
- set execution mode
- <u>set server def</u>
- value and gradients function
- <u>Variable</u>
- metrics
 - Overview
 - Accuracy
 - BinaryAccuracy
 - CategoricalAccuracy
 - Mean
 - Metric
 - <u>SparseAccuracy</u>

o estimator

- Overview
- add metrics
- binary classification head
- boosted trees classifier train in memory
- boosted trees regressor train in memory
- build raw supervised input receiver fn
- build supervised input receiver fn from input fn
- call logit fn
- clip gradients by norm
- DNNClassifierWithLayerAnnotations
- DNNRegressorWithLayerAnnotations
- dnn logit fn builder
- export all saved models
- export saved model for mode
- forward features
- <u>linear logit fn builder</u>
- <u>logistic regression head</u>
- multi class head
- multi head
- multi label head
- poisson regression head
- regression head
- replicate model fn
- RNNClassifier
- RNNEstimator
- SavedModelEstimator
- TowerOptimizer
- factorization
 - Overview
 - **■ GMM**

- <u>gmm</u>
- GmmAlgorithm
- KMeans
- KMeansClustering
- WALSMatrixFactorization
- WALSModel
- o feature column
 - Overview
 - sequence categorical column with hash bucket
 - sequence categorical column with identity
 - sequence categorical column with vocabulary file
 - sequence categorical column with vocabulary list
 - sequence input layer
 - sequence numeric column
- ffmpeg
 - Overview
 - decode audio
 - decode video
 - encode audio
- framework
 - Overview
 - add arg scope
 - add model variable
 - arg scope
 - arg scoped arguments
 - assert global step
 - assert or get global step
 - assert scalar int
 - assign from checkpoint
 - assign from checkpoint fn
 - assign from values
 - assign from values fn
 - BoundedTensorSpec
 - convolutional delta orthogonal
 - convolutional orthogonal 1d
 - convolutional orthogonal 2d
 - convolutional orthogonal 3d
 - create global step
 - current arg scope
 - deprecated
 - deprecated args
 - deprecated arg_values
 - filter variables
 - fuse op
 - get global step
 - get graph from inputs
 - get local variables
 - get model variables
 - get name scope
 - get or create global step
 - get placeholders
 - get trainable variables
 - get unique variable
 - get variables
 - get variables by name
 - get variables by suffix
 - get variables to restore
 - get variable full name
 - global variable
 - has arg scope

- init_from_checkpoint
- list variables
- load and remap matrix initializer
- load checkpoint
- load embedding initializer
- load linear multiclass bias initializer
- load variable
- load variable slot initializer
- local variable
- model variable
- prepend name scope
- py func
- RecordInput
- reduce sum n
- remove squeezable dimensions
- smart case
- smart cond
- smart constant value
- strip name scope
- variable
- VariableDeviceChooser
- with same shape
- with shape
- zero initializer
- nest
 - Overview
 - assert shallow structure
 - flatten dict items
 - flatten up to
 - flatten with joined string paths
 - flatten with tuple paths
 - flatten with tuple paths up to
 - get traverse shallow structure
 - <u>is_sequence</u>
 - is sequence or composite
 - map structure up to
 - map structure with paths
 - map structure with tuple paths
 - map structure with tuple paths up to
 - yield flat paths
- graph_editor
 - Overview
 - add control inputs
 - assign renamed collections handler
 - bypass
 - can be regex
 - check cios
 - compute boundary ts
 - connect
 - ControlOutputs
 - copy
 - copy op handler
 - copy with input replacements
 - detach
 - detach control inputs
 - detach control outputs
 - detach_inputs
 - detach outputs
 - <u>filter ops</u>
 - <u>filter ops from regex</u>

- filter ts
- filter ts from regex
- get backward walk ops
- get consuming ops
- get forward walk ops
- get_generating_ops
- get name scope ops
- get ops ios
- get tensors
- get walks intersection ops
- get walks union ops
- get within boundary ops
- graph_replace
- keep t if possible handler
- make list of op
- make list of t
- make placeholder from dtype and shape
- make placeholder from tensor
- make regex
- make view
- make view from scope
- placeholder name
- remove control inputs
- replace t with placeholder handler
- reroute inputs
- reroute ios
- reroute_outputs
- reroute ts
- select ops
- select ops and ts
- select ts
- <u>SubGraphView</u>
- swap inputs
- swap_ios
- swap outputs
- swap ts
- Transformer
- TransformerInfo
- transform op if inside handler
- edit
- Overview
- reroute
 - Overview
- select
 - Overview
- subgraph
 - Overview
- transform
 - Overview
- util
 - Overview
- o grid_rnn
 - Overview
- image
 - Overview
 - angles to projective transforms
 - bipartite match
 - compose transforms
 - connected components
 - dense image warp

- flat transforms to matrices
- interpolate spline
- matrices to flat transforms
- rotate
- single image random dot stereograms
- sparse_image_warp
- transform
- translate
- translations to projective transforms
- input_pipeline
 - Overview
 - obtain next
- integrate
 - Overview
 - odeint
 - odeint fixed
- keras
 - Overview
- o kernel_methods
 - Overview
 - KernelLinearClassifier
 - RandomFourierFeatureMapper
 - sparse multiclass hinge loss
- o labeled_tensor
 - Overview
- layers
 - Overview
 - apply regularization
 - avg_pool2d
 - avg_pool3d
 - batch norm
 - bias add
 - bow encoder
 - bucketized_column
 - check feature columns
 - conv1d
 - conv2d
 - conv2d in plane
 - conv2d transpose
 - conv3d
 - conv3d_transpose
 - convolution
 - create feature spec for parsing
 - crossed column
 - dense to sparse
 - dropout
 - embedding column
 - embedding lookup unique
 - embed sequence
 - flatten
 - fully connected
 - GDN
 - gdn
 - group norm
 - images to sequence
 - infer real valued columns
 - input from feature columns
 - <u>instance norm</u>
 - joint weighted sum from feature columns
 - 11 12 regularizer

- 11 regularizer
- 12 regularizer
- <u>layer norm</u>
- <u>legacy fully connected</u>
- make place holder tensors for base features
- maxout
- max pool2d
- max_pool3d
- multi class target
- one hot column
- one hot encoding
- optimize loss
- parse feature columns from examples
- parse feature columns from sequence examples
- real_valued_column
- recompute grad
- regression target
- repeat
- RevBlock
- rev block
- safe embedding lookup sparse
- scattered embedding column
- separable conv2d
- sequence input from feature columns
- sequence to images
- shared embedding columns
- softmax
- sparse column with hash bucket
- sparse column with integerized feature
- sparse column with keys
- sparse column with vocabulary file
- spatial softmax
- stack
- <u>summarize_activation</u>
- summarize activations
- summarize collection
- summarize tensor
- summarize tensorssum regularizer
- transform features
- unit norm
- variance scaling initializer
- weighted sparse column
- weighted sum from feature columns
- xavier initializer
- feature column
 - Overview
- summaries
 - Overview
- learn
 - Overview
 - BaseEstimator
 - binary svm head
 - build parsing serving input fn
 - DNNClassifier
 - DNNEstimator
 - <u>DNNLinearCombinedClassifier</u>
 - <u>DNNLinearCombinedEstimator</u>
 - <u>DNNLinearCombinedRegressor</u>
 - <u>DNNRegressor</u>

- <u>DynamicRnnEstimator</u>
- Estimator
- Evaluable
- evaluate
- Experiment
- <u>ExportStrategy</u>
- extract dask data
- extract dask labels
- extract pandas data
- extract pandas labels
- extract pandas matrix
- Head
- infer
- infer real valued columns from input
- infer real valued columns from input fn
- InputFnOps
- KMeansClustering
- LinearClassifier
- LinearEstimator
- LinearRegressor
- LogisticRegressor
- make export strategy
- MetricSpec
- ModeKeys
- ModelFnOps
- multi class head
- multi head
- multi label head
- <u>NanLossDuringTrainingError</u>
- NotFittedError
- no op train fn
- poisson regression head
- PredictionKey
- <u>ProblemType</u>
- read batch examples
- read batch features
- read batch record features
- <u>read keyed batch examples</u>
- read keyed batch examples shared queue
- read keyed batch features
- read keyed batch features shared queue
- regression head
- RunConfig
- run feeds
- <u>run n</u>
- SKCompat
- SVM
- <u>TaskType</u>
- train
- Trainable
- datasets
 - Overview
- graph_actions
 - Overview
- head
 - Overview
- io
- Overview
- learn_runner
 - Overview

- <u>run</u>
- tune
- models
 - Overview
- monitors
 - Overview
- ops
 - Overview
- preprocessing
 - Overview
- utils
 - Overview
- legacy_seq2seq
 - Overview
 - attention decoder
 - basic rnn seq2seq
 - embedding attention decoder
 - embedding attention seq2seq
 - embedding rnn decoder
 - embedding rnn seq2seq
 - embedding tied rnn seq2seq
 - model with buckets
 - <u>one2many rnn seq2seq</u>
 - rnn decoder
 - sequence loss
 - sequence loss by example
 - tied rnn seq2seq
- linear_optimizer
 - Overview
 - SdcaModel
 - SDCAOptimizer
 - SparseFeatureColumn
- lookup
 - Overview
 - <u>HasherSpec</u>
 - HashTable
 - IdTableWithHashBuckets
 - index table from file
 - index table from tensor
 - index to string
 - index to string table from file
 - index to string table from tensor
 - InitializableLookupTableBase
 - LookupInterface
 - MutableHashTable
 - string to index
 - string to index table from file
 - string to index table from tensor
 - <u>StrongHashSpec</u>
 - <u>TableInitializerBase</u>
 - TextFileIdTableInitializer
 - <u>TextFileStringTableInitializer</u>
- o losses
 - Overview
 - absolute difference
 - add loss
 - compute weighted loss
 - cosine distance
 - get losses
 - get regularization losses

- get total loss
- hinge loss
- <u>log_loss</u>
- mean pairwise squared error
- mean squared error
- sigmoid cross entropy
- softmax cross entropy
- sparse softmax cross entropy
- metric_learning
 - Overview
 - cluster loss
 - contrastive loss
 - lifted struct loss
 - npairs loss
 - npairs loss multilabel
 - triplet semihard loss
- o memory_stats
 - Overview
 - BytesInUse
 - BytesLimit
 - MaxBytesInUse
- metrics
 - Overview
 - accuracy
 - aggregate metrics
 - aggregate metric map
 - auc using histogram
 - auc with confidence intervals
 - cohen kappa
 - confusion matrix
 - count
 - f1 score
 - precision at recall
 - precision recall at equal thresholds
 - recall at precision
 - sparse recall at top k
 - streaming accuracy
 - streaming auc
 - streaming concat
 - streaming covariance
 - streaming curve points
 - streaming dynamic auc
 - streaming false negatives
 - streaming false negatives at thresholds
 - streaming false negative rate
 - streaming false negative rate at thresholds
 - streaming false positives
 - streaming false positives at thresholds
 - streaming false positive rate
 - streaming false positive rate at thresholds
 - streaming mean
 - streaming mean absolute error
 - streaming mean cosine distance
 - streaming mean iou
 - streaming mean relative error
 - streaming mean squared error
 - streaming mean tensor
 - streaming pearson correlation
 - streaming percentage less
 - streaming precision

- streaming precision at thresholds
- streaming recall
- streaming recall at k
- streaming recall at thresholds
- streaming root mean squared error
- streaming sensitivity at specificity
- streaming sparse average precision at k
- streaming sparse average precision at top k
- streaming sparse precision at k
- streaming sparse precision at top k
- streaming sparse recall at k
- streaming specificity at sensitivity
- streaming true negatives
- streaming true negatives at thresholds
- streaming true positives
- streaming true positives at thresholds
- mixed_precision
 - Overview
 - <u>ExponentialUpdateLossScaleManager</u>
 - FixedLossScaleManager
 - LossScaleManager
 - LossScaleOptimizer
- model_pruning
 - Overview
 - apply mask
 - get masked weights
 - get masks
 - get pruning hparams
 - get_thresholds
 - get weights
 - get weight sparsity
 - graph def from checkpoint
 - MaskedBasicLSTMCell
 - MaskedLSTMCell
 - masked conv2d
 - masked fully connected
 - Pruning
 - strip pruning vars fn
 - train
- o nn
- Overview
- alpha dropout
- deprecated flipped sigmoid cross entropy with logits
- deprecated flipped softmax cross entropy with logits
- deprecated flipped sparse softmax cross entropy with logits
- <u>nth element</u>
- rank sampled softmax loss
- sampled sparse softmax loss
- scaled softplus
- o opt
 - Overview
 - AdaMaxOptimizer
 - AdamGSOptimizer
 - AdamWOptimizer
 - AddSignOptimizer
 - AGNCustomGetter
 - AGNOptimizer
 - clip gradients by global norm
 - <u>DecoupledWeightDecayExtension</u>
 - <u>DropStaleGradientOptimizer</u>

- <u>ElasticAverageCustomGetter</u>
- ElasticAverageOptimizer
- extend with decoupled weight decay
- ExternalOptimizerInterface
- GGTOptimizer
- <u>LARSOptimizer</u>
- <u>LazyAdamGSOptimizer</u>
- <u>LazyAdamOptimizer</u>
- <u>ModelAverageCustomGetter</u>
- ModelAverageOptimizer
- MomentumWOptimizer
- MovingAverageOptimizer
- <u>MultitaskOptimizerWrapper</u>
- NadamOptimizer
- PowerSignOptimizer
- RegAdagradOptimizer
- <u>ScipyOptimizerInterface</u>
- ShampooOptimizer
- VariableClippingOptimizer
- o optimizer_v2
 - Overview
 - AdadeltaOptimizer
 - AdagradOptimizer
 - AdamOptimizer
 - <u>GradientDescentOptimizer</u>
 - MomentumOptimizer
 - OptimizerV2
 - <u>RMSPropOptimizer</u>
- o periodic_resample
 - Overview
 - periodic resample
- predictor
 - Overview
 - from contrib estimator
 - from estimator
 - from saved model
- o proto
 - Overview
- quantization
 - Overview
- quantize
 - Overview
 - create eval graph
 - create training graph
 - experimental create eval graph
 - experimental create training graph
- o receptive_field
 - Overview
 - compute receptive field from graph def
 - get_compute_order
- o recurrent
 - Overview
 - bidirectional functional rnn
 - functional rnn
 - Recurrent
- reduce_slice_ops
 - Overview
 - python
 - Overview
 - ops

Overview

- o remote_fused_graph
 - Overview
 - remote fused graph execute
- resampler
 - Overview
 - resampler
- o rnn
 - Overview
 - AttentionCellWrapper
 - best effort input batch size
 - BidirectionalGridLSTMCell
 - CompiledWrapper
 - Conv1DLSTMCell
 - Conv2DLSTMCell
 - Conv3DLSTMCell
 - ConvLSTMCell
 - CoupledInputForgetGateLSTMCell
 - EmbeddingWrapper
 - FusedRNNCell
 - FusedRNNCellAdaptor
 - GLSTMCell
 - GridLSTMCell
 - GRUBlockCell
 - GRUBlockCellV2
 - HighwayWrapper
 - IndRNNCell
 - IndyGRUCell
 - <u>IndyLSTMCell</u>
 - <u>InputProjectionWrapper</u>
 - IntersectionRNNCell
 - <u>LayerNormBasicLSTMCell</u>
 - <u>LayerRNNCell</u>
 - LSTMBlockCell
 - <u>LSTMBlockFusedCell</u>
 - <u>LSTMBlockWrapper</u>
 - NASCell
 - OutputProjectionWrapper
 - PhasedLSTMCell
 - SRUCell
 - stack bidirectional dynamic rnn
 - stack bidirectional rnn
 - <u>TimeFreqLSTMCell</u>
 - <u>TimeReversedFusedRNN</u>
 - transpose batch time
 - UGRNNCell
- o rpc
 - Overview
 - <u>rpc</u>
 - <u>try_rpc</u>
- o saved model
 - Overview
- seq2seq
 - Overview
 - AttentionMechanism
 - AttentionWrapper
 - AttentionWrapperState
 - BahdanauAttention
 - BahdanauMonotonicAttention
 - BasicDecoder

- <u>BasicDecoderOutput</u>
- BeamSearchDecoder
- BeamSearchDecoderOutput
- BeamSearchDecoderState
- CustomHelper
- Decoder
- dynamic decode
- FinalBeamSearchDecoderOutput
- gather tree
- GreedyEmbeddingHelper
- hardmax
- <u>Helper</u>
- <u>InferenceHelper</u>
- LuongAttention
- <u>LuongMonotonicAttention</u>
- monotonic attention
- safe cumprod
- <u>SampleEmbeddingHelper</u>
- <u>ScheduledEmbeddingTrainingHelper</u>
- <u>ScheduledOutputTrainingHelper</u>
- sequence loss
- tile batch
- <u>TrainingHelper</u>
- o signal
 - Overview
- o slim
 - Overview
- o solvers
 - Overview
- o sparsemax
 - Overview
 - sparsemax
 - sparsemax loss
- o specs
 - Overview
- staging
 - Overview
 - <u>StagingArea</u>
- stat_summarizer
 - Overview
 - StatSummarizer
- stateless
 - Overview
- summary
 - Overview
 - <u>always record summaries</u>
 - audio
 - create db writer
 - create file writer
 - create summary file writer
 - eval dir
 - generic
 - graph
 - histogram
 - <u>image</u>
 - <u>import event</u>
 - never record summaries
 - record summaries every n global steps
 - scalar
 - should record summaries

- summary writer initializer op
- o tensor forest
 - Overview
- o tensorboard
 - Overview
- testing
 - Overview
- tfprof
 - Overview
- timeseries
 - Overview
 - ARModel
 - ARRegressor
 - CSVReader
 - FilteringResults
 - NumpyReader
 - OneShotPredictionHead
 - predict continuation input fn
 - RandomWindowInputFn
 - <u>StructuralEnsembleRegressor</u>
 - <u>TimeSeriesRegressor</u>
 - <u>TrainEvalFeatures</u>
 - WholeDatasetInputFn
 - saved_model_utils
 - Overview
 - cold start filter
 - filter continuation
 - predict continuation
- o tpu
 - Overview
 - AsyncCheckpointSaverHook
 - device assignment
 - export estimator savedmodel
 - <u>InfeedQueue</u>
 - infeed dequeue
 - infeed dequeue tuple
 - <u>infeed enqueue</u>
 - infeed enqueue tuple
 - keras to tpu model
 - outfeed dequeue
 - outfeed dequeue tuple
 - outfeed enqueue
 - outfeed enqueue tuple
 - repeat
 - <u>Topology</u>
 - <u>TPUDistributionStrategy</u>
 - while loop
 - profiler
 - Overview
 - Device
 - Device.ResourcesEntry
 - Resource
 - Trace
 - Trace.DevicesEntry
 - TraceEvent
 - <u>TraceEvent.ArgsEntry</u>
- training
 - Overview
 - add gradients summaries
 - batch sequences with states

- bucket
- bucket by sequence length
- byte size load fn
- checkpoints iterator
- clip gradient norms
- clip gradient norms fn
- create train op
- evaluate once
- evaluate repeatedly
- <u>FeedingQueueRunner</u>
- get or create eval step
- GreedyLoadBalancingStrategy
- HParams
- multiply gradients
- NextQueuedSequenceBatch
- parse values
- RandomStrategy
- rejection sample
- resample at rate
- <u>SequenceQueueingStateSaver</u>
- StopAfterNEvalsHook
- stratified_sample
- SummaryAtEndHook
- train
- wait for new checkpoint
- weighted resample
- o util
 - Overview
 - ops used by graph def
 - stripped op list for graph
 - loader
 - Overview
- tf.data
 - Overview
 - Dataset
 - <u>DatasetSpec</u>
 - FixedLengthRecordDataset
 - o get output classes
 - o get output shapes
 - o get output types
 - <u>Iterator</u>
 - o make initializable iterator
 - o make one shot iterator
 - o Options
 - TextLineDataset
 - TFRecordDataset
 - o experimental
 - Overview
 - bucket by sequence length
 - bytes_produced_stats
 - cardinality
 - <u>CheckpointInputPipelineHook</u>
 - choose from datasets
 - copy to device
 - Counter
 - <u>CsvDataset</u>
 - dense to sparse batch
 - DistributeOptions
 - enumerate dataset
 - from variant

- get next as optional
- get single element
- get structure
- group by reducer
- group by window
- ignore errors
- latency stats
- make batched features dataset
- make csv dataset
- make saveable from iterator
- MapVectorizationOptions
- map and batch
- map and batch with legacy function
- OptimizationOptions
- Optional
- parallel interleave
- parse example dataset
- prefetch to device
- RaggedTensorStructure
- RandomDataset
- Reducer
- rejection_resample
- sample from datasets
- scan
- shuffle and repeat
- SparseTensorStructure
- <u>SqlDataset</u>
- <u>StatsAggregator</u>
- <u>StatsOptions</u>
- take while
- <u>TensorArrayStructure</u>
- TensorStructure
- TFRecordWriter
- ThreadingOptions
- to variant
- unbatch
- <u>unique</u>
- tf.debugging
 - Overview
 - Assert
 - o assert all finite
 - o assert equal
 - <u>assert_greater</u>
 - o <u>assert greater equal</u>
 - o <u>assert integer</u>
 - o <u>assert less</u>
 - o <u>assert less equal</u>
 - o assert near
 - assert negative
 - o assert none equal
 - assert non negative
 - assert non positive
 - o <u>assert positive</u>
 - assert proper iterable
 - o assert rank
 - <u>assert rank at least</u>
 - o assert rank in
 - assert same float dtype
 - <u>assert scalar</u>
 - <u>assert shapes</u>

- o <u>assert type</u>
- check numerics
- o get log device placement
- o is numeric tensor
- o set log device placement

• tf.distribute

- Overview
- <u>CrossDeviceOps</u>
- o experimental set strategy
- o get loss reduction
- o get replica context
- o get strategy
- has strategy
- <u>HierarchicalCopyAllReduce</u>
- <u>InputContext</u>
- InputReplicationMode
- o in cross replica context
- MirroredStrategy
- NcclAllReduce
- OneDeviceStrategy
- ReduceOp
- ReductionToOneDevice
- ReplicaContext
- o <u>Server</u>
- Strategy
- StrategyExtended
- o cluster_resolver
 - Overview
 - ClusterResolver
 - GCEClusterResolver
 - KubernetesClusterResolver
 - SimpleClusterResolver
 - <u>SlurmClusterResolver</u>
 - <u>TFConfigClusterResolver</u>
 - TPUClusterResolver
 - UnionResolver
- o experimental
 - Overview
 - CentralStorageStrategy
 - CollectiveCommunication
 - MultiWorkerMirroredStrategy
 - ParameterServerStrategy
 - <u>TPUStrategy</u>
- tf.distributions
 - Overview
 - <u>Bernoulli</u>
 - o Beta
 - Categorical
 - Dirichlet
 - DirichletMultinomial
 - <u>Distribution</u>
 - Exponential
 - Gamma
 - o kl divergence
 - Laplace
 - Multinomial
 - Normal
 - RegisterKL
 - ReparameterizationType
 - <u>StudentT</u>

- <u>Uniform</u>
- tf.dtypes
 - Overview
 - o as dtype
 - o <u>complex</u>
 - o <u>DType</u>
 - o saturate cast
- tf.errors
 - o Overview
 - AbortedError
 - AlreadyExistsError
 - CancelledError
 - DataLossError
 - <u>DeadlineExceededError</u>
 - o error code from exception type
 - o exception type from error code
 - FailedPreconditionError
 - InternalError
 - InvalidArgumentError
 - NotFoundError
 - OpError
 - OutOfRangeError
 - PermissionDeniedError
 - o raise exception on not ok status
 - ResourceExhaustedError
 - UnauthenticatedError
 - <u>UnavailableError</u>
 - <u>UnimplementedError</u>
 - <u>UnknownError</u>
- tf.estimator
 - o Overview
 - add metrics
 - BaselineClassifier
 - BaselineEstimator
 - BaselineRegressor
 - BestExporter
 - BinaryClassHead
 - BoostedTreesClassifier
 - <u>BoostedTreesEstimator</u>
 - BoostedTreesRegressor
 - o classifier parse example spec
 - DNNClassifier
 - DNNEstimator
 - <u>DNNLinearCombinedClassifier</u>
 - <u>DNNLinearCombinedEstimator</u>
 - <u>DNNLinearCombinedRegressor</u>
 - <u>DNNRegressor</u>
 - Estimator
 - EstimatorSpec
 - EvalSpec
 - Exporter
 - FinalExporter
 - Head
 - LatestExporter
 - <u>LinearClassifier</u>
 - LinearEstimator
 - <u>LinearRegressor</u>
 - <u>LogisticRegressionHead</u>
 - ModeKeys
 - MultiClassHead

- MultiHead
- MultiLabelHead
- PoissonRegressionHead
- RegressionHead
- o regressor parse example spec
- RunConfig
- TrainSpec
- o train and evaluate
- WarmStartSettings
- experimental
 - Overview
 - call logit fn
 - <u>InMemoryEvaluatorHook</u>
 - KMeans
 - LinearSDCA
 - make early stopping hook
 - make stop at checkpoint step hook
 - stop if higher hook
 - stop if lower hook
 - stop if no decrease hook
 - stop if no increase hook
- export
 - Overview
 - build parsing serving input receiver fn
 - build raw serving input receiver fn
 - ClassificationOutput
 - ExportOutput
 - PredictOutput
 - RegressionOutput
 - ServingInputReceiver
 - <u>TensorServingInputReceiver</u>
- o inputs
 - Overview
 - <u>numpy_input_fn</u>
 - pandas input fn
- o tpu
 - Overview
 - <u>InputPipelineConfig</u>
 - RunConfig
 - TPUConfig
 - TPUEstimator
 - TPUEstimatorSpec
 - experimental
 - Overview
 - <u>EmbeddingConfigSpec</u>
- tf.experimental
 - o Overview
 - <u>function executor type</u>
 - o output all intermediates
- tf.feature column
 - Overview
 - bucketized column
 - o categorical column with hash bucket
 - o categorical column with identity
 - o categorical column with vocabulary file
 - o categorical column with vocabulary list
 - o crossed column
 - o embedding column
 - o indicator column
 - o <u>input layer</u>

- <u>linear model</u>
- o make parse example spec
- o numeric column
- o sequence categorical column with hash bucket
- o sequence categorical column with identity
- o sequence categorical column with vocabulary file
- o sequence categorical column with vocabulary list
- o sequence numeric column
- shared embedding columns
- o weighted categorical column

• tf.gfile

- Overview
- Copy
- <u>DeleteRecursively</u>
- Exists
- FastGFile
- o Glob
- <u>IsDirectory</u>
- <u>ListDirectory</u>
- o MakeDirs
- MkDir
- Remove
- Rename
- Stat
- Walk

• tf.graph_util

- o Overview
- o convert variables to constants
- o extract sub graph
- o import graph def
- o must run on cpu
- o remove training nodes
- o tensor shape from node def name

• tf.image

- Overview
- o adjust brightness
- o adjust contrast
- o adjust gamma
- o <u>adjust hue</u>
- o adjust jpeg quality
- o adjust saturation
- o central crop
- o combined non max suppression
- o convert image dtype
- o crop and resize
- o crop to bounding box
- o draw bounding boxes
- o encode png
- o extract glimpse
- o extract image patches
- extract patches
- o <u>flip left right</u>
- o flip up down
- o grayscale to rgb
- hsv to rgb
- o image gradients
- o non max suppression
- o non max suppression overlaps
- o non max suppression padded
- o non max suppression with scores

- o pad to bounding box
- o per image standardization
- o psnr
- random brightness
- o random contrast
- random crop
- random flip left right
- o random flip up down
- o random hue
- random jpeg quality
- o random saturation
- ResizeMethod
- o resize area
- o resize bicubic
- o resize bilinear
- o resize images
- o resize image with pad
- o resize nearest neighbor
- o resize with crop or pad
- o rgb to grayscale
- o rgb to hsv
- o rgb to yiq
- o rgb to yuv
- o <u>rot90</u>
- o sample distorted bounding box
- sobel edges
- o ssim
- o ssim multiscale
- total variation
- o <u>transpose</u>
- o yiq to rgb
- o yuv to rgb
- tf.initializers
 - o <u>Overview</u>
 - constant
 - o global variables
 - he normal
 - he uniform
 - <u>identity</u>
 - lecun normal
 - o lecun uniform
 - o local variables
 - o ones
 - orthogonal
 - tables initializer
 - o truncated normal
 - o uniform unit scaling
 - variables
 - o variance scaling
- tf.io
 - Overview
 - o decode and crop jpeg
 - o decode base64
 - decode bmp
 - decode compressed
 - o decode csv
 - o decode gif
 - decode image
 - o <u>decode jpeg</u>
 - o decode json example

- decode png
- o decode proto
- o deserialize many sparse
- encode base64
- encode jpeg
- o encode proto
- o extract jpeg shape
- FixedLenFeature
- FixedLenSequenceFeature
- o <u>is jpeg</u>
- matching files
- o match filenames once
- o parse_example
- o parse sequence example
- o parse single example
- o parse single sequence example
- o parse tensor
- o read file
- o serialize many sparse
- o <u>serialize sparse</u>
- o serialize tensor
- SparseFeature
- TFRecordCompressionType
- TFRecordOptions
- TFRecordWriter
- tf record iterator
- <u>VarLenFeature</u>
- o write file
- o write graph
- o gfile
 - Overview
 - <u>copy</u>
 - exists
 - GFile
 - glob
 - <u>isdir</u>
 - listdir
 - makedirs
 - <u>mkdir</u>
 - remove
 - rename
 - <u>rmtree</u>
 - <u>stat</u>
 - walk
- tf.keras
 - Overview
 - <u>Input</u>
 - Model
 - Sequential
 - activations
 - Overview
 - deserialize
 - elu
 - exponential
 - get
 - hard sigmoid
 - <u>linear</u>
 - <u>relu</u>
 - <u>selu</u>
 - serialize

- sigmoid
- softmax
- softplus
- softsign
- tanh
- applications
 - Overview
 - DenseNet121
 - DenseNet169
 - DenseNet201
 - InceptionResNetV2
 - <u>InceptionV3</u>
 - MobileNet
 - MobileNetV2
 - NASNetLarge
 - NASNetMobile
 - ResNet101
 - ResNet101V2
 - ResNet152
 - ResNet152V2
 - ResNet50
 - ResNet50V2
 - VGG16
 - <u>VGG19</u>
 - Xception
 - densenet
 - Overview
 - decode predictions
 - preprocess input
 - imagenet_utils
 - Overview
 - decode predictions
 - preprocess input
 - inception_resnet_v2
 - Overview
 - decode_predictions
 - preprocess input
 - inception_v3
 - Overview
 - decode predictions
 - preprocess input
 - mobilenet
 - Overview
 - decode predictions
 - preprocess input
 - mobilenet_v2
 - Overview
 - decode_predictions
 - preprocess input
 - nasnet
 - Overview
 - decode predictions
 - preprocess input
 - resnet
 - Overview
 - decode predictions
 - <u>preprocess_input</u>
 - resnet50
 - Overview
 - resnet_v2

- Overview
- decode predictions
- preprocess input
- vgg16
 - Overview
 - decode_predictions
 - preprocess input
- vgg19
 - Overview
 - decode predictions
 - preprocess input
- xception
 - Overview
 - decode predictions
 - <u>preprocess_input</u>
- o backend
 - Overview
 - <u>abs</u>
 - <u>all</u>
 - <u>any</u>
 - arange
 - argmax
 - <u>argmin</u>
 - backend
 - batch dot
 - batch flatten
 - batch_get_value
 - batch normalization
 - batch set value
 - bias add
 - binary crossentropy
 - cast
 - cast to floatx
 - <u>categorical_crossentropy</u>
 - clear session
 - clip
 - concatenate
 - constant
 - conv1d
 - conv2d
 - conv2d_transpose
 - conv3d
 - COS
 - count params
 - ctc batch cost
 - ctc decode
 - ctc label dense to sparse
 - cumprod
 - cumsum
 - <u>dot</u>
 - dropout
 - <u>dtype</u>
 - <u>elu</u>
 - epsilon
 - equal
 - eval
 - <u>exp</u>
 - expand dims
 - <u>eye</u>
 - <u>flatten</u>

- <u>floatx</u>
- foldl
- foldr
- function
- gather
- get session
- get uid
- get value
- gradients
- greater
- greater equal
- hard sigmoid
- image data format
- <u>int shape</u>
- in test phase
- <u>in top k</u>
- <u>in train phase</u>
- <u>is sparse</u>
- 12 normalize
- <u>learning_phase</u>
- learning phase scope
- less
- less equal
- local conv1d
- local conv2d
- log
- manual variable initialization
- <u>map fn</u>
- <u>max</u>
- <u>maximum</u>
- mean
- min
- minimum
- moving average update
- ndim
- normalize batch in training
- <u>not equal</u>
- ones
- ones like
- one hot
- permute dimensions
- placeholder
- pool2d
- pool3d
- pow
- print tensor
- prod
- random binomial
- random normal
- random normal variable
- random uniform
- random uniform variable
- <u>relu</u>
- repeat
- repeat_elements
- reset uids
- <u>reshape</u>
- resize images
- resize volumes
- reverse

- rnn
- round
- separable conv2d
- <u>set epsilon</u>
- set floatx
- set image data format
- set learning phase
- set session
- set value
- shape
- sigmoid
- sign
- <u>sin</u>
- <u>softmax</u>
- softplus
- <u>softsign</u>
- sparse categorical crossentropy
- spatial 2d padding
- spatial 3d padding
- <u>sqrt</u>
- square
- <u>squeeze</u>
- stack
- std
- stop gradient
- sum
- switch
- tanh
- <u>temporal_padding</u>
- <u>tile</u>
- to dense
- <u>transpose</u>
- truncated normal
- <u>update</u>
- update add
- update sub
- <u>var</u>
- variable
- zeros
- zeros like
- callbacks
 - Overview
 - <u>BaseLogger</u>
 - Callback
 - <u>CSVLogger</u>
 - <u>EarlyStopping</u>
 - History
 - LambdaCallback
 - LearningRateScheduler
 - ModelCheckpoint
 - ProgbarLogger
 - ReduceLROnPlateau
 - RemoteMonitor
 - TensorBoard
 - TerminateOnNaN
- o constraints
 - Overview
 - Constraint
 - deserialize
 - get

- MaxNorm
- MinMaxNorm
- NonNeg
- RadialConstraint
- serialize
- UnitNorm
- datasets
 - Overview
 - boston_housing
 - Overview
 - load data
 - cifar10
 - Overview
 - <u>load data</u>
 - cifar100
 - Overview
 - load data
 - fashion mnist
 - Overview
 - load data
 - imdb
 - Overview
 - get word index
 - <u>load data</u>
 - mnist
 - Overview
 - load data
 - reuters
 - Overview
 - get word index
 - load data
- o estimator
 - Overview
 - model to estimator
- experimental
 - Overview
 - CosineDecay
 - CosineDecayRestarts
 - export saved model
 - LinearCosineDecay
 - LinearModel
 - load from saved model
 - NoisyLinearCosineDecay
 - PeepholeLSTMCell
 - SequenceFeatures
 - terminate keras multiprocessing pools
 - WideDeepModel
- initializers
 - Overview
 - deserialize
 - get
 - <u>Initializer</u>
 - RandomNormal
 - RandomUniform
 - serialize
 - TruncatedNormal
- o layers
 - Overview
 - AbstractRNNCell
 - Activation

- ActivityRegularization
- Add
- add
- AdditiveAttention
- AlphaDropout
- Attention
- Average
- average
- AveragePooling1D
- AveragePooling2D
- AveragePooling3D
- BatchNormalization
- Bidirectional
- Concatenate
- concatenate
- Conv1D
- Conv2D
- Conv2DTranspose
- Conv3D
- Conv3DTranspose
- ConvLSTM2D
- Cropping1D
- Cropping2D
- Cropping3D
- CuDNNGRU
- CuDNNLSTM
- Dense
- DenseFeatures
- <u>DepthwiseConv2D</u>
- deserialize
- <u>Dot</u>
- <u>dot</u>
- Dropout
- ELU
- Embedding
- Flatten
- GaussianDropout
- GaussianNoise
- GlobalAveragePooling1D
- GlobalAveragePooling2D
- GlobalAveragePooling3D
- GlobalMaxPool1D
- GlobalMaxPool2D
- GlobalMaxPool3D
- GRU
- GRUCell
- InputLayer
- <u>Lambda</u>
- Layer
- <u>LayerNormalization</u>
- LeakyReLU
- LocallyConnected1D
- <u>LocallyConnected2D</u>
- LSTM
- LSTMCell
- Masking
- Maximum
- maximum
- MaxPool1D
- MaxPool2D

- MaxPool3D
- Minimum
- minimum
- Multiply
- <u>multiply</u>
- Permute
- PReLU
- ReLU
- RepeatVector
- Reshape
- RNN
- SeparableConv1D
- SeparableConv2D
- serialize
- SimpleRNN
- SimpleRNNCell
- Softmax
- SpatialDropout1D
- <u>SpatialDropout2D</u>
- <u>SpatialDropout3D</u>
- StackedRNNCells
- Subtract
- subtract
- ThresholdedReLU
- TimeDistributed
- <u>UpSampling1D</u>
- <u>UpSampling2D</u>
- <u>UpSampling3D</u>
- <u>Wrapper</u>
- ZeroPadding1D
- ZeroPadding2D
- ZeroPadding3D

o losses

- Overview
- <u>BinaryCrossentropy</u>
- binary crossentropy
- <u>CategoricalCrossentropy</u>
- CategoricalHinge
- categorical crossentropy
- categorical hinge
- cosine
- CosineSimilarity
- deserialize
- get
- Hinge
- hinge
- Huber
- KLD
- KLDivergence
- <u>LogCosh</u>
- logcosh
- Loss
- MAE
- MAPE
- MeanAbsoluteError
- MeanAbsolutePercentageError
- MeanSquaredError
- MeanSquaredLogarithmicError
- MSE
- MSLE

- Poisson
- poisson
- serialize
- <u>SparseCategoricalCrossentropy</u>
- sparse categorical crossentropy
- SquaredHinge
- squared hinge

metrics

- Overview
- Accuracy
- AUC
- BinaryAccuracy
- <u>BinaryCrossentropy</u>
- binary accuracy
- <u>CategoricalAccuracy</u>
- CategoricalCrossentropy
- CategoricalHinge
- categorical accuracy
- CosineSimilarity
- deserialize
- FalseNegatives
- FalsePositives
- get
- <u>Hinge</u>
- KLDivergence
- LogCoshError
- Mean
- MeanAbsoluteError
- MeanAbsolutePercentageError
- MeanIoU
- MeanRelativeError
- MeanSquaredError
- MeanSquaredLogarithmicError
- MeanTensor
- Metric
- Poisson
- Precision
- Recall
- RootMeanSquaredError
- SensitivityAtSpecificity
- serialize
- SparseCategoricalAccuracy
- SparseCategoricalCrossentropy
- SparseTopKCategoricalAccuracy
- sparse categorical accuracy
- sparse top k categorical accuracy
- <u>SpecificityAtSensitivity</u>
- SquaredHinge
- Sum
- <u>TopKCategoricalAccuracy</u>
- top k categorical accuracy
- <u>TrueNegatives</u>
- <u>TruePositives</u>
- o mixed precision
 - Overview
 - experimental
 - Overview
 - global policy
 - LossScaleOptimizer
 - Policy

- <u>set_policy</u>
- o models
 - Overview
 - clone model
 - <u>load model</u>
 - model_from_config
 - <u>model from json</u>
 - model_from_yaml
 - save model
- o optimizers
 - Overview
 - Adadelta
 - Adagrad
 - Adam
 - Adamax
 - deserialize
 - Ftrl
 - get
 - <u>Nadam</u>
 - Optimizer
 - RMSprop
 - serialize
 - SGD
 - schedules
 - Overview
 - deserialize
 - ExponentialDecay
 - InverseTimeDecay
 - <u>LearningRateSchedule</u>
 - <u>PiecewiseConstantDecay</u>
 - PolynomialDecay
 - serialize
- preprocessing
 - Overview
 - image
 - Overview
 - apply affine transform
 - apply brightness shift
 - apply channel shift
 - array to img
 - DirectoryIterator
 - <u>ImageDataGenerator</u>
 - img_to_array
 - Iterator
 - <u>load img</u>
 - NumpyArrayIterator
 - random brightness
 - random channel shift
 - random rotation
 - random shear
 - random shift
 - random zoom
 - save img
 - sequence
 - Overview
 - make sampling table
 - pad sequences
 - skipgrams
 - <u>TimeseriesGenerator</u>
 - text

- Overview
- hashing trick
- one hot
- text to word sequence
- Tokenizer
- o regularizers
 - Overview
 - deserialize
 - get
 - **1**1
 - L1L2
 - **11** 12
 - **1**2
 - Regularizer
 - serialize
- utils
 - Overview
 - convert all kernels in model
 - <u>CustomObjectScope</u>
 - custom object scope
 - deserialize keras object
 - GeneratorEnqueuer
 - get custom objects
 - get file
 - get source inputs
 - HDF5Matrix
 - model to dot
 - multi gpu model
 - <u>normalize</u>
 - OrderedEnqueuer
 - plot model
 - Progbar
 - Sequence
 - SequenceEnqueuer
 - serialize keras object
 - to_categorical
- o wrappers
 - Overview
 - scikit_learn
 - Overview
 - KerasClassifier
 - KerasRegressor
- tf.layers
 - o <u>Overview</u>
 - AveragePooling1D
 - AveragePooling2D
 - AveragePooling3D
 - o average_pooling1d
 - o average pooling2d
 - o average_pooling3d
 - BatchNormalization
 - batch normalization
 - Conv1D
 - o conv1d
 - o Conv2D
 - o conv2d
 - <u>Conv2DTranspose</u>
 - o conv2d transpose
 - Conv3D
 - o conv3d

- Conv3DTranspose
- o conv3d transpose
- Dense
- o <u>dense</u>
- <u>Dropout</u>
- dropout
- Flatten
- flatten
- InputSpec
- o <u>Layer</u>
- MaxPooling1D
- MaxPooling2D
- MaxPooling3D
- o max pooling1d
- o max pooling2d
- max pooling3d
- SeparableConv1D
- SeparableConv2D
- o separable conv1d
- o separable conv2d
- experimental
 - Overview
 - keras style scope
 - <u>set keras style</u>

tf.linalg

- Overview
- o <u>adjoint</u>
- o band part
- o cholesky
- o cholesky solve
- o cross
- o <u>det</u>
- o diag
- o diag_part
- o eigh
- o eigvalsh
- o <u>expm</u>
- global norm
- inv
- <u>LinearOperator</u>
- <u>LinearOperatorAdjoint</u>
- <u>LinearOperatorBlockDiag</u>
- <u>LinearOperatorCirculant</u>
- <u>LinearOperatorCirculant2D</u>
- <u>LinearOperatorCirculant3D</u>
- <u>LinearOperatorComposition</u>
- LinearOperatorDiag
- <u>LinearOperatorFullMatrix</u>
- <u>LinearOperatorHouseholder</u>
- <u>LinearOperatorIdentity</u>
- <u>LinearOperatorInversion</u>
- <u>LinearOperatorKronecker</u>
- <u>LinearOperatorLowerTriangular</u>
- <u>LinearOperatorLowRankUpdate</u>
- <u>LinearOperatorScaledIdentity</u>
- <u>LinearOperatorToeplitz</u>
- <u>LinearOperatorZeros</u>
- <u>logdet</u>
- o <u>logm</u>
- <u>lstsq</u>

- <u>lu</u>
- matmul
- o matrix rank
- o matrix transpose
- o matvec
- o <u>normalize</u>
- o pinv
- <u>qr</u>
- o set diag
- o <u>slogdet</u>
- o solve
- o sqrtm
- o <u>svd</u>
- o tensor diag
- o tensor_diag_part
- o trace
- o triangular solve
- o tridiagonal matmul
- o tridiagonal solve
- tf.lite
 - Overview
 - <u>Interpreter</u>
 - OpHint
 - <u>OpHint.OpHintArgumentTracker</u>
 - OpsSet
 - o Optimize
 - RepresentativeDataset
 - <u>TargetSpec</u>
 - <u>TFLiteConverter</u>
 - TocoConverter
 - o toco convert
 - o constants
 - Overview
 - experimental
 - Overview
 - convert op hints to stubs
 - get potentially supported ops
 - load delegate
 - nn
- Overview
- dynamic rnn
- <u>TFLiteLSTMCell</u>
- <u>TfLiteRNNCell</u>
- tf.logging
 - o <u>Overview</u>
 - <u>debug</u>
 - o <u>error</u>
 - <u>fatal</u>
 - flush
 - o get_verbosity
 - <u>info</u>
 - <u>log</u>
 - o <u>log every n</u>
 - o log first n
 - log_if
 - <u>set verbosity</u>
 - <u>TaskLevelStatusMessage</u>
 - o <u>vlog</u>
 - o <u>warn</u>
 - <u>warning</u>

- tf.lookup
 - Overview
 - <u>KeyValueTensorInitializer</u>
 - StaticHashTable
 - <u>StaticVocabularyTable</u>
 - <u>TextFileIndex</u>
 - TextFileInitializer
 - experimental
 - Overview
 - DenseHashTable
- tf.losses
 - Overview
 - o absolute difference
 - o add loss
 - o compute weighted loss
 - o cosine distance
 - o get losses
 - o get regularization loss
 - o get regularization losses
 - o get total loss
 - hinge loss
 - o huber loss
 - o <u>log loss</u>
 - o mean pairwise squared error
 - mean squared error
 - Reduction
 - o sigmoid cross entropy
 - o softmax cross entropy
 - o sparse softmax cross entropy
- tf.manip
 - o <u>Overview</u>
- tf.math
 - o Overview
 - o <u>abs</u>
 - o accumulate n
 - o acos
 - o acosh
 - o <u>add</u>
 - o add n
 - o angle
 - o <u>argmax</u>
 - o argmin
 - o <u>asin</u>
 - o asinh
 - o <u>atan</u>
 - o atan2
 - o atanh
 - bessel i0
 - o bessel i0e
 - o bessel_i1
 - bessel ile
 - betaincbincount
 - o ceil
 - o confusion matrix
 - o conj
 - o cos
 - o cosh
 - o count nonzero
 - <u>cumprod</u>

- o <u>cumsum</u>
- o <u>cumulative logsumexp</u>
- o <u>digamma</u>
- divide
- o divide no nan
- o <u>equal</u>
- o erf
- o erfc
- o <u>exp</u>
- expm1
- o floor
- floordiv
- floormod
- o greater
- o greater equal
- igamma
- o <u>igammac</u>
- <u>imag</u>
- invert permutation
- o in top k
- is finite
- o is inf
- is nan
- o is non decreasing
- o is strictly increasing
- 12 normalize
- o <u>lbeta</u>
- o <u>less</u>
- o <u>less_equal</u>
- o <u>lgamma</u>
- o <u>log</u>
- <u>log1p</u>
- o logical and
- o logical not
- o logical or
- o logical xor
- o <u>log sigmoid</u>
- <u>maximum</u>
- o minimum
- multiply
- o multiply no nan
- o <u>negative</u>
- o <u>nextafter</u>
- o not equal
- o polygamma
- o polyval
- o <u>pow</u>
- o <u>real</u>
- reciprocal
- o reciprocal_no_nan
- o reduce all
- reduce any
- o reduce euclidean norm
- reduce logsumexp
- o reduce max
- o reduce mean
- o reduce min
- reduce prodreduce std
- reduce sum

- reduce variance
- rint
- round
- o <u>rsqrt</u>
- o scalar mul
- o segment max
- o segment mean
- o <u>segment_min</u>
- o segment prod
- o segment sum
- sigmoid
- o <u>sign</u>
- o sin
- o sinh
- o <u>softplus</u>
- o <u>sqrt</u>
- o <u>square</u>
- squared difference
- subtract
- o <u>tan</u>
- o tanh
- o top k
- o truediv
- o unsorted segment max
- o unsorted segment mean
- o unsorted segment min
- o unsorted segment prod
- o unsorted segment sqrt n
- o unsorted segment sum
- o <u>xdivy</u>
- o <u>xlogy</u>
- o zero fraction
- o <u>zeta</u>

• tf.metrics

- Overview
- o <u>accuracy</u>
- o <u>auc</u>
- o average precision at k
- false negatives
- o false negatives at thresholds
- false positives
- o false positives at thresholds
- o mean
- o mean absolute error
- o mean cosine distance
- mean iou
- o mean per class accuracy
- o mean_relative_error
- o mean squared error
- o mean_tensor
- o percentage below
- o <u>precision</u>
- o precision at k
- o precision at thresholds
- o precision at top k
- o recall
- o recall at k
- o recall at thresholds
- o recall at top k
- o root mean squared error

- sensitivity at specificity
- o sparse average precision at k
- o sparse precision at k
- o specificity at sensitivity
- o <u>true negatives</u>
- o true negatives at thresholds
- o true positives
- o true positives at thresholds

• tf.nest

- Overview
- o assert same structure
- flatten
- o is nested
- o map structure
- o pack sequence as

• tf.nn

- Overview
- o atrous conv2d
- o atrous conv2d transpose
- o <u>avg_pool</u>
- o avg_pool1d
- o <u>avg_pool3d</u>
- o avg pool v2
- o batch normalization
- o batch norm with global normalization
- o bias add
- o bidirectional dynamic rnn
- o collapse repeated
- o compute accidental hits
- o compute average loss
- o conv1d
- o conv1d transpose
- o conv2d
- o conv2d backprop filter
- conv2d backprop input
- o conv2d transpose
- o conv3d
- conv3d backprop filter
- o conv3d transpose
- convolution
- o conv transpose
- o <u>crelu</u>
- o ctc beam search decoder
- o ctc beam search decoder v2
- o ctc greedy decoder
- o ctc loss
- o ctc loss v2
- o ctc unique labels
- o depthwise conv2d
- o depthwise conv2d backprop filter
- o depthwise conv2d backprop input
- <u>depthwise conv2d native</u>
- o depth to space
- o dilation2d
- <u>dropout</u>
- o dynamic rnn
- o <u>elu</u>
- <u>embedding lookup</u>
- o embedding lookup sparse
- erosion2d

- <u>fractional avg pool</u>
- fractional max pool
- o fused batch norm
- <u>12 loss</u>
- o <u>leaky relu</u>
- o <u>local response normalization</u>
- o <u>log poisson loss</u>
- log softmax
- o max pool
- o max pool1d
- o max pool2d
- o max pool3d
- o max pool v2
- o <u>max pool with argmax</u>
- o moments
- o nce loss
- o normalize moments
- o pool
- o quantized avg pool
- o quantized conv2d
- o quantized max pool
- o quantized relu x
- o <u>raw rnn</u>
- o <u>relu</u>
- o relu6
- o relu layer
- safe embedding lookup sparse
- sampled softmax loss
- o scale regularization loss
- o <u>selu</u>
- separable conv2d
- o sigmoid cross entropy with logits
- softmax
- o softmax cross entropy with logits
- o softmax cross entropy with logits v2
- softsign
- o space to batch
- space to depth
- o sparse softmax cross entropy with logits
- o static bidirectional rnn
- o static rnn
- o static state saving rnn
- sufficient_statistics
- <u>swish</u>
- weighted cross entropy with logits
- weighted moments
- o with space to batch
- o xw plus b
- o rnn cell
 - Overview
 - BasicLSTMCell
 - BasicRNNCell
 - DeviceWrapper
 - <u>DropoutWrapper</u>
 - GRUCell
 - LSTMCell
 - LSTMStateTuple
 - MultiRNNCell
 - ResidualWrapper
 - RNNCell

- tf.profiler
 - Overview
 - AdviceProto
 - AdviceProto.Checker
 - AdviceProto.CheckersEntry
 - o <u>advise</u>
 - GraphNodeProto
 - <u>GraphNodeProto.InputShapesEntry</u>
 - <u>MultiGraphNodeProto</u>
 - OpLogProto
 - OpLogProto.IdToStringEntry
 - o profile
 - <u>ProfileOptionBuilder</u>
 - Profiler
 - o write op log
- tf.python io
 - Overview
- tf.quantization
 - Overview
 - o <u>dequantize</u>
 - o fake quant with min max args
 - o fake quant with min max args gradient
 - o fake quant with min max vars
 - o fake quant with min max vars gradient
 - o fake quant with min max vars per channel
 - o fake quant with min max vars per channel gradient
 - o quantize
 - o quantized concat
 - o quantize and dequantize
- tf.queue
 - Overview
 - FIFOQueue
 - PaddingFIFOQueue
 - PriorityQueue
 - QueueBase
 - RandomShuffleQueue
- tf.ragged
 - o <u>Overview</u>
 - o boolean mask
 - o <u>constant</u>
 - o constant value
 - o map flat values
 - placeholder
 - RaggedTensorValue
 - o <u>range</u>
 - o row splits to segment ids
 - o segment ids to row splits
 - o stack
 - stack dynamic partitions
- tf.random
 - Overview
 - o all candidate sampler
 - o categorical
 - o fixed unigram candidate sampler
 - o gamma
 - o get seed
 - o <u>learned unigram candidate sampler</u>
 - o log uniform candidate sampler
 - multinomial
 - normal

- o <u>poisson</u>
- o set random seed
- shuffle
- stateless categorical
- o stateless multinomial
- o stateless normal
- o stateless truncated normal
- stateless uniform
- o truncated normal
- uniform
- o uniform candidate sampler
- experimental
 - Overview
 - create rng state
 - Generator
 - get global generator
 - set global generator
- tf.raw_ops
 - o <u>Overview</u>
- · tf.resource loader
 - Overview
 - o get data files path
 - o get path to datafile
 - o get root dir with all resources
 - load resource
 - o readahead file path
- tf.saved_model
 - o Overview
 - Builder
 - o <u>build signature def</u>
 - build tensor info
 - o classification signature def
 - contains saved model
 - o get tensor from tensor info
 - o is valid signature
 - load
 - o <u>load v2</u>
 - o main op with restore
 - o predict signature def
 - o regression signature def
 - o save
 - o simple save
 - builder
 - Overview
 - constants
 - Overview
 - o experimental
 - Overview
 - loader
 - Overview
 - o main_op
 - Overview
 - <u>main op</u>
 - o signature constants
 - Overview
 - signature_def_utils
 - Overview
 - tag_constants
 - Overview
 - utils

Overview

- tf.sets
 - Overview
 - difference
 - intersection
 - o <u>size</u>
 - o union
- tf.signal
 - Overview
 - o <u>dct</u>
 - o fft
 - o fft2d
 - o fft3d
 - <u>fftshift</u>
 - frame
 - hamming window
 - hann window
 - o idct
 - o <u>ifft</u>
 - o ifft2d
 - o ifft3d
 - ifftshift
 - o <u>inverse stft</u>
 - o inverse stft window fn
 - irfft
 - o irfft2d
 - o irfft3d
 - <u>linear to mel weight matrix</u>
 - o mfccs from log mel spectrograms
 - o overlap and add
 - o rfft
 - o rfft2d
 - o rfft3d
 - o <u>stft</u>
- tf.sparse
 - o <u>Overview</u>
 - o add
 - o concat
 - o cross
 - o cross hashed
 - o expand dims
 - o <u>eye</u>
 - fill_empty_rows
 - from dense
 - o <u>mask</u>
 - o <u>maximum</u>
 - o <u>merge</u>
 - minimum
 - o placeholder
 - o reduce max
 - o reduce max sparse
 - o reduce sum
 - o reduce sum sparse
 - reorder
 - o reset_shape
 - <u>reshape</u>
 - o <u>retain</u>
 - o segment mean
 - o segment sqrt n
 - o <u>segment sum</u>

- slice
- softmax
- SparseConditionalAccumulator
- SparseTensor
- o sparse dense matmul
- o <u>split</u>
- o to dense
- o to indicator
- o transpose
- tf.spectral
 - Overview
- tf.strings
 - o Overview
 - o as string
 - o bytes split
 - format
 - join
 - length
 - o <u>lower</u>
 - o <u>ngrams</u>
 - reduce join
 - o regex full match
 - o regex replace
 - o <u>split</u>
 - o strip
 - substr
 - o to hash bucket
 - o to hash bucket fast
 - o to hash bucket strong
 - o to number
 - o unicode decode
 - o unicode decode with offsets
 - o unicode encode
 - o unicode_script
 - o unicode split
 - o unicode split with offsets
 - unicode transcode
 - o unsorted segment join
 - o <u>upper</u>
- tf.summary
 - Overview
 - o all v2 summary ops
 - o <u>audio</u>
 - FileWriter
 - o FileWriterCache
 - o get summary description
 - histogram
 - o <u>image</u>
 - <u>initialize</u>
 - o <u>merge</u>
 - o merge all
 - o <u>scalar</u>
 - Summary.Audio
 - Summary.Image
 - Summary.Value
 - <u>SummaryDescription</u>
 - <u>TaggedRunMetadata</u><u>tensor summary</u>
 - o text
- tf.sysconfig

- Overview
- o get compile flags
- o get include
- o get lib
- o get link flags

• tf.test

- Overview
- o assert equal graph def
- Benchmark
- benchmark config
- o compute gradient
- o compute gradient error
- o create local cluster
- o get temp dir
- o gpu device name
- o is built with cuda
- o is built with gpu support
- o is built with rocm
- o is gpu available
- o main
- StubOutForTesting
- TestCase
- TestCase.failureException
- o test src dir path

• tf.tpu

- Overview
- o batch parallel
- bfloat16 scope
- o core
- CrossShardOptimizer
- o cross replica sum
- o <u>initialize system</u>
- outside compilation
- replicate
- o rewrite
- shard
- <u>shutdown system</u>
- experimental
 - Overview
 - AdagradParameters
 - AdamParameters
 - DeviceAssignment
 - embedding_column
 - <u>initialize tpu system</u>
 - shared embedding columns
 - StochasticGradientDescentParameters

• tf.train

- o Overview
- AdadeltaOptimizer
- AdagradDAOptimizer
- AdagradOptimizer
- AdamOptimizer
- o assert global step
- basic train loop
- o batch
- o batch join
- BytesList
- Checkpoint
- CheckpointManager
- CheckpointSaverHook

- <u>CheckpointSaverListener</u>
- checkpoints iterator
- checkpoint exists
- ChiefSessionCreator
- <u>ClusterDef</u>
- ClusterSpec
- Coordinator
- cosine_decay
- o cosine decay restarts
- o create global step
- o do quantize training on graphdef
- Example
- ExponentialMovingAverage
- o exponential decay
- o export meta graph
- Feature
- FeatureList
- FeatureLists
- FeatureLists.FeatureListEntry
- Features
- Features.FeatureEntry
- FeedFnHook
- FinalOpsHook
- FloatList
- <u>FtrlOptimizer</u>
- o generate checkpoint state proto
- o get checkpoint mtimes
- o get checkpoint state
- o get global step
- o get or create global step
- GlobalStepWaiterHook
- o global step
- GradientDescentOptimizer
- o import meta graph
- o init from checkpoint
- input producer
- Int64List
- inverse time decay
- JobDef
- JobDef.TasksEntry
- latest checkpoint
- <u>limit epochs</u>
- linear cosine decay
- list variables
- load checkpoint
- o <u>load variable</u>
- <u>LoggingTensorHook</u>
- <u>LooperThread</u>
- o maybe batch
- o maybe batch join
- o maybe shuffle batch
- o maybe shuffle batch join
- MomentumOptimizer
- MonitoredSession
- MonitoredSession.StepContext
- MonitoredTrainingSession
- NanLossDuringTrainingError
- NanTensorHook
- natural exp decay
- NewCheckpointReader

- noisy linear cosine decay
- Optimizer
- o piecewise constant decay
- polynomial decay
- ProfilerHook
- <u>ProximalAdagradOptimizer</u>
- <u>ProximalGradientDescentOptimizer</u>
- range input producer
- remove checkpoint
- o replica device setter
- RMSPropOptimizer
- Saver
- SaverDef
- Scaffold
- o sdca fprint
- sdca optimizer
- o sdca shrink 11
- <u>SecondOrStepTimer</u>
- <u>SequenceExample</u>
- ServerDef
- SessionCreator
- SessionManager
- SessionRunArgs
- SessionRunContext
- SessionRunHook
- SessionRunValues
- shuffle batch
- shuffle batch join
- SingularMonitoredSession
- slice input producer
- <u>StepCounterHook</u>
- StopAtStepHook
- string input producer
- <u>SummarySaverHook</u>
- o summary iterator
- Supervisor
- <u>SyncReplicasOptimizer</u>
- o update checkpoint state
- VocabInfo
- warm start
- WorkerSessionCreator
- o experimental
 - Overview
 - disable mixed precision graph rewrite
 - <u>DynamicLossScale</u>
 - enable mixed precision graph rewrite
 - FixedLossScale
 - LossScale
 - <u>MixedPrecisionLossScaleOptimizer</u>
 - PythonState
- o queue_runner
 - Overview
 - add queue runner
 - QueueRunner
 - start queue runners
- tf.user_ops
 - o Overview
 - o my fact
- tf.version
 - Overview

- tf.xla
 - Overview
 - o experimental
 - Overview
 - compile
 - jit_scope
- All Symbols

- Contents
- <u>Class RMSPropOptimizer</u>
 - Aliases:
- <u>init</u>
- Methods
 - o apply gradients
 - o compute gradients
 - o get name
 - o get slot
 - o get slot names
 - o minimize
 - o variables
- Class Members

Missed TensorFlow World? Check out the recap. Learn more

- TensorFlow
- API
- TensorFlow Core r1.15
- <u>Python</u>

tf.train.RMSPropOptimizer

- Contents
- Class RMSPropOptimizer
 - Aliases:
- init
- Methods
- [



Class RMSPropOptimizer

Optimizer that implements the RMSProp algorithm.

Inherits From: Optimizer

Aliases:

• Class <u>tf.compat.v1.train.RMSPropOptimizer</u>

See the <u>paper</u>.

$_$ init $_$

View source

```
__init__(
    learning_rate,
    decay=0.9,
    momentum=0.0,
    epsilon=1e-10,
    use_locking=False,
    centered=False,
    name='RMSProp'
)
```

Construct a new RMSProp optimizer.

Note that in the dense implementation of this algorithm, variables and their corresponding accumulators (momentum, gradient moving average, square gradient moving average) will be updated even if the gradient is zero (i.e. accumulators will decay, momentum will be applied). The sparse implementation (used when the gradient is an IndexedSlices object, typically because of tf.gather or an embedding lookup in the forward pass) will not update variable slices or their accumulators unless those slices were used in the forward pass (nor is there an "eventual" correction to account for these omitted updates). This leads to more efficient updates for large embedding lookup tables (where most of the slices are not accessed in a particular graph execution), but differs from the published algorithm.

Args:

- learning rate: A Tensor or a floating point value. The learning rate.
- decay: Discounting factor for the history/coming gradient
- momentum: A scalar tensor.
- epsilon: Small value to avoid zero denominator.
- use locking: If True use locks for update operation.
- **centered**: If True, gradients are normalized by the estimated variance of the gradient; if False, by the uncentered second moment. Setting this to True may help with training, but is slightly more expensive in terms of computation and memory. Defaults to False.
- name: Optional name prefix for the operations created when applying gradients. Defaults to "RMSProp".

Eager Compatibility

When eager execution is enabled, <code>learning_rate</code>, <code>decay</code>, <code>momentum</code>, and <code>epsilon</code> can each be a callable that takes no arguments and returns the actual value to use. This can be useful for changing these values across different invocations of optimizer functions.

Methods

apply_gradients

View source

```
apply_gradients(
    grads_and_vars,
    global_step=None,
    name=None
)
```

Apply gradients to variables.

This is the second part of minimize(). It returns an operation that applies gradients.

Args:

- grads and vars: List of (gradient, variable) pairs as returned by compute gradients().
- global_step: Optional variable to increment by one after the variables have been updated.
- name: Optional name for the returned operation. Default to the name passed to the optimizer constructor.

Returns:

An Operation that applies the specified gradients. If global_step was not None, that operation also increments global step.

Raises:

- TypeError: If grads_and_vars is malformed.
- **ValueError**: If none of the variables have gradients.
- RuntimeError: If you should use _distributed_apply() instead.

compute gradients

View source

```
compute_gradients(
   loss,
   var_list=None,
   gate_gradients=GATE_OP,
   aggregation_method=None,
   colocate_gradients_with_ops=False,
   grad_loss=None
)
```

Compute gradients of loss for the variables in var list.

This is the first part of minimize(). It returns a list of (gradient, variable) pairs where "gradient" is the gradient for "variable". Note that "gradient" can be a Tensor, an IndexedSlices, or None if there is no gradient for the given variable.

Args:

- **loss**: A Tensor containing the value to minimize or a callable taking no arguments which returns the value to minimize. When eager execution is enabled it must be a callable.
- var_list: Optional list or tuple of tf.Variable to update to minimize loss. Defaults to the list of variables collected in the graph under the key GraphKeys.TRAINABLE VARIABLES.
- gate_gradients: How to gate the computation of gradients. Can be GATE_NONE, GATE_OP, or GATE_GRAPH.
- aggregation_method: Specifies the method used to combine gradient terms. Valid values are defined in the class AggregationMethod.
- colocate_gradients_with_ops: If True, try colocating gradients with the corresponding op.
- grad loss: Optional. A Tensor holding the gradient computed for loss.

Returns:

A list of (gradient, variable) pairs. Variable is always present, but gradient can be None.

Raises:

- TypeError: If var list contains anything else than Variable objects.
- **ValueError**: If some arguments are invalid.
- RuntimeError: If called with eager execution enabled and loss is not callable.

Eager Compatibility

When eager execution is enabled, gate_gradients, aggregation_method, and colocate_gradients_with_ops are ignored.

get_name

View source

```
get_name()
```

get_slot

View source

```
get_slot(
    var,
    name
)
```

Return a slot named name created for var by the Optimizer.

Some Optimizer subclasses use additional variables. For example Momentum and Adagrad use variables to accumulate updates. This method gives access to these Variable objects if for some reason you need them.

Use get_slot_names() to get the list of slot names created by the Optimizer.

Args:

- var: A variable passed to minimize() or apply_gradients().
- name: A string.

Returns:

The variable for the slot if it was created, None otherwise.

get_slot_names

View source

```
get slot names()
```

Return a list of the names of slots created by the Optimizer.

```
See get slot().
```

Returns:

A list of strings.

minimize

View source

```
minimize(
    loss,
    global_step=None,
    var_list=None,
    gate_gradients=GATE_OP,
```

```
aggregation_method=None,
colocate_gradients_with_ops=False,
name=None,
grad_loss=None
```

Add operations to minimize loss by updating var list.

This method simply combines calls compute_gradients() and apply_gradients(). If you want to process the gradient before applying them call compute_gradients() and apply_gradients() explicitly instead of using this function.

Args:

- loss: A Tensor containing the value to minimize.
- global_step: Optional variable to increment by one after the variables have been updated.
- var_list: Optional list or tuple of variable objects to update to minimize loss. Defaults to the list of variables collected in the graph under the key GraphKeys.TRAINABLE VARIABLES.
- gate_gradients: How to gate the computation of gradients. Can be gate none, gate op, or gate graph.
- aggregation_method: Specifies the method used to combine gradient terms. Valid values are defined in the class AggregationMethod.
- colocate_gradients_with_ops: If True, try colocating gradients with the corresponding op.
- name: Optional name for the returned operation.
- grad loss: Optional. A Tensor holding the gradient computed for loss.

Returns:

An Operation that updates the variables in var_list. If global_step was not None, that operation also increments global step.

Raises:

• ValueError: If some of the variables are not Variable objects.

Eager Compatibility

When eager execution is enabled, loss should be a Python function that takes no arguments and computes the value to be minimized. Minimization (and gradient computation) is done with respect to the elements of var_list if not None, else with respect to any trainable variables created during the execution of the loss function. gate_gradients, aggregation_method, colocate_gradients_with_ops and grad_loss are ignored when eager execution is enabled.

variables

View source

```
variables()
```

A list of variables which encode the current state of optimizer.

Includes slot variables and additional global variables created by the optimizer in the current default graph.

Returns:

A list of variables.

Class Members

- GATE GRAPH = 2
- GATE NONE = 0
- GATE OP = 1

Was this page helpful?

stars træstkerstkerstkerrdberrder

Was this page helpful?

stars two stars dans dans dans de modern de m

Except as otherwise noted, the content of this page is licensed under the <u>Creative Commons Attribution 4.0 License</u>, and code samples are licensed under the <u>Apache 2.0 License</u>. For details, see the <u>Google Developers Site Policies</u>. Java is a registered trademark of Oracle and/or its affiliates.

Stay connected

- o Blog
- GitHub
- <u>Twitter</u>
- YouTube

• Support

- <u>Issue tracker</u>
- Release notes
- Stack Overflow
- Brand guidelines
- Terms
- Privacy
- Sign up for the TensorFlow monthly newsletter <u>Subscribe</u>



- Language
- English
- 中文 简体

Language

- Language
- English
- 中文 简体