

Visual Learning and Recognition of 3-D Objects from Appearance

CS663 Fundamentals of Digital Image Processing

Rathour Param Jitendrakumar, 190070049
Tirthankar Mazumder, 20b090012
Divyansh Tiwari, 200020049

Indian Institute of Technology Bombay
<https://github.com/wermos/CS-663-Project>

Autumn 2023-24

Guide: Prof. Ajit Rajwade

Outline

- 1 Implementation
 - High-Level Overview
 - Dataset
 - Code Optimizations
- 2 Results and Observations
 - Optimal PCA Threshold and Training Data Split
 - Variation with PCA Threshold and Training Data Split one at a time
 - Incorrect Object Detection
 - Simultaneous variation with PCA Threshold and Training Data Split
 - Variation with Object Complexity
- 3 Theory (optional)

Implementation

High-Level Overview


- Data-Loading
 - ▶ Generate Training, Testing sets (COIL-100 Dataset)
 - ▶ Image Pre-processing (RGB to Grayscale conversion)
- Train Model
 - ▶ Normalise Image Sets
 - ▶ Construct Universal Image Set and Object-specific Image Sets
 - ▶ Construct Universal Eigenspace and Object-specific Eigenspaces (Principal Component Analysis)
 - ▶ Construct Universal Manifolds and Object-specific Manifolds (Cubic Spline Interpolation)
- Test Model
 - ▶ Normalise Image
 - ▶ Construct Universal Eigencoefficients (Project to Universal Eigenspace)
 - ▶ Recognise Object (Closest universal manifold from projection of given image)
 - ▶ Construct Object-specific Eigencoefficients (Project to Eigenspace of recognised object)
 - ▶ Recognise Pose (Closest point on Object-specific Manifold from Eigencoefficients vector)

Manifold (Parametric Appearance Representation)

Benefits


- Provides a parameterised approach to approximate eigencoefficients for unknown poses
- Possible parameters
 - ▶ Rotation about x -axis, y -axis, z -axis
 - ▶ Illumination conditions of the environment
- Storage compression over PCA: cubic polynomials gives eigencoefficients of each eigenspace

Parametric Eigenspace Representation for object₂ using three at most prominent dimensions



(a) Available Poses of object

Parametric Eigenspace Representation for object₂ using three at most prominent dimensions



(b) Manifold (Cubic Spline interpolation)

Figure: Object 2

Dataset

Columbia University Image Library (COIL-100)

100 objects! Each object has 72 pose images with pose angle $\{0, 5, 10, \dots, 345, 350, 355\}$



Figure: COIL-100 Dataset by Columbia Imaging and Vision Laboratory (CAVE)¹

These objects can be categorised into two sets

- uniform reflectance but similar shape
- complex reflectance and geometric properties

¹ "Columbia Object Image Library," S. A. Nene, S. K. Nayar and H. Murase, CUCS-006-96, February 1996.

Dataset

Assumptions

COIL-100 dataset satisfies these assumptions

- Image Assumptions

- ▶ Background region is assigned zero brightness value
- ▶ Imaging sensor has a linear response (image brightness is proportional to scene radiance)
- ▶ Object images
 - ★ are not occluded by other objects
 - ★ can be object segmented from the remaining scene
 - ★ are invariant to image magnification and illumination intensity as segmented image region is
 - normalized with respect to scale re-sampled to fit image size
 - normalized with respect to brightness normalised by dividing euclidean norm

- Object Assumptions

- ▶ Neither highly specular nor has a high-frequency texture


Manifold (Parametric Appearance Representation)

Examples




(a) Object 2

Parametric Eigenspace Representation for object₂ using three at most prominent dimensions




(d) Corresponding Manifold



(b) Object 3

Parametric Eigenspace Representation for object₃ using three at most prominent dimensions




(e) Corresponding Manifold



(c) Object 4

Parametric Eigenspace Representation for object₄ using three at most prominent dimensions



(f) Corresponding Manifold

Code Optimizations

Implementation

- Principal Component Analysis (PCA)
 - ▶ Eigenvector computation of $X^T X$ instead of the covariance matrix (XX^T)
 - ▶ `numpy.linalg.eigh` instead to `numpy.linalg.eig` to exploit the algorithms assuming symmetric input matrices
- Extensive usage of numpy objects and functions to facilitate multi-threading in numba
- `os.environ['OMP_NUM_THREADS'] = '16'` to increase number of parallel threads to 16
- Ability to store and load saved learnt variables using pickle

Optimal Values

PCA Threshold = 0.6 and Training Data Split = 0.7

Object Recognition accuracy 99.172%

Pose Estimation accuracy 76.172%

Mean Pose error 6.872°


In the next two slides, we see some examples of incorrect recognition.
Even in such cases we see that our model's outputs are reasonable.

- 180° pose errors are most frequent among pose recognition
- similar-looking objects get recognised incorrectly

These errors usually occur in bursts (consecutive poses), which implies that nearby points in manifolds might be too far to interpolate in between points accurately.

One way to solve this is by training on uniformly pose-separated object images.

Incorrect Object Detection (True and Estimated)



(a) Object 7, Angle 75



(b) Object 22, Angle 280



(c) Object 97, Angle 195



(d) Object 22, Angle 80



(e) Object 75, Angle 280



(f) Object 83, Angle 25

Incorrect Pose Recognition (True and Estimated)



(a) Object 33, Angle 75



(d) Object 33, Angle 80



(b) Object 21, Angle 280



(e) Object 21, Angle 95



(c) Object 20, Angle 100



(f) Object 20, Angle 280



Variation with PCA Threshold and Training Data Split one at a time

In the coming plots, we vary each parameter one by one and then vary them simultaneously

- Vary PCA Threshold as $\{0.05, 0.1, \dots, 0.9, 0.95\}$, set Training Data Split to 0.6
 - ▶ higher PCA Threshold leads to overfitting
- Vary Training Data Split as $\{0.05, 0.1, \dots, 0.9, 0.95\}$, set PCA Threshold to 0.7
 - ▶ more training data creates more accurate manifold which leads to better recognition
- Vary PCA Threshold as $\{0.05, 0.1, \dots, 0.9, 0.95\}$ and vary Training Data Split as $\{0.05, 0.1, \dots, 0.9, 0.95\}$



Variation with PCA Threshold and Training Data Split one at a time

Accuracy





Variation with PCA Threshold and Training Data Split one at a time

Mean Error





Variation with PCA Threshold and Training Data Split one at a time

Object Accuracy





Variation with PCA Threshold and Training Data Split one at a time

Pose Accuracy





Variation with PCA Threshold and Training Data Split one at a time

Mean Error




Variation with PCA Threshold and Training Data Split one at a time

Exact Error




Simultaneous variation with PCA Threshold and Training Data Split

Object recognition accuracy overall with varying PCA Threshold and Training Data Split




(a) Object Accuracy

Pose recognition accuracy overall with varying PCA Threshold and Training Data Split



(b) Pose Accuracy

Average pose error overall with varying PCA Threshold and Training Data Split



(c) Mean Error

Variation with Object Complexity

Three types of objects

- Simple Objects, almost no variation in poses due to symmetrical nature and less details
- Simple Objects, almost no variation in poses due to symmetrical nature but highly detailed
- Complex Objects, different shapes in different poses



(a) Object 69



(b) Object 98




(c) Object 67

Observations

Types of Wireframe: Mean Accuracy


- as object complexity increases, more training data is needed for lower mean error
- only slightly higher pca threshold needed for complex objects

Average pose error for object₆₉ with varying PCA Threshold and Training Data Split




(a) Object 69

Average pose error for object₉₈ with varying PCA Threshold and Training Data Split



(b) Object 98

Average pose error for object₆₇ with varying PCA Threshold and Training Data Split




(c) Object 67

Observations

Types of Wireframe: Object Accuracy


- as object complexity increases, more training data is needed for higher accuracy
15-20 objects poses are enough for learning the simple objects, but 30-40 object poses are needed to learn complex dataset
- higher pca threshold only needed in complex objects

Object recognition accuracy for object₆₉ with varying PCA Threshold and Training Data Split




(a) Object 69

Object recognition accuracy for object₉₈ with varying PCA Threshold and Training Data Split



(b) Object 98

Object recognition accuracy for object₆₇ with varying PCA Threshold and Training Data Split




(c) Object 67

Observations

Types of Wireframe: Pose Accuracy


- accuracy increases as object complexity increases, because pose becomes easier to distinguish
- for simpler objects, more training data or pca threshold doesn't help much to estimate exactly

Pose recognition accuracy for object₆₉ with varying PCA Threshold and Training Data Split




(a) Object 69

Pose recognition accuracy for object₉₈ with varying PCA Threshold and Training Data Split



(b) Object 98

Pose recognition accuracy for object₆₇ with varying PCA Threshold and Training Data Split



(c) Object 67

Theory I

Notation

Single image (normalised)

$$\hat{\mathbf{x}} = [\hat{x}_1, \hat{x}_2, \dots, \hat{x}_N]^T \quad (1)$$

Universal Image Set

$$\mathbf{X} \triangleq \{\mathbf{x}_1^{(1)} - \mathbf{c}, \mathbf{x}_2^{(1)} - \mathbf{c}, \dots, \mathbf{x}_R^{(1)} - \mathbf{c}, \dots, \mathbf{x}_R^{(p)} - \mathbf{c}\} \quad (2)$$

Object Image Sets

$$\mathbf{X}^{(p)} = \{\hat{\mathbf{x}}_1^{(p)} - \mathbf{c}^{(p)}, \hat{\mathbf{x}}_2^{(p)} - \mathbf{c}^{(p)}, \dots, \hat{\mathbf{x}}_R^{(p)} - \mathbf{c}^{(p)}\} \quad (3)$$

Compute Universal Eigenspace

$$\hat{\mathbf{Q}} \triangleq \mathbf{X}^T \mathbf{X} \quad (4)$$

$$\lambda_i \hat{\mathbf{e}}_i = \hat{\mathbf{Q}} \mathbf{e}_i \quad (5)$$

Utilise PCA Threshold (T_i)

$$\frac{\sum_{i=1}^k \lambda_i}{\sum_{i=1}^N \lambda_i} \geq T_i \quad (6)$$

Theory II

Notation

$$\mathbf{Q} = \mathbf{X} [\hat{\mathbf{e}}_1, \quad \hat{\mathbf{e}}_2, \quad \dots \quad \hat{\mathbf{e}}_k] \quad (7)$$

Similarly, Compute Object Eigenspaces

$$\hat{\mathbf{Q}}^{(p)} \triangleq \mathbf{X}^{(p)T} \mathbf{X}^{(p)} \quad (8)$$

$$\lambda_i^{(p)} \hat{\mathbf{e}}_i^{(p)} = \hat{\mathbf{Q}}^{(p)} \hat{\mathbf{e}}_i^{(p)} \quad (9)$$

Utilise PCA Threshold (T_i)

$$\frac{\sum_{i=1}^{k^{(p)}} \lambda_i^{(p)}}{\sum_{i=1}^N \lambda_i^{(p)}} \geq T_i \quad (10)$$

$$\mathbf{Q}^{(p)} = \mathbf{X}^{(p)} [\hat{\mathbf{e}}_1^{(p)}, \quad \hat{\mathbf{e}}_2^{(p)}, \quad \dots \quad \hat{\mathbf{e}}_{k^{(p)}}^{(p)}] \quad (11)$$

Compute manifolds

$$\mathbf{g}_i^{(p)} = \mathbf{Q}^T (\mathbf{x}_i^{(p)} - \mathbf{c}) \quad (12)$$

Theory III

Notation

$$\mathbf{f}_i^{(p)} = \mathbf{Q}^{(p)T} (\mathbf{x}_i^{(p)} - \mathbf{c}^{(p)}) \quad (13)$$

Interpolate manifolds

Universal Manifolds

$$\mathbf{g}^{(p)}(\theta) \quad (14)$$

Object-specific Manifolds

$$\mathbf{f}^{(p)}(\theta) \quad (15)$$

Closest universal manifold from projection of given image \mathbf{y}

$$\mathbf{z} = \mathbf{Q}^T (\mathbf{y} - \mathbf{c}) \quad (16)$$

$$d_1^{(p)} = \min_{\theta} \|\mathbf{z} - \mathbf{g}^p(\theta)\| \quad (17)$$

Point on object manifold closest from project of given image \mathbf{y}

$$\mathbf{z}^{(p)} = \mathbf{Q}^{(p)T} (\mathbf{y} - \mathbf{c}^{(p)}) \quad (18)$$

$$d_2^{(p)} = \min_{\theta} \|\mathbf{z}^{(p)} - \mathbf{f}^p(\theta)\| \quad (19)$$

References



Hiroshi Murase and Shree K. Nayar.

Visual learning and recognition of 3-d objects from appearance.

International Journal of Computer Vision, 14:5–24, 2005.

URL: <https://api.semanticscholar.org/CorpusID:6611218>.