

Breakpoints for farm field runoff

Wesley Brooks

The following is the R code used to produce a piecewise regression model:

```
> piecewise <- function(th, x, y) { #
+   X <- cbind( ifelse(x>=th, 1, 0), x, pmax(0, x-th) )
+   fit = lsfit(X, y) #actually fit the model
+
+   #Counts how many observations lie above and below the breakpoint
+   upper = as.logical( ifelse(x-th>=0, 1, 0) )
+   n_upper = sum(upper)
+   n_lower = dim(X)[1] - n_upper
+
+   #Sum of squared residuals on either side of the breakpoint
+   ssr_upper = sum( fit$resid[upper]**2 )
+   ssr_lower = sum( fit$resid[!upper]**2 )
+
+   #Return the residual standard error:
+   return( n_lower*sqrt(ssr_lower/(n_lower-2))
+         + n_upper*sqrt(ssr_upper/(n_upper-2)) ) }
```

We identify the best breakpoint by using R's optimize function to minimize the residual standard error:

```
> soil_moisture_limits = c(33, 43) #set the limits
> optimize(piecewise, soil_moisture_limits, x=data$sm, y=data$rc)$minimum
```

First, let us do the soil moisture breakpoint analysis. The breakpoints at each farm

individually, and for all farms in aggregate are:

Kp: 35

P: 35

Pf: 36

R: 36

S: 40

aggregate: 35

Now get the I30 breakpoints:

Kp: 0.5

P: 0.8

Pf: 0.7

R: 0.6

S: 0.9

aggregate: 0.6

When we put the events in bins based on their antecedent soil moisture (SM: high, medium, and low), the following are the I30 breakpoints (inches of rain per hour):

-Inf <= SM < 30: 1.7

30 <= SM < 35: 0.5

35 <= SM < Inf: 0.8

When we put the events in bins based on their antecedent soil moisture (SM: high, medium, and low), the following are the rain depth breakpoints (inches of rain):

-Inf <= SM < 30: 1.3

30 <= SM < 35: 0.94

35 <= SM < Inf: 0.45




Figure 1: caption.




Figure 2: caption.




Figure 3: caption.