

# Bayesian surprise as a tool for monitoring sensor networks

Wesley Brooks

USGS Wisconsin Water Science Center  
and University of Wisconsin-Madison Department of Statistics  
Madison, WI

[wrbrooks@usgs.gov](mailto:wrbrooks@usgs.gov)

May 3, 2012



# Table of Contents

- 1 Overview
- 2 Methodological Background
  - Surprise theory
  - Bayesian statistics
- 3 Examples
  - Simulations
  - Field data
- 4 Future directions

# Table of Contents

## 1 Overview

## 2 Methodological Background

- Surprise theory
- Bayesian statistics

## 3 Examples

- Simulations
- Field data

## 4 Future directions

# Intro

- Real-time monitoring: big data

# Intro

- Real-time monitoring: big data
- Lots of new instruments are going in
  - ▶ That hardware needs to be maintained

# Intro

- Real-time monitoring: big data
- Lots of new instruments are going in
  - ▶ That hardware needs to be maintained
- Each instrument is producing more data
  - ▶ Let's use that data to tell us when there's been a change that needs attention

# Presenting Bayesian Surprise

- Automated
- Data-driven
- Detects unusual events in real-time data.

# Presenting Bayesian Surprise

- Automated
- Data-driven
- Detects unusual events in real-time data.
- Basic idea: learn a model for the historical data and compare it to the newest incoming data.



# Table of Contents


- 1 Overview
- 2 Methodological Background
  - Surprise theory
  - Bayesian statistics
- 3 Examples
  - Simulations
  - Field data
- 4 Future directions

# Table of Contents

- 1 Overview
- 2 Methodological Background
  - Surprise theory
  - Bayesian statistics
- 3 Examples
  - Simulations
  - Field data
- 4 Future directions

# Surprise theory

- Original idea of “Bayesian surprise” (2004):
  - ▶ Laurent Itti - University of Southern California Neuroscientist
  - ▶ Pierre Baldi - University of California-Irvine Computer Scientist
- Used to mimic human response to video images:



# Surprise theory

- Adaptation to sensors:
  - ▶ Owen Langman's M.S. thesis - UW Limnology, 2009
- Uses identical surprise model (Gamma-Poisson) as Itti and Baldi

# Surprise theory

- Problems with original theory:
  - ▶ Ad-hoc “memory” parameter must be tuned manually
  - ▶ Cannot track mean and variance simultaneously
  - ▶ Technically only applicable to discrete data (e.g. counts)

# Table of Contents




- 1 Overview
- 2 Methodological Background
  - Surprise theory
  - Bayesian statistics
- 3 Examples
  - Simulations
  - Field data
- 4 Future directions

# Bayesian statistics

Bayesian statistics views a probability distribution as representing our degree of belief. This idea can be applied both to our data and to the underlying data-generating model.

- Examples of the three distributions used in this work:

- ▶  $X \sim \text{Normal}(\mu = 0, \tau = 1)$
- ▶  $Y \sim \text{Gamma}(\alpha = 2, \beta = 1)$
- ▶  $Z \sim t_{\nu=4}(\mu = 0, \sigma^2 = 1)$




# Hierarchical models

- A hierarchical model has more than one random element
- Randomness at one level feeds into the next




# Hierarchical models

- A hierarchical model has more than one random element
- Randomness at one level feeds into the next



# Hierarchical models




# Hierarchical models

$$\iint [Y|m,p,\mu,\alpha,\beta] \times [m|\mu,p] \times [p|\alpha,\beta] \, dm \, dp = [Y|\mu,\alpha,\beta]$$


Result is the predictive distribution for new data:

$$Y|\mu,\alpha,\beta \sim t(\mu,\alpha,\beta)$$




Use the data to estimate new values of  $\mu, \alpha, \beta$

Compare the **estimated** distribution to the **predictive** distribution  
(Two different t-distributions):




# Calculate the surprise



# Iterate the process

Use moving windows to iterate the process as new data comes in:



# Table of Contents


- 1 Overview
- 2 Methodological Background
  - Surprise theory
  - Bayesian statistics
- 3 Examples
  - Simulations
  - Field data
- 4 Future directions

# Table of Contents

- 1 Overview
- 2 Methodological Background
  - Surprise theory
  - Bayesian statistics
- 3 Examples
  - Simulations
  - Field data
- 4 Future directions

# Simulated surprise



Surprise generated by a sudden change in mean:





# Simulated surprise

Surprise generated by a sudden change in variance:





# Table of Contents

- 1 Overview
- 2 Methodological Background
  - Surprise theory
  - Bayesian statistics
- 3 Examples
  - Simulations
  - Field data
- 4 Future directions


# Field data

Pheasant Branch (Middleton, WI) water temp (Dec 2011 - Jan 2012):



# Field data

Trout Lake LTER site (northern WI) CDOM (Nov. 2009):




# Table of Contents

- 1 Overview
- 2 Methodological Background
  - Surprise theory
  - Bayesian statistics
- 3 Examples
  - Simulations
  - Field data
- 4 Future directions

# Future directions

Add dependence on other variables (regression):



# Conclusion

- Surprise is a data-driven tool that can help to quickly detect problems with real-time sensors and therefore improve the up-time of a monitoring effort.