In-Flight Reconfiguration of a Cable-Suspended Ring Carried by a Team of Quadrotors

Wesley Donald, Mitchell Torok, and Mohammad Deghat

***Abstract*—Teams of quadrotors carrying a cable-suspended payload usually keep a fixed composition throughout a flight. We show that model predictive control lets such a team drop and re-add carriers in flight. A centralised planner solves an optimal control problem over a 0.86 kg ring and every carrier's cable, and per-carrier trackers follow its plan on unmodified Betaflight quadrotors. Because the attachment geometry is a runtime parameter, a change of team is a switch to a pre-built problem of the new size, warm-started from the measured state. Three reconfigurations are handled: an unannounced release, detected when the leaver's rod reads longer than itself; the rejoin of a departed carrier, welded within 1.5 cm of its own plate and blended into the load over 10 s with the path held; and the attach of a newcomer flown by another controller, admitted only after magnet contact and a motion-capture proof of co-motion. It is validated in a digital twin built from the rig's thrust map and geometry, and on a motion-capture rig, where an unannounced release is detected in 0.42 s and the ring's tilt peaks at 6.5°, back within its band 1.8 s later. In the twin a team of eight carriers drops to four and rejoins all four, and on a 0.4 m/s line our planner's path error is about half that of the dissipative network of Quan et al., whose point-load model leaves a rim-hung ring's yaw undamped.**

***Index Terms*—Aerial systems: mechanics and control, multi-robot systems, cooperative manipulation, model predictive control, cable-suspended payload.**

I. Introduction

Several quadrotors sharing a payload on cables can lift what none of them could carry alone, and spread the load so that each flies with margin [1], [2]. Such a team is almost always treated as fixed: the carriers are attached on the ground, take off together and land together. A team that could change in the air would be more useful and more robust. A carrier with a low battery or a fault could leave and come back; a fresh carrier could join to take up a heavier load or relieve another; and a carrier that is lost without warning, a released magnet or a failed motor, need not bring the payload down with it. This letter asks what a controller needs to let a team carrying a cable-suspended payload lose and gain carriers in flight.

Cooperative cable transport. The statics of a rigid payload hung from several cables, and the internal forces the team may choose freely, are well understood [3]–[5]. Controllers range from decentralised schemes that need no communication between carriers [4], [6], [7] through geometric and leader–follower designs [8], [9] to the passivity-based dissipative network of Quan et al. [10]. Model predictive control (MPC) suits the problem because cable tensions are bounded and the payload's motion couples every carrier: nonlinear MPC of the full payload pose [11], [12], kinodynamic planning for the team [13], and distributed formulations [14], [15] all fly a team of a fixed size.

Reconfiguration and attach. Plug-and-play MPC adds and removes subsystems from a distributed controller [16]–[19], but for networks of loosely coupled plants, not for carriers that share one payload. Modular aerial robots dock and undock in flight [20]–[22], and magnetic grippers let a multirotor pick up and release objects [23], [24]. Fault-tolerant cooperative transport keeps a payload up after a carrier fails [25], [26]. We know of no work in which a team carrying a cable-suspended payload both loses carriers without warning and admits carriers that join in the air, nor of one flown on hardware.

The working hypothesis of this letter is that a centralised optimal control problem suits a change of team because the planner solves for the force distribution of the team it actually has in the first tick after the event, instead of leaving the survivors to find it from the motion that follows. The contributions are:

- a cooperative MPC for a cable-suspended ring whose attachment geometry is a runtime parameter, so that a change of team is a switch to a pre-built problem of the new size, warm-started from the measured state (Section III);
- detection of an unannounced release from motion capture alone, a drop rule from the support margin of the survivors, and the rejoin of a departed carrier to its own plate in flight (Sections III-B and III-C);
- the attach of a newcomer flown by another team's controller, admitted only on a motion-capture proof that its magnet moves with the ring;
- validation in a digital twin built from the rig's identified thrust map and geometry and on a motion-capture rig with unmodified Betaflight quadrotors, with a scalability study and a comparison against our port of Quan et al.'s method [10] (Sections IV-A–IV-C).

II. System

Payload. The payload is a ring of mass $m_L = 0.86\,\mathrm{kg}$ carrying twelve magnet plates every 30° at radius $r = 0.225\,\mathrm{m}$ (Fig. 1). Plates are numbered clockwise from the ring's $+x$ axis seen from above. A carrier hangs from a plate on a link of length l_i, 1 m in the results here, whose lower end holds an electromagnet switched over the carrier's radio channel; the links fly at about 60° from horizontal. The magnet catches

The authors are with the School of Mechanical and Manufacturing Engineering, UNSW Sydney, Australia [affiliations and e-mail addresses to confirm].

only on contact with its plate, so a release needs no mechanism beyond switching it off.

Rig. The carriers are 0.55 kg quadrotors on unmodified Betaflight flight controllers, whose inner rate loop is kept; our trackers send a collective throttle and three body-rate commands over the radio link. A motion-capture system measures the pose of every quadrotor, the ring and the links' lower ends in a $6 \times 6 \times 4$ m cage, and a position limit of ± 1.75 m lands the fleet if any quadrotor leaves it. Thrust is affine in throttle, with an offset that grows with the carried mass and falls with battery voltage; the map was identified on the rig from free hovers with hung masses over the battery's range.

Digital twin. A Gazebo [27] model under ROS 2 [28] reproduces the rig: the same masses, geometry, identified thrust map and rate-loop model, the motion-capture velocity filter, and the same planner, trackers and safety logic, launched unchanged against simulated topics. The twin models every link as rigid, whereas the rig's tethers can go slack; slack-cable effects and the rig's unmodelled aerodynamics are therefore its honest limit, and the rig flights are the check on it.

III. Method

The controller is a two-level cascade. A centralised planner plans the motion of the ring and of every link over a horizon; a tracking MPC on each carrier follows that carrier's share of the plan. A change of team is handled inside the planner, by changing the problem it solves.

A. Cooperative planner and trackers

The planner's model is the ring as a rigid body, pose $(\mathbf{p}_L, \mathbf{q}_L)$ and twist $(\mathbf{v}_L, \boldsymbol{\omega}_L)$, with each of the N carriers reduced to a link of length l_i attached at the plate point $\boldsymbol{\rho}_i$ in the ring frame, with unit direction $\mathbf{q}_i$ and tension λ_i. The carrier positions follow kinematically, $\mathbf{p}_i = \mathbf{p}_L + R(\mathbf{q}_L)\boldsymbol{\rho}_i - l_i\mathbf{q}_i$, and the thrust each must produce follows from its link's acceleration and tension. At every tick the planner solves

$$\begin{aligned} \min_{\mathbf{x}_{0:N_h},\, \mathbf{u}_{0:N_h-1}} \; & \sum_{k=0}^{N_h-1} \|\mathbf{y}_k - \mathbf{y}_k^{\mathrm{ref}}\|_W^2 + \|\mathbf{y}_{N_h} - \mathbf{y}_{N_h}^{\mathrm{ref}}\|_{W_{N_h}}^2 \\ \text{s.t. } & \mathbf{x}_{k+1} = \mathbf{F}(\mathbf{x}_k, \mathbf{u}_k; \{\boldsymbol{\rho}_i, l_i\}, \mathbf{d}), \quad C_0\mathbf{x}_0 = C_0\hat{\mathbf{x}}(t), \\ & \lambda_{\min} \le \lambda_{i,k} \le \lambda_{\max}, \quad f_{\min} \le \|\mathbf{f}_{i,k}\| \le f_{\max}, \end{aligned} \tag{1}$$

where the output $\mathbf{y}$ stacks the ring's position, velocity, attitude error and rate, the link directions, tensions and rates, and the inputs; $\mathbf{f}_{i,k}$ is carrier i's planned thrust, its bounds softened with slack. The horizon has $N_h = 20$ nodes over 2 s, so a node is the 100 ms planner tick. The constraint on node 0 pins only what motion capture measures, the ring's pose and twist and the link directions; the tensions and link rates are left free and warm-started from the previous solution. A lumped force $\mathbf{d}$ on the ring, formed from the integral of its position error in steady flight, removes steady offsets through the model [29], [30]. The references follow from the ring's trajectory by flatness, with the nominal formation tilted along the effective gravity and the tensions scaled with it.

Problem (1) is solved with acados [31] in a real-time iteration scheme [32]: one Gauss–Newton SQP iteration per tick, warm-started, with HPIPM [33] solving the QP. On the rig no new iteration starts after 60 ms of the tick, and a plan not ready by then is replaced by the previous one shifted by a node.

Each carrier's tracker is an MPC on a 17-state model in which the four stick commands are states and their rates the inputs, with the flight controller's rate loop modelled as first order and the identified affine thrust map. It solves every 20 ms over the same 2 s horizon, following the planner's position, velocity and thrust direction. The link's pull enters its model as a known parameter along the horizon: the planned pull, shifted by the difference between the pull measured from motion capture and the planned one at the first node, so that the tracker anticipates the link's force rather than reacting to it.

B. Reconfiguration: release and drop

Two properties of (1) make an in-flight change of team possible. The plate points $\boldsymbol{\rho}_i$ and link lengths l_i are runtime parameters, so only the team size fixes the problem's dimensions, and one solver per size, built in advance and primed on the measured state, covers any layout. And the survivors keep their own plates: the nominal tensions come from a moment balance at the actual plate points, so the ring's reference stays level without re-spacing the team.

Detection. A release the planner is told of is a DETACH command, which switches the leaver's magnet off and resizes on the same tick. An unannounced release is detected from the link alone. A rigid link on its plate cannot measure longer than itself, so when the leaver's link, measured by motion capture between the carrier's pivot and its plate point, reads more than 6 cm over its length for two consecutive ticks, the planner removes that carrier. No force sensor and no message from the leaver are needed.

Resize. At the event the planner swaps to the solver for $N-1$ carriers, sets the survivors' plate points and link lengths, and warm-starts it from the measured state with the tensions and link directions free at node 0. The first solve redistributes the load; there is no separate hand-off phase. With three survivors the vertical shares are fixed by statics: each is the ring's weight times the barycentric coordinate of its centre in the survivors' triangle, and a level ring exists only while the centre lies inside the polygon of the plates [3]. For plates on a circle of radius r, with $g_{\max}$ the survivors' largest angular gap, the support margin

$$m = r\cos(g_{\max}/2) \tag{2}$$

is the distance from the centre to the nearest edge. Losing one of four evenly spaced carriers puts the centre on an edge, so the four-carrier layout uses plates 3, 7, 9 and 11, where losing plate 9 leaves an even triangle with a 112 mm margin.

Drop rule. A loss that leaves fewer survivors than the configured minimum (three by default), or a ring tilt above 30°, drops the ring: every magnet is switched off and every carrier lands. Release chains that continue below three carriers fly on while the survivors' largest gap is at most 200°, which




Fig. 1. Payload and rod geometry, to scale. (a) Top view of the 0.86 kg ring with its twelve magnet plates at a radius of 0.225 m, numbered clockwise from the x_L axis seen from above, so that plate k sits $30k$ degrees clockwise from x_L. The four-UAV layout uses plates 3, 7, 9 and 11; when the UAV on plate 9 leaves, the three on plates 3, 7 and 11 form an even triangle (dashed), under which the ring hangs level. (b) Side view of one rod at the planned elevation of 60°: the rod direction $\mathbf{q}_i$ points from the plate to the UAV, and the rod pivots $\boldsymbol{\delta}$ = 4 cm below the UAV's centre. Rig dimensions (0.55 m rods); the twin results use 1 m cables.

keeps a T and an opposite pair. The freed carrier steps out radially, clear of the ring, and lands and disarms alone while the survivors carry on.

C. Rejoin of a departed carrier

A departed carrier can return to its own plate. At its release the planner records its plate point and the link's measured length. *Staging:* the carrier is held on its plate's bearing 0.3 m beyond the formation's reach, the point moving and turning with the planned ring and kept inside the position limit. *Approach:* on the rejoin command, given only while the ring holds its path, the carrier descends at 0.1 m/s so that its link's lower end lands on the plate point of the measured ring, with a feedback loop on the measured end correcting the end's height. *Weld:* the magnet is switched on once the end has stayed within 1.5 cm of its plate point on every sample over 0.3 s (at least eight samples) at under 2 cm/s; the joint must then report attached, or the carrier is let go and backs out to staging. *Fold-in:* the planner grows to $N + 1$ with the plate point and the link re-measured from pivot to plate; the rejoiner is seeded at 0.1 N and every tension is blended to the balanced split over 10 s, with its link feedforward ramped over 1.5 s and the ring's path held throughout, as a dock blends thrust across a switch [21]. Through the blend the rejoiner's height reference is capped at the weld height, so that it cannot lift its plate and tilt the ring before it carries its share, and it counts as absent for the drop rule. LAND or a drop sends every staged or rejoining carrier up, out along its bearing and down alone.

D. Attach of a newcomer

A newcomer is flown by another team's controller down to contact; its magnet catches only there. Our side admits it from motion capture alone, with its magnet tip expressed in the plate's frame. A *contact* is the tip within 24 mm of the plate point and close to the plate's face, nearly still for 0.3 s. A contact is only a candidate, since a tip resting on a plate and a caught magnet look alike, so the catch is *confirmed* by co-motion: after the newcomer's small lift, the tip has stayed within 6 mm of its contact point while the plate moved with it, on a taut tether. Only then do our trackers take the newcomer over and the planner grows to $N + 1$ with the recorded plate point, the newcomer seeded at 0.1 N and blended as in Section III-C. A newcomer not confirmed in time is taken back: our tracker latches onto its measured state, lifts it clear and lands it alone.

IV. Results

We test our planner on the rig and in its simulated twin. The rig carries the 0.86 kg ring with magnet plates every 30° on its rim; the twin models the same ring, the same quadrotors and the rig's thrust map and motion-capture filter, but its cable links are rigid. Unless stated otherwise the twin flies 1 m cables with the ring at 1.0 m. Bars were written before each set of runs, and a run is scored against the bars of its set only.

A. Release and rejoin

a) An unannounced release on the rig: Four carriers hover the ring on the rig, and one of them lets go of its plate without telling the planner. Fig. 2 shows the reaction of Section III-B. The planner sees the released cable stretch past its threshold 0.42 s after the release and resizes its problem to three carriers 0.09 s later, each survivor then planned at about 3.2–3.3 N. The ring's tilt peaks at 6.5° and is back in its band 1.8 s after the release (Table I). Over all three rig releases, detection took 0.33–0.42 s and the ring was back in band within 1.8–3.8 s; the slowest, with the largest tilt, left a 150° gap between survivors. An announced detach, by contrast, resizes at the command but tilted the ring further, to 15.4°. In the twin, the same release on 1 m cables resized after 0.37 s with a 5.9° tilt peak.




Fig. 2. An unannounced release on the rig: one of four carriers (red) lets go of its plate in hover. The planner detects the loose cable from its stretch, resizes to the three survivors (blue), and the ring's tilt (black) returns to its band.

TABLE I
REACTION TO A LOST CARRIER, FOUR CARRIERS IN HOVER. TIMES FROM THE RELEASE (OR THE COMMAND). RIG: 0.55 M RODS; TWIN: 1 M CABLES.

Case	Detected (s)	Resized (s)	Tilt peak (°)	Back in band (s)
Rig, release (Fig. 2)	0.42	0.51	6.5	1.8
Rig, all three releases	0.33–0.42	[to measure]	6.5–17.8	1.8–3.8
Rig, announced detach	–	0	15.4	1.95
Twin, release	–	0.37	5.9	3.4

b) A departed carrier rejoins (twin): A released carrier is not landed: it holds a staging point beyond its own plate and, on the operator's command, flies back, is re-attached and is folded into the team (Section III-C). This is a twin result only, since the twin's joint welds the cable wherever its end lies, while the rig's magnet catches only on contact. A rejoin is scored in stages, each against a bar frozen before the runs: the cable's end on its plate within 30 s; the joint attached within 0.5 s of that; then the fold-in, with the ring's tilt at most 5° from the weld to 15 s after it, the end within 2 cm of its plate through the 10 s blend, and the rejoiner's planned pull at the blend's end within 10 % of its share. Table II gives the results onto a square (four carriers back from three) and onto a T (three back from an opposite pair); Fig. 3 shows one rejoin onto the T.

Every rejoin welded within 1.5 cm of its plate point, and the fold-in tilted the ring by 1.3–3.4°. With a steady torque leaning the T's pair about 3°, the rejoin passed 3 of 4 runs: in one run leaning toward the rejoin plate the ring tipped to 5.28° for 0.19 s, missing the bar by 0.28°. There the rejoiner's height reference, held at or below its weld height through the blend to stop its rigid link lifting the T's free side, dipped 1.1 cm at the fold-in. The hold patches a twin artefact, a rigid link, which the rig's slack tethers do not share. Two neighbouring checks also passed: a LAND during the rejoin's descent sends the rejoiner up, out and down alone, 1.245 m from the ring's centre (bar 1.2 m), and a carrier staged through a figure-eight lap of the T stays inside the position limit, with its attach command refused while the path moves.

TABLE II
A DEPARTED CARRIER REJOINS ITS OWN PLATE (TWIN, HOVER, 1 M CABLES), FINAL CODE TREE. BARS, FROZEN BEFORE THE RUNS, IN BRACKETS. LEANING: A STEADY TORQUE LEANS THE T'S PAIR ABOUT 3°. RANGES OVER n RUNS.

Rejoin	n	On plate after (s) [30]	Weld after (s) [0.5]	Fold-in tilt (°) [5]	End from plate (cm) [2]
Square	4	23.9–24.9	0.029–0.036	1.27–1.55	1.3–1.6
T	3	16.6–17.7	0.012–0.021	1.45–3.02	1.3–1.5
T, leaning toward	2	15.6–16.5	0.015–0.018	3.12–**5.28**	1.3–1.5
T, leaning away	2	17.7–18.6	0.015–0.018	2.91–3.37	1.4–1.5




Fig. 3. A carrier released from the T flies back to its own plate in the twin, re-welds 17.8 s after the rejoin command and folds back in. (a) The rejoiner's path, side view, with its cable at the weld and folded in; (b) the ring's tilt, peaking at 1.45° in the fold-in, against the 5° bar.

c) Eight to four and back (twin): Release and rejoin compose into a chain. Eight carriers at 45° on 1 m cables lift a 0.9 kg ring of radius 0.5 m from the floor; every other carrier is released unannounced, in opposite pairs, down to a square of four, and the four freed carriers then rejoin one at a time back to eight (Fig. 4). Over the eight events no drop or abort fired, each rejoin welded 15.1–19.4 s after its start with its cable's end within 1.3–1.6 cm of the plate through its blend, and the ring's tilt peaked at 3.35°. Back at eight, the ring's position error was 6.3 mm (rms). The world runs slower than real time here, so this run is about the plan and the physics, not about timing; it flew one solver iteration per tick in a single exploratory run, and the claim runs at five iterations are pending (Section IV-B).

d) A newcomer attaches on the rig: [The rig attach of a newcomer on 1 m cables (three carriers to four with the basket): flies 29 Oct.]

B. Scalability

Our planner solves the OCP (1) with a fixed number of sequential-quadratic-programming (SQP) iterations per 100 ms tick, warm-started from the previous plan. Fewer iterations shorten the tick but leave the plan short of convergence. We measure what that costs against the fleet size in two ways. In closed loop, the four-carrier twin flew a hover, the figure-eight at 0.2 m/s and an unannounced release, each from a floor start, at one iteration and at five. Offline, each plan at one and two iterations was compared with the plan converged from the same iterate. The bars of both checks were fixed before the runs: the dynamics residual of the plan, the error of the references the trackers fly at the next node and the fifth, the




Fig. 4. Eight carriers take the 0.9 kg, 0.5 m ring through four unannounced releases down to four and four rejoins back to eight (twin, not real time). (a) The team size the planner flies; (b) the ring's tilt, peaking at 3.35°.

TABLE III
PLAN QUALITY AT EIGHT CARRIERS AGAINST SQP ITERATIONS PER TICK: THE FIGURE-EIGHT AT 0.2 M/S, EACH WARM START 1 CM AND 10 CM/S OFF THE PLAN, COMPARED WITH THE PLAN CONVERGED FROM THE SAME ITERATE; 95TH PERCENTILES OVER 200 TICKS. BOLD: OVER THE BAR. NO SOLVE FAILED.

Measure	Bar	5	2	1
Cost ratio, median / 95th pct.	1.10 / 1.50	1.000 / 1.001	1.003 / 1.010	**miss**[a]
Dynamics residual	10^{-3}	3.2×10^{-7}	8.8×10^{-5}	**9.3×10^{-3}**
Reference, node 1 / 5 (mm)	5 / 10	0.9 / 0.9	3.2 / 5.1	**7.3 / 14.5**
Feed-forward (m/s^2)	0.3	0.12	**0.316**	**0.60**

[a] 170 of 200 ticks over the residual bar, each counted as a miss.

error of the thrust feed-forward, and the cost's ratio to the converged plan's.

In closed loop at four carriers, one iteration a tick flew as well as five in every cell. The ring's path error and tilt stayed inside the bars set from the five-iteration runs through the lift, the path and the release, and no run dropped, aborted or failed a solve. The plans were not converged, however: their dynamics residual peaked at the release, under the closed loop's limit but over the offline bar.

Offline, the answer depends on the fleet. Replayed tick by tick, nine recorded flights with two to four carriers, the rig's among them, converge by every bar at two iterations; at one iteration every rig flight breaks the residual bar. At eight carriers on the figure-eight, with each warm start moved off the plan by about the rig's ring error, one iteration misses every bar, two miss only the feed-forward bar (0.316 against 0.3 m/s^2), and five pass all of them (Table III, Fig. 5). The iteration count must therefore grow with the fleet: two suffice up to four carriers, while eight need five.

What this means for real time is set by the slowest tick. On the rig laptop, a bench calibrated against the rig's own flights gives the largest team our planner flies within the 100 ms period at five iterations as [$N_{\max}$ on the rig laptop at 5 iterations, from the bench with the speed-ups and the pivot]. At eight carriers the plan must be read at five iterations, which the rig laptop cannot run in real time; the eight-carrier results are therefore the twin's, with its clock slowed, and say nothing about real time. In the twin, eight carriers lifted a larger ring from the floor and carried it through four unannounced releases, in opposite pairs, to a square of four and back to eight by rejoins (Fig. 4), with the ring's tilt peaking at a few degrees and no drop. [the eight-carrier claim runs at 5 iterations, hover and $8 \to 4 \to 8$, two each: ring position error and tilt peak with the team back at eight, scored from 2 s after the last rejoin's blend ends; release tilt peak; achieved real-time factor and late ticks].




Fig. 5. Plan quality at eight carriers against SQP iterations per tick, relative to the converged plan: the dynamics residual, the reference error at the next node and the thrust feed-forward error (95th percentiles), with the bars fixed before the runs. One iteration misses every bar, two miss only the feed-forward bar, five pass.

C. Comparison with a dissipative network

A virtual spring–damper network [10] is the natural comparison for a team that changes in flight: a member leaving or joining needs no new solver. We ported Quan et al.'s dissipative network to our system and flew it against our planner in the twin. Four carriers sit on plates 0, 3, 6 and 9, with 1 m cables and the ring at 1.0 m. The cases are a hover and a 0.9 m line out and back. Both arms are our planner up to the hand-over (creep, lift and a 5 s hover). After it, our arm keeps the planner of Sec. III and its trackers. The network instead drives the trackers' velocity loop with no integral per UAV. The comparison is therefore between the two methods as flown after the lift, not of the network alone. The port turns the formation with the ring's measured yaw, because our ring has a yaw and the paper's payload does not. Every run is exploratory, one or two per cell (Table IV).

As ported, the network capsizes in yaw. At its first gains the ring's yaw swung with a growing amplitude, in hover and on the line at 0.2 m/s, until the ring tipped past the abort limit (Fig. 7). A bounded offline retune followed, set before the comparison flew: a grid over the damping and the velocity loop's position gain, then a descent over eight gains, ranked on safety guards and then on the line's error at 0.4 m/s. At the search's best gains the network held the ring in every run, but not its yaw: the yaw swung through 22–51° in hover and about 14° on the 0.4 m/s line. On that line its error was 99–105 mm against our planner's 46 mm, about twice as large. The network also ran about 1.1 s behind the schedule and turned short of each end (Fig. 6). Our planner ran 0.03 s late and its ring's yaw moved 0.2°. [our planner's hover and 0.2 m/s line cells, $n = 2$ each].

Why the yaw is lost. The paper models the load as a point, with every cable attached at its centre of mass [10]. Our ring hangs from plates on its rim, at 0.225 m from the axis. The cables then torque the ring, which gives it a yaw mode that the method has no term for, and the yaw-following formation of our port feeds that mode. To test this we moved every cable's lower end to a hub at the ring's centre, which is the paper's own geometry, and changed nothing else. In one hover each, the network at its best gains held the ring's yaw within 0.1°,

TABLE IV

OUR PLANNER AGAINST OUR PORT OF THE DISSIPATIVE NETWORK [10] IN THE TWIN, FOUR CARRIERS ON 1 M CABLES, RIM PLATES UNLESS MARKED HUB; 1–2 EXPLORATORY RUNS PER CELL. ERROR: IN HOVER THE RING'S 3-D ERROR; ON A LINE THE CLOCK-FREE ERROR PLUS THE SHORTFALL AT THE LINE'S ENDS. LAG: BEHIND THE SCHEDULE. YAW: THE RING'S LARGEST CHANGE OF YAW AFTER THE HAND-OVER. [a] CAPSIZED IN YAW; THE RUN ABORTED AND ITS ERROR IS NOT SCORED.

Arm	Case	Error (mm)	Lag (s)	Yaw (°)
Our planner	hover	[–]	–	[–]
	line 0.2 m/s	[–]	[–]	[–]
	line 0.4 m/s	46.2	+0.03	0.2
Network, as ported	hover	–[a]	–	125
	line 0.2 m/s	–[a]	–	474
Network, retuned	hover	16.1–18.7	–	22–51
	line 0.2 m/s	41.5–42.1	+1.25	29–48
	line 0.4 m/s	99.3–104.5	+1.12–1.13	14
Our planner, hub	hover	1.4	–	0.0
Network, retuned, hub	hover	11.8	–	0.1




Fig. 6. The 0.4 m/s line in the twin: the ring's position along the line against the schedule, our planner and the retuned network. The network runs about 1.1 s late and turns short of each end.

against 22–51° on the rim; our planner held it within 0.0°. [the full hub test, both arms in hover and on the lines, $n = 2$; and the paper's own form of the damping and feed-forward in the twin].

The result is about porting a point-load method to a rigid ring hung from its rim, not a verdict on Quan et al.'s method as published. Its formation, its damping and its decentralised structure are untouched by it. What the rim attachment adds is a rotational state that a team carrying a rigid ring must regulate; our planner held it on both geometries.

V. DISCUSSION

a) Rigid links in the twin, slack tethers on the rig: The twin models every cable as a rigid link, which can push as well as pull and welds wherever its end lies. This flatters the rejoin and also creates its own failure: on a T, the rejoiner's rigid link set the ring's pitch, so a rising height reference lifted the ring's free side, and the height hold that cured it is a patch for the twin's links. On the rig the tethers go slack, so that lift cannot arise, but the attach is harder: the magnet catches only on contact, which is why the rig's attach is confirmed from motion capture before the newcomer is folded in. The rig's release reaction, by contrast, needs no such caveat: it was measured on the rig, and the twin's release on longer cables agreed in resize time and tilt.




Fig. 7. The ring's yaw after the hand-over in hover: the network as ported (it capsizes and the run aborts), the retuned network (the yaw swings but the ring is held), and our planner.

b) Timing: Every reconfiguration in Section IV is paced by detection and blending rather than by the solver: a lost carrier is seen from its cable's stretch in 0.33–0.42 s and the problem is resized within about 0.1 s more, and a rejoin's fold-in is blended over 10 s. The solver sets the size of the team instead. At four carriers one SQP iteration per tick flies as well as five in the twin's closed loop, but its plans are not converged on the rig's flights, and at eight carriers only five iterations pass every bar (Section IV-B). The eight-carrier chain ran slower than real time, so it shows that the plan and the physics compose, not that the rig's laptop can fly it.

c) The rim geometry: The comparison with Quan et al. [10] turned on the attachment geometry rather than on the method's code. With every cable at the ring's centre, the network held the ring's yaw to 0.1°; with the cables on the rim, as any payload with discrete attachment plates has them, the cables torque the ring in yaw and the network, which has no yaw term, lets it swing (Section IV-C). A planner that models each cable's attachment point, as ours does, holds the yaw because the torque is in its model. For reconfiguration this matters doubly: a release or a rejoin changes which plates carry the ring and so changes that torque.

d) Next on the rig: The next rig flights test the attach of a newcomer on 1 m cables, three carriers to four with a basket, with the attach confirmed by motion capture before the fold-in; the four-carrier hover and paths on 1 m cables; and the planner's tick in flight with the speed-ups, which sets the real-time limit. The rejoin of a departed carrier, which in the twin depends on the joint's weld, waits for a rig attach that has been shown repeatable.

VI. CONCLUSION

We presented a planner that lets a team of quadrotors carry a cable-suspended ring through changes of its own membership in flight. On the rig, an unannounced release of one of four carriers was detected in 0.42 s, the team was resized 0.09 s later, and the ring tilted at most 6.5° before returning to its band in 1.8 s. In the twin, a departed carrier flew back to its own plate, welded within 1.5 cm and was folded in with the ring tilting 1.3–3.4°, and eight carriers took a larger ring down to four and back with a tilt peak of 3.35°. Two SQP iterations per tick converge for every fleet of up to four. Against a port of Quan et al.'s network method, our planner held the ring's

yaw where the network, lacking a yaw term for rim-attached cables, did not. The rig attach of a newcomer on 1 m cables is the next step [result from 29 Oct].

REFERENCES

[1] A. Ollero, M. Tognon, A. Suarez, D. Lee, and A. Franchi, "Past, Present, and Future of Aerial Robotic Manipulators," vol. 38, no. 1, pp. 626–645. [Online]. Available: https://ieeexplore.ieee.org/document/9462539/

[2] J. Estevez, G. Garate, J. M. Lopez-Guede, and M. Larrea, "Review of Aerial Transportation of Suspended-Cable Payloads with Quadrotors," vol. 8, no. 2, p. 35. [Online]. Available: https://www.mdpi.com/2504-446X/8/2/35

[3] N. Michael, J. Fink, and V. Kumar, "Cooperative manipulation and transportation with aerial robots," *Autonomous Robots*, vol. 30, no. 1, pp. 73–86, 2011.

[4] M. Tognon, C. Gabellieri, L. Pallottino, and A. Franchi, "Aerial co-manipulation with cables: The role of internal force for equilibria, stability, and passivity," *IEEE Robotics and Automation Letters*, vol. 3, no. 3, pp. 2577–2583, 2018.

[5] C. Gabellieri, M. Tognon, D. Sanalitro, and A. Franchi, "Equilibria, stability, and sensitivity for the aerial suspended beam robotic system subject to parameter uncertainty," *IEEE Transactions on Robotics*, vol. 39, no. 5, pp. 3977–3993, 2023.

[6] ——, "Force-based pose regulation of a cable-suspended load using UAVs with force bias," in *2023 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2023, pp. 6920–6926.

[7] K. Klausen, C. Meissen, T. I. Fossen, M. Arcak, and T. A. Johansen, "Cooperative control for multirotors transporting an unknown suspended load under environmental disturbances," *IEEE Transactions on Control Systems Technology*, vol. 28, no. 2, pp. 653–660, 2020.

[8] T. Lee, "Geometric control of quadrotor UAVs transporting a cable-suspended rigid body," *IEEE Transactions on Control Systems Technology*, vol. 26, no. 1, pp. 255–264, 2018.

[9] G. Loianno and V. Kumar, "Cooperative transportation using small quadrotors using monocular vision and inertial sensing," *IEEE Robotics and Automation Letters*, vol. 3, no. 2, pp. 680–687, 2018.

[10] Q. Quan, J. Xu, R. Liu, Y. Ding, J. Che, and K.-Y. Cai, "Self-organizing aerial swarm robotics for resilient load transportation : A table-mechanics-inspired approach." [Online]. Available: https://arxiv.org/abs/2509.03563

[11] S. Sun and A. Franchi. Nonlinear MPC for Full-Pose Manipulation of a Cable-Suspended Load using Multiple UAVs. [Online]. Available: http://arxiv.org/abs/2301.08545

[12] G. Li and G. Loianno, "Nonlinear Model Predictive Control for Cooperative Transportation and Manipulation of Cable Suspended Payloads with Multiple Quadrotors," in *2023 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 5034–5041. [Online]. Available: https://ieeexplore.ieee.org/document/10341785

[13] K. Wahba, J. Ortiz-Haro, M. Toussaint, and W. Hönig, "Kinodynamic Motion Planning for a Team of Multirotors Transporting a Cable-Suspended Payload in Cluttered Environments," in *2024 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, pp. 12 750–12 757. [Online]. Available: https://ieeexplore.ieee.org/document/10802794

[14] N. de Carli, R. Belletti, E. Buzzurro, A. Testa, and M. Tognon, "Distributed NMPC for Cooperative Aerial Manipulation of Cable-Suspended Loads."

[15] N. De Carli, R. Belletti, E. Buzzurro, A. Testa, G. Notarstefano, and M. Tognon, "Distributed NMPC for cooperative aerial manipulation of cable-suspended loads," vol. 10, no. 10, pp. 10 546–10 553.

[16] S. Riverso, M. Farina, and G. Ferrari-Trecate, "Plug-and-play decentralized model predictive control for linear systems," *IEEE Transactions on Automatic Control*, vol. 58, no. 10, pp. 2608–2614, 2013.

[17] M. N. Zeilinger, Y. Pu, S. Riverso, G. Ferrari-Trecate, and C. N. Jones, "Plug and play distributed model predictive control based on distributed invariance and optimization," in *52nd IEEE Conference on Decision and Control (CDC)*, 2013, pp. 5770–5776.

[18] A. Aboudonia, A. Martinelli, N. Hoischen, and J. Lygeros, "Reconfigurable plug-and-play distributed model predictive control for reference tracking," in *2022 IEEE 61st Conference on Decision and Control (CDC)*, 2022, pp. 1130–1135.

[19] D. Saccani, L. Fagiano, M. N. Zeilinger, and A. Carron, "Model predictive control for multi-agent systems under limited communication and time-varying network topology," in *2023 62nd IEEE Conference on Decision and Control (CDC)*, 2023, pp. 3764–3769.

[20] D. Saldaña, B. Gabrich, G. Li, M. Yim, and V. Kumar, "ModQuad: The flying modular structure that self-assembles in midair," in *2018 IEEE International Conference on Robotics and Automation (ICRA)*, 2018, pp. 691–698.

[21] J. Sugihara, T. Nishio, K. Nagato, M. Nakao, and M. Zhao, "Design, control, and motion strategy of TRADY: Tilted-rotor-equipped aerial robot with autonomous in-flight assembly and disassembly ability," *Advanced Intelligent Systems*, vol. 5, no. 10, 2023.

[22] J. Sugihara, M. Kitagawa, J. Li, Y. Li, T. Nishio, K. Okada, and M. Zhao, "Self-assembling modular aerial robot for versatile aerial tasks," preprint. [Online]. Available: https://arxiv.org/abs/2605.19431

[23] A. Gawel, M. Kamel, T. Novkovic, J. Widauer, D. Schindler, B. Pfyffer von Altishofen, R. Siegwart, and J. Nieto, "Aerial picking and delivery of magnetic objects with MAVs," in *2017 IEEE International Conference on Robotics and Automation (ICRA)*, 2017, pp. 5746–5752.

[24] R. Miyazaki, R. Jiang, H. Paul, K. Ono, and K. Shimonomura, "Airborne docking for multi-rotor aerial manipulations," in *2018 IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2018, pp. 4708–4714.

[25] X. Liang, Z. Su, W. Zhou, G. Meng, and L. Zhu, "Fault-tolerant control for the multi-quadrotors cooperative transportation under suspension failures," *Aerospace Science and Technology*, vol. 119, 2021.

[26] A. A. Farras, A. Santoso, and Y. E. Nugraha, "Fault-Tolerant Control for Multi-Quadcopter with Suspended Payload under Wind Disturbance," vol. 8, no. 2. [Online]. Available: http://jaree.its.ac.id/index.php/jaree/article/view/406

[27] N. Koenig and A. Howard, "Design and use paradigms for Gazebo, an open-source multi-robot simulator," in *Proceedings of the IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*, 2004, pp. 2149–2154.

[28] S. Macenski, T. Foote, B. Gerkey, C. Lalancette, and W. Woodall, "Robot operating system 2: Design, architecture, and uses in the wild," *Science Robotics*, vol. 7, no. 66, p. eabm6074, 2022.

[29] G. Pannocchia and J. B. Rawlings, "Disturbance models for offset-free model-predictive control," *AIChE Journal*, vol. 49, no. 2, pp. 426–437, 2003.

[30] U. Maeder, F. Borrelli, and M. Morari, "Linear offset-free model predictive control," *Automatica*, vol. 45, no. 10, pp. 2214–2222, 2009.

[31] R. Verschueren, G. Frison, D. Kouzoupis, J. Frey, N. van Duijkeren, A. Zanelli, B. Novoselnik, T. Albin, R. Quirynen, and M. Diehl, "acados – a modular open-source framework for fast embedded optimal control," *Mathematical Programming Computation*, vol. 14, pp. 147–183, 2022.

[32] M. Diehl, H. G. Bock, J. P. Schlöder, R. Findeisen, Z. Nagy, and F. Allgöwer, "Real-time optimization and nonlinear model predictive control of processes governed by differential-algebraic equations," *Journal of Process Control*, vol. 12, no. 4, pp. 577–585, 2002.

[33] G. Frison and M. Diehl, "HPIPM: a high-performance quadratic programming framework for model predictive control," *IFAC-PapersOnLine*, vol. 53, no. 2, pp. 6563–6569, 2020.