Cellular Automata

Weston Dransfield

March 21, 2016

Outline

Spacial Structure

- ► Spacial Structure
- ► Local Interactions

- ► Spacial Structure
- ► Local Interactions
- ► Cell State

- ► Spacial Structure
- ► Local Interactions
- ► Cell State
- Cell Transitions


Spacial Structure

► Grid - Like a city

Spacial Structure

- ► Grid Like a city
- Agents Like a home in the city

Spacial Structure



Agents may only interact with a set number of agents around them. This region is called a neighborhood.

Von Neumann neighborhood (most local).

Agents may only interact with a set number of agents around them. This region is called a neighborhood.

- Von Neumann neighborhood (most local).
- Moore neighborhood (less local).


Agents may only interact with a set number of agents around them. This region is called a neighborhood.

- ▶ Von Neumann neighborhood (most local).
- Moore neighborhood (less local).
- ▶ n * n Moore neighborhood for n > 3 (least local).

Agents may only interact with a set number of agents around them. This region is called a neighborhood.

- Von Neumann neighborhood (most local).
- Moore neighborhood (less local).
- ▶ n * n Moore neighborhood for n > 3 (least local).

Locality indicates how many agents a single agent interacts with. High locality indicates more interactions (Think of how a rumor spreads).



papergraph.com @ 3.0 by-nc-sa Pere Millán

Cell State

Cells have a state

Binary

Cell State

Cells have a state

- Binary
- ► Any number of states

CA have discrete chunks of time called rounds. Each round produces the next "generation" of cells.

The next state of a cell is a function of:

▶ It's current state

The next state of a cell is a function of:

- ▶ It's current state
- The state of cells in its neighborhood

The next state of a cell is a function of:

- It's current state
- ▶ The state of cells in its neighborhood

Think of your opinion on a topic changing by being surrounded by people with a different view.

What is the simplest...

► Grid of cells?

What is the simplest...

- ► Grid of cells?
- Useful number of states?

What is the simplest...

- ► Grid of cells?
- Useful number of states?
- ► Neighborhood?

What is the simplest...

- Grid of cells an array
- Useful number of states binary
- ▶ Neighborhood 2 adjacent cells of the agent

How do we describe the state of cell c_t as a function of the neighbors of c_t at time t-1?

► There are $2^3 = 8$ neighborhood combinations for any given neighborhood.

How do we describe the state of cell c_t as a function of the neighbors of c_t at time t-1?

- ► There are $2^3 = 8$ neighborhood combinations for any given neighborhood.
- Simply create an assignment for each combination!

How do we describe the state of cell c_t as a function of the neighbors of c_t at time t-1?

- ► There are $2^3 = 8$ neighborhood combinations for any given neighborhood.
- Simply create an assignment for each combination!
- ➤ This assignment is called a rule set (how many possible rule sets?)

Example Program

2D CA Example - Conway's Game of Life

Conway's Game of Life

Conway's Game of Life Rules

Conway's Game of Life Entities

Conway's Game of Life Decidability

The question - "Given a starting pattern and an ending pattern, will the starting pattern ever reach the ending pattern?"

Conway's Game of Life Decidability

The question - "Given a starting pattern and an ending pattern, will the starting pattern ever reach the ending pattern?"

Undecidable - halting problem

Conway's Game of Life Decidability

The question - "Given a starting pattern and an ending pattern, will the starting pattern ever reach the ending pattern?"

- Undecidable halting problem
- "Indeed, since the game of life includes a pattern that is equivalent to a UTM (universal Turing machine), this "deciding" algorithm, if existed, could have been used to solve the halting problem, by taking the initial pattern as the one corresponding to a UTM+input and the later pattern as the one corresponding to a halting state of the machine with an empty tape (as one can modify the Turing machine to always erase the tape before halting). However the halting problem is provably undecidable and so such an algorithm does not exist" (Wikipedia).

Demo

Summary

Sources