Completeness: 3COLOR

Weston Dransfield


March 16, 2016

Outline


Description

 $3COLOR = \{\langle G \rangle \mid \text{the nodes of G can be colored with three colors such that no two adjacent nodes are the same color }$

Example



Example



The Problem

Is a given graph G a member of 3COLOR?

The Problem

Is a given graph G a member of 3COLOR?

▶ This is tough to decide, but easy to verify!

$$V = "On input \langle G, c \rangle$$
,

1. Check that c includes 3 colors.

$$V =$$
"On input $\langle G, c \rangle$,

- 1. Check that c includes 3 colors.
- 2. Color each node of G as specified by c.

```
V = "On input \langle G, c \rangle,
```

- 1. Check that c includes 3 colors.
- 2. Color each node of G as specified by c.
- 3. For each node, check that each adjacent node is not the same color.

```
V = "On input \langle G, c \rangle,
```

- 1. Check that c includes 3 colors.
- 2. Color each node of G as specified by c.
- 3. For each node, check that each adjacent node is not the same color.
- 4. If all checks pass accept, otherwise reject."

- V = "On input $\langle G, c \rangle$,
 - 1. Check that c includes 3 colors.
 - 2. Color each node of G as specified by c.
 - 3. For each node, check that each adjacent node is not the same color.
 - 4. If all checks pass accept, otherwise reject."
 - ▶ Step 3 has largest time complexity of $O(n^2)$. 3COLOR is in NP because it can be verified in polynomial time.

Construct a transformation T from 3SAT to 3COLOR.

Construct a transformation T from 3SAT to 3COLOR.

1. Establish Truthiness


Construct a transformation T from 3SAT to 3COLOR.

- 1. Establish Truthiness
- 2. Force variables to be true or false


Construct a transformation T from 3SAT to 3COLOR.

- 1. Establish Truthiness
- 2. Force variables to be true or false
- 3. Use these subgraphs to create a graph that is 3 colorable iff the statement is satisfiable


Constructing the Reduction - Truthiness




Constructing the Reduction - Variables




Constructing the Reduction - Variables






Output node is colored false if both input nodes are colored false


Need to attach to truthiness gadget



Constructing the Reduction - Clause



Constructing the Reduction - Clause





Transform expression S to graph G_s $T = "On input <math>\langle S \rangle$,

1. Construct the truthiness subgraph T

- 1. Construct the truthiness subgraph *T*
- 2. For each clause in S add a 3 way OR gate subgraph O_i

- 1. Construct the truthiness subgraph *T*
- 2. For each clause in S add a 3 way OR gate subgraph O_i
- 3. Connect the "output" node of O_i to both the "false" and "unused" nodes of T

- 1. Construct the truthiness subgraph *T*
- 2. For each clause in S add a 3 way OR gate subgraph O_i
- 3. Connect the "output" node of O_i to both the "false" and "unused" nodes of T
- 4. For each variable in the S:

- 1. Construct the truthiness subgraph *T*
- 2. For each clause in S add a 3 way OR gate subgraph O_i
- 3. Connect the "output" node of O_i to both the "false" and "unused" nodes of T
- 4. For each variable in the S:
- ▶ Add nodes v and v_0 connected by an edge

- 1. Construct the truthiness subgraph *T*
- 2. For each clause in S add a 3 way OR gate subgraph O_i
- 3. Connect the "output" node of O_i to both the "false" and "unused" nodes of T
- 4. For each variable in the S:
- ▶ Add nodes v and v_0 connected by an edge
- ▶ Connect nodes v and v₀ to the "unused" end of t

- 1. Construct the truthiness subgraph *T*
- 2. For each clause in S add a 3 way OR gate subgraph O_i
- 3. Connect the "output" node of O_i to both the "false" and "unused" nodes of T
- 4. For each variable in the S:
- \triangleright Add nodes v and v_0 connected by an edge
- ▶ Connect nodes v and v_0 to the "unused" end of t
- Connect the corresponding node (v₀ or v) to one input of the clause's 3 way OR gate O_i"

Example

$$(x \lor y \lor \neg z) \lor (\neg x \lor \neg y \lor z)$$

Transformation - Forward

If boolean expression S is satisfiable, G_s is 3 colorable

▶ If *S* is satisfialbe at least one literal in each clause is colored true.

Transformation - Forward

If boolean expression S is satisfiable, G_s is 3 colorable

- ▶ If *S* is satisfialbe at least one literal in each clause is colored true.
- Output of 3-way OR gate can be colored with true as the output. This leads to a valid 3 coloring

Transformation - Backward

If graph G_s is 3 colorable, S is satisfiable

► A coloring of the graph forces the output of the 3-way OR gades to be colored true

Transformation - Backward

If graph G_s is 3 colorable, S is satisfiable

- ► A coloring of the graph forces the output of the 3-way OR gades to be colored true
- For each clause in S there must be at least one varaible colored true

► Truthiness nodes - *O*(1)

- ► Truthiness nodes O(1)
- ▶ Variable T/F nodes O(n)

- ► Truthiness nodes O(1)
- ▶ Variable T/F nodes O(n)
- \triangleright O(n) for n clauses

- ► Truthiness nodes O(1)
- ▶ Variable T/F nodes O(n)
- \triangleright O(n) for n clauses
- ► Overall O(n)

Sources

```
http://web.stanford.edu/class/archive/cs/cs103/cs103.1132/lectures/27/Small27.pdf
http://www.cs.princeton.edu/courses/archive/spring07/cos226/lectures/23Reductions.pdf
```