



Wf4Ever: Advanced Workflow Preservation Technologies for Enhanced Science

STREP FP7-ICT-2007-6 270192

Objective: ICT-2009.4.1b — “Advanced preservation scenarios”

D2.2v1 Design, implementation and deployment of workflow lifecycle management components - Phase I

Deliverable Co-ordinator: Sean Bechhofer

Deliverable Co-ordinating Institution: University of Manchester

Other Authors: Khalid Belhajjame, Esteban Garcia

This deliverable describes the first phase of delivery of workflow lifecycle management components. It includes a description of the Research Object Model, which facilitates interoperation between components; an initial Research Object Storage and Retrieval Service; RO Manager command line tool; and a definition of a model for workflow abstraction.

Document Identifier:	Wf4Ever/2012/D2.2v1/0.8	Date due:	July 31, 2012
Class Deliverable:	Wf4Ever FP7-ICT-2007-6 270192	Submission date:	July 31, 2012
Project start date	December 1, 2010	Version:	0.8
Project duration:	3 years	State:	Final
		Distribution:	Public

Wf4Ever Consortium

This document is part of the Wf4Ever research project funded by the IST Programme of the Commission of the European Communities by the grant number FP7-ICT-2007-6 270192. The following partners are involved in the project:

Intelligent Software Components S.A. (ISOCO) – Coordinator Edificio Testa, Avda. del Partenón 16-18, 1 ^o , 7 ^a Campo de las Naciones, 28042 Madrid Spain Contact person: Jose Manuel Gómez Pérez E-mail address: jmgomez@isoco.com	University of Manchester (UNIMAN) School of Computer Science Oxford Road, Manchester M13 9PL United Kingdom Contact person: Carole Goble E-mail address: carole.goble@manchester.ac.uk
Universidad Politécnica de Madrid (UPM) Departamento de Inteligencia Artificial, Facultad de Informática. 28660 Boadilla del Monte. Madrid Spain Contact person: Oscar Corcho E-mail address: ocorcho@fi.upm.es	Instytut Chemii Bioorganicznej PAN - Poznan Supercomputing and Netowrking Center (PSNC) Network Services Department Ul Z. Noskowskiego 12-14 61704 Poznań Poland Contact person: Raul Palma E-mail address: rpalma@man.poznan.pl
University of Oxford (OXF) Department of Zoology South Parks Road, Oxford OX1 3PS United Kingdom Contact person: Jun Zhao, David De Roure E-mail address: jun.zhao@zoo.ox.ac.uk david.deroure@oerc.ox.ac.uk	Instituto de Astrofísica de Andalucía (IAA) Dpto. Astronomía Extragaláctica. Glorieta de la Astronomía s/n, 18008 Granada Spain Contact person: Lourdes Verdes-Montenegro E-mail address: lourdes@iaa.es
Leiden University Medical Centre (LUMC) Department of Human Genetics Albinusdreef 2, 2333 ZA Leiden The Netherlands Contact person: Marco Roos E-mail address: M.Roos1@uva.nl	

Work package participants

The following partners have taken an active part in the work leading to the elaboration of this document, even if they might not have directly contributed to the writing of this document or its parts:

- iSOCO
- OXF
- PSNC
- UNIMAN
- UPM

Change Log

Version	Date	Amended by	Changes
0.1	02-07-2012	Sean Bechhofer	Initial Version
0.2	17-07-2012	Sean Bechhofer	Updates and Examples
0.3	18-07-2012	Sean Bechhofer	Adding PURLs
0.4	19-07-2012	Khalid Belhajjame	Adding decay section
0.5	19-07-2012	Esteban Garcia	Adding abstraction section
0.6	20-07-2012	Sean Bechhofer	Editing Executive summary. Addition of figure.
0.7	22-07-2012	Esteban Garcia	Editing abstraction section
0.8	26-07-2012	Sean Bechhofer	Changes addressing QA comments
0.9	27-07-2012	Khalid Belhajjame	Changes addressing QA comments for Section 8

Executive Summary

This deliverable describes the first phase of delivery of workflow lifecycle management components. These components are focused around the Wf4Ever Research Object Model (RO model), which provides descriptions of workflow-centric ROs – aggregations of content. This model is used to structure and describe ROs which are then stored and manipulated by the components of the Wf4Ever Toolkit.

The RO Model provides a framework for describing aggregations of content along with annotations of the aggregated resources, a vocabulary for describing workflows, and a vocabulary for describing provenance. We provide here a summary of the RO Model and its accompanying documentation (the RO Primer), and highlight components developed for creating and management of Research Objects: the Research Object Storage and Retrieval API (implemented as part of the Research Object Digital Library (RODL)) and a command line tool – the RO Manager. These components and services are also discussed in D1.2v2 (Wf4Ever Sandbox – Phase II), D1.3v1 (Wf4Ever Architecture – Phase I) and D1.4v1 (Reference Wf4Ever Implementation – Phase I).

We also discuss preliminary work in defining a model for workflow abstraction, with the aim of supporting reuse of workflows (or their constituent parts), and present an initial characterisation of workflow decay, identifying causes of workflow decay based on an analysis of existing workflows in the myExperiment repository. This deliverable should be read in tandem with D1.3v1 (Wf4Ever Architecture – Phase I), D1.4v1 (Reference Wf4Ever Implementation – Phase I), D1.2v2 (Wf4Ever Sandbox – Phase II), D3.2v1 (Design, implementation and deployment of Workflow Evolution, Sharing and Collaboration components – Phase I) and D4.2v1 (Design, implementation and deployment of Workflow Integrity and Authenticity Maintenance components – Phase I) in order to provide a complete picture of the state of the Wf4Ever Phase I components.

Contents

1	Introduction	7
2	The Research Object Model	7
3	Research Objects Primer	9
4	Research Object Examples	9
4.1	Astrophysical Quantities	9
4.2	InterProScan	10
4.3	Repeatability and Reproducibility	10
5	Research Object Storage and Retrieval	11
6	Research Object Manager	11
7	Workflow Abstraction	12
8	Characterising Workflow Decay	14
8.1	Volatile third-party resources	15
8.2	Missing example data	16
8.3	Missing execution environment	16
8.4	Insufficient descriptions about workflows	16
	Bibliography	18

List of Tables

1	Categorisation of Decay Caused by Third-party Resources	16
---	---	----

List of Figures

1	RO Schematic	8
2	HyperLEDA Luminosities Example RO	9
3	InterProScan Example RO	10
4	RO with Workflow description	11
5	RO with Workflow provenance	12
6	Workflow Abstraction Discovery Process	14
7	Distribution of the domain studied by our test workflows.	15
8	Number of Taverna workflows tested and failed	15
9	Results of workflow decay analysis.	17

1 Introduction

This deliverable describes Phase I of the design, implementation and deployment of the Wf4Ever components that will support workflow lifecycle management. The document should be read in tandem with other Month 20 deliverables, in particular D3.2v1 (Design, implementation and deployment of Workflow Evolution, Sharing and Collaboration components – Phase I) [GC12b] and D4.2v1 (Design, implementation and deployment of Workflow Integrity and Authenticity Maintenance components – Phase I) [GC12a] which address complementary aspects of the overall wf4ever architecture and components.

According to the Description of Work, *This prototype will include the following functionalities: an initial Research Object model, implemented by means of an ontology network, and basic management functions (storage and access), validation functionalities based on RO provenance, and definition of semantic overlays and workflow provenance matching techniques for abstraction..*

These requirements are addressed in the following way:

Sections 2, 3 and 4 discuss the Research Object Model defined within Wf4Ever along with a Primer document providing an introduction to that model and a collection of example Research Objects.

Sections 5 and 6 describe the initial Research Object Storage and Retrieval API and Command Line Manager. Both of these tools use the Research Object Model to structure the objects that they produce and consume. The RO Model is thus the “glue” that joins together the components and enables interoperation.

Section 7 discusses an initial model for workflow abstraction, while Section 8 presents a characterisation of workflow decay.

Note that this document represents the results from Phase I of the project – as a result, some areas are not yet complete and we expect updates, changes and extensions to be reported in Phase II of the project, due for completion in M32. For example, we expect that RO models reported here will be subject to change following further usage and experience, both within and outside the project.

2 The Research Object Model

The Wf4Ever Research Object model defines vocabularies that describe Workflow-centric Research Objects within Wf4Ever. The concept of Research Object is described in [B⁺11] and further refined in [BCG⁺12]. A complete, functional RO based ecosystem also requires a number of different services for creation, storage, manipulation, recommendation, visualisation etc. of Research Objects. These services are not considered as part of the model (although implemented services are described in this deliverable in Sections 5 and 6). Nor does the core model describe the evolution of Research Objects (ROs) – this is discussed in D3.2v1 (Design, implementation and deployment of Workflow Evolution, Sharing and Collaboration components – Phase I) [GC12b].

Narrative text describing the model is published online¹ and the ontologies themselves also available². We will not reproduce all this narrative text here, but provide an overview of the model and rationale.

A simple schematic of an RO is shown in Figure 1. The RO contains a workflow, input data and results along with a paper that presents the results and links to the investigators responsible. Annotations on each of the resources (and on the RO itself) provide additional information and characterise, e.g. the provenance of the results (the results were obtained by executing the workflow on the input data).

Research Objects play multiple roles. In the first case, they are *technical* objects. They provide access to the resources that are needed to support execution of investigations and record the provenance traces of those executions. They encapsulate dependencies between resources and maintain versioning information about the lineage and evolution of those resources.

At the same time, ROs they are *social* objects. They encapsulate reusable protocols and know-how, record best practices and support reproducibility. They are citable artifacts that can be referred to and quoted, and

¹<http://wf4ever.github.com/ro/>

²<https://github.com/wf4ever/ro/>




Figure 1: RO Schematic

record and represent information about the people involved in investigations – those who create, use, extend and curate the objects.

These roles bring requirements on the representation structure and vocabularies used to describe Research Objects. The specification of the RO model focuses on the technical aspects and describes the core Wf4Ever Research Object vocabularies that provide container structures and vocabulary for describing workflow objects. Additional vocabularies covering evolution, lifecycle, versioning and other social aspects will be covered elsewhere (See D3.2v1 (Design, implementation and deployment of Workflow Evolution, Sharing and Collaboration components – Phase I) [GC12b] and D4.2v1 (Design, implementation and deployment of Workflow Integrity and Authenticity Maintenance components – Phase I) [GC12a]).

ROs allow for the aggregation of resources along with annotations on those resources concerning their provenance, use, characteristics etc. Aggregation is supported through the use of the OAI-ORE vocabulary³ and annotation is supported through the use of the Annotation Ontology⁴. Re-use of these existing vocabulary will facilitate third party tools in understanding and processing Research Objects described using the model. Finally, the RO Model provides a number of basic ontologies that are used within this aggregation/annotation framework to describe specifics of the Workflow-centric Research Objects. These are:

ro Provides basic structure for the description of aggregated resources and the annotations that are made on those resources.

wfdesc A vocabulary for the description of workflows. This provides an abstraction that can be mapped to different particular workflow systems. The ontology is intended as an upport ontology for more specific workflow definitions, and as a way to express abstract workflows, which could either be hand-crafted by users, or extracted from workflow definitions, for example Taverna's `t2flow` or Scuf2 formats. A prototype service that transforms workflows into Research Objects, using the wfdesc ontologies has been developed (See D1.4v1 (Reference Wf4Ever Implementation – Phase I) [PH12]).

wfprov A vocabulary for the description of provenance information. This provides an abstraction that can be mapped to different provenance vocabularies, for example PROV-O⁵ as developed by the W3C Provenance Working Group.

³OAI-ORE is not a ratified standard produced by a body such as the W3C or IETF, but it is becoming widely used as a vocabulary for aggregation.

⁴Again, AO is not as yet a standardised vocabulary, but a W3C community group has been set up to oversee the drafting of a specification: <http://www.w3.org/community/openannotation/>

⁵<http://www.w3.org/TR/prov-o/>

All three ontologies, ro⁶, wfdesc⁷ and wfprov⁸ are published online.

3 Research Objects Primer

The Research Object Ontologies and Vocabularies Primer is a document targeted at users, providing an accessible introduction to the Wf4Ever RO Model. This will enable readers to understand *what* the RO Model provides and *how* the RO Ontologies and Vocabularies can be used to describe an aggregation object that represents scientific experiments in a structured format.

The document is published online⁹

4 Research Object Examples

A number of exemplar Research Objects have been created. These provide illustrative examples of how the model may be used to describe aggregations of content.

4.1 Astrophysical Quantities

This RO collects together several resources including input and output datasets, scripts, web services and other documents. These relate to various tasks and stages of the experiment including *gathering*, *propagation* and *comparison* with intermediate results being passed from one stage to another.

A screenshot of the RO within the RODL is shown in Figure 2. This shows the conceptual view of the RO, with folders containing Workflow Runs expanded.




Figure 2: HyperLEDA Luminosities Example RO

⁶<http://purl.org/wf4ever/ro>

⁷<http://purl.org/wf4ever/wfdesc>

⁸<http://purl.org/wf4ever/wfprov>

⁹<http://wf4ever.github.com/ro-primer/>

We can see here the relationships between a particular workflow run aggregated in the RO and its input, the workflow executed etc. These relationships are described using the RO model vocabulary, and the portal allows for export/publication of this metadata.

The RO is available in the RODL portal¹⁰

4.2 InterProScan

This is an example of an RO built around a workflow taken from myExperiment. The workflow performs an InterProScan analysis of a protein sequence using the EBI's¹¹ WSInterProScan service¹². The workflow illustrates the issue of workflow *decay* as it can no longer be enacted. This is because the workflow involves EBI asynchronous services that were suspended as the EBI changed the way asynchronous services are handled.




Figure 3: InterProScan Example RO

Again, a snapshot of the RO in RODL is shown in Figure 3. Here, we can see annotation applied to the workflow within the RO, in particular a description discussing the problems with the workflow.

The RO is available in the RODL portal¹³

4.3 Repeatability and Reproducibility

Two example ROs illustrate how different levels of information can be recorded within the ROs in order to support a rerunning of an experiment. Figure 4) includes a workflow (along with its abstract description using the **wfdesc** ontology). In Figure 5, the RO also includes details of a workflow execution or run, using the **wfprov** ontology.

¹⁰http://purl.org/net/wf4ever/ro/HyperLEDA_Luminosities

¹¹European Bioinformatics Institute

¹²<http://www.ebi.ac.uk/Tools/webservices/services/archive/pfa/wsinterproscan>

¹³http://purl.org/net/wf4ever/ro/InterProScan_RO1




Figure 4: RO with Workflow description

The ROs are available in the RODL portal¹⁴

5 Research Object Storage and Retrieval

The Research Object Storage and Retrieval API supports the creation, management and manipulation of Research Objects (ROs). The Research Object Digital Library provides an implementation of this functionality.

The ROSR API is provided as a RESTful interface, with the following functionality:

- Storing and retrieving research objects;
- Storing and retrieving resources aggregated within the research objects;
- Annotating the aggregated resources, including the research object itself.

The ROSR API uses the RO Model (as discussion in Section 2 to structure and describe the objects it creates).

Further information describing the details of the ROSR API are contained in D1.4v1 (Reference Wf4Ever Implementation – Phase I) [PH12].

6 Research Object Manager

The Research Object Manager provides a command line tool for creating, displaying and manipulating Research Objects. The RO Manager functionality is complementary to that provided by the ROSR described

¹⁴<http://purl.org/net/wf4ever/ro/repeatability> and <http://purl.org/net/wf4ever/ro/reproducibility>




Figure 5: RO with Workflow provenance

in Section 5. In particular, the RO Manager is primarily designed to support a user working with ROs in the host computer's local file system, with the intention being that the ROSRS and RO Manager can exchange ROs between them – in part facilitated by the use of the shared RO vocabulary and model.

Past experience has suggested that lightweight, command line tools give users early access to functionality and provide an opportunity to gather additional feedback and requirements on that functionality. Command line tools can also be used with built in operating system functionality as pipes and input/output redirection in order to quickly build prototype tool chains.

The RO Manager allows users to

- Create local ROs;
- Add resources to an RO;
- Add annotations to an RO;
- Read and write ROs to the RODL.

As with the ROSR, the RO Manager uses the RO Model to structure and describe the objects it creates.

Further information describing the details of the RO Manager are contained in D1.4v1 (Reference Wf4Ever Implementation – Phase I) [PH12] and D1.2v2 (Wf4Ever Sandbox – Phase II) [PHKG12].

7 Workflow Abstraction

The main purpose of the work done so far for workflow abstraction is related to the creation of a trie structure which captures the sequences of execution of a workflow and keeps track of their statistics. A trie is an ordered tree that stores a dynamic set of keys which they usually are strings. For our purposes we have used it for storing the workflow execution in an ordered way by including at different levels of the tree the different inputs, processes and outputs (resources) which are run. Therefore all the descendants of a node have a

common prefix of the resource associated with that node. This is very useful for detecting common parts of different workflows because we can easily keep track of the number of times that a specific sequence of resources has been executed.

The goal of making an abstraction of a workflow is to make them more reusable as a whole or some parts of it. Then, we define abstraction as the pattern that appears when a sequence of resources are executed together by a minimum number of times. This definition leads also to the concept of pattern or macro identification which applied to workflows leads to finding common sub-workflows.

The presented work is a bottom-up approach in order to study the actual provenance of workflow results (which represents the dataflow of an executed workflow described in D4.2v1) from a set of available workflows at WINGS¹⁵ and Taverna¹⁶ created for this purpose. The description of the provenance of workflow results and **wfprov** ontology can be found in D4.2v1 [GC12a] and online¹⁷ respectively, and an example of a RO containing the provenance of workflow results for the Protein Discovery Workflow is available¹⁸ which is part of the RO testbed¹⁹.

This study uses the provenance of the workflow results of different workflows as inputs for creating the trie structure introduced above. Every time a resource is executed its associated node in the trie structure is updated by increasing the number of times that it has been used and afterwards an analysis of the trie can be done to obtain the most common set of resources or macros.

Though this is still a preliminary work, once a set of macros have been identified it would be possible to categorize them (manually or automatically e.g. by using workflow tags) and afterwards create the associated taxonomy by using the trie membership relations.

The use of the provenance of the workflow results seems to be more appealing than using the workflow templates, which are the static description of a workflow, mainly due to it representing the workflows which are actually running and being used, and also allows to undo control structures as e.g. "if".

The code developed for the creation and maintenance of the trie structure and for accessing to the provenance of the workflow results repository is available at²⁰ and provides the following functionality:

- It stores the provenance of the workflow results in an ordered way and the appearance frequency of their resources
- It calculates relative frequencies at different levels of the trie
- It provides different modes to traverse the structure (pre-ordered/level-ordered)
- It provides an output XML structure with relative frequencies per level and per process (an output example is available at²¹)

The Figure 6 shows the overall discovery process introduced in this section. The inputs have been obtained by using workflows from WINGS and Taverna and transforming them into **wfdesc** and **wfprov** vocabularies to get the provenance of workflow results. That provenance has been stored in a trie structure which captures the order of the executed resources and stores the frequencies of appearance. Then, that information can be used to obtain the most frequent set of ordered executed resources which we have called macros and are

¹⁵<http://wings.isi.edu/>

¹⁶<http://www.taverna.org.uk/>

¹⁷<http://purl.org/wf4ever/wfprov>

¹⁸<http://sandbox.wf4ever-project.org/portal/ro?0&ro=http://sandbox.wf4ever-project.org/rosrs5/ROs/wf74/>

¹⁹<http://www.wf4ever-project.org/wiki/display/docs/RO+testbed>

²⁰<https://github.com/wf4ever/wf-abstraction>

²¹<https://github.com/wf4ever/wf-abstraction/blob/master/outputExample.xml>




Figure 6: Workflow Abstraction Discovery Process

identified in the figure of the bottom by black squares. Afterwards these detected macros, which represent some common workflow structures, could be hand-annotated in order to tag them or could be annotated automatically for example by assigning to them the same tags as the workflows that they belong to. Finally a taxonomy which includes all the identified macros by membership (bigger macros contain the smaller ones) will be created for indexing.

8 Characterising Workflow Decay

The main impediment to workflow preservation is workflow decay. Indeed, our experience with scientific workflows suggests that a large proportion of workflows suffer from decay [Bel07], which decreases their value over time. Broadly speaking, we can distinguish two forms of decay. i)- **Inability to re-execute the workflow**: due to many factors, including the unavailability of third party resources that are responsible for executing the tasks that compose the workflows, we may not be able to re-execute a given workflow. ii)- **Inability to reproduce workflow results**: a less severe, yet relevant, form of decay, is the inability to obtain the same (or similar) results when re-executing the workflow. Reproducing previous results can be primordial in reinforcing trust in scientific results and can be used in peer-reviewing as a mechanism to validate the results claimed by given scientists [FBS11, GRB12].

The above discussion raises the following question. *What are the causes of workflow decay?* To identify and characterise the causes of workflow decay, we adopted a bottom-up approach, whereby we manually analyzed 92 Taverna workflows from the myExperiment repository. We chose Taverna workflows because they form the largest available workflow collection (more than half of the workflows in myExperiment are Taverna workflows at the time of writing), and Taverna workflows have been published on myExperiment since its launch in 2007, therefore providing a good insight into decay over those years.

To base our analysis on a sample of workflows that is representative of the set of workflows in myExperiment, we selected workflows using the following three criteria:

- The year of creation of the workflow: we believe that the decay of workflows could be directly impacted by the year of their creation, hence we tried to make an even coverage of Taverna 1 workflows [OAF⁺04] and Taverna 2 workflows [MSRO⁺10] between the years 2007 and 2012.
- The creator of the workflow: in order to reduce possible bias introduced by specific workflow creators, we avoided choosing workflows created by the same person in the same year.
- The domain of the workflow: our workflow selection also had a good coverage of domains, covering 18 different scientific (such as life sciences, astronomy and cheminformatics) and non-scientific domains (such as testing of Grid services). Figures 7 illustrates the domains of the workflows that we selected for decay analysis.




Figure 7: Distribution of the domain studied by our test workflows.


Although we focus on a particular family of workflows, i.e., Taverna workflows, we expect our approach and analysis to be applicable to many others and our analysis to be repeatable on a different corpus of workflows. To identify the causes of decay that the workflows we selected may suffer from, we attempted to execute them using the Taverna 2.3 workbench. We then manually examined their results, diagnosed broken links, etc. Our analysis showed that nearly 80% of the tested workflows failed to be either executed or produce the same results, and those from earlier years (2007-2009) had more than 80% failure rate (as shown in Figures 8). The causes of workflow decay can be classified into four categories, which we present in the rest of this section.

8.1 Volatile third-party resources


Most of the workflows that we analysed make use of third-party resources such as web services and databases. The provision of such resources may be interrupted or changed, causing failure of the workflow to execute. In certain cases, the workflow cannot be run, even when the third party resources that it relies on are available, e.g., when such resources require authentication. Another cause that may lead to workflow decay, is changes to third party resources. For example, if the web service provider decides to change the implementation of the web service, then the workflow execution may not deliver the same results, or worse, it may not be possible to execute. Table 1 summarises these causes of decay with concrete examples.

8.2 Missing example data

It is not always obvious which data can be used as inputs to the workflow execution, and example inputs are often helpful. Example outputs can also be useful to gain an insight of the outcome anticipated from the workflow. However, our analysis revealed that they are not always made available. Provenance traces of previous runs are also useful as indications of where example data may be found.



(a) Number of Taverna 1 workflows tested and failed between 2007-2009.



(b) Number of Taverna 2 workflows tested and failed between 2009-2012

Figure 8: Number of Taverna workflows tested and failed

8.3 Missing execution environment

The execution of a workflow may rely on a particular local execution environment, for example, a local R server or a specific version of workflow execution software. Some of our test workflows exhibit this type of decay. Taverna often provides sufficient information about missing libraries, and sometimes workflow descriptions provide a warning about the requirement for a specific library. This type of decay appears to be fixable by installing the missing software, albeit requiring some effort.

8.4 Insufficient descriptions about workflows


Sometimes a workflow workbench cannot provide sufficient information about what caused the failure of a workflow run. Additional descriptions in the workflow can play an important role in assisting re-users to understand the purpose of the workflow and its expected outcomes.

The results of the above analysis are summarised in Figure 9-a, which illustrates the number of workflows that suffer from each of the causes of decay presented above. It shows that 50% workflows suffer from decay due to third party resources.


To better understand the causes of decay due to third party resources. Figure 9-b illustrates the number of workflows that suffer from the causes presented in Table 1. It shows that the unavailability of third party resources is the leading cause of decay, followed by resources inaccessibility, and then resources changes. The above results confirms our hypothesis that workflow decay is a serious problem. It also suggests that there is a need for additional information that can assist workflow designers detecting and repairing decayed workflows. We report in a separate deliverable [GC12a], on a minimal model and associated checklists, that were designed and developed with the objective to prevent and repair workflow decay.

Table 1: Categorisation of Decay Caused by Third-party Resources

Causes	Refined causes	Examples
Third party resources are not available	Underlying datasets, particularly those locally hosted in-house datasets, are no longer available	Researcher hosting the data changed institution, server is no longer available
	Services are deprecated	(DNA Data Bank of Japan) DDBJ web services are not longer provided despite the fact that they are used in many myExperiment workflows
Third party resources are available but not accessible	Data is available but identified using different IDs than the one known to the user	Due to scalability reasons the input data is superseded by a new version making the workflow not executable or providing wrong results
	Data is available but permission, certificate, or network to access it is needed	Cannot get the input, which is a security token that can only be obtained by a registered user of ChemiSpider
	Services are available but need permission, certificate, or network to access and invoke them	The security policies of the execution framework are updated due to new hosting institution rules
Third party resources have changed	Services are still available by using the same identifiers but their functionality have changed	The web services are updated intentionally or unintentionally (e.g.malware) providing wrong results



(a) A summary of workflow decay causes



(b) Workflow decay due to third party resources

Figure 9: Results of workflow decay analysis.

References

- [B⁺11] S. Bechhofer et al. Why Linked Data is Not Enough for Scientists. *Future Generation Computer Systems*, 2011.
- [BCG⁺12] Khalid Belhajjame, Oscar Corcho, Daniel Garijo, Jun Zhao, Paolo Missier, David Newman, Raúl Palma, Sean Bechhofer, Esteban García Cuesta, José Manuel Gómez-Pérez, Graham Klyne, Kevin Page, Marco Roos, José Enrique Ruiz, Stian Soiland-Reyes, Lourdes Verdes-Montenegro, David De Roure, and Carole A. Goble. Workflow-Centric Research Objects: First Class Citizens in Scholarly Discourse. In *SePublica2012 workshop at ESWC2012*, 2012.
- [Bel07] Khalid Belhajjame. Semantic replaceability of escience web services. In *eScience*, pages 449–456. IEEE Computer Society, 2007.
- [FBS11] Juliana Freire, Philippe Bonnet, and Dennis Shasha. Exploring the coming repositories of reproducible experiments: Challenges and opportunities. *PVLDB*, 4(12):1494–1497, 2011.
- [GC12a] Esteban García Cuesta. Design, implementation and deployment of Workflow Integrity and Authenticity Maintenance components – Phase I. Deliverable D4.2v1, Wf4Ever Project, 2012.
- [GC12b] Rafael González-Cabero. Design, implementation and deployment of Workflow Evolution, Sharing and Collaboration components – Phase I. Deliverable D3.2v1, Wf4Ever Project, 2012.
- [GRB12] Carole A. Goble, David De Roure, and Sean Bechhofer. Accelerating scientists’ knowledge turns. In *Proceedings of The 3rd international IC3K joint conference on Knowledge Discovery, Knowledge Engineering and Knowledge Management.*, 2012. in press.
- [MSRO⁺10] Paolo Missier, Stian Soiland-Reyes, Stuart Owen, Wei Tan, Aleksandra Nenadic, Ian Dunlop, Alan Williams, Tom Oinn, and Carole A. Goble. Taverna, reloaded. In *SSDBM*, pages 471–481. Springer, 2010.
- [OAF⁺04] Thomas M. Oinn, Matthew Addis, Justin Ferris, Darren Marvin, Martin Senger, R. Mark Greenwood, Tim Carver, Kevin Glover, Matthew R. Pocock, Anil Wipat, and Peter Li. Taverna: a tool for the composition and enactment of bioinformatics workflows. *Bioinformatics*, 20(17):3045–3054, 2004.
- [PH12] Raul Palma and Piotr Holubowicz. Reference Wf4Ever Implementation – Phase I. Deliverable D1.4v1, Wf4Ever Project, 2012.
- [PHKG12] Raul Palma, Piotr Holubowicz, Graham Klyne, and Aleix Garrido. Wf4Ever Sanbox – Phase II. Deliverable D1.2v2, Wf4Ever Project, 2012.