

F33617.1525

Fasson®
DT200HD FSC® S2049
BG33WHN

An FSC compliant, white, back coated woodfree paper with a barrier coated thermo-sensitive layer.

FSC

Applications





Key Features

> FSC Approved facestock and liner (License Code: FSC-C122337).
> Excellent adhesive performance on a wide variety difficult substrates.
> Designed for use in thermal printing at printing speed up to 200mm/s.
> Safe to use on packaging of food products where FDA 175.105 is required.

F33617.1525

Fasson®
DT200HD FSC® S2049 BG33WH





Facestock
An FSC compliant, white, back coated woodfree paper with a barrier-coated thermo-sensitive layer.

Basis Weight:	78 g/m²	ISO 536
Caliper:	81 µm	ISO 534

Adhesive
A general-purpose permanent, rubber-based adhesive suitable for rough surfaces such as recycled board.

Liner
An FSC compliant, supercalendered glassine paper specially designed for medium to high speed conversion. Designed for accurate kiss / die-cutting.

Basis Weight	50 g/m²	TAPPI T410
Caliper	48 µm	TAPPI T411

Laminate

Total Caliper	135 µm ±10%	Calculated

Typical Performance Data

Initial Tack	600 N/m FTM 9 glass
Peel Adhes. 90°	290 N/m FTM 2 st.st.
Min. appl. temp.	0°C
Service temp.	-40°C to 70°C subject to facestock limitations

**Typical Performance Data only serves as reference to product performance under specified testing conditions and does not represent a product specification. Customers are recommended to test under actual conditions of use to determine its suitability.*

Applications and Use
Designed for use in thermal printing at print speed up to 200mm/s and where image resistance is required. Typical applications include barcode labels for pre-packed food (e.g meat, fish, poultry, and fish) and industrial barcoding (e.g laboratories, hospitals, and pharmaceutical applications). Avoid prolonged temperature of 50°C or more for long periods. Exposure to direct sunlight or strong fluorescent light may invalidate the image.

Adhesive Performance
S2049 features excellent performance on a wide variety of substrates, including apolar, textured HDPE, recycled corrugated cardboard, slightly rough, curved and difficult substrates. It is suitable for use in chilled or room temperature environments and provides some moisture resistance after applying on a dry surface. Exposure to chemicals and sunlight could degrade the adhesive. Not suitable for storage near ozone sources such as electrical devices.

Conversion/Printing
Can be used on all conventional label printing technologies. UV Flexo and Letterpress are recommended. Suitable for conventional die-cutting processes and conventional inks and varnishes. Consult specialists for details. Thermal coating may exhibit poor scuff resistance in wet environments. Inks containing alcohol or volatile organic solvents may cause discolouration of the thermosensitive coating.

Food Industry Labels
The adhesive complies with FDA 175.105 and German recommendations XIV as published by BfR. This adhesive can be used in direct contact with dry and moist, non fatty foodstuffs.

Statement of Practical Use
As with all pressure sensitive materials, this product should be tested thoroughly under end-use conditions to ensure it meets the requirements of the specific application.

Shelf life
One year when stored at 20 ± 5°C and 50 ± 10% RH

Australia
1124 Centre Rd
Oakleigh South
VIC 3167
Australia
Tel +61 3 9271 0300
Fax +61 3 9271 033

Warranty

All statements, technical information and recommendations about AVERY DENNISON products are based upon tests believed to be reliable but but do not constitute a guarantee or warranty. All AVERY DENNISON products are sold with the understanding that PURCHASER has independently determined the suitability of such products for its purposes. AVERY DENNISON products are warranted to be free of defects in material or workmanship for a period of one year from the date of shipment. Any product shown to the satisfaction of AVERY DENNISON within the time provided to be so defective shall be replaced without charge of AVERY DENNISON may issue credit in such amount as it seems reasonable however, in no event shall AVERY DENNISON be responsible for claims beyond the replacement value of the defective product or in any way liable or responsible for consequential or incidental damages.

NO EXPRESS WARRANTIES, WHETHER OF MERCHANTABILITY OR FITNESS FOR ANY ARTICULAR USE, OR OTHERWISE, EXCEPT AS SET FORTH ABOVE (WHICH IS MADE EXPRESSLY IN LIEU OF ALL OTHER WARRANTIES) SHALL APPLY TO PRODUCTS SOLD BY AVERY DENNISON. AVERY DENNISON SPECIFICALLY DISCLAIMS AND EXCLUDES ALL OTHER SUCH WARRANTIES. NO WAIVER, ALTERNATION, ADDITION OR MODIFICATION OF THE FOREGOING CONDITIONS SHALL BE VALID UNLESS MADE IN WRITING AND SIGNED BY AN EXECUTIVE OFFICER OF AVERY DENNISON. No salesman, representative, or agent of AVERY DENNISON is authorized to give any guarantee, warranty or make any representation contrary to the above.