

Universal Serial Bus Device Class Definition for Video Devices: Uncompressed Payload

Revision 1.5
August 9, 2012

Contributors

Abdul R. Ismail	Intel Corp.
Anand Ganesh	Microsoft Corp.
Anshuman Saxena	Texas Instruments
Bertrand Lee	Microsoft Corp.
David Goll	Microsoft Corp.
Eric Luttmann	Cypress Semiconductor Corp.
Geraud Mudry	Logitech Inc.
Hiro Kobayashi	Microsoft Corp.
Jean-Michel Chardon	Logitech Inc.
Jeff Zhu	Microsoft Corp.
Olivier Lechenne	Logitech Inc.
Remy Zimmermann	Logitech Inc.
Stephen Cooper	Microsoft
Richard Webb	Microsoft
Maribel Figuera	Microsoft
Chandrashekhara Rao	Logitech Inc.

**Copyright © 2012, USB Implementers Forum, Inc.
All rights reserved.**

A LICENSE IS HEREBY GRANTED TO REPRODUCE THIS SPECIFICATION FOR INTERNAL USE ONLY. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE, IS GRANTED OR INTENDED HEREBY.

USB-IF AND THE AUTHORS OF THIS SPECIFICATION EXPRESSLY DISCLAIM ALL LIABILITY FOR INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS, RELATING TO IMPLEMENTATION OF INFORMATION IN THIS SPECIFICATION. USB-IF AND THE AUTHORS OF THIS SPECIFICATION ALSO DO NOT WARRANT OR REPRESENT THAT SUCH IMPLEMENTATION(S) WILL NOT INFRINGE THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS.

THIS SPECIFICATION IS PROVIDED "AS IS" AND WITH NO WARRANTIES, EXPRESS OR IMPLIED, STATUTORY OR OTHERWISE. ALL WARRANTIES ARE EXPRESSLY DISCLAIMED. NO WARRANTY OF MERCHANTABILITY, NO WARRANTY OF NON-INFRINGEMENT, NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, AND NO WARRANTY ARISING OUT OF ANY PROPOSAL, SPECIFICATION, OR SAMPLE.

IN NO EVENT WILL USB-IF OR USB-IF MEMBERS BE LIABLE TO ANOTHER FOR THE COST OF PROCURING SUBSTITUTE GOODS OR SERVICES, LOST PROFITS, LOSS OF USE, LOSS OF DATA OR ANY INCIDENTAL, CONSEQUENTIAL, INDIRECT, OR SPECIAL DAMAGES, WHETHER UNDER CONTRACT, TORT, WARRANTY, OR OTHERWISE, ARISING IN ANY WAY OUT OF THE USE OF THIS SPECIFICATION, WHETHER OR NOT SUCH PARTY HAD ADVANCE NOTICE OF THE POSSIBILITY OF SUCH DAMAGES.

All product names are trademarks, registered trademarks, or service marks of their respective owners.

Please send comments via electronic mail to <video-chair>@usb.org

Revision History

Version	Date	Description
1.0	September 4, 2003	Initial release
1.1	June 1 st , 2005	<p>Removed restrictions on use of Aspect Ratio fields</p> <p>Updated Table 3-1 to remove the Display Mode bits from the bmInterlaceFlags field</p> <p>Flag added to distinguish between fixed and dynamic frame rate devices (RR0043)</p> <p>Corrected the Frame Descriptor length</p> <p>Update SCR/PTS field. Deprecated the field dwMaxVideoFrameBufferSize in Table 3-2. (RR0064)</p>
1.5	July 25 th , 2012	Updated the list of allowed colorspace

Table of Contents

1	Introduction	1
1.1	Purpose	1
1.2	Scope	1
1.3	Related Documents	1
1.4	Terms and Abbreviations	1
2	Video Class-Specific Information	1
2.1	Compression Class	1
2.2	Compression Formats	1
2.3	Format Constraints	2
2.4	Stream Header	2
3	Payload-Specific Information	4
3.1	Descriptors	4
3.1.1	Uncompressed Video Format Descriptor	4
3.1.2	Uncompressed Frame Descriptor	5
3.2	Video Samples	8
3.3	Uncompressed Payload Information	8
3.3.1	Planar Formats	8
3.3.2	Packed Formats	8

List of Tables

Table 2-1 Compression Formats	1
Table 2-2 Stream Header Format for Uncompressed Streams	2
Table 3-1 Uncompressed Video Format Descriptor	4
Table 3-2 Uncompressed Video Frame Descriptors	6
Table 3-3 Continuous Frame Intervals	7
Table 3-4 Discrete Frame Intervals	8

1 Introduction

1.1 Purpose

This document defines uncompressed payload formats for devices that are compliant with the *USB Device Class Definition for Video Devices* document.

1.2 Scope

The payload format and associated header information are fully specified in this document. This includes:

- USB Video Class stream header
- List of supported formats
- List of format identifiers

1.3 Related Documents

USB Specification Revision 2.0, April 27, 2000, www.usb.org

USB Device Class Definition for Video Devices www.usb.org

<http://www.fourcc.org> The [almost definitive] FourCC definition list

1.4 Terms and Abbreviations

This section defines terms and abbreviations used throughout this document.

Term	Description
Macropixel	Block consists of one or more packed pixel(s) that contain all the component information.
Packed	Pixel components are transmitted in interleaved order.
Planar	Pixel components are transmitted in separate successive planes.
YUV	Luminance and chrominance components

2 Video Class-Specific Information

2.1 Compression Class

This specification defines uncompressed streams in YUV color spaces. Each frame is independently sent by the device to the host.

2.2 Compression Formats

The following compression formats are supported.

Table 2-1 Compression Formats

Format	GUID
YUY2	32595559-0000-0010-8000-00AA00389B71
NV12	3231564E-0000-0010-8000-00AA00389B71
M420	3032344D-0000-0010-8000-00AA00389B71
I420	30323449-0000-0010-8000-00AA00389B71

2.3 Format Constraints

The vertical and horizontal dimensions of the image are constrained by the color component subsampling; image size must be a multiple of macropixel block size. No padding is allowed. This Uncompressed video payload specification supports any YUV format. The recommended YUV formats are one packed 4:2:2 YUV format (YUY2), one packed 4:2:0 YUV format (M420), and two planar 4:2:0 YUV formats (NV12, I420).

2.4 Stream Header

The following is a description of the packet header format for uncompressed streams.

Table 2-2 Stream Header Format for Uncompressed Streams

HLE	Header Length							
BFH [0]	EOH	ERR	STI	RES	SCR	PTS	EOF	FID
PTS	PTS [7:0]							
	PTS [15:8]							
	PTS [23:16]							
	PTS [31:24]							
SCR	SCR [7:0]							
	SCR [15:8]							
	SCR [23:16]							
	SCR [31:24]							
	SCR [39:32]							
	SCR [47:40]							

Header length field

The header length field specifies the length of the header, in bytes.

Bit field header field

FID: Frame Identifier

This bit toggles at each frame start boundary and stays constant for the rest of the frame.

EOF: End of Frame

This bit indicates the end of a video frame and is set in the last video sample belonging to a frame.

PTS: Presentation Time Stamp

This bit, when set, indicates the presence of a PTS field.

SCR: Source Clock Reference

This bit, when set, indicates the presence of a SCR field.

RES: Reserved.

Set to 0.

STI: Still Image

This bit, when set, identifies a video sample as belonging to a still image.

ERR: Error Bit

This bit, when set, indicates an error in the device streaming.

EOH: End of Header

This bit, when set, indicates the end of the BFH fields.

Presentation time stamp (PTS) field

The PTS field is present when the PTS bit is set in the BFH[0] field. See Section 2.4.3.3 “Video and Still Image Payload Headers” in the “USB Device Class Definition for Video Devices” specification.

Source clock reference (SCR) field

The SCR field is present when the SCR bit is set in the BFH[0] field. See Section 2.4.3.3 “Video and Still Image Payload Headers” in the “USB Device Class Definition for Video Devices” specification.

3 Payload-Specific Information

The Color Matching descriptor is mandatory for uncompressed video formats. For detailed information, see section "Color Matching Descriptor" in *Universal Serial Bus Device Class Definition for Video Devices* documentation.

3.1 Descriptors

This section provides detailed information about the following descriptors:

- Uncompressed Video Format Descriptor
- Uncompressed Frame Descriptor

3.1.1 Uncompressed Video Format Descriptor

The Uncompressed Video Format descriptor defines the characteristics of a specific video stream. It is used for formats that carry uncompressed video information, including all YUV variants.

A Terminal corresponding to a USB IN or OUT endpoint, and the interface it belongs to, supports one or more format definitions. To select a particular format, host software sends control requests to the corresponding interface.

The **bFormatIndex** field contains the one-based index of this format descriptor, and is used by requests from the host to set and get the current video format.

The **guidFormat** field uniquely identifies the video data format that shall be used when communicating with this interface at the corresponding format index. For a video source function, the host software will deploy the corresponding video format decoder (if necessary) based on the format specified in this field.

The **bAspectRatioX** and **bAspectRatioY** fields specify the X and Y dimensions of the picture aspect ratio respectively for video field (interlaced) data. For example, **bAspectRatioX** will be 16 and **bAspectRatioY** will be 9 for a 16:9 display.

An Uncompressed Video Format Descriptor is followed by one or more Uncompressed Video Frame Descriptor(s); each Video Frame Descriptor conveys information specific to a frame size supported for the format.

An Uncompressed Video format descriptor identifies the following.

Table 3-1 Uncompressed Video Format Descriptor

Offset	Field	Size	Value	Description
0	bLength	1	Number	Size of this descriptor in bytes: 27
1	bDescriptorType	1	Constant	CS_INTERFACE descriptor type
2	bDescriptorSubtype	1	Constant	VS_FORMAT_UNCOMPRESSED descriptor subtype
3	bFormatIndex	1	Number	Index of this format descriptor

4	bNumFrameDescriptors	1	Number	Number of frame descriptors following that correspond to this format
5	guidFormat	16	GUID	Globally Unique Identifier used to identify stream-encoding format
21	bBitsPerPixel	1	Number	Number of bits per pixel used to specify color in the decoded video frame
22	bDefaultFrameIndex	1	Number	Optimum Frame Index (used to select resolution) for this stream
23	bAspectRatioX	1	Number	The X dimension of the picture aspect ratio.
24	bAspectRatioY	1	Number	The Y dimension of the picture aspect ratio.
25	bmInterlaceFlags	1	Bitmap	Specifies interlace information. If the scanning mode control in the Camera Terminal is supported for this stream, this field shall reflect the field format used in interlaced mode. (Top field in PAL is field 1, top field in NTSC is field 2.): D0: Interlaced stream or variable. 1 = Yes D1: Fields per frame. 0= 2 fields, 1 = 1 field D2: Field 1 first. 1 = Yes D3: Reserved D5..4: Field pattern 00 = Field 1 only 01 = Field 2 only 10 = Regular pattern of fields 1 and 2 11 = Random pattern of fields 1 and 2 D7..6: Reserved. Do not use.
26	bCopyProtect	1	Boolean	Specifies whether duplication of the video stream is restricted: 0: No restrictions 1: Restrict duplication

3.1.2 Uncompressed Frame Descriptor

Uncompressed Video Frame descriptors (or Frame descriptors for short) are used to describe the decoded video and still-image frame dimensions and other frame-specific characteristics supported by a particular stream. One or more Frame descriptors follow the Uncompressed

Video Format descriptor they correspond to. The Frame descriptor is also used to determine the range of frame intervals supported for the frame size specified.

The Uncompressed Video Frame descriptor is used only for video formats for which the Uncompressed Video Format descriptor applies (see section 3.1.1, "Uncompressed Video Format Descriptor").

The **bFrameIndex** field contains the one-based index of this frame descriptor, and is used by requests from the host to set and get the current frame index for the format in use. This index is one-based for each corresponding format descriptor supported by the device.

The range of frame intervals supported can be either a continuous range or a discrete set of values. For a continuous range, **dwMinFrameInterval**, **dwMaxFrameInterval** and **dwFrameIntervalStep** indicate the limits and granularity of the range. For discrete values, the **dwFrameInterval(x)** fields indicate the range of frame intervals (and therefore frame rates) supported at this frame size. The frame interval is the average display time of a single decoded video frame in 100ns units.

A Frame descriptor identifies the following.

Table 3-2 Uncompressed Video Frame Descriptors

Offset	Field	Size	Value	Description
0	bLength	1	Number	Size of this descriptor in bytes when bFrameIntervalType is 0: 38 Size of this descriptor in bytes when bFrameIntervalType > 0: 26+(4*n)
1	bDescriptorType	1	Constant	CS_INTERFACE descriptor type
2	bDescriptorSubtype	1	Constant	VS_FRAME_UNCOMPRESSED descriptor subtype
3	bFrameIndex	1	Number	Index of this frame descriptor
4	bmCapabilities	1	Number	D0: Still image supported Specifies whether still images are supported at this frame setting. This is only applicable for VS interfaces with an IN video endpoint using Still Image Capture Method 1, and should be set to 0 in all other cases. D1: Fixed frame-rate Specifies whether the device provides a fixed frame rate on a stream associated with this frame descriptor.

				Set to 1 if fixed rate is enabled; otherwise, set to 0. D7..2: Reserved, set to 0.
5	wWidth	2	Number	Width of decoded bitmap frame in pixels
7	wHeight	2	Number	Height of decoded bitmap frame in pixels
9	dwMinBitRate	4	Number	Specifies the minimum bit rate at the longest frame interval in units of bps at which the data can be transmitted.
13	dwMaxBitRate	4	Number	Specifies the maximum bit rate at the shortest frame interval in units of bps at which the data can be transmitted.
17	dwMaxVideoFrameBufferSize	4	Number	Use of this field has been deprecated. Specifies the maximum number of bytes that the compressor will produce for a video frame or still image. The dwMaxVideoFrameSize field of the Video Probe and Commit control replaces this descriptor field. A value for this field shall be chosen for compatibility with host software that implements an earlier version of this specification.
21	dwDefaultFrameInterval	4	Number	Specifies the frame interval the device would like to indicate for use as a default. This must be a valid frame interval described in the fields below.
25	bFrameIntervalType	1	Number	Indicates how the frame interval can be programmed: 0: Continuous frame interval 1..255: The number of discrete frame intervals supported (n)
26...				See the following frame interval tables.

Table 3-3 Continuous Frame Intervals

Offset	Field	Size	Value	Description
26	dwMinFrameInterval	4	Number	Shortest frame interval supported (at highest frame rate), in 100 ns units.

30	dwMaxFrameInterval	4	Number	Longest frame interval supported (at lowest frame rate), in 100 ns units.
34	dwFrameIntervalStep	4	Number	Indicates granularity of frame interval range, in 100 ns units.

Table 3-4 Discrete Frame Intervals

Offset	Field	Size	Value	Description
26	dwFrameInterval(1)	4	Number	Shortest frame interval supported (at highest frame rate), in 100 ns units.
...
26+(4*n)-4	dwFrameInterval(n)	4	Number	Longest frame interval supported (at lowest frame rate), in 100 ns units.

3.2 Video Samples

Each Uncompressed frame is considered a single video sample. A video sample is made up of one or more *payload transfers* (as defined in the USB Device Class Specification for Video Devices).

For an isochronous pipe, each (micro) frame will contain a single payload transfer. Each payload transfer will consist of a payload header immediately followed by payload data in one or more data transactions (up to 3 data transactions for high speed high bandwidth endpoints).

For a bulk pipe, the first bulk data packet of each payload transfer shall contain a payload header at the beginning of the packet, followed by payload data, extending through additional bulk data transactions as needed.

3.3 Uncompressed Payload Information

The following paragraphs describe constraints on the payload transfers.

3.3.1 Planar Formats

Transfers of planar payloads have no data alignment restrictions.

3.3.2 Packed Formats

Transfers of a packed payload format must be aligned on macro-pixel boundaries.