

Castle Link Program Settings Report

Title:

3/10/2015 2:17:32 AM Date:

т	h	ro	tt	l۵
•				

Vehicle Type Helicopter Throttle Type Governor Mode Governor Gain Low (15) (Default) **Initial Spool-Up Rate** Medium (5) (Default)

Head Speed Change Rate High (8) **Auto Rotate Enabled** False **Governor Mode Type** Fixed Vehicle Setup - Battery Type LiPo Vehicle Setup - Number of Cells 3 Vehicle Setup - Battery Voltage 11.10 Vehicle Setup - Gear Ratio 1.0000 Vehicle Setup - Motor Kv 1050 **Vehicle Setup - Motor Number of Poles** 10 **Desired Head Speed 1** 8000

Desired Head Speed 2 9000 **Desired Head Speed 3** 10000

Brake

Cutoffs

Cutoff Voltage Auto Li-Po (Default) 3.2 Volts/Cell (Default) **Auto-Lipo Volts/Cell**

Hard Cutoff **Voltage Cutoff Type**

Current Limiting Normal (70A) (Default)

Current Cutoff Type Hard Cutoff

Motor

Motor Start Power Medium (59) (Default) **Motor Timing** Normal (5) (Default) Forward (Default) **Direction PWM Rate Outrunner Mode**

Other

Power-On Beep **Enabled (Default)** Link Live Enable Disabled (Default) **BEC Voltage** 5.0V (Default) **Auxiliary Wire Mode** Disabled (Default)

Logging

Data Log Enabled 511

Sample Frequency 5 Sample / Sec

Automatic Data Reset Disabled (100%) (Default)

Software

EDGE 50 (F367.2) **Device Name**

V 4.11 **Current Firmware**