

COSTIC Castle Link Program Settings Report

7000

Title:

3/10/2015 4:15:27 AM Date:

T	_	 _	4	41	е
	n	n	т	П	\mathbf{a}

Vehicle Type Helicopter Throttle Type Governor Mode Governor Gain Low (15) (Default) Initial Spool-Up Rate Medium (5) (Default) High (8)

Head Speed Change Rate Auto Rotate Enabled False **Governor Mode Type** Fixed Vehicle Setup - Battery Type LiPo Vehicle Setup - Number of Cells 3 Vehicle Setup - Battery Voltage 11.1000 Vehicle Setup - Gear Ratio 1.000 Vehicle Setup - Motor Kv 1050 Vehicle Setup - Motor Number of Poles 10 **Desired Head Speed 1** 3000 Desired Head Speed 2 5000

Brake

Cutoffs

Desired Head Speed 3

Cutoff Voltage Auto Li-Po (Default) Auto-Lipo Volts/Cell 3.2 Volts/Cell (Default)

Voltage Cutoff Type Hard Cutoff

Current Limiting Normal (70A) (Default)

Current Cutoff Type Hard Cutoff

Motor

Motor Start Power Medium (59) (Default) **Motor Timina** Normal (5) (Default) Direction Forward (Default) **PWM Rate** Outrunner Mode

Other

Power-On Beep Enabled (Default) Link Live Enable Disabled (Default) 5.0V (Default) **BEC Voltage** Auxiliary Wire Mode Disabled (Default)

Logging

Data Log Enabled 239

Sample Frequency 5 Sample / Sec

Automatic Data Reset Disabled (100%) (Default)

Software

EDGE 50 (F367.2) **Device Name**

V 4.11 **Current Firmware**