

Encapsulation

Programming Languages

CS 214



Review

A *type* consists of two things:

- a set of _____; and
- a set of _____ onto those values.

An *abstract data type (ADT)* consists of:

- a collection of _____: $\text{type}_1 \times \text{type}_2 \times \dots \times \text{type}_n$
- a collection of _____ on the data:

$F(\text{type}_1 \times \text{type}_2 \times \dots \times \text{type}_n) \rightarrow \text{ADT}$

$G(\text{ADT}) \rightarrow \text{type}_1$

...

$H(\text{ADT}) \rightarrow \emptyset$

Obviously, these two are related...



Encapsulation

An encapsulation mechanism is a language's construct for _____ into a *single syntactic structure*.

Two different encapsulation mechanisms have evolved:

- The _____, a mechanism that lets programmers create new types that encapsulate data and operations; and
- The _____ (aka *package*), a mechanism that lets programmers store new types and their operations in a distinct container.

The evolutionary history of these provides useful context, so we'll examine the history of each separately...



ADTs

In the early 1970s, *imperative* programming languages had evolved to the point where much of programming was building _____, which consisted of an _____ and its supported _____.

For example, a *Stack* ADT consists of:

- *Initialization(&Stack)* $\rightarrow \emptyset$
- *push(value \times &Stack)* $\rightarrow \emptyset$
- *isEmpty(Stack)* $\rightarrow bool$
- *pop(&Stack)* $\rightarrow \emptyset$
- *isFull(Stack)* $\rightarrow bool$
- *top(Stack)* $\rightarrow value$


The ADT's operations make up its _____, through which users are to interact with the ADT.



ADT Example in C

```
/* IntStack.h (minus precondition checks)*/
```

```
#define STACK_MAX 32
typedef struct StackStruct {
    int myTop;
    int myValues[STACK_MAX];
} IntStack;
```



```
void init(IntStack* sRef) { sRef->myTop = -1; }

int isEmpty(IntStack s) { return s.myTop < 0; }

int isFull(IntStack s) {return s.myTop >= STACK_MAX-1;}

void push(int value, IntStack* sRef) {
    sRef->myTop++;
    sRef->myValues[sRef->myTop] = value;
}

void pop(IntStack* sRef) { sRef->myTop--; }

int top(IntStack s) { return s.myValues[s.myTop]; }
```



Problem 1

Nothing prevents a programmer from _____:

Instead of writing:

```
while ( !isFull(s) )  
    // ... do something with s
```

a programmer
can write:

```
while ( s.myTop < STACK_MAX )  
    // ... do something with s
```

If we upgrade our
array-based stack
to a linked stack:

```
/* IntStack.h ... */
```

```
typedef struct Node {  
    int value;  
    struct Node * next;  
} IntStackNode;
```

```
typedef struct StackStruct {  
    IntStackNode * top;  
} IntStack;
```

then the programmer's code _____ (↑ maintenance costs)!



Problem 2

Nothing prevents the
programmer from

```
_____ #include "IntStack.h"
_____
_____ int peekUnderTop(IntStack s)
_____ {
_____     return s.values[s.top-1];
_____ }
_____ ...
```

Such operations will also _____ if we change the implementation details that underlie the *Stack* ADT (↑ maintenance costs)!

Recall: High maintenance costs led industry from *spaghetti coding* to *structured programming*.

Eliminating the maintenance costs of “broken” code led industry from *structured programming* to _____ *programming*.



Modules and Packages

The problem with structured programming was that it did nothing to _____.

In 1977, Wirth designed *Modula* with a new “container” construct in which a type and its operations could be stored.

- Wirth called this container the _____.
- Rather than thinking of a type as values and operations, Wirth considered a type to be *just values* (i.e., data).
- The *module* was Wirth’s construct for “wrapping” a type and its operations together (i.e., building an ADT).
- Fortran (90 and later) also provides a *Module* construct

In the 1980s, Ada adopted a similar approach for ADTs, but called their container the _____ instead of the module.



ADT Example in Ada

```
-- IntStackPackage.ads is the IntStackPackage specification  
-- the Ada equivalent of a C header file
```

```
package IntStackPackage is  
  type IntStack is private;  
  
  procedure init(s: in out IntStack);  
  function isEmpty(s: in IntStack) return Boolean;  
  function isFull(s: in IntStack) return Boolean;  
  procedure push(value: in Integer; s: in out IntStack);  
  procedure pop(s: in out IntStack);  
  function top(s: in IntStack) return Integer;  
  
  private  
    STACK_MAX: constant Integer := 32;  
  
  type IntStack is  
    record  
      myTop: Integer;  
      myValues: array(1..STACK_MAX) of Integer;  
    end Stack;  
end IntStackPackage;
```

All declarations before
private are visible
externally; those after
private are local to the
package.



ADT Example in Ada (ii)

```
-- IntStackPackage.adb is the IntStackPackage body
--   the Ada equivalent of a C implementation file

package body IntStackPackage is
  procedure init(s: in out IntStack) is
  begin
    s.myTop:= 0;
  end init;

  function isEmpty(s: in IntStack) return Boolean is
  begin
    return s.myTop < 1;
  end isEmpty;

  procedure push(value: in Integer; s: in out IntStack) is
  begin
    s.myTop:= s.myTop + 1; s.myValues(s.myTop):= value;
  end;

  -- ... definitions of isFull(), pop(), top(), ...

end IntStackPackage;
```



Package Specifications

The “public section” of the specification creates its _____

- Nothing else in the package is accessible;
- If a programmer wishes to use the ADT, they must do so using the declarations in its interface.

An Ada package specification differs from a C header file:

- Its private section allows the package to _____
_____ from the programmer (everything in a header file is public).
- The specification file *must be compiled* before it can be used (and before the package body can be compiled).

By separating the ADT's *public* _____ from its *private* _____, *a programmer cannot write programs that depend upon the ADT's implementation details.*



Example Usage

Given such an ADT, a programmer can write:

```
-- IntStackTest.adb
with TextIO, IntStackPackage; use TextIO, IntStackPackage;

procedure IntStackTest is
  s1, s2: IntStack;
  i: Integer;
begin
  init(s1);

  while (not isFull(s1)) loop
    get(i); push(i, s1);
  end loop;

  s2:= s1;

  while (not isEmpty(s2)) loop
    put(top(s2)); pop(s2);
  end loop;

end IntStackTest;
```

In modular programming, ADT operations are subprograms that

Used in this way, a package/module is a container in which an ADT can be “wrapped”.



Modules/Packages As “Objects”

Modules/packages can also be used as “objects”:

```
-- IntStack.ads is the IntStack specification
```

```
package IntStack is
  function isEmpty() return Boolean;
  function isFull() return Boolean;
  procedure push(value: in Integer);
  procedure pop;
  function top() return Integer;
end IntStack;
```

All of these identifiers are public (there is no *private* section).

The operations do *not* receive the ADT via a parameter.

There is no *init* subprogram in this kind of module/package (we’ll see why shortly).



“Object” Package Bodies

```
-- IntStack.adb is the IntStack body

package body IntStack is

  STACK_MAX: constant Integer := 32;
  myTop: Integer;
  myValues: array(1..STACK_MAX) of Integer;

  function isEmpty() return Boolean is
  begin
    return myTop < 1;
  end;

  procedure push(value: in Integer) is
  begin
    myTop:= myTop+1; myValues(myTop) := value;
  end push;

  -- ... definitions of isFull, pop, top, ...
begin
  myTop:= 0;
end IntStack;
```

Note 1: All of the implementation details are here in the body, making them _____.

Note 2: A package may have an

at its end that is executed when a program using the package is run...



“Object” Modules in Use

Such modules/packages can be used in an object-like way:

```
-- IntStackTest.adb tests the IntStack package
```

```
with Text_IO, IntStack; use Text_IO;
```

```
procedure IntStackTest is  
  i: Integer;  
begin
```

```
  while (not IntStack.isFull()) loop  
    get(i);  
    IntStack.push(i);  
  end loop;
```

```
  while (not IntStack.isEmpty()) loop  
    put(IntStack.top());  
    IntStack.pop;  
  end loop;
```

```
end IntStackTest;
```

In this approach, a module/package superficially resembles an OO-language object (created from a class)...

But a module/package is _____, so it cannot be used to create variables.

→ *Only one such “object” can exist at a time.*



Generic Packages

Ada also allows packages to be given _____, providing a way to circumvent the “one object” problem:

```
-- Stack.ads is the generic Stack specification
generic
  type Item is private;           -- Item is a type parameter
  Integer size;                  -- size is a data parameter
package Stack is
  function isEmpty() return boolean;
  function isFull() return boolean;
  procedure push(v: in Item);
  procedure pop();
  function top() return Item;
end Stack;
```

Ada’s keyword _____ tells the compiler that the parameters *Item* and *size* will be supplied by the ADT’s user (ideal for containers).

Such a *Stack* stores “generic” *Items*, instead of “hardwired” *Integers*.



Generic Package Bodies

```
-- Stack.adb is the generic Stack body

package body Stack is

  myCapacity: Integer := size;
  myTop: Integer;
  myValues: array(1..myCapacity) of Item;

  function isEmpty() return Boolean is
  begin
    return myTop < 1;
  end;

  procedure push(value: in Item) is
  begin
    myTop:= myTop+1; myValues(myTop) := value;
  end push;

  -- ... definitions of isFull, pop, top, ...
begin
  myTop:= 0;
end Stack;
```

This far more elegant than _____: the compiler already knows that *Stack* is a generic package because the spec. is compiled first.

Recent versions of Fortran's *module* have added this *generic mechanism*.



Generic Instantiation

Now we can dynamically create multiple *Stack* “objects”:

```
-- StackTest.adb tests the generic Stack package
```

```
with Text_IO, Stack; use Text_IO;
procedure StackTest is
  i: Integer;
  package intStack1 is new Stack(integer, 8);
  package intStack2 is new Stack(integer, 8);
begin
  while (not intStack1.isFull()) loop
    get(i);
    intStack1.push(i);
  end loop;

  intStack2:= intStack1;

  while (not intStack2.isEmpty()) loop
    put(intStack2.top());
    intStack2.pop;
  end loop;
end StackTest;
```

This permits generic
Ada packages to be
constructed and
operated on in a way
similar to objects.



History: Simula

Back in 1967, *Dahl & Nygaard* noted that at its simplest, *programming consists of* _____.

That is, variables are _____, and since types consist of values and operations, programming can be reduced to operating on variables.

Dahl & Nygaard were working on constructs to simplify the representation of “*real world*” *objects* in software, so that real-world processes could be more easily _____.

Their language was *Simula* (*Simple universal language*) and it provided useful *Simulation* and *Process* constructs...



Simula Classes

Dahl & Nygaard reasoned that if types are *values plus operations*, then a language should provide a syntactic structure that explicitly combines data and operations.

They took the _____ construct, extended it to store *subprograms* as well as *data* and christened it the _____ (from mathematics).

Subprograms

(operations)

Data

(state information)

Their *class* construct provided for creating _____, which could then be used to *declare variables*.

In time, variables were replaced by *objects* and object-oriented programming (OOP), culminating in _____.



Example: An *IntStack* Class

```
! IntStack.sim (minus precondition checks);

Class IntStack(Size);                                ! Classes can have parameters;
  Integer Size;                                       ! Params precede 'Begin';
Begin

                                                    ! Attribute variables;
  Integer myTop;                                     ! Data encapsulated;
  Integer Array myValues(1:Size);                   ! but not hidden

                                                    ! Methods;
                                                    ! Operations encapsulated;
  Procedure Init;                                    ! Initialization;
    myTop:= 0;                                       ! 1-line methods need no 'end';

  Boolean Procedure IsEmpty;                          ! Functions are typed procs;
    IsEmpty:= myTop < 1;                            ! Assign RV to function name;

  Boolean Procedure IsFull;
    IsFull:= myTop >= Size;

! ... continued on next page ... ;
```



Example: An *IntStack* Class (ii)

! IntStack.sim (continued)

```
Procedure Push(Value);      ! Methods can have parameters;  
  Integer Value;           ! Parameters precede 'Begin';  
Begin                       ! Methods with multiple statements;  
  myTop:= myTop + 1;        ! must be 'wrapped' in a block;  
  myValues(myTop) := Value;  
End of Push;
```

```
Procedure Pop;  
  myTop:= myTop - 1;
```

```
Integer Procedure Top;  
  Top:= myValues(myTop);
```

```
Init;  
End of Stack;
```

```
! Life: code following methods;  
! is executed on object creation;
```

Simula-67 _____: nothing prevented code from:

- *accessing the class's implementation details; or*
- *violating the intent of the creator of the class.*



Simula: Using the *IntStack* Class

To use the class, we write something like this:

```
! IntStackTest.sim

Begin
  Ref(IntStack) S1, S2;           ! Reference (pointer) variables;
  Integer value;                  ! Normal variable;

  S1 :- New IntStack(8);          ! Special reference assignment;

  While Not S1.IsFull Do Begin    ! Dot-notation for messages;
    Value:= InInt;                ! no args, no parentheses;
    S1.Push(Value);               ! args require parentheses;
  End;

  S2 :- S1;                       ! Reference assignment

  While Not S2.IsEmpty Do Begin
    OutInt(S2.Top);
    S2.Pop;
  End;
End of Program;
```




Smalltalk

Smalltalk took the ideas of Simula and extended them:

- Everything (including programs) are _____
- Attribute variables are _____
- A large predefined *class library* is provided
- A GUI *integrated development environment (IDE)* is provided

Building a
Smalltalk *Stack*
class is simple,
as most of the
syntax is auto-
generated by the
IDE:





Smalltalk Operations

Adding *Stack* operations to our class is also easy: as the IDE makes templates for us

Smalltalk *Arrays* store *Objects* (more later)...

new: is a message we send the class (i.e., a *class method*):



Smalltalk Operations (ii)

Messages that are sent to an object are _____;
messages that are sent to the class are _____.

Mutators like
push and *pop* are
equally easy:

Other *Stack*
operations
(*isEmpty*, *isFull*,
top) are just as
easy...

System Browser				
Numeric-Numbers	RunArray		-- all --	pop
Collections-Abstract	Stack		initialization	push:
Collections-Unordered	WordArray		State	
Collections-Sequence			mutators	
Collections-Text			accessors	
Collections-Arrayed	instance	?	class	
Collections-Streams				
push: value myValues at: myTop put: value. myTop ← myTop + 1				

System Browser				
Numeric-Numbers	RunArray		-- all --	top
Collections-Abstract	Stack		initialization	
Collections-Unordered	WordArray		State	
Collections-Sequence			mutators	
Collections-Text			accessors	
Collections-Arrayed	instance	?	class	
Collections-Streams				
top				
↑ myValues at: myTop - 1				




Smalltalk “Programs”

“Programs” are
classes with _____
and _____ methods:

Note that we send
new: to the *class*,
not an *instance* of
the class (i.e., an
object)...

To run such
programs:




```
System Browser
My Stuff
Alice2.0-Worlds
Alice2.0-Undo
Alt-Classes
Alice2.0-Interface

StackTester
-- all --
behavior
run

instance ? class

run
| aStack aValue |
aStack ← Stack new: 32.
aValue ← 1.
[aStack isFull]
whileFalse:
    [aStack push: aValue.
    aValue ← aValue + 1].
[aStack isEmpty]
whileFalse:
    [Transcript cr; show: aStack top printString.
    aStack pop]
```



```
Workspace
st := StackTester new run.
```



C++ Classes

In 1986, _____...

```
// IntStack.h

class IntStack {
public:
    IntStack(int size);
    bool isEmpty() const;
    bool isFull() const;
    void push(int value);
    void pop();
    int top() const;
private:
    int myTop, myCapacity;
    int * myValues;
};
```

```
// IntStack.h (cont'd)

inline IntStack::IntStack(int size){
    myTop = -1;
    myCapacity = size;
    myValues = new int[size];
}

inline
bool IntStack::isEmpty() const{
    return myTop < 0;
}

inline void
IntStack::push(int value) const {
    myValues[++myTop] = value;
}

// ... other operation definitions ...
```

More complex operations can be separately compiled...



Using C++ Classes

C++ objects can be _____:

```
// IntStackTest1.cpp

#include "IntStack.h"

int main() {
    IntStack s(8);
    int aValue;

    while ( !s.isFull() ) {
        cin >> aValue;
        s.push(aValue);
    }

    while ( !s.isEmpty() ) {
        cout << s.top() << ' ';
        s.pop();
    }
}
```

```
// IntStackTest2.cpp

#include "IntStack.h"

int main() {
    IntStack* s = new IntStack(8);
    int aValue;

    while ( !s->isFull() ) {
        cin >> aValue;
        s->push(aValue);
    }

    while ( !s->isEmpty() ) {
        cout << s->top() << ' ';
        s->pop();
    }
}
```

In _____ languages, objects *must* be dynamically allocated.



Java Classes

In 1993, _____, based on C++ and Smalltalk.

```
// IntStack.java

public class IntStack {
    public IntStack(int size) {
        myTop = -1;
        myCapacity = size;
        myValues = new int[size];
    }

    public boolean isEmpty() {
        return myTop < 0;
    }

    public boolean isFull() {
        return myTop >= myCapacity;
    }
}
```

```
// IntStack.java (cont'd)

    public void push(int value) {
        myValues[++myTop] = value;
    }

    public void pop() {
        --myTop;
    }

    public int top() {
        return myValues[myTop];
    }

    private int    myTop,
                  myCapacity;
    private int [] myValues;
}
```

Java mixes _____ ...



Using Java Classes

Like Smalltalk,
Java objects *must*
be dynamically
allocated:

Class variables are

so dot notation is
used (vs. C++ ->)

Also like Smalltalk,
every Java subprog.

But most of Java's _____ is more similar to C++ than Smalltalk...

```
// IntStackTest.java

import IntStack;

class IntStackTest {
    public static void main(String [] args) {
        IntStack s = new IntStack(8);
        int aValue = 11;

        while ( !s.isFull() ) {
            s.push(aValue);
            aValue++;
        }

        while ( !s.isEmpty() ) {
            System.out.println( s.top() );
            s.pop();
        }
    }
}
```



C++ Templates

C++ classes can have _____ (→ Ada *generic packages*):

```
// Stack.h
template<class Item>
class Stack {
public:
    Stack(int size);
    bool isEmpty() const;
    bool isFull() const;
    void push(Item value);
    void pop();
    Item top() const;
private:
    int myTop, myCapacity;
    Item * myValues;
};

#include "Stack.cpp"
```

```
// Stack.cpp
template<class Item>
inline Stack<Item>::Stack(int size) {
    myTop = -1;
    myCapacity = size;
    myValues = new Item[size];
}

template<class Item>
inline bool Stack<Item>::isEmpty() {
    return myTop < 0;
}

template<class Item>
inline Item Stack<Item>::top() {
    return myValues[myTop];
}

// ... isFull, push, pop, ...
```

This is pretty clunky compared to Ada's *generic mechanism*...



C++ Template Instantiation

A template is a _____...

```
// StackTest1.cpp
```

```
#include "Stack.h"
```

```
int main() {  
    Stack<int> s(32);  
    int aValue;
```

```
    while ( !s.isFull() ) {  
        cin >> aValue;  
        s.push(aValue);  
    }
```

```
    while ( !s.isEmpty() ) {  
        cout << s.top() << ' ' ;  
        s.pop();  
    }
```

```
}
```

```
// StackTest1.cpp
```

```
#include "Stack.h"
```

```
#include "Student.h"
```

```
int main() {  
    Stack<Student> s(32);  
    Student aValue;
```

```
    while ( !s.isFull() ) {  
        cin >> aValue;  
        s.push(aValue);  
    }
```

```
    while ( !s.isEmpty() ) {  
        cout << s.top() << ' ' ;  
        s.pop();  
    }
```

```
}
```

Templates are esp. useful in creating classes that *contain* other objects.



Old Java Containers

Prior to Java 1.5, Java had no generics, but all classes have a common ancestor *Object*, so _____ were used:

```
// Stack.java

public class Stack {
    public Stack(int size) {
        myTop = -1;
        myCapacity = size;
        myValues = new Object[size];
    }

    public boolean isEmpty() {
        return myTop < 0;
    }

    public boolean isFull() {
        return myTop >= myCapacity-1;
    }
}
```

```
// Stack.java (cont'd)

public void push(Object value) {
    myValues[++myTop] = value;
}

public void pop() {
    --myTop;
}

public Object top() {
    return myValues[myTop];
}

private int        myTop,
                   myCapacity;
private Object [] myValues;
}
```

This can store *any object* _____



Old Java: Using *Object* Containers

Since our *Stack*
stores *Objects*...

1. We can't store a
primitive type
(e.g., *int*) directly,
but Java provides a

for each primitive
type...

2. _____ must
be used to retrieve
the stored values...

```
// StackTest.java

import Stack;

class StackTest {
    public static void main(String [] args) {
        Stack s = new Stack(8);
        int aValue = 11;

        while ( !s.isFull() ) {
            s.push( new Integer(aValue) );
            aValue++;
        }

        while ( !s.isEmpty() ) {
            Integer anInteger = (Integer) s.top();
            int anInt = anInteger.intValue();
            System.out.println(anInt);
            s.pop();
        }
    }
}
```



Newer Java Containers

Java 1.5 added _____ and _____:

```
// Stack.java

public class Stack<Item> {
    public Stack(int size) {
        myTop = -1;
        myCapacity = size;
        myValues = (Item[])
                    new Object[size];
    }
    public boolean isEmpty() {
        return myTop < 0;
    }
    public boolean isFull() {
        return myTop >= myCapacity-1;
    }
}
```

```
// Stack.java (cont'd)

public void push(Item value) {
    myValues[++myTop] = value;
}

public void pop() {
    --myTop;
}

public Item top() {
    return myValues[myTop];
}

private int      myTop,
                myCapacity;
private Item []  myValues;
}
```

Such a *Stack* can still store _____...



Java: Using *Generic* Containers

Since *Stack*<*Item*>
stores *Objects*...

1. We can't pass a
primitive type arg
(e.g., *int*), but we can
pass a _____.

2. _____ lets
us pass primitive-
type-values as args.

3. _____ lets
us retrieve *Items* as
primitive type-vals.

```
// StackTester.java

import Stack;

class StackTester {
    public static void main(String [] args) {
        Stack<Integer> s = new Stack<>(8);
        int aValue = 11;

        while ( !s.isFull() ) {
            s.push( aValue ); // int auto-boxed
            aValue++;
        }

        while ( !s.isEmpty() ) {
            int anInt = s.top(); // auto-unboxed
            System.out.println(anInt);
            s.pop();
        }
    }
}
```



Summary

To achieve the goals of abstract data typing, we need:

- _____: data and operations in _____;
- _____: the ability to _____.

Two different mechanisms have evolved for doing so:

- *The* _____: a container for storing a data-type and its operations (aka the _____).
- *The* _____: a type-constructor that stores data and operations.

The class is better for _____;
the module is better for _____.

Containers are packages or classes that _____.

- _____ support stronglytyped containers.
- *Generic containers* can be built in most modern languages.

