

Specifying Syntax with BNFs (Backus Naur Forms)

Programming Languages

CS 214



Sentence Structure

Consider the following “sentences”

- *there is hair in my soup*
- *there is soup in my hair*
- *is there soup in my hair*

What does each “sentence” mean?

What about this “sentence”?

- *hair soup there my is in*

→ The _____ determines the meaning...

What determines which word-orders are *meaningful*?



Grammar & Syntax

Every language has a set of rules - its _____ -
that specifies the word-sequences that form valid sentences.

The “sentence”:

- *hair soup there my is in*

is not valid, because it violates English’s grammar rules
(i.e., it contains _____).

Grammar and syntax help us decode a sentence’s meaning:

syntax were read to easier sentence would unimportant this if be



Syntax Matters In Real Life



© 2003 GEC, Inc./Dist. by UFS, Inc.



Semantics

When a sentence has correct syntax, our brains can determine what the words in the sentence mean: their _____.

Consider: *time flies like an arrow, fruit flies like a banana*

→ *flies* and *like* have two different meanings

We decode a word's meaning using its _____.

Since a word's semantics (meaning) depends on its context,
English is a _____.

If a sentence contains syntax errors, we can't understand it, because syntax specifies what words can be adjacent, and a word's semantics depends on the words surrounding it.



Program Sentences

A program is a “sentence” in a programming language.

A program’s “meaning” depends on the order of its symbols.

To be valid, the order must obey the syntax rules of the language; for example:

x = y + 1;

is a valid statement in some languages (e.g., _____)
but not in others (e.g., _____).

The meanings of the “words” in a program are determined by the _____ of the language in which it’s written.



Syntax Errors

Syntax rules specify those symbol-orderings that are valid, allowing a compiler to determine symbol-meanings.

```
x = y + 1;      →  MOV  y,  R0
                  ADD  #1,  R0
                  STO  R0,  x
```

When a program contains syntax errors, a compiler is unable to translate it (i.e., determine its meaning):

y + 1 = x; → ?

A compiler cannot determine the meaning of any “phrase” that violates the language’s syntax rules.



BNF

The _____ is a tool for specifying the syntax of a high level language (HLL).

Example: A BNF giving the structure of C++ identifiers is:

```
<identifier>      ::= <first_letter> <valid_sequence>
<first_letter>    ::= <letter> | _
<valid_sequence>  ::= <valid_symbol> <valid_sequence> | ε
<valid_symbol>    ::= <letter> | <digit> | _
<letter>          ::= A|B|C|D|E|F|G|H|I|J|K|L|M|N|O|P|Q|
                    R|S|T|U|V|W|X|Y|Z|a|b|c|d|e|f|g|h|i|
                    j|k|l|m|n|o|p|q|r|s|t|u|v|w|x|y|z
<digit>           ::= 0|1|2|3|4|5|6|7|8|9
```

A correct BNF specifies all valid “sentences”, and prohibits all invalid “sentences”.



Examples:

Is *R2D2* a valid sentence in our <identifier> language?

<identifier>
<first_letter> <valid_sequence>
<letter> <valid_sequence>
R <valid_sequence>
R <valid_symbol> <valid_sequence>
R <digit> <valid_sequence>
R 2 <valid_sequence>
R 2 <valid_symbol> <valid_sequence>
R 2 <letter> <valid_sequence>
R 2 D <valid_sequence>
R 2 D <valid_symbol> <valid_sequence>
R 2 D <digit> <valid_sequence>
R 2 D 2 <valid_sequence>
R 2 D 2 ϵ

This sequence of steps
is called a *derivation*.

“Sentences” not conforming to the BNF are *invalid*.



Formal Definitions

Let Σ be a set of symbols.

- A *string over Σ* is a finite sequence of zero or more symbols from the set Σ .
- Symbols whose meaning is predefined are called *terminals*.
 - Symbols like `A`, `_`, `6`, etc. are terminals in our `<identifier>` BNF.
- Symbols whose meanings must be defined are called *non-terminals*, and are enclosed in angle-brackets (`<` and `>`).
 - Symbols like `<identifier>`, `<letter>`, etc. are non-terminals.
 - Like variables, non-terminals usually describe what they represent.
- One symbol is designated as the *starting non-terminal*.
 - The symbol `<identifier>` is the starting non-terminal in our BNF.



Formal Definitions (ii)

- Each non-terminal must be defined by a *production* (rule):

$$\langle \text{LHS} \rangle ::= \langle \text{RHS} \rangle$$

where: $\langle \text{LHS} \rangle$ is the nonterminal being defined,
 $\langle \text{RHS} \rangle$ is a string of terminals and/or
nonterminals defining $\langle \text{LHS} \rangle$.

- Different productions defining the same non-terminal:

$$\langle \text{NT}_i \rangle ::= \text{Def}_1$$
$$\langle \text{NT}_i \rangle ::= \text{Def}_2$$
$$\dots$$
$$\langle \text{NT}_i \rangle ::= \text{Def}_n$$

can be written in shorthand using the OR (|) operator:

$$\langle \text{NT}_i \rangle ::= \text{Def}_1 \mid \text{Def}_2 \mid \dots \mid \text{Def}_n$$


Formal Definitions (iii)

- A BNF is a quadruple: (Σ, N, P, S) , where:
 - Σ is the set of symbols in the BNF;
 - N is the subset of Σ that are nonterminals in the language;
 - P is the set of productions defining the symbols in N ; and
 - S is the element of N that is the starting nonterminal.
- A *derivation* is a sequence of strings, beginning with the starting nonterminal S , in which each successive string replaces a nonterminal with one of its productions, and in which the final string consists solely of terminals.
 - A derivation is sometimes called a *parse*.



Formal Definitions (iv)

- A BNF _____ is a tree, such that
 - the root of the tree is the starting nonterminal (S) in the BNF;
 - the children of the root are the symbols (L to R) in a production whose <LHS> is S, the starting nonterminal;
 - each terminal child is a leaf; and
 - each nonterminal child is the root of a derivation tree for that nonterminal.
- The act of building a derivation tree for a sentence (to check its correctness) is called _____ that sentence.
 - The set of valid sentences in a language is the set of all sentences for which a parse tree exists!
- A _____ is a derivation built by *always expanding the left-most non-terminal* in a production.



Examples

Do parse trees (using our <identifier> BNF) exist for these?

i

a1b2

5

\$



Recursive Productions

Our identifier-BNF permits identifiers to have arbitrary lengths through the use of *recursive productions*:

$$\langle \text{valid_sequence} \rangle ::= \langle \text{valid_symbol} \rangle \langle \text{valid_sequence} \rangle \mid \epsilon$$

This production is recursive because the non-terminal on the <LHS> appears in the production (on the <RHS>).

The recursive production provides for *unrestricted repetition* of the non-terminal being defined, which is useful what is being defined can be appear _____.

The ϵ -production provides both:

- a *base-case* for trivial instances of the non-terminal, and
- an *anchor* to terminate the recursion.



Writing BNFs: A 3-Step Process

A. Start with _____.

B. Build the productions to define the non-terminal:

1. Start with the question: _____?

2. If a construct is _____:

- a. create a new nonterminal for that construct;
- b. add a production for the non-optional case;
- c. add an ϵ -production for the optional case.

3. If a construct can be _____:

- a. create a new nonterminal for that construct;
- b. add an ϵ -production for the zero-reps case;
- c. add a recursive production for the other cases.

C. For each nonterminal in the <RHS> of every production:

repeat step B until all nonterminals have been defined.



Example: C++ *if* Statement

A. Create a non-terminal for what we're defining:

`<if_stmt>`

B. Build a production to define it: what comes first?

1. keyword _____

2. open parentheses

3. _____

4. close parentheses

5. _____

6. _____

`<if_stmt>` ::= _____

C. Repeat B for each undefined non-terminal:

`<else_part>` ::= _____

(We'll see how to define `<expr>` and `<stmt>` a bit later...)



A Small Problem

The C++ if statement presents a small problem: Consider...

```
if ( a < b) if (a < c) S1 else S2
```

Take a moment to build a parse tree for this “sentence”...



Ambiguities

When a “sentence” has multiple parse trees, it is _____
(i.e., it has multiple interpretations and/or meanings).

The two parses reflect different ways to associate the **else**:

```
if (a < b)
    if (a < c)
        S1
    else
        S2
```

```
if (a < b)
    if (a < c)
        S1
else
    S2
```

The grammar cannot resolve which is meant,
so C++ uses a _____ to resolve the ambiguity:

*An **else** associates with the closest prior unterminated **if**.*



Example: C++ *do* Statement

A. Create a non-terminal for what we're defining:

`<do_stmt>`

B. Build a production to define it: what comes first?

- | | |
|------------------|----------------------|
| 1. keyword _____ | 2. _____ |
| 3. keyword _____ | 4. open parentheses |
| 5. an expression | 6. close parentheses |
| 6. a semicolon | |

`<do_stmt>` ::= _____

C. Repeat B for each undefined non-terminal...

`<stmt>` isn't too bad, so let's tackle it next.



Example: C++ <stmt>

A. Create a non-terminal for what we're defining:

<stmt>

B. Build a production to define it: what comes first?

- It depends on the kind of statement being described...
- There are seven different kinds of C++ statements, so let's introduce a new non-terminal for each one:

<stmt> ::= <compound_stmt> | <selection_stmt> |
<iteration_stmt> | <expression_stmt> |
<jump_stmt> | <labeled_stmt> | <declaration_stmt>

C. Repeat B for each undefined non-terminal...

<compound_stmt> ::= _____

<stmt_list> ::= _____



Example: C++ <stmt> (ii)

<selection_stmt>	::= <if_stmt> <switch_stmt>
<iteration_stmt>	::= <while_stmt> <do_stmt> <for_stmt>
<expression_stmt>	::= <opt_expr> ;
<opt_expr>	::= <expr> ε
<jump_stmt>	::= break ; continue ; return <opt_expr> ; goto <identifier> ;
<labeled_stmt>	::= <identifier> : <stmt> case <literal> : <stmt> default : <stmt>
<declaration_stmt>	::= <object_dec> <function_dec> <class_dec>
<object_dec>	::= <modifier> <type> <identifier> <initializer> <more_ids> ;
<modifier>	::= register const static auto extern mutable ε
<type>	::= char wchar_t bool short int long signed unsigned float double <identifier> <identifier> :: <type>
<initializer>	::= = <expr> ε
<more_ids>	::= , <identifier> <initializer> <more_ids> ε
...	



Example: C++ Assignment Exprs

A. Create a non-terminal for what we're defining:

`<assign_expr>`

B. Build a production to define it: what comes first?

- Many things might come first (variable, pointer, array, ...) so let's introduce a non-terminal to hide the details.
- Next comes an assignment operator; then an expression:

`<assign_expr> ::= _____`

C. Repeat B for each undefined non-terminal...

`<lvalue> ::= _____`

`<unary_op> ::= _____`

`<id_suffix> ::= [<expr>] <id_suffix> | . <lvalue> <id_suffix> |
-> <lvalue> <id_suffix> | ε`

`<assign_op> ::= _____ | += | -= | *= | /= | %= | <<= | >>= | &= | |= | ^=`



Expressions

C++ expressions are complicated:

- Each of its 52 operators must be included
- Each of its 17 precedence levels must be included
- Associativity rules must be enforced
- The grammar/BNF must be unambiguous

Example: For the expression:

$$2 + 3 * 4$$

our grammar must ensure that:


$$2 + (3 * 4) = 14$$

is evaluated, not:

$$(2 + 3) * 4 = 20$$

Which parse tree is correct?

Our grammar must *only* generate the correct one.



Grammar and Precedence

To ensure that higher precedence operators appear lower in the parse tree, we must build _____ into our BNF:

```
<expr>          ::= ... | <add_expr> | ...
<add_expr>      ::= <mul_expr> | <add_expr> + <mul_expr> |
                   <add_expr> - <mul_expr>
<mul_expr>      ::= <value> | <mul_expr> * <expr> |
                   <mul_expr> / <expr> | <mul_expr> % <expr>
```

Rules like these ensure that
“multiply-level” operators
will be applied before “add-
level” operators...

```

      <expr>
      <add_expr>
      <add_expr> + <mul_expr>
<mul_expr>  <mul_expr> * <expr>
<value>    <value>    <add_expr>
      2          3      <mul_expr>
                      <value>
                      4
```




Grammar and Associativity


_____ gives ordering of equal-precedence operators.

Examples: $8 - 4 - 2$ vs. $x = y = z$

- is left-associative;
which is correct?



= is right-associative;
which is correct?



Associativity can be built into a grammar by using _____
_____ *productions* for left-associative operators; and
_____ *productions* for right-associative operators.



Associativity Examples

Example: Since +, - are left-associative, we write:

$\langle \text{add_expr} \rangle ::= \langle \text{mul_expr} \rangle \mid \underline{\hspace{10em}} \mid$

but since = is right-associative, we write what amounts to:

$\langle \text{assign_expr} \rangle ::= \underline{\hspace{10em}}$

These generate the correct parse trees for each expression:

```

      <expr>
      <add_expr>
    <add_expr> - <mul_expr>
<add_expr> - <mul_expr> <value>
<mul_expr>      <value>      2
  <value>          4
    8
    
```

```

      <expr>
      <assign_expr>
    <lvalue> <assign_op> <assign_expr>
<identifier> = <lvalue> <assign_op> <assign_expr>
  x          <identifier>      =      <add_expr>
                                   <mul_expr>
                                   <identifier>
                                   z
    
```



C++ Expressions

<expr>	::=	<assign_expr> <expr> , <assign_expr>
<assign_expr>	::=	<lvalue> <assign_op> <assign_expr> <cond_expr>
<cond_expr>	::=	<lor_expr> <lor_expr> ? <expr> : <cond_expr>
<lor_expr>	::=	<land_expr> <lor_expr> <land_expr>
<land_expr>	::=	<bor_expr> <land_expr> && <bor_expr>
<bor_expr>	::=	<xor_expr> <bor_expr> <xor_expr>
<xor_expr>	::=	<band_expr> <xor_expr> ^ <band_expr>
<band_expr>	::=	<equ_expr> <band_expr> & <equ_expr>
<equ_expr>	::=	<rel_expr> <equ_expr> == <rel_expr> <equ_expr> != <rel_expr>
<rel_expr>	::=	<shft_expr> <rel_expr> < <shft_expr> <rel_expr> > <shft_expr> <rel_expr> <= <shft_expr> <rel_expr> >= <shft_expr>
<shft_expr>	::=	<add_expr> <shft_expr> << <add_expr> <shft_expr> >> <add_expr>
<add_expr>	::=	<mul_expr> <add_expr> + <mul_expr> <add_expr> - <mul_expr>
<mul_expr>	::=	<ptr_expr> <mul_expr> * <ptr_expr> <mul_expr> / <ptr_expr> <mul_expr> % <ptr_expr>
<ptr_expr>	::=	...



Exercise

Build a parse tree for: $a = x + y / z ;$



EBNF

The BNF is the most general tool for expressing syntax.

Another tool frequently used is the _____.

The differences are:

- EBNF terminals are distinguished from non-terminals by
 - Capitalizing the first-letter of non-terminals, AND
 - Underlining, single-quoting, or bolding terminals (instead of surrounding non-terminals by angle-brackets).
- Parentheses may be used to denote grouping.
- _____ surround symbols that are _____.
 - No recursion!
- _____ surround symbols that are _____.
 - No ϵ -productions!



Examples

1. To specify a C++ block using EBNF:

- First comes a brace, then zero or more statements, then a brace:

_____ ::= _____

2. To specify a C++ int literal using EBNF:

- An optional sign, an optional base specifier, at least one digit

_____ ::= _____

Sign ::= + | -

Digit ::= 0 | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9

3. To specify a C++ do statement using EBNF:

- Keyword do, a statement, keyword while, an open-parentheses, an expression, a close-parentheses, a semicolon:

_____ ::= _____



Problems

1. Specify a C++ identifier using EBNF:
2. Specify a C++ while statement using EBNF:
3. Specify a C++ if statement using EBNF:



Why use BNFs instead of EBNFs?

The recursive productions in BNFs make it easier for a compiler to parse “sentences” in the language...

Basic Parsing Algorithm:

0. Push S (the starting symbol) onto a stack.
 1. Get the first terminal symbol t from the input file.
 2. Repeat the following steps:
 - a. Pop the stack into $topSymbol$;
 - b. If $topSymbol$ is a nonterminal:
 - 1) Choose a production p of $topSymbol$ based on t
 - 2) If $p \neq \epsilon$:
Push p right-to-left onto the stack.
 - c. Else if $topSymbol$ is a terminal && $topSymbol == t$:
Get the next terminal symbol t from the input file.
 - d. Else
Generate a ‘parse error’ message.
- while the stack is not empty.



Example

Suppose our rules are:

$\langle \text{var_dec} \rangle ::= \langle \text{type} \rangle \text{ id } \langle \text{id_list} \rangle ; \langle \text{var_dec} \rangle \mid \epsilon$

$\langle \text{type} \rangle ::= \text{int} \mid \text{char} \mid \text{float} \mid \text{double} \mid \dots$

$\langle \text{id_list} \rangle ::= , \langle \text{id} \rangle \langle \text{id_list} \rangle \mid \epsilon$

Let's parse the declaration: **int x, y;**
assuming that $\langle \text{var_dec} \rangle$ is our starting symbol.

stack:

<var_dec>	<type>	int	id	<id_list>	,	id	<id_list>	;	<var_dec>
	id	id	<id_list>	;	id	<id_list>	;	<var_dec>	
	<id_list>	<id_list>	;	<var_dec>	<id_list>	;	<var_dec>		
	;	;	<var_dec>		;	<var_dec>			
	<var_dec>	<var_dec>			<var_dec>				

t: _____



Summary

There are different ways to specify the syntax of a language.
Two of them are:

- _____
- _____

The EBNF is simpler and easier to use, so it is frequently used in _____.

The BNF's recursive- and ϵ -productions simplify the task of parsing, so it is more useful to _____.

