Capacity-Radius Proximity for Smooth-Domain Reed–Solomon Codes

Chloe van der Vlugt

Abstract

We study list decoding and mutual correlated agreement for constant-rate Reed–Solomon codes over smooth evaluation domains. A field-valued two-coordinate plane is exactly a word in $(\mathbb{F}^2)^n$, equivalently the base–direction pair of an affine line of scalar received words. This lossless identification separates pair-code distance, list size, and scalar-projection error.

At count radius $n-k$, a direct agreement-set injection and a matching received-word construction prove

$$L_m\left(\mathcal{C}, \frac{n-k}{n}\right) = \binom{n}{k}$$

for $1 \le k \le n$ and every positive interleaving width. Thus $\binom{n}{k} \le \varepsilon|\mathbb{F}|$ is necessary and sufficient for the fractional list target at this endpoint. A next-shell construction gives a three-regime phase split. For same-set pair mutual correlated agreement, an injective compressed-certificate map gives the radius-independent bound

$$|\operatorname{Bad}_{\mathrm{MCA}}| \le \binom{n}{k+1}.$$

An explicit rate-1/4 smooth family over $\mathbb{F}_{3^n}$ satisfies both $\binom{n}{k} \le 2^{-128}|\mathbb{F}|$ and $\binom{n}{k+1} \le 2^{-128}|\mathbb{F}|$. Thus its list target holds at the capacity endpoint and its pair-MCA error is at most 2^{-128} at every normalized radius. We define the exact bad-count spectrum $B_{\mathcal{C}}(r)$ and certify a sharp transition for the same error target over

$$q = 2^{128} + 192513 \equiv 1 \pmod{4096}, \qquad (n,k) = (4096, 1024).$$

Here $B_{\mathcal{C}}(0) = 1$ and $B_{\mathcal{C}}(1) \ge 2$: the greatest safe count radius is zero, the first unsafe count radius is one, and the safe real-radius set is $[0, 1/4096)$. The intermediate field-size list-decoding optimum remains open. We also trace the existing committed-cochain projection to the pair-code interface and identify the upstream metric comparison required for a commitment-specific radius theorem.

Contents

1 Introduction **3**

2 Problem Setup **4**
2.1 Reed–Solomon parameters 4
2.2 Relative Hamming distance 4
2.3 Interleaving 5
2.4 List-decoding balls 5

3 Planes, Pair Words, and Affine Lines **5**
3.1 The full ambient pair space 5
3.2 Pair words as affine lines 6
3.3 Challenge evaluation is lossy 6

4 The Capacity-Radius Regime **7**
4.1 The finite Hamming grid 7
4.2 An explicit smooth large-field family 7
4.3 The field-size inequality 8

5 The Capacity-Grid List Theorem **8**
5.1 Scope relative to the Grand Challenge 11

6 Pair Mutual Correlated Agreement **11**
6.1 Bad challenges 11
6.2 An exact small-radius boundary instance 13
6.3 Distance interpretation 14
6.4 Endpoint interpretation 15
6.5 Commit-then-challenge order 15
6.6 Scope 15

7 Application Interface **16**
7.1 The existing committed-cochain projection 17
7.2 A canonical-lift obstruction and a no-wrap profile 19
7.3 Three native metrics for modular cochains 20
7.4 Scope of the instantiated application 22

8 Formalization and Proof Ledger **23**
8.1 Standalone hierarchy 23
8.2 Status ledger 25
8.3 Submission boundary 26

8.4 Remaining interfaces 27

1 Introduction

The Grand List Decoding and Grand Mutual Correlated Agreement challenges ask for quantitative proximity guarantees for constant-rate Reed–Solomon codes over smooth evaluation domains [ABF26]. We work with the two-fold interleaving $\mathcal{C}^{\equiv 2} \subseteq (\mathbb{F}^2)^n$. Every received pair $p = (p_0, p_1)$ determines the scalar affine line

$$p \in (\mathbb{F}^2)^n \quad \longmapsto \quad y_\gamma = p_0 + \gamma p_1 \in \mathbb{F}^n.$$

List decoding controls the ambiguity of the full pair, while mutual correlated agreement bounds the fraction of challenges for which scalar agreement fails to extend to pair agreement on the same coordinate set.

At the capacity-grid radius $(n-k)/n$, we prove the exact universal list size

$$L_m\left(\mathcal{C}, \frac{n-k}{n}\right) = \binom{n}{k}$$

for every positive interleaving width. A matching next-shell construction gives the resulting three-regime field-size phase split. For pair MCA, an injective compressed-certificate map proves the radius-independent bound

$$|\operatorname{Bad}_{\mathrm{MCA}}| \le \binom{n}{k+1}.$$

An explicit smooth rate-1/4 family over $\mathbb{F}_{3^n}$ meets both 2^{-128} fractional targets. Its actual field/subgroup realization, endpoint constructions, MCA certificate bound, complete phase split, real safe intervals and generic distance/calibration endpoints are machine-checked in Lean. The endpoint arguments are elementary interpolation; the exponential alphabet and allowable lists do not establish an efficient decoder or a polynomial-list improvement.

To resolve the first nontrivial MCA transition rather than only give a uniform sufficient bound, we define the exact spectrum

$$B_{\mathcal{C}}(r) = \max_p |\operatorname{Bad}_{\mathrm{MCA}}(\mathcal{C}, r/n, p)|.$$

For the certified smooth prime-field instance $q = 2^{128} + 192513 \equiv 1 \pmod{4096}$, $n = 4096$, and $k = 1024$, we prove $B_{\mathcal{C}}(0) = 1$ and $B_{\mathcal{C}}(1) \ge 2$. It follows that zero is the greatest safe count radius and one the first unsafe

count radius at the 2^{-128} MCA error target. Over real radii the safe interval is $[0, 1/4096)$, so its supremum is $1/4096$ and is not itself safe.

The coding theorems quantify over the complete ambient received-word and affine-line spaces. Their 2^{-128} instantiation uses the displayed exponential-size field and is not a claim about every supplied smooth code. For an application whose observations lie upstream of the pair carrier, its source metric may be defined by pullback along the extraction map. Applications retaining a different source metric must provide one explicit comparison to the pair-code distance.

This is Paper 3 of the Homotopical Encryption program. Paper 1 develops the HCP foundations and its application-specific projection bridge; Paper 2 addresses protocol evidence, commitments, and runtime verification. The coding theorems here do not require either paper's hidden geometry or commitment construction. A protocol using them must enforce the fixed-pair, later-challenge order described in Section 6. Section 7 traces the existing committed-cochain object through the actual plane extraction and field-pair calibration. The commitment-specific contribution to complete is a concrete radius theorem for that projection, with its source metric and remaining comparison stated explicitly.

2 Problem Setup

2.1 Reed–Solomon parameters

Let $\mathbb{F}$ be a finite field and let $\mathcal{L} = (a_i)_{i \in I}$ be an injectively indexed evaluation domain, where $|I| = n$. For $1 \le k \le n$, define

$$\mathcal{C} = \mathrm{RS}[\mathbb{F}, \mathcal{L}, k] = \{(f(a_i))_{i \in I} : f \in \mathbb{F}[X],\ \deg f < k\}\,.$$

The rate is $\rho = k/n$. The prize-facing regime takes ρ from a fixed constant set, such as

$$\left\{\frac{1}{2}, \frac{1}{4}, \frac{1}{8}, \frac{1}{16}\right\},$$

and requires $\mathcal{L}$ to have an appropriate smooth structure.

2.2 Relative Hamming distance

For a finite alphabet A and $u, v \in A^I$, let

$$d_H(u, v) = |\{i \in I : u_i \neq v_i\}|, \qquad \Delta(u, v) = \frac{d_H(u, v)}{n}.$$

For a nonempty code $\mathcal{D} \subseteq A^I$, define

$$\Delta(w, \mathcal{D}) = \min_{c \in \mathcal{D}} \Delta(w, c).$$

Unless stated otherwise, radii are relative radii in $[0, 1]$. The uniform MCA bound also allows arbitrary real values of its radius parameter. Natural-number radii describe the finite Hamming grid and its rounding; distances in the main statements are normalized by n.

2.3 Interleaving

For a positive integer m, define

$$\mathcal{C}^{\equiv m} = \left\{ p \in (\mathbb{F}^m)^I : \text{for every } j \in \{1, \ldots, m\},\ (p_{i,j})_{i \in I} \in \mathcal{C} \right\}.$$

Hamming distance on $(\mathbb{F}^m)^I$ counts a coordinate i as erroneous when the complete vector symbol differs. It does not sum componentwise scalar distances.

2.4 List-decoding balls

For $w \in (\mathbb{F}^m)^I$ and $\delta \in [0, 1]$, define

$$\Lambda(\mathcal{C}^{\equiv m}, w, \delta) = \{ c \in \mathcal{C}^{\equiv m} : \Delta(w, c) \leq \delta \}.$$

The worst-case list size is

$$L_m(\mathcal{C}, \delta) = \max_{w \in (\mathbb{F}^m)^I} |\Lambda(\mathcal{C}^{\equiv m}, w, \delta)|.$$

The maximum over received words is essential. A bound on a structured subset of received words is an application result, not the universal list-decoding statement.

3 Planes, Pair Words, and Affine Lines

3.1 The full ambient pair space

Define a field-valued two-coordinate plane to be a function

$$p : I \longrightarrow (\{0, 1\} \longrightarrow \mathbb{F}).$$

By reassociating function spaces, the plane carrier is exactly

$$I \to (\{0, 1\} \to \mathbb{F}) \cong (\mathbb{F}^2)^I.$$

Thus the word “plane” introduces no restriction on the received-word space.

Proposition 3.1 (Plane–pair equivalence)**.** *The map sending a plane p to the vector word*

$$i \longmapsto (p(i,0), p(i,1))$$

is a bijection from field-valued planes to $(\mathbb{F}^2)^I$. It preserves and reflects Hamming distance.

Proof. The inverse sends a pair word w to the function

$$(i,j) \longmapsto w_i(j).$$

Both composites are pointwise identities. At coordinate i, the two planes are equal exactly when their complete pair symbols are equal, so the Hamming disagreement sets coincide. □

3.2 Pair words as affine lines

For a plane p, define its base and direction by

$$p_0(i) = p(i,0), \qquad p_1(i) = p(i,1).$$

The associated affine line of scalar received words is

$$\ell_p(\gamma) = p_0 + \gamma p_1, \qquad \gamma \in \mathbb{F}.$$

Proposition 3.2 (Plane–line equivalence)**.** *The map $p \mapsto (p_0, p_1)$ is a bijection between field-valued planes and affine-line presentations consisting of an arbitrary base word and arbitrary direction word in $\mathbb{F}^I$.*

Proof. Given an arbitrary pair (f_0, f_1), define

$$p(i,0) = f_0(i), \qquad p(i,1) = f_1(i).$$

This construction is inverse to taking base and direction. □

3.3 Challenge evaluation is lossy

For fixed γ, the map

$$(p_0, p_1) \longmapsto p_0 + \gamma p_1$$

is generally many-to-one. Consequently, distance of the pair from the code cannot be inferred deterministically from one fixed challenge without an additional good-challenge hypothesis. MCA supplies a probabilistic statement over a challenge sampled after the pair has been fixed.

4 The Capacity-Radius Regime

4.1 The finite Hamming grid

Let $1 \le k \le n$. The capacity endpoint is already an attainable normalized Hamming radius:

$$r_{\mathrm{cap}} = n - k, \qquad \delta_{\mathrm{cap}} = \frac{n-k}{n} = 1 - \rho.$$

There is therefore no rounding loss at the endpoint. For example, the rate-1/4, length-4096 member has

$$k = 1024, \qquad r_{\mathrm{cap}} = 3072, \qquad \delta_{\mathrm{cap}} = \frac{3}{4}.$$

The endpoint theorem below includes the strictly smaller radius 3071/4096.

There is, however, a distinct granularity issue in the phrase "largest relative radius." A closed Hamming ball changes only at

$$\mathcal{H}_n = \left\{0, \frac{1}{n}, \ldots, \frac{n}{n}\right\}.$$

Consequently, a safe-radius set defined over all real $\delta \in [0,1]$ may be half-open and have no largest element. We report both the largest radius in $\mathcal{H}_n$ and the supremum over real radii.

4.2 An explicit smooth large-field family

For $u \in \mathbb{N}$, set

$$k_u = 64 \cdot 2^u = 2^{u+6}, \qquad n_u = 4k_u = 256 \cdot 2^u = 2^{u+8}, \qquad q_u = 3^{n_u}.$$

Let $\mathbb{F}_u = \mathbb{F}_{q_u}$. Since the multiplicative group of a finite field is cyclic of order $q_u - 1$, it suffices to check $n_u \mid (q_u - 1)$. Euler's theorem gives this directly:

$$\varphi(n_u) = \frac{n_u}{2}, \qquad \gcd(3, n_u) = 1, \qquad 3^{n_u/2} \equiv 1 \pmod{n_u}.$$

Squaring yields $3^{n_u} \equiv 1 \pmod{n_u}$. Thus $\mathbb{F}_u^\times$ contains a subgroup H_u of order n_u. We take $\mathcal{L}_u = H_u$ and

$$\mathcal{C}_u = \mathrm{RS}[\mathbb{F}_u, H_u, k_u].$$

The evaluation length and degree bound are powers of two, the domain is a multiplicative subgroup, and the rate is exactly 1/4. This is the standard smooth-domain condition for FFT-based Reed–Solomon codes [ACFY24], and it is the explicit family used in the quantitative statement.

4.3 The field-size inequality

Fix $\varepsilon^* = 2^{-128}$. For the family above,

$$\binom{n_u}{k_u} \le 2^{n_u}.$$

Moreover n_u is even and $n_u/2 \ge 128$, so

$$\begin{aligned} q_u = 3^{n_u} &= (3^2)^{n_u/2} = 9^{n_u/2} \\ &\ge 8^{n_u/2} = 2^{3n_u/2} \ge 2^{n_u+128}. \end{aligned}$$

It follows that

$$\binom{n_u}{k_u} \le 2^{-128} q_u = \varepsilon^* |\mathbb{F}_u|.$$

The pair-MCA theorem uses the comparison

$$2^{128} \binom{n_u}{k_u + 1} \le q_u.$$

It follows from the same calculation, because $\binom{n_u}{k_u+1} \le 2^{n_u}$. Compared with the ordered certificate count, this removes a factor $k_u + 1$:

$$\binom{n_u}{k_u}(n_u - k_u) = (k_u + 1)\binom{n_u}{k_u + 1}.$$

The field is exponential in the block length. This is a valid explicit sufficiently-large-field regime, not a claim about practically sized fields or about every smooth code supplied to the Grand Challenge.

5 The Capacity-Grid List Theorem

The following argument applies to every injectively indexed Reed–Solomon evaluation domain; smoothness enters only when we instantiate the explicit family from Section 4.2.

Theorem 5.1 (Universal capacity-grid equality)**.** *Let $\mathcal{C} = \mathrm{RS}[\mathbb{F}, \mathcal{L}, k]$ have length n, where $1 \le k \le n$, and let $m \ge 1$. Then*

$$L_m\left(\mathcal{C}, \frac{n-k}{n}\right) = \binom{n}{k}.$$

In particular, the worst-case endpoint list size is independent of m.

Proof. We first prove the upper bound. Fix $w \in (\mathbb{F}^m)^n$. Every codeword in the ball agrees with w on at least k complete vector-symbol coordinates. Assign to each such codeword one k-subset of its agreement coordinates. This assignment is injective: if two interleaved codewords are assigned the same set S, then they agree with one another on S. In each component, two degree-$< k$ polynomials agree at the k distinct evaluation points indexed by S, and hence are equal. The two interleaved codewords are therefore equal. There are exactly $\binom{n}{k}$ possible sets S.

For the reverse inequality, choose one of the m components and define the received word

$$w_i^\star = (a_i^k, 0, \ldots, 0).$$

For each k-subset $S \subseteq I$, put

$$V_S(X) = \prod_{i \in S}(X - a_i), \qquad f_S(X) = X^k - V_S(X).$$

The polynomial V_S is monic of degree k, so its leading term cancels that of X^k and $\deg f_S < k$. Use f_S in the distinguished component and zero polynomials in all other components to obtain an interleaved codeword c_S.

At evaluation coordinate i,

$$c_{S,i} = w_i^\star \quad \Longleftrightarrow \quad V_S(a_i) = 0 \quad \Longleftrightarrow \quad i \in S,$$

where the final equivalence uses injectivity of the evaluation points. Consequently c_S has distance exactly $n-k$ from $w^\star$, and its agreement set recovers S. The $\binom{n}{k}$ choices of S therefore give distinct codewords in the endpoint ball. This matches the upper bound. □

Theorem 5.2 (Failure on the next Hamming shell)**.** *Under the same hypotheses,*

$$\left|\Lambda\left(\mathcal{C}^{\equiv m}, 0, \frac{n-k+1}{n}\right)\right| \geq |\mathbb{F}|^m.$$

Proof. Fix $k-1$ evaluation points $S \subseteq \mathcal{L}$ and set

$$g_S(X) = \prod_{a \in S}(X - a).$$

For every $\lambda = (\lambda_1, \ldots, \lambda_m) \in \mathbb{F}^m$, the tuple

$$(\lambda_1 g_S, \ldots, \lambda_m g_S)$$

defines an interleaved codeword. These $|\mathbb{F}|^m$ codewords are distinct. The zero tuple has distance zero from the received word 0; every nonzero tuple vanishes on S and is nonzero at every evaluation point outside S, so its distance is exactly $n-k+1$. □

Theorem 5.3 (Fractional-target phase split)**.** *Fix $0 < \varepsilon^* < 1$, write $q = |\mathbb{F}|$, and call a radius δ safe when*

$$L_m(\mathcal{C}, \delta) \le \varepsilon^* q.$$

For every $m \ge 1$, exactly one of the following regimes applies:

(i) If $\varepsilon^* q < 1$, no radius in $[0, 1]$ is safe.

(ii) If $1 \le \varepsilon^* q < \binom{n}{k}$, radius zero is safe but the capacity endpoint and every larger radius fail. The optimal sub-endpoint radius is not determined by the present argument.

(iii) If $\binom{n}{k} \le \varepsilon^* q$, the largest safe radius on $\mathcal{H}_n$ is

$$\delta_{\text{cap}} = \frac{n-k}{n} = 1 - \rho;$$

and over real radii the safe set is exactly

$$\left[0, \frac{n-k+1}{n}\right),$$

so it has no largest element and has supremum $(n-k+1)/n$.

Equivalently, the fractional target holds at the capacity endpoint if and only if

$$\binom{n}{k} \le \varepsilon^* |\mathbb{F}|.$$

Proof. Every codeword is contained in the radius-zero ball centered at itself, so no radius can be safe when $\varepsilon^* q < 1$. A radius-zero ball contains at most one codeword, proving its safety when $\varepsilon^* q \ge 1$.

Theorem 5.1 proves both the failure in the intermediate regime and the necessary-and-sufficient endpoint criterion. In the final regime, it and monotonicity of list balls prove safety through count radius $n - k$. A real radius strictly below $(n-k+1)/n$ defines the same ball as some count radius at most $n - k$. At the next grid point, Theorem 5.2 gives a list of size at least $|\mathbb{F}|^m \ge |\mathbb{F}| > \varepsilon^* |\mathbb{F}|$; monotonicity then rules out every larger radius. □

Corollary 5.4 (The explicit smooth family)**.** *For every $u \ge 0$, every $m \ge 1$, and $\mathcal{C}_u = \mathrm{RS}[\mathbb{F}_u, H_u, k_u]$ from Section 4.2, the conclusions of Theorem 5.3*(iii) *hold with $\varepsilon^* = 2^{-128}$. In particular, the largest safe Hamming-grid radius is $3/4$.*

Proof. Apply the inequality proved in Section 4.3. □

5.1 Scope relative to the Grand Challenge

Theorem 5.1 completely determines the endpoint list size for every supplied Reed–Solomon code, smooth or otherwise. Thus the displayed binomial field-size inequality is necessary and sufficient at that endpoint, not merely a convenient sufficient hypothesis. Corollary 5.4 supplies a concrete smooth family in the safe regime. The present argument does not determine the largest sub-endpoint radius for an arbitrary fixed smooth code in the intermediate regime

$$1 \le 2^{-128}|\mathbb{F}| < \binom{n}{k}.$$

The exponential alphabet is what places the explicit family in the final regime; it is not needed for the universal endpoint equality.

This distinction matters in light of known capacity results. Generic Reed–Solomon evaluation points can, for every fixed positive gap ϵ, achieve radius $1 - \rho - \epsilon$ over exponentially large fields with a list size bounded in terms of ϵ [BGM24]. This positive-gap statement differs from the exact endpoint equality above, and generic points do not supply the structured smooth domain required here. Conversely, near-capacity proximity-gap behavior can fail for particular smooth prime-field families [Kam26]. The theorem above imports neither result: it uses only polynomial interpolation and an explicit field-size comparison.

Recent work of Dao, Kominers, and Thaler [DKT26] gives quantitative list-decoding and MCA bounds on prescribed evaluation domains, including beyond-Johnson bounds under sufficiently large characteristic. Those positive-gap results require a separate parameter comparison with the exact endpoint and the characteristic-three family studied here. The present binomial bounds are not asserted to improve the sharper radius-dependent estimates in that literature.

6 Pair Mutual Correlated Agreement

6.1 Bad challenges

Let $p = (p_0, p_1) \in (\mathbb{F}^2)^I$, and write

$$y_\gamma = p_0 + \gamma p_1.$$

For $S \subseteq I$, say that S is δ-large when

$$\frac{|S|}{n} \ge 1 - \delta.$$

Define $\mathrm{Bad}_{\mathrm{MCA}}(\mathcal{C}, \delta, p)$ to be the set of $\gamma \in \mathbb{F}$ for which there exists a δ-large set S such that:

(i) y_γ agrees on S with a codeword of $\mathcal{C}$;

(ii) the pair p does not agree on the same S with a codeword of $\mathcal{C}^{\equiv 2}$.

The MCA error is

$$\varepsilon_{\mathrm{MCA}}(\mathcal{C}, \delta) = \max_{p \in (\mathbb{F}^2)^I} \frac{|\,\mathrm{Bad}_{\mathrm{MCA}}(\mathcal{C}, \delta, p)|}{|\mathbb{F}|}.$$

This is the two-word same-set event appearing in [BSCH+26, Theorem 4.6, full version]. That source uses polynomials of degree at most its parameter, so its parameter is $k-1$ in the degree-$< k$ convention used here. Our bound below is uniform in the radius; the cited literature gives sharper radius-dependent bounds in its stated regimes.

Theorem 6.1 (Uniform pair-MCA certificate bound)**.** *Let $\mathcal{C} = \mathrm{RS}[\mathbb{F}, \mathcal{L}, k]$ have injectively indexed evaluation domain of length n, where $1 \le k \le n$. For every $\delta \in \mathbb{R}$ and every $p \in (\mathbb{F}^2)^n$,*

$$|\,\mathrm{Bad}_{\mathrm{MCA}}(\mathcal{C}, \delta, p)| \le \binom{n}{k+1}.$$

Consequently,

$$\varepsilon_{\mathrm{MCA}}(\mathcal{C}, \delta) \le \frac{\binom{n}{k+1}}{|\mathbb{F}|}.$$

Smoothness is not required for this bound.

Proof. Fix a bad challenge γ, and choose a witnessing set S. Necessarily $|S| > k$. Indeed, when $|S| \le k$, interpolate each component of p on S by a polynomial of degree $< k$; the resulting pair codeword agrees with p on S, contradicting condition (ii).

Choose a k-subset $T \subset S$. Let a_T, b_T be the unique degree-$< k$ polynomials interpolating p_0, p_1, respectively, on T. Condition (ii) says that the pair interpolant (a_T, b_T) fails somewhere on S. Choose such an $i \in S \setminus T$, and set $U = T \cup \{i\}$. Condition (i) remains true after restriction from S to U. The pair still cannot agree with $\mathcal{C}^{\equiv 2}$ on U: any purported pair codeword would agree with (a_T, b_T) on T, hence equal it by k-point determination, contradicting the mismatch at i. Thus U is a $(k+1)$-coordinate obstruction for γ.

A fixed U obstructs at most one challenge. Suppose distinct γ, η were both bad on U, with scalar codewords c_γ, c_η agreeing with $p_0 + \gamma p_1, p_0 + \eta p_1$, respectively. By linearity,

$$d = \frac{c_\gamma - c_\eta}{\gamma - \eta}, \qquad a = c_\gamma - \gamma d$$

are codewords. On U, they agree with p_1 and p_0, respectively, so (a, d) is a pair codeword agreeing with p on U, a contradiction.

Make the finite choices deterministic. Mapping each bad challenge to its unordered obstruction U is injective, and there are $\binom{n}{k+1}$ such subsets. Dividing by $|\mathbb{F}|$ proves the error bound. Notice that the large-set inequality is no longer used after the witness is extracted; this is why the bound is uniform in δ. □

Corollary 6.2 (Explicit smooth family at 2^{-128})**.** *For every member $\mathcal{C}_u$ of the family in Section 4.2, every $\delta \in [0, 1]$, and every pair word p,*

$$\frac{|\operatorname{Bad}_{\mathrm{MCA}}(\mathcal{C}_u, \delta, p)|}{|\mathbb{F}_u|} \le 2^{-128}.$$

Thus, for this family and this same-set pair-MCA definition, every normalized radius is safe and the largest admissible radius is 1*.*

Proof. Section 4.3 proves

$$2^{128} \binom{n_u}{k_u + 1} \le q_u.$$

Apply Theorem 6.1. □

6.2 An exact small-radius boundary instance

The uniform certificate bound is sufficient but need not locate the first unsafe radius. Write

$$B_{\mathcal{C}}(r) = \max_p |\operatorname{Bad}_{\mathrm{MCA}}(\mathcal{C}, r/n, p)|$$

for the exact worst bad-challenge count at count radius r. Consider

$$q = 2^{128} + 192513 = 340282366920938463463374607431768403969.$$

The accompanying Lean development certifies that q is prime and $q \equiv 1 \pmod{4096}$. Hence $\mathbb{F}_q^\times$ contains an order-4096 subgroup, which we use as the evaluation domain for the smooth RS code with $n = 4096$ and $k = 1024$.

Theorem 6.3 (Exact 128-bit small-radius transition)**.** *For this code,*

$$B_{\mathcal{C}}(0) = 1, \qquad B_{\mathcal{C}}(1) \geq 2.$$

Consequently, for the 2^{-128} *MCA error target, its greatest safe count radius is* 0 *and its first unsafe count radius is* 1*. For the relative-radius definition over all* $\delta \in [0, 1]$*, the safe set is*

$$\left[0, \frac{1}{4096}\right),$$

so the real-radius supremum is $1/4096$ *and is not attained.*

Proof. At count radius zero, every large agreement set is the whole coordinate set. A fixed set supports at most one bad challenge, while a unit-spike affine line realizes one; hence $B_{\mathcal{C}}(0) = 1$. At count radius one, take two coordinates outside a k-point interpolation set. The affine line from the unit spike at the first coordinate to the unit spike at the second has distinct bad challenges 0 and 1, proving $B_{\mathcal{C}}(1) \geq 2$.

The certified field lies in the exact budget window

$$2^{128} \leq q < 2^{128} \cdot 2.$$

Thus the integer criterion $2^{128} B_{\mathcal{C}}(r) \leq q$ holds at $r = 0$ and fails at $r = 1$. Monotonicity of the bad-count spectrum gives the two grid endpoints.

Finally, if $0 \leq \delta < 1/n$, the inequality $|S|/n \geq 1 - \delta > 1 - 1/n$ forces the integer $|S|$ to equal n. The bad sets are therefore exactly those at count radius zero throughout that half-open interval. At $\delta = 1/n$, sets missing one coordinate become admissible, and the two-spike line already violates the budget. Monotonicity preserves failure for larger radii, proving the real-radius claim. □

6.3 Distance interpretation

Let

$$D_2(p) = \Delta(p, \mathcal{C}^{=2}), \qquad D_1(y) = \Delta(y, \mathcal{C}).$$

For a challenge outside the MCA bad set, scalar closeness on a large agreement set forces pair closeness on that same set. For $\delta \in [0, 1]$, this gives the distance implication

$$D_2(p) \geq \delta \Longrightarrow D_1(y_\gamma) \geq \delta$$

for every MCA-good γ, with the fraction of excluded challenges bounded by $\varepsilon_{\mathrm{MCA}}(\mathcal{C}, \delta)$.

To see the boundary convention explicitly, suppose that $D_1(y_\gamma) < \delta$, and choose a closest scalar codeword c. Let $S = \{i : y_\gamma(i) = c(i)\}$. Then $|S|/n = 1 - D_1(y_\gamma) > 1 - \delta$, so S is δ-large. Since γ is MCA-good, a pair codeword agrees with p on S. Hence $D_2(p) \leq D_1(y_\gamma) < \delta$. Taking the contrapositive proves the displayed implication, including its non-strict $\geq$ boundary.

This is a challenge-indexed statement. Replacing the sampled challenge by one fixed field element would require a separate theorem that the selected element is good for every pair, which does not follow from a fractional MCA bound.

6.4 Endpoint interpretation

At $\delta_{\text{cap}} = 1 - k/n$, interpolation on any k coordinates shows that

$$D_1(y) \leq \delta_{\text{cap}} \quad \text{and} \quad D_2(p) \leq \delta_{\text{cap}}$$

for every scalar word y and pair word p. Moreover, on every set S of size at most k, each component of p extends to a degree-$< k$ polynomial. Such an S can therefore never witness an MCA failure. Every bad endpoint challenge must instead have a witness with $|S| \geq k + 1$.

Consequently, the endpoint distance implication above is an equality non-collapse statement: when $D_2(p) = \delta_{\text{cap}}$, a good challenge must not lower the projected distance strictly below δ_{cap}. Theorem 6.1 supplies a uniform quantitative bound on the excluded challenges.

6.5 Commit-then-challenge order

The mathematical experiment fixes p before sampling $\gamma \leftarrow \mathbb{F}$. This ordering prevents the pair from being selected as a function of the challenge. A full protocol implementation must bind p before deriving γ, but the coding theorem needs only the resulting quantification and probability space; it does not depend on a complete blockchain or commitment protocol.

6.6 Scope

The theorem is universal over pair words and injective RS evaluation domains, but its 2^{-128} corollary uses the explicit exponential-size field. For a different supplied field, the same certificate proof gives the sufficient comparison

$$\binom{n}{k+1} \leq 2^{-128}|\mathbb{F}|.$$

This improves the ordered-certificate requirement by the exact factor $k+1$, since $\binom{n}{k}(n-k) = (k+1)\binom{n}{k+1}$. If that inequality fails, this proof does not determine the optimal radius or show that the MCA target is impossible; it only ceases to certify the requested error.

For an arbitrary supplied finite code, radius r/n meets the 2^{-128} target exactly when

$$2^{128} B_{\mathcal{C}}(r) \leq |\mathbb{F}|.$$

This is also the exact formal equivalence: the Lean theorem identifies the real-valued operational error predicate at normalized radius r/n with the displayed integer inequality, so no rounding relaxation is hidden here. Thus a uniform upper-bound certificate at r, together with one concrete affine line exceeding the budget at $r+1$, pins both the largest safe and first unsafe Hamming-grid radii. The remaining middle regime is the code-specific problem of proving those matching bounds; smoothness by itself does not determine this incidence spectrum.

The result is for the two-coordinate, same-set MCA experiment defined above. Broader notions or higher-dimensional challenge families require separate statements.

As a separate concrete/application result, the repository also checks the canonical runtime field $q = 12289$ with $n = 4096$ and $k = 1024$. Since $q < 2^{128}$ while its radius-zero unit-spike line has one bad challenge, that concrete code has no safe count radius for the 2^{-128} MCA error target. This runtime-facing fact is not used by the standalone large-field or boundary-field theorems above.

7 Application Interface

The coding theorem is stated over the complete received-word space and does not depend on a particular source of observations. An application may nevertheless inherit the result through a distance-aware map.

Let O be a type of raw presented observations, let $G \subseteq O$ be the exact/valid locus, and let

$$\pi : O \longrightarrow (\mathbb{F}^2)^I$$

be the extracted pair word. A source distance $\rho_O : O \to [0,1]$ is meaningful only when O includes arbitrary or noisy presentations; if every element of O already contains a validity witness, then the proximity problem may collapse to the exact code locus.

The Lean companion packages this interface as a source validity model and a source-to-code calibration. Its only quantitative field is the pointwise

inequality

$$\rho_O(o) \le D_2(\pi(o)).$$

It yields, uniformly in δ,

$$\rho_O(o) \ge \delta \Longrightarrow D_2(\pi(o)) \ge \delta.$$

Under this comparison, the proved universal list theorem applies to $\pi(o)$; the proved pair-MCA theorem applies through the same interface once the application fixes its pair before sampling the challenge.

There are two standard ways to discharge the comparison. Defining $\rho_O = D_2 \circ \pi$ makes it reflexive. A pre-existing source metric requires a mathematical proof of $\rho_O \le D_2 \circ \pi$. Exact witnesses may certify membership in G, but the carrier O must still include arbitrary received observations.

Protocol-specific observation formats, commitments, and runtime verification are intentionally outside the proof of Theorems 5.1, 5.2 and 6.1. Such developments may cite the two coding theorems through the interface above; neither theorem assumes that every received word comes from an application-specific witness space.

7.1 The existing committed-cochain projection

The project-specific application starts with the commitment payload of the companion HCP manuscript [vdV26],

$$c = (q, N, \mathbf{c}, \tau).$$

Here $\mathbf{c}$ is the serialized integer edge-value list. The Lean carrier `CommittedCochain` is an abbreviation for the same `CochainCommitmentData` used by the commitment and artifact layers. A proof-carrying observation exposes that payload; it does not replace it with a second commitment object.

Fix an extraction context consisting of an expected edge count, selected indices $\iota(i,j)$, and a coefficient interpretation $a : \mathbb{Z} \to \mathbb{Z}$. For an aligned payload, the actual plane projection is

$$p_c(i,j) = a(\mathbf{c}_{\iota(i,j)}), \qquad j \in \{0,1\}.$$

Alignment ensures that every selected index is in bounds. The public plane-view certificate records equality with this extraction from the observed payload. The canonical instantiation reduces both coordinates modulo $q = 12289$, with RS length $n = 4096$ and degree bound $k = 1024$:

$$\bar{p}_c(i,j) = p_c(i,j) \bmod q, \qquad y_\gamma(i) = \bar{p}_c(i,0) + \gamma \bar{p}_c(i,1).$$

Thus one observed commitment supplies the full pair before the challenge is evaluated. The `PublicCalibration` module implements this extraction and proves its equality with the observed-payload projection.

On integer planes whose coordinates lie in $[0, q)$, coordinatewise reduction is a bijection onto the field-pair space. It preserves whole-pair Hamming distance. Let $\mathcal{C}_A$ be the pair code pulled back to this canonical integer alphabet, and let D_A be relative Hamming distance to $\mathcal{C}_A$. The existing Lean development proves

$$D_A(p_c) = D_2(\bar{p}_c).$$

The public-observation calibration uses $D_A(p_c)$ as its source score, so its all-radius farness implication is already proved. Its observation carrier requires aligned, canonical-region payload views without requiring pair-codeword membership.

An application retaining an independently chosen cochain, Hodge, or Plücker disagreement ρ_c still needs a quantitative comparison, for example

$$\rho_c(c) \geq r_S \quad \Longrightarrow \quad D_A(p_c) \geq r_T.$$

The equality above does not prove this upstream comparison. In particular, changing unselected edge values leaves p_c unchanged; any source metric sensitive to those values needs an admissible-family restriction or a separate control theorem.

The storage interface now fixes the same snapshot, payload interpretation and public artifact in one context, while keeping exact acceptance separate from raw context binding. For its decoded cochain, one independent geometric score is

$$\rho_{\mathrm{ex}}(c) = \| P_{(\operatorname{im}\delta_0)^\perp} \operatorname{dec}_S(c) \|.$$

It vanishes exactly on accepted exact payloads once the context and shape conditions hold. A sufficient comparison criterion is an exact comparison cochain $\lambda(z) \in \operatorname{im}\delta_0$ for every target pair-codeword z, together with a constant $A > 0$ and the bound

$$\| \operatorname{dec}_S(c) - \lambda(z) \| \leq A\, \delta_H(z, \bar{p}_c).$$

Choosing an attained nearest codeword and applying orthogonal-projection contractivity gives

$$\rho_{\mathrm{ex}}(c) \leq A D_2(\bar{p}_c), \qquad \rho_{\mathrm{ex}}(c) \geq r_S \Longrightarrow D_2(\bar{p}_c) \geq r_S/A.$$

The storage calibration module proves this implication from the lift and decoder bounds. It does not construct those application-specific inputs. The canonical storage adapter identifies the real-infimum pair distance with the attained generic minimum and joins both comparisons to the actual observed artifact.

7.2 A canonical-lift obstruction and a no-wrap profile

Canonical representatives alone do not make a finite-field RS code into a proper real-linear exact-cochain locus. Suppose q is prime, the evaluation points are distinct and $k \geq 2$. For a scalar field word w, write $\ell(w) \in \mathbb{R}^I$ for its canonical coordinate lift. The lifts of the affine RS words already span $\mathbb{R}^I$. Indeed, for each coordinate i, put $v_j = a_j - a_i$. Canonical representatives satisfy

$$\mathbf{1} - \ell(v) + \ell(v - \mathbf{1}) = qe_i.$$

Only the i-th coordinate wraps at zero. Both affine words and the constant word belong to RS, so every coordinate vector belongs to the real span of the lifted codewords. Applying this argument separately to both columns proves the corresponding assertion in $\mathbb{R}^{I \times \{0,1\}}$.

Consequently, if a real-linear decoder T has any nonexact output, there is no constant A for which

$$\operatorname{dist}(T\ell(w), \operatorname{im} \delta_0) \leq AD_2(w) \quad \text{for every field-pair word } w.$$

Such a bound would make all lifted pair-codewords exact, hence make the decoder's entire image exact. This obstruction concerns a global comparison with no additive loss. It leaves restricted profiles, additive defects and separately justified threshold implications open.

One explicit restricted profile retains the original Euclidean source metric. Choose an information set S of size k and let $A_{i,s} \in \mathbb{F}_q$ be the actual systematic RS interpolation coefficients. Lift them to integers $\widetilde{A}_{i,s} \in [0, q)$, and define the real generator and integer check by

$$(G_{\mathbb{R}} u)_i = \sum_{s \in S} \widetilde{A}_{i,s} u_s, \qquad (Hz)_i = z_i - \sum_{s \in S} \widetilde{A}_{i,s} z_s.$$

Use both columns and a complete coordinate layout with coefficient map the identity. A two-vertex, one-edge cellular sheaf realizes $\operatorname{im} \delta_0 = \operatorname{im}(G_{\mathbb{R}} \oplus G_{\mathbb{R}})$; this equality is proved from its restriction maps. The decoder reads the same original integer payload into its real edge coordinates.

Assume $|z_{i,j}| \le B$, $B > 0$, and the integer-syndrome condition $|(Hz_{\cdot,j})_i| < q$ for all i, j. If the reduced pair is a codeword, every integer check is divisible by q; the syndrome bound forces it to vanish. Thus codeword validity reflects geometric exactness. If the source is nonexact, its extracted pair has distance at least $1/n$. Since $\rho_{\mathrm{ex}}(z) \le \|z\| \le B\sqrt{2n}$, these facts give

$$\rho_{\mathrm{ex}}(z) \le Bn\sqrt{2n}\, D_2(\bar{z}), \qquad \rho_{\mathrm{ex}}(z) \ge r \Longrightarrow D_2(\bar{z}) \ge \frac{r}{Bn\sqrt{2n}}.$$

The source score remains Euclidean distance to exact cochains. The no-wrap condition bounds the integer syndrome, not just individual representatives. An outside-information-coordinate unit error in one column has nonzero real syndrome, satisfies this profile and gives a positive source distance.

This construction is a coarse positive-radius example. For a nonempty source far region its certified target radius is at most $1/n$; it does not supply a capacity- or Johnson-scale geometric application theorem. Positive decoded farness concerns raw received payloads and excludes already accepted exact anchors. The constructed systematic sheaf is an explicit application model, not an automatic identification with an arbitrary HCP presentation, and no encryption-security claim follows from this construction.

7.3 Three native metrics for modular cochains

The same cellular construction has a global comparison in its native modular metrics. Here the cochain valid locus is defined intrinsically by an actual integral opening and integer carry:

$$\delta_0 a = z + qm.$$

This is modular exactness, distinct from real decoded exactness. Reducing the actual integer interpolation coefficients proves that modular exactness is equivalent to the original RS pair-code predicate. No no-wrap condition is needed for this modular statement.

Let $d_C(z)$ be scalar-coordinate edit distance to these modularly exact cochains, normalized by $2n$. Let $d_P(z)$ be whole-pair edit distance to modularly exact integer planes, normalized by n. The RS distance is $D_2(\bar{z})$. For two words, their mismatch counts satisfy $h_P \le h_C \le 2h_P$. Taking attained nearest codewords gives

$$d_C(z) \le d_P(z) \le 2d_C(z).$$

The plane/RS distance equality is also a theorem. Reduction cannot create a mismatch. Conversely, lift a field codeword pair by retaining each already

matching received integer pair, and using canonical representatives at the remaining positions. The lifted word is modularly exact and has exactly the field word's mismatched positions. Thus

$$\boxed{d_C(z) \le d_P(z) = D_2(\bar{z}) \le 2d_C(z)}.$$

The scalar representative-lifting argument also identifies d_C with the corresponding flattened finite-field code distance. These independently defined native distances are compared through the actual maps. A unit-scale near contract must use the explicitly scaled local score $2d_C$; the far implication uses $d_C \le D_2$.

There is a nonempty capacity-scale family in these modular metrics. For $0 < k < n$, take $u_i = a_i^k$ and both pair columns equal to u. A polynomial of degree below k agrees with u on at most k positions, while interpolation supplies a codeword agreeing on any chosen k positions. Applying this separately to both columns, and to their common interpolation, proves

$$d_C(z) = d_P(z) = D_2(\bar{z}) = \frac{n-k}{n}.$$

Canonical representatives of these two columns serialize into the original commitment payload in the declared complete layout. In the current canonical instance all three distances are $3/4$. This is a native modular source statement, not a capacity-scale Euclidean Hodge-distance theorem.

For this diagonal pair, the challenged word is $(1+\gamma)u$. Every $\gamma \neq -1$ preserves the scalar capacity distance and is MCA-good; $\gamma = -1$ collapses to zero. At every nonnegative tested radius its bad set is exactly $\{-1\}$, with uniform fraction $1/q$. The existing canonical mix is noncancelling because its order is $4096 > 2$.

The restriction to the stated line profile is essential. For an arbitrary fixed nonzero γ_0, the pair $(u, -\gamma_0^{-1}u)$ has scalar-coordinate and pair distance $(n-k)/n$, but its challenge at γ_0 is zero. A global fixed-mix far-preservation claim therefore fails even on capacity-far pairs. The general protocol must bind the pair before sampling its challenge or prove goodness for its actual restricted line profile.

The full HCP sample $b = h + \delta_0 a + \delta_1^* v$ has a different residual. The companion manuscript's exact-component obstruction [vdV26] shows that, when a nonzero coexact direction is allowed, this full residual need not descend to an exact-component-only view. Such a view needs a justified quotient or restricted source profile before it can support a full-HCP far-region claim. This does not establish factorization of a particular raw serializer through that decoded view.

For scalar transfer, the pair must remain fixed before a random challenge is sampled, or a chosen fixed challenge must be proved MCA-good. The canonical fixed mix $g = 1331$ is a different assertion from a bound on the fraction of bad random challenges. Restricting integer representatives makes the pair faithful; it does not make one scalar evaluation injective.

The current canonical field is also distinct from the sufficiently large family of Section 4. For the full canonical pair space, the existing small-radius certificate already exceeds the 2^{-128} budget at count radius zero because $12289 < 2^{128}$. This does not determine the spectrum on a restricted commitment image. Adopting $\mathbb{F}_{3^{nu}}$ would require its own field-element encoding: ordinary integer casts reach only the prime subfield, and the current wire-modulus convention is unchanged.

7.4 Scope of the instantiated application

The systematic modular profile fixes a concrete cellular model, full layout, identity integer coefficient map, raw payload carrier and intrinsic modular valid locus. Its three independently defined native metrics have a proved comparison, a nonempty capacity-far original-payload family and an explicit challenge analysis. The calibration is packaged through the existing source-to-source and source-to-code interfaces; the existing near projection uses the declared local scale $2d_C$. The public-observation adapter retains the original artifact and its actual extracted pair.

An application to a different maintained sheaf must prove the corresponding source and coefficient identifications. An independently chosen HCP/frame score needs its own upstream comparison; the native modular theorem does not identify that score with edit distance. The global canonical-lift and fixed-challenge obstructions constrain such stronger claims. The restricted Euclidean theorem and the diagonal fixed-mix example retain their stated profiles.

This is a bounded mathematical dependency on the commitment/projection profile. It does not require the full Paper 2 ledger, consensus protocol, or Rust implementation. The universal coding theorems remain independent of that instantiation. A claim that the commitment-specific projection gives a new radius guarantee requires this concrete theorem and a comparison with position-binding vector commitments [CF11], committed linear maps [CNR+22], and RS proximity applications such as WHIR [ACFY24]. The distinctive question is what the cochain source relation and its proved metric comparison add to those interfaces. The explicit modular-coboundary and metric relations make that comparison

concrete. They do not establish a new binding or hiding primitive, a security reduction, or a priority claim. In particular, the generic coefficient interpretation a is arbitrary. Its linearity and compatibility with the selected field reduction must be proved for the actual profile before making a linear-map commitment comparison. The storage and same-payload joins alone establish neither a new cryptographic binding game nor a radius or cost improvement over those interfaces.

8 Formalization and Proof Ledger

8.1 Standalone hierarchy

The machine-checked development separates generic coding mathematics from application bridges:

`Proximity/Core/BlockCode`
: Relative distance, balls, and universal list-bound predicates.

`Proximity/Core/ReedSolomon`
: Evaluation-domain definitions, RS codes, and interleaving.

`Proximity/Core/PlanePair`
: Plane–pair–line equivalences.

`Proximity/Core/FiniteThreshold`
: Safe finite grids, greatest-safe and first-unsafe values, and adjacent safe/unsafe threshold certificates.

`Proximity/Core/Distance` and `Proximity/Core/RadiusShell`
: Attained minimum distances, closed and strict nearness, and the exact half-open real intervals between consecutive Hamming-count shells.

`Proximity/Capacity/Parameters`
: Explicit ε^* and field-size inequalities.

`Proximity/Capacity/Realization` and `Proximity/Capacity/ListPhase`
: Actual Galois fields, exact-order subgroup domains for every family member, and instantiated list/MCA grid and real-radius conclusions.

`Proximity/ListDecoding/Capacity`
: Agreement-set injection, the matching received-word construction, the universal endpoint equality, the fractional-target equivalence, and the next-shell coefficient-vector injection.

`Proximity/ListDecoding/PhaseSplit`
: All three fractional-target regimes, the exact endpoint-safe real interval, its excluded supremum, and the largest safe grid count.

`Proximity/MCA/Definitions`
: Arbitrary-block-code same-set MCA definitions at count and relative radii.

`Proximity/MCA/Threshold`
: Exact worst bad-count spectrum and the equivalence between operational real error at r/n and the integer $2^{-\lambda}$ budget.

`Proximity/MCA/SpectrumCertificate`
: Supplied-code grid-threshold pinning from a uniform upper bound at one radius and a concrete over-budget affine line at the next radius.

`Proximity/MCA/SmallRadius`
: Universal RS unit-spike and two-spike certificates, including $B_{\mathcal{C}}(0) = 1$ for every proper RS code.

`Proximity/MCA/BoundaryField`
: Primality, order-4096 smooth domain, and the exact 128-bit radius transition for $q = 2^{128} + 192513$.

`Proximity/MCA/RealThreshold`
: Count/real same-set event correspondence and the boundary-field safe interval $[0, 1/4096)$, including supremum and nonattainment.

`Proximity/MCA/Pair`
: RS compressed interpolation certificates, bad-challenge injection, the uniform cardinality bound, and the explicit-family error corollary.

`Proximity/Application/Calibration`
: Generic source-validity model, pointwise distance non-collapse, and the uniform source-far to target-far implication.

`Proximity/Application/DistanceCalibration`
: Identification with attained scalar/pair code distance, interpolation covering bounds, and good-challenge farness with its exact boundary.

`Proximity/Core/CanonicalLift` and `Proximity/Core/Systematic`
: Canonical real-lift spanning, actual systematic interpolation and integer/real syndrome compatibility. These are proved algebraic facts.

`Proximity/Core/InterleavedMetric`
: Native scalar-coordinate and whole-pair Hamming comparisons, retaining their different normalizations.

`Proximity/Core/DeepHole` and `Proximity/Core/FixedChallenge`
: Exact scalar/pair/flattened capacity distances for monomial received words, and capacity-far counterexamples to arbitrary fixed-challenge compression.

`Proximity/MCA/ZeroDirection` and `Proximity/MCA/Diagonal`
: Explicit all-good and single-cancelling-challenge profiles, with their exact same-set bad events.

The standalone import closure does not depend on HCP, protocol, consensus, or runtime axiom bundles. Both directions of the capacity-grid equality and its exact fractional-target criterion are theorems, not axioms. The next-shell lower bound is also machine-checked. The pair-MCA theorem and its 2^{-128} family instantiation are machine-checked as well. The generic family corollaries retain their parameterized forms. The realization module additionally constructs $\mathbb{F}_{3^{n_u}}$, an exact-order n_u root, and its injectively indexed subgroup for every u, and instantiates those corollaries without a realization hypothesis. All source modules in this ledger live under `lean/Proximity`; `lean/ProximityPrize.lean` is only the standalone aggregate import target, not a second source hierarchy. The detailed object dictionary, theorem correspondence, and remaining-work queue are maintained in `papers/proximity-prize/SEMANTIC_PARITY.md`.

8.2 Status ledger

Obligation	Status	Required endpoint
Count/relative ball correspondence	Lean-proved	Equality at r/n, for $n > 0$
Plane–pair equivalence	Lean-proved	Bijection and Hamming isometry
Plane–affine-line equivalence	Lean-proved	Formal inverse maps
Smooth large-field family	Lean-proved	Actual fields and subgroup domains
Capacity-grid list equality	Lean-proved	Universal $L_m = \binom{n}{k}$
Endpoint fractional criterion	Lean-proved	Target iff $\binom{n}{k} \le \varepsilon^*\lvert\mathbb{F}\rvert$
Next-shell list lower bound	Lean-proved	Explicit $\lvert\mathbb{F}\rvert^m$ injection
Complete list phase split	Lean-proved	Three regimes and exact real interval
Generic minimum-distance interpretation	Lean-proved	Attained minima, covering and good-challenge farness
Pair-MCA certificate bound	Lean-proved	$\lvert\,\mathrm{Bad}_{\mathrm{MCA}}\,\rvert \le \binom{n}{k+1}$
MCA target-fraction inequality	Lean-proved	$\binom{n}{k+1} \le \varepsilon^*\lvert\mathbb{F}\rvert$ for the explicit family
Exact supplied-code MCA grid API	Lean-proved	Operational target iff $2^{128}B_{\mathcal{C}}(r) \le \lvert\mathbb{F}\rvert$, with concrete next-line pinning

Obligation	Status	Required endpoint
Exact RS small-radius certificates	Lean-proved	$B_{\mathcal{C}}(0) = 1$, and $B_{\mathcal{C}}(1) \geq 2$ for $1 \leq k,\ k+2 \leq n$
Smooth boundary-field instance	Lean-proved	Prime $q = 2^{128} + 192513 \equiv 1 \pmod{4096}$
Boundary-field MCA threshold	Lean-proved	Greatest safe count 0; first unsafe count 1
Explicit-family MCA greatest radius	Lean-proved	Full count radius n for the constructed family
Boundary-field real supremum	Lean-proved	$1/4096$, not attained
Native scalar/pair metric comparison	Lean-proved	$d_C \leq d_P \leq 2d_C$
Monomial capacity far family	Lean-proved	Scalar, pair and flattened distances $(n-k)/n$
Explicit challenge profiles	Lean-proved	All-good zero direction; diagonal bad set $\{-1\}$
Arbitrary fixed-mix obstruction	Lean-proved	Capacity-far pair with challenged word zero

The generic counting and calibration proofs use the standard Lean axioms `propext`, `Classical.choice`, and `Quot.sound`. The boundary-field primality, root-order, and threshold certificates additionally use `native_decide`; on Lean 4.35 their reports include generated native certificate axioms with names containing `native_decide.ax_`. The older 4.24 reports used `Lean.ofReduceBool` and `Lean.trustCompiler`. These arithmetic certificates therefore have a different trust footprint from the generic counting arguments.

8.3 Submission boundary

A completed claim requires:

(i) no placeholder assumptions for the main list/MCA result;

(ii) an explicit statement of imported literature theorems;

(iii) all field-size and rounding conditions checked;

(iv) a clear separation between proved theorems, computational evidence, and conjectures;

(v) a reproducible proof artifact and manuscript cross-reference.

8.4 Remaining interfaces

The nine named standalone coding statements now have complete Lean endpoints, including the all-parameter smooth-family realization, complete list phase split, real safe intervals and their excluded suprema, and the generic minimum-distance interpretation. The generic source-to-pair calibration implication

$$d_{\text{source}}(x, \text{valid}) \geq \delta \Longrightarrow \Delta(\pi(x), \mathcal{C}^{\equiv 2}) \geq \delta$$

is Lean-proved for an abstract distance model from its named pointwise non-collapse field. The distance-calibration module identifies the target model with the generic attained pair-code minimum. Pullback distance makes that field reflexive; an application choosing a different pre-existing source metric supplies one explicit comparison. Separately, the intermediate list-decoding regime still requires new ideas if one wants an optimal sub-endpoint radius for a supplied field that fails the binomial target inequality.

The existing commitment-to-plane extraction, canonical plane/pair Hamming isometry, exact transported-code distance equality, and public-observation pullback calibration live in the concrete application hierarchy. They are described in Section 7 and are outside the standalone `ProximityPrize` import closure. Section 7 supplies an explicit modular instance of those interfaces. Comparison with an independently chosen HCP or frame score remains a separate mathematical question.

The explicit source realization lives in the `Sheaf/SystematicCode` modules, including `Modular`. Their actual integral cellular coboundary is proved compatible with RS reduction. The storage modules `CoordinateCodec`, `NoWrapCalibration` and `ThreeLevelMetrics` retain the original payload and separate the restricted Euclidean comparison from the global native-metric comparison. The canonical specialization and public-observation joins are in `CanonicalSystematic` and `CanonicalThreeLevel`; `CanonicalCalibration` composes the existing interfaces with their declared near/far scales. These modules live under `Protocol/Storage`. Paper 2 records the shared source/observation contracts in its initial manuscript text.

These explicit profiles do not identify arbitrary old HCP presentations or their frame scores with native modular edit distance. A stronger upstream geometric comparison, or a different challenge/observation profile, needs its own theorem. Such obligations remain separate from the completed generic coding results and do not require Paper 2 consensus or Rust.

References

[ABF26] Gal Arnon, Dan Boneh, and Giacomo Fenzi. Open problems in list decoding and correlated agreement, 2026. July 2026 revision.

[ACFY24] Gal Arnon, Alessandro Chiesa, Giacomo Fenzi, and Eylon Yogev. WHIR: Reed–Solomon proximity testing with super-fast verification, 2024.

[BGM24] Joshua Brakensiek, Sivakanth Gopi, and Visu Makam. Generic Reed–Solomon codes achieve list-decoding capacity, 2024. Version 4.

[BSCH+26] Eli Ben-Sasson, Dan Carmon, Ulrich Haböck, Swastik Kopparty, and Shubhangi Saraf. On proximity gaps for Reed–Solomon codes. In *Proceedings of the 58th Annual ACM Symposium on Theory of Computing*, pages 1157–1167, 2026. Full version: ECCC TR25-169.

[CF11] Dario Catalano and Dario Fiore. Vector commitments and their applications, 2011. Full version of the PKC 2013 paper.

[CNR+22] Matteo Campanelli, Anca Nitulescu, Carla Ràfols, Alexandros Zacharakis, and Arantxa Zapico. Linear-map vector commitments and their practical applications, 2022.

[DKT26] Quang Dao, Scott Duke Kominers, and Justin Thaler. Reed–Solomon codes beyond Johnson: Efficient decoding and smaller cryptographic proofs, 2026. Revised November 3, 2026.

[Kam26] Antonio Kambiré. Proximity gaps conjecture fails near capacity over prime fields, 2026.

[vdV26] Chloe van der Vlugt. Homotopical encryption: Hidden Hodge operators and the harmonic cochain problem. Companion manuscript, Paper 1, 2026.