Homotopical Encryption: Hidden Hodge Operators and the Harmonic Cochain Problem

Chloe van der Vlugt

Abstract

We introduce the Harmonic Cochain Problem (HCP): recovering the operative harmonic component $h = P_{\ker(\Delta_1)}b$ from public data (α, b). The degree-one Hodge–Laplacian Δ_1 is induced by an operative hidden representative $x \in A_\alpha = \pi^{-1}(\alpha)$ of the public classifier value α. Its adjacent coboundaries δ_0, δ_1 determine the Hodge decomposition $b = h + e$, with $e \in \mathrm{im}(\delta_0) \oplus \mathrm{im}(\delta_1^*)$. We compare HCP with the closest-vector problem (CVP), distinguishing the field-linear image $\mathcal{V}_B(R) = \{Bx : x \in R^n\}$ from the discrete lattice $\Lambda_B = B\mathbb{Z}^n$. The former can be realized as a linear kernel. For an explicitly supplied inclusion $\Lambda_B \subseteq W$, orthogonal projection onto the harmonic subspace W preserves the closest lattice vectors. We then prove a hidden-operator separation: if publicly equivalent hidden operators disagree on harmonicity, a correct known-lattice CVP oracle cannot supply a uniformly exact public-data HCP solver.

Contents

1 Introduction **3**
1.1 Motivation and Contributions 3

2 The Harmonic Cochain Problem **5**
2.1 Hodge Encryption and Correctness 8
2.2 Public and Hidden Data 10
2.3 Recovery Target 13
2.4 Computational Scope 14

3 CVP Comparison and Kernel Ambiguity **14**
3.1 Known-Lattice CVP 14
3.2 Presented Linear Images 15
3.3 Explicit Harmonic-Lattice Bridge 17

3.4 Oracle Insufficiency 18
3.5 A Constructed Integral Cellular Family 19

4 Semantic Classifiers and the Homological Model 21
4.1 Fibrational Semantics 21
4.2 Path-Object Semantics for Equality 22
4.3 Public Classifier Fibers 23
4.4 The Constructed Homological Fragment 24
4.5 Scope of the Semantic Model 25

5 Observation Boundaries and Recovery 25
5.1 Exact Cochains and Full Hodge Samples 25
5.2 The Exact-Component Obstruction 26
5.3 Additional Public Observations 26
5.4 Frames and Projective Coordinates 27
5.5 Recovery from the Full Point 27

6 Conclusion and Further Work 28
6.1 Further Questions 28

A Statement–Lean Parity Table 29

B Formal Objects and Proof Boundaries 35

1 Introduction

1.1 Motivation and Contributions

Helfer's first-order homotopical logic [Hel25] provides the original semantic motivation for this framework: equality is interpreted through path objects and, under the stated hypotheses, closed-formula truth is invariant under homotopy equivalence of interpretations. This motivates distinguishing a hidden presentation from the semantic information retained by a public classifier. HCP asks how that distinction interacts with the harmonic target determined by a hidden Hodge operator.

Homotopical Encryption studies the recovery of an operative harmonic component when the Hodge operator is hidden. The public input specifies an observed cochain and a class of possible private presentations. In a known-lattice closest-vector problem, the lattice is presented before the search begins. In HCP, the recovery target is

$$h = P_H(b) \in \ker(\Delta_1),$$

but the public class does not include the degree-one Hodge–Laplacian Δ_1, its kernel, or the restriction maps from which Δ_1 is built. A solver must recover the harmonic cochain selected by the operative hidden Hodge operator.

The operator dependence can be summarized as follows. A hidden representative determines the restriction data, which determine the adjacent coboundaries and hence the degree-one Hodge operator:

$$x \longmapsto \{R^x_{\sigma\to\tau}\}_{\sigma\prec\tau} \longmapsto (\delta_{0,x}, \delta_{1,x}) \longmapsto \Delta_{1,x} \longmapsto (\ker \Delta_{1,x}, P_{H_x}).$$

The recovery operation is Hodge-theoretic; "homotopical" describes the framework in which multiple hidden representatives may occupy the same public class while inducing different operators. The public data can then leave the operative target undetermined.

The CVP comparison makes this dependence on the input precise. A real linear span can be realized as the kernel of a suitable linear operator, but a discrete lattice cannot equal a nonzero real kernel. If an explicit lattice Λ is supplied inside a harmonic subspace $W = \ker(\Delta_W)$, orthogonal projection of the target onto W preserves the closest vectors of Λ. This gives a solution-preserving comparison once the harmonic subspace and lattice inclusion are supplied. It does not recover the operative kernel from the public class.

Observation choice is part of the recovery problem. Section 5 compares exact-component observations with full projective data of the operative kernel.

The principal notation is fixed globally as follows. Symbols used only inside a single proposition or construction are defined locally.

Symbol	Meaning
$p : E \to B$	Helfer-style fibration projection
$\mathcal{P}_X(x, y)$	path object from x to y in X
$\pi : A \to P$	path-respecting public classifier
$\alpha = \pi(x) \in P$	realized public classifier value
$A_\alpha = [x]_\pi$	fiber of hidden representatives with public label α
(α, b)	public HCP observation
$\Delta_A : A \to A \times A$	diagonal map in the fibrational semantics
$a \in C^0,\ c = \delta_0 a \in C^1$	degree-zero opening and committed exact one-cochain
$\delta_0, \delta_1, \Delta_1$	adjacent coboundaries and degree-one Hodge–Laplacian
$\ker(\Delta_1),\ P_H$	harmonic subspace and harmonic projection
$\Delta_W = I - P_W$	kernel-normalized projection operator associated with W

Table 1: Core notation for the semantic interpretation and HCP.

This paper develops this boundary through the following statements.

(i) The Harmonic Cochain Problem (HCP): recovery of the operative component $h = P_H b$ for a hidden degree-one Hodge operator Δ_1.

(ii) A Hodge-structured noise model with cochain decomposition $b = h + e$, where $h \in \ker(\Delta_1)$ and $e \in \mathrm{im}(\delta_0) \oplus \mathrm{im}(\delta_1^*)$.

(iii) A CVP comparison with constructed ambiguity examples. Field-linear images are distinguished from discrete lattices; when $\Lambda \subseteq W$ is explicitly supplied, projection onto W preserves the discrete closest-vector condition on Λ. Publicly equivalent hidden Hodge operators may nevertheless disagree on harmonicity, preventing a correct explicit-lattice CVP oracle from yielding a uniform exact public-data HCP solver. Integral cellular examples have one homological public observation and distinct nonzero harmonic targets; a weighted pair shares $b = (1, 2)$ with integer coefficients two and one, with a unique CVP answer for each private lattice.

(iv) Observation boundaries: exact-component extraction can lose full Hodge residual, whereas full projective data of the operative kernel determine its fixed-metric projector and harmonic target.

Finite Hodge theory follows the cellular-cochain framework of Hansen–Ghrist [HG19]; the algebraic model used here is specified in Section 2.

Kernel realization and the Pythagorean projection identity are elementary linear-algebraic foundations. Helfer's homotopy-invariant semantics [Hel25] motivates the public classifier; the constructed examples prove only the explicitly named nonzero-cohomology-test fragment. These objects support the constructed observation ambiguities and recovery boundaries under the stated hypotheses. The computational scope is specified in Section 2.4.

The statement correspondence and formal proof boundaries are collected in the parity table after the conclusion (Section A).

2 The Harmonic Cochain Problem

We use finite graded cell carriers, integer incidence numbers and face-to-coface linear stalk maps whose induced coboundaries satisfy $\delta_1\delta_0 = 0$. This algebraic model adapts the finite Hodge setup of [HG19] without assuming a regular CW or simplicial realization for every admitted incidence structure. All cellular examples below use this declared model; stronger topological realization and the separate simplicial-coherence conditions require additional data.

Let A denote the type of hidden representatives, let P denote the type of public class data, and let

$$\pi : A \to P, \qquad \alpha \in \mathrm{im}(\pi), \qquad A_\alpha = \pi^{-1}(\alpha) = \{x \in A : \pi(x) = \alpha\}.$$

For $x \in A$, we also write $[x]_\pi := A_{\pi(x)}$. Thus, whenever $\alpha = \pi(x)$, the two descriptions agree: $A_\alpha = [x]_\pi$.

Definition 2.1 (Harmonic Cochain Problem)**.** *The* Harmonic Cochain Problem *(HCP) asks, given public data (α, b) consisting of a realized public classifier value $\alpha \in \mathrm{im}(\pi)$ and a cochain-facing observation b, to recover the operative harmonic component*

$$h = P_{\ker(\Delta_1)} b \in \ker(\Delta_1),$$

equivalently the harmonic term in the orthogonal Hodge decomposition of b. Here Δ_1 is the degree-one Hodge–Laplacian induced by the operative hidden representative $x \in A_\alpha = \pi^{-1}(\alpha)$ bound to the instance by its hidden witness.

In the Homotopical Encryption public-sample model, the visible cochain has the form

$$b = h + e, \qquad h \in \ker(\Delta_1), \qquad e \in \mathrm{im}(\delta_0) \oplus \mathrm{im}(\delta_1^*).$$

Here h is the degree-one harmonic cochain, equivalently a harmonic representative of its degree-one cohomology class, and e is Hodge-structured noise. The hidden-operator ambiguity studied below is the condition that the public data do not determine a unique Δ_1 or $\ker(\Delta_1)$. The algebraic recovery chain is

$$x \longmapsto \{R_{\sigma\to\tau}\}_{\sigma\prec\tau} \longmapsto (\delta_0, \delta_1) \longmapsto \Delta_1 \longmapsto P_H : C^1 \to \ker(\Delta_1),$$

where $x \in A_\alpha$ is a hidden representative and $R_{\sigma\to\tau}$ are the face-to-coface restriction maps, including vertex-to-edge and edge-to-face maps, that determine the adjacent coboundaries

$$\delta_0 : C^0 \to C^1, \qquad \delta_1 : C^1 \to C^2,$$

and

$$\Delta_1 = \delta_0\delta_0^* + \delta_1^*\delta_1$$

is the induced degree-one Hodge–Laplacian. The map P_H is the orthogonal projection onto $\ker(\Delta_1)$. When the degree is fixed, we write Δ for this operative Laplacian. A concrete public artifact may commit to or certify values derived from this chain without revealing the restriction maps or the induced operator.

Definition 2.2 (Matrix harmonicity)**.** *For a hidden linear Hodge operator Δ, a cochain $h \in \mathbb{R}^N$ is Δ-harmonic when*

$$\Delta h = 0.$$

Thus the harmonic kernel is $\ker(\Delta)$*. In the projection model this agrees with the condition $h \in W$ for the kernel-normalized operator $\Delta_W = I - P_W$.*

Definition 2.3 (Kernel-normalized operator, harmonic projection, and residual)**.** *Let $V = \mathbb{R}^n$ be equipped with its standard inner product, and let $W \subset V$ be a linear subspace. Write*

$$P_W : V \to W \subset V \qquad \textit{and} \qquad P_{W^\perp} : V \to W^\perp \subset V$$

for the orthogonal projections. The kernel-normalized projection operator attached to W is

$$\Delta_W = I - P_W.$$

For $b \in V$, define the residual vector and residual score by

$$r_W(b) = \Delta_W b, \qquad \rho_W(b) = \|r_W(b)\|.$$

We say that b is W-harmonic when $r_W(b) = 0$. This operator records exactly the harmonic kernel and its orthogonal projection. It is not asserted to equal a cellular Hodge–Laplacian $\delta_0\delta_0^* + \delta_1^*\delta_1$, or to have the same positive spectrum, unless the cellular Laplacian additionally acts as the identity on $W^\perp$.

Proposition 2.4 (Projection harmonicity equivalences)**.** *For every $b \in V$,*

$$r_W(b) = P_{W^\perp} b, \qquad \rho_W(b) = \|P_{W^\perp} b\|, \qquad \rho_W(b) \geq 0.$$

Moreover

$$P_W b \in W, \qquad r_W(P_W b) = 0,$$

and the following conditions are equivalent:

$$r_W(b) = 0 \iff \rho_W(b) = 0 \iff b \in W.$$

Proof. Since $V = W \oplus W^\perp$ orthogonally, every $b \in V$ decomposes uniquely as

$$b = P_W b + P_{W^\perp} b.$$

Hence

$$(I - P_W)b = b - P_W b = P_{W^\perp} b,$$

giving $r_W(b) = P_{W^\perp} b$ and the displayed formula for $\rho_W(b)$. Nonnegativity is the nonnegativity of the norm. The projection $P_W b$ lies in W, so its orthogonal component is zero; therefore $r_W(P_W b) = 0$. Finally, $r_W(b) = 0$ iff $P_{W^\perp} b = 0$, which holds iff $b \in W$. The equivalence with $\rho_W(b) = 0$ follows from $\|x\| = 0$ iff $x = 0$. □

Proposition 2.5 (Hodge decomposition surface)**.** *Let the three consecutive cochain spaces be finite-dimensional real inner product spaces, and let the displayed stars denote adjoints. Suppose*

$$d_{\text{next}} d_{\text{prev}} = 0, \qquad \Delta = d_{\text{prev}} d_{\text{prev}}^* + d_{\text{next}}^* d_{\text{next}}.$$

Then every cochain b admits a decomposition

$$b = h + e_1 + e_2$$

with

$$\Delta h = 0, \qquad e_1 \in \operatorname{im}(d_{\text{prev}}), \qquad e_2 \in \operatorname{im}(d_{\text{next}}^*),$$

and

$$\langle h, e_1 \rangle = \langle h, e_2 \rangle = \langle e_1, e_2 \rangle = 0.$$

The decomposition is unique.

Proof. Each summand defining Δ is self-adjoint, so Δ is self-adjoint. In finite dimension, $\mathrm{im}(\Delta) = (\ker \Delta)^{\perp}$, and hence the ambient cochain space decomposes as

$$\ker(\Delta) \oplus \mathrm{im}(\Delta).$$

Since

$$\mathrm{im}(\Delta) \subseteq \mathrm{im}(d_{\mathrm{prev}}) + \mathrm{im}(d^*_{\mathrm{next}}),$$

every cochain b can be written as $h + e_1 + e_2$ with $h \in \ker \Delta$, $e_1 \in \mathrm{im}(d_{\mathrm{prev}})$, and $e_2 \in \mathrm{im}(d^*_{\mathrm{next}})$. From $\Delta h = 0$, one obtains

$$\|d^*_{\mathrm{prev}} h\|^2 + \|d_{\mathrm{next}} h\|^2 = 0,$$

hence $d^*_{\mathrm{prev}} h = 0$ and $d_{\mathrm{next}} h = 0$. These identities give $\langle h, e_1 \rangle = 0$ and $\langle h, e_2 \rangle = 0$, while $d_{\mathrm{next}} d_{\mathrm{prev}} = 0$ gives $\langle e_1, e_2 \rangle = 0$. Hence the harmonic, exact, and coexact subspaces are pairwise orthogonal. Their sum is therefore direct, which makes the three components unique. □

2.1 Hodge Encryption and Correctness

For a hidden representative x, write

$$\mathcal{H}_x = \ker(\Delta_x), \qquad \mathcal{E}_x = \mathcal{H}_x^{\perp}.$$

The Hodge decomposition identifies the noise space as the orthogonal direct sum

$$\mathcal{E}_x = \mathrm{im}(\delta_{0,x}) \oplus^{\perp} \mathrm{im}(\delta^*_{1,x}),$$

and gives the orthogonal decomposition

$$C^1_x = \mathcal{H}_x \oplus^{\perp} \mathcal{E}_x.$$

Consequently,

$$\begin{aligned} \mathrm{combine}_x : \mathcal{H}_x \times \mathcal{E}_x &\longrightarrow C^1_x, & (h, e) &\longmapsto h + e, \\ \mathrm{split}_x : C^1_x &\longrightarrow \mathcal{H}_x \times \mathcal{E}_x, & b &\longmapsto (P_{\mathcal{H}_x} b, P_{\mathcal{E}_x} b) \end{aligned}$$

are inverse linear bijections. Orthogonality also gives

$$\|h + e\|^2 = \|h\|^2 + \|e\|^2.$$

This bijection is the algebraic encryption/decryption construction. Given a harmonic message $h \in \mathcal{H}_x$, randomized Hodge encryption samples, or otherwise chooses, admissible noise $e \in \mathcal{E}_x$ and sets

$$\mathsf{Enc}_x(h; e) = \mathrm{combine}_x(h, e) = h + e.$$

Full coordinate recovery is split_x; message decryption retains its harmonic coordinate:

$$\mathsf{Dec}_x(b) = \mathrm{pr}_{\mathcal{H}_x}\big(\mathrm{split}_x(b)\big) = P_{\mathcal{H}_x} b.$$

For every admissible noise value,

$$\mathsf{Dec}_x\big(\mathsf{Enc}_x(h;e)\big) = h, \qquad \mathrm{split}_x\big(\mathrm{combine}_x(h,e)\big) = (h,e).$$

Thus the bijection is between the full message–randomness pair and C_x^1. After randomness is sampled, Enc_x is a randomized procedure and Dec_x is its message-correct left inverse; this does not assert that a randomized map from messages alone is a bijection.

The subscript x is essential. The hidden representative—and, in a keyed instantiation, the private material selecting or opening it—determines Δ_x, the two summands, and the splitting map. The correctness identity is pointwise and requires no uniform distribution on an infinite noise space. It is not an indistinguishability or one-wayness claim; those require separate assumptions about key generation, randomness, and the public view.

When several presentation-dependent spaces C_x^1 are compared using one public coordinate vector, we fix isometric coordinate charts $\iota_x : C_x^1 \xrightarrow{\sim} V$ into a common finite-dimensional real inner-product space V. Operators denoted $\Delta_x \in \mathrm{End}(V)$ below are the corresponding conjugated operators. The charts are comparison data; they are not asserted to be recoverable from the public classifier.

Proposition 2.6 (Exact-component obstruction)**.** *Suppose $v \in C^2$ and $\delta_1^* v \neq 0$. On the unrestricted Hodge-noise carrier, the samples*

$$b_t = t\delta_1^* v, \qquad t \in \mathbb{R},$$

have zero harmonic message and zero exact component, while

$$\|P_{\mathcal{H}^\perp} b_t\| = |t|\,\|\delta_1^* v\|.$$

Thus this full-observation residual does not factor through the exact component. If an extraction depends only on that component and its zero image has target distance zero, it cannot preserve any positive target far radius uniformly on this unrestricted carrier, at any source radius.

Proof. A coexact vector is orthogonal to $\mathcal{H}$, so its orthogonal projection onto $\mathcal{H}^\perp$ is itself. Homogeneity gives the displayed norm. The exact-component view is constantly zero, whereas this norm is zero at $t = 0$ and positive at $t = 1$, proving nonfactorization. For any fixed source radius, choose positive t large enough to exceed it. The extracted value still has distance zero, contradicting every positive target far radius. □

This statement concerns a map factoring through the decoded exact component. Equal decoded components do not by themselves imply equal raw payload bytes for an arbitrary decoder. A restricted noise or authenticated realization profile may exclude this family; a theorem about such a profile requires its explicit hypotheses. The statement does not identify distance to exactness with the full HCP residual.

2.2 Public and Hidden Data

Definition 2.7 (Public observation)**.** *The public HCP observation consists of a realized public classifier value α together with an observed degree-one cochain b.*

Thus (α, b) is the protocol-independent vector-level observation. The value α records the public classifier value, while b is the full cochain actually released by the selected observation profile. Acceptance of an exact payload, an opening of its exact component, or a proof about that component does not by itself expose b. Instantiating the vector-level interface requires a relation binding the full sample to the artifact and an explicit disclosure or specified extraction of that sample. Section 5 records this mathematical distinction. The hidden-kernel ambiguity comparison uses the resulting mathematical pair; equality of a larger artifact or storage view requires its own hypotheses.

The public observation is not the hidden Hodge system. It classifies a public equivalence class of possible hidden representatives. Fibrational and homotopical semantics enter through this distinction: public equality is equality after applying a public classifier, not strict equality of hidden representatives. Section 4 develops this semantic interpretation.

Definition 2.8 (Hidden-operator public projection)**.** *For a public class type P, a public projection is a map*

$$\pi_\Delta : \{\textit{hidden Hodge operators } \Delta\} \longrightarrow P.$$

Two hidden operators are publicly equivalent when $\pi_\Delta(\Delta) = \pi_\Delta(\Delta')$. The hidden operator fiber over $\alpha \in P$ is

$$\mathrm{Fib}_{\pi_\Delta}(\alpha) = \pi_\Delta^{-1}(\alpha) = \{\Delta : \pi_\Delta(\Delta) = \alpha\},$$

and the hidden class of Δ is $\mathrm{Fib}_{\pi_\Delta}(\pi_\Delta(\Delta))$.

Definition 2.9 (Lossiness and kernel ambiguity)**.** *The public projection π_Δ is* lossy *if there exist $\Delta \neq \Delta'$ with $\pi_\Delta(\Delta) = \pi_\Delta(\Delta')$. The two operators have*

the same harmonic kernel if

$$\forall v, \quad \Delta v = 0 \Longleftrightarrow \Delta' v = 0.$$

The projection is kernel-ambiguous *if there are publicly equivalent operators* Δ, Δ' *whose harmonic kernels are not the same.*

Definition 2.10 (Public-compatible Hodge ambiguity)**.** *Public-compatible Hodge ambiguity means that there exist publicly equivalent operators* Δ, Δ' *and a cochain-facing observation* b *such that*

$$\Delta b = 0 \qquad \textit{but} \qquad \Delta' b \neq 0.$$

Definition 2.11 (Typed HCP semantic realization)**.** *Fix a multi-sorted algebraic signature* σ*, a model category* $\mathcal{C}$ *with terminal object and binary products, and, for each hidden representative* $x \in A$*, a base interpretation* $M_x : \sigma \to \mathcal{C}_{\mathrm{f}}$ *together with homotopical formula semantics over* M_x*. Write*

$$\mathrm{Th}(M_x) = \{\varphi \textit{ closed} : M_x \vDash \varphi\}$$

for its closed first-order theory. Use the chosen coordinate charts to compare cochains in a common finite-dimensional real inner-product space V*. A typed HCP semantic realization consists additionally of maps*

$$\begin{aligned} x &\longmapsto \Delta_x \in \mathrm{End}(V), \\ \kappa &: \{\textit{closed theories}\} \longrightarrow P, \\ \pi_\Delta &: \{\textit{Hodge operators}\} \longrightarrow P, \end{aligned}$$

satisfying the two factorization identities

$$\pi(x) = \kappa(\mathrm{Th}(M_x)), \qquad \pi_\Delta(\Delta_x) = \pi(x).$$

The Laplacian Δ_x *is presentation-level Hodge data extending the semantic core* M_x*; it is not silently included among the symbols whose closed theory is asserted to be homotopy invariant.*

Proposition 2.12 (Helfer-to-HCP classifier bridge)**.** *Let* $x, y \in A$ *belong to a typed HCP semantic realization. If* M_x *and* M_y *are homotopy equivalent interpretations in the sense of Helfer, then*

$$\pi(x) = \pi(y) \qquad \textit{and} \qquad \pi_\Delta(\Delta_x) = \pi_\Delta(\Delta_y).$$

If, independently, there is a cochain b *for which*

$$\Delta_x b = 0, \qquad \Delta_y b \neq 0,$$

then π_Δ *has public-compatible Hodge ambiguity, and hence is kernel-ambiguous and lossy.*

Proof. The closed-formula case of Helfer's homotopy-invariance theorem [Hel25, Theorem 12.3] gives, for every closed σ-formula φ,

$$M_x \models \varphi \quad \Longleftrightarrow \quad M_y \models \varphi.$$

Hence $\mathrm{Th}(M_x) = \mathrm{Th}(M_y)$. Applying κ and then the two factorization identities gives

$$\pi(x) = \pi(y), \qquad \pi_\Delta(\Delta_x) = \pi_\Delta(\Delta_y).$$

The additional displayed harmonicity and non-harmonicity conditions now exhibit (Δ_x, Δ_y, b) as a public-compatible Hodge-ambiguity witness. The ambiguity hierarchy below supplies kernel ambiguity and lossiness. □

The direction in Proposition 2.12 is one-way. Homotopy-equivalent interpretations have the same factored public value, but equality of public values need not reconstruct a homotopy equivalence: a classifier fiber may be strictly coarser than an equivalence class. Likewise, the equivalence itself does not produce kernel disagreement. If Δ-harmonicity were included in the invariant first-order signature, and the common coordinate b were named compatibly in both interpretations, Helfer's theorem would instead rule out the displayed disagreement.

There is a second, geometric distinction. Suppose an equivalence of hidden presentations induces degreewise linear isometric equivalences U_0, U_1, U_2 satisfying

$$U_1 \delta_{0,x} = \delta_{0,y} U_0, \qquad U_2 \delta_{1,x} = \delta_{1,y} U_1.$$

After conjugating by the fixed coordinate charts, U_1 is an isometry of the common comparison space V. Because the U_k preserve inner products, the adjoints transport as well, and hence

$$\Delta_y U_1 = U_1 \Delta_x, \qquad U_1(\ker \Delta_x) = \ker \Delta_y.$$

The corresponding orthogonal projections commute with transport:

$$U_1 P_{\ker \Delta_x} b = P_{\ker \Delta_y} U_1 b.$$

Thus a transported observation preserves both the operative target and harmonicity:

$$\Delta_x b = 0 \quad \Longleftrightarrow \quad \Delta_y(U_1 b) = 0.$$

The ambiguity witness in Proposition 2.12 deliberately compares the same untransported public coordinate $b \in V$, not the pair $(b, U_1 b)$. Under the displayed conjugacy, its extra separation condition is equivalently

$$b \in \ker \Delta_x, \qquad b \notin U_1(\ker \Delta_x).$$

It therefore requires a nonstabilization witness in addition to the equivalence, and it models a public view that neither reveals nor applies the private transport U_1. If the observation were transported together with the hidden presentation, this particular ambiguity would disappear.

Proposition 2.13 (Ambiguity hierarchy)**.** *Public-compatible Hodge ambiguity implies kernel ambiguity, and kernel ambiguity implies that the public projection is lossy.*

Proof. If b is harmonic for Δ but not for Δ', then the two operators cannot have the same harmonic kernel. This gives kernel ambiguity. If publicly equivalent operators have different kernels, they cannot be the same operator, since equality of operators implies equality of kernels. Therefore the public projection identifies two distinct hidden operators. □

Definition 2.14 (Hidden Hodge witness)**.** *A hidden Hodge witness for a public observation (α, b) is a hidden representative $x \in A$ satisfying $\pi(x) = \alpha$. Through the typed realization, it selects the operative operator Δ_x. The witness and b then determine, rather than independently assume, the coordinates*

$$h_x(b) := P_{\ker(\Delta_x)} b, \qquad e_x(b) := b - h_x(b).$$

For a genuine degree-one Hodge operator $\Delta_x = \delta_{0,x}\delta_{0,x}^* + \delta_{1,x}^*\delta_{1,x}$, the Hodge decomposition gives

$$h_x(b) \in \ker(\Delta_x), \qquad e_x(b) \in \operatorname{im}(\delta_{0,x}) \oplus \operatorname{im}(\delta_{1,x}^*), \qquad b = h_x(b) + e_x(b).$$

The hidden data include the fibration representative, restriction maps, the induced Laplacian, its harmonic kernel, and private witness/cochain data. Public data may bind to this hidden data through commitments or proof-carrying artifacts, but it does not present the operative kernel.

Definition 2.15 (HCP solution)**.** *Relative to an operative hidden witness x, a solution to an HCP instance (α, b) is the cochain $h' = h_x(b) = P_{\ker(\Delta_x)} b$. A public-data-only solver is* uniformly exact *if the same output has this value for every hidden witness compatible with its public input. The hidden-operator separation concerns this uniform contract; it does not deny that decryption succeeds once the operative private geometry is supplied.*

2.3 Recovery Target

The recovery target is the orthogonal projection of b into the operative kernel, not the entire kernel subspace. Thus CVP asks for a closest vector in a

presented lattice, while HCP asks for $P_{\ker(\Delta_x)}b$ for the operative hidden representative.

In the metric variant used for comparison with CVP, the continuous target is the closest harmonic cochain to b. Presenting Δ or a basis for $\ker(\Delta)$ presents a real subspace, not a discrete lattice. A genuine CVP instance additionally requires an explicit lattice $\Lambda \subseteq \ker(\Delta)$; Proposition 3.2 shows that projection onto the kernel preserves the closest vectors of that supplied lattice. The hidden-operator model withholds the operative subspace itself.

2.4 Computational Scope

The comparisons below concern exact recovery and preservation of discrete CVP solutions when the harmonic subspace, lattice and inclusion are supplied. The ambiguity examples show that the stated public input can fail to identify its operative target, ruling out a uniformly exact solver on that family. A computational hardness assumption requires encoded instance families, a specified measure of input size, an algorithm class and a success criterion; the present results do not constitute an asymptotic CVP-hardness reduction. Distributional encryption security would further require a sampling model and a defined adversary view.

3 CVP Comparison and Kernel Ambiguity

CVP asks for a closest vector in an explicitly presented lattice [MG02]. HCP asks for the projection of b into the kernel of the operative hidden Hodge operator. In the Homotopical Encryption model, public data need not determine the corresponding harmonic kernel.

3.1 Known-Lattice CVP

An explicit Euclidean CVP instance consists of a full-column-rank generator matrix $B \in \mathbb{R}^{m\times n}$ and a target $t \in \mathbb{R}^m$. Its discrete lattice is

$$\Lambda_B = B\mathbb{Z}^n = \{Bz : z \in \mathbb{Z}^n\}.$$

The injectivity of $z \mapsto Bz$ records that the displayed columns are a lattice basis. A correct closest-vector answer is a vector $v \in \Lambda_B$ such that

$$\|t - v\|^2 \leq \|t - w\|^2 \qquad \text{for every } w \in \Lambda_B.$$

Thus, for fixed dimensions, a CVP oracle O is correct when

$$\begin{aligned}\mathsf{CVP}_{\mathrm{corr}}(O) \quad \Longleftrightarrow \quad & \forall \text{ full-column-rank } B, t, \\ & O(B,t) \in \Lambda_B \quad \text{and} \quad \forall w \in \Lambda_B, \\ & \|t - O(B,t)\|^2 \le \|t - w\|^2.\end{aligned}$$

The weaker output condition is merely lattice membership:

$$\forall B, t,\ O(B,t) \in \Lambda_B.$$

Fix a class $\mathcal{C}$ of admissible algorithms, such as polynomial-time or probabilistic polynomial-time algorithms. The external CVP hardness assumption is the schema

$$\mathsf{CVP}_{\mathrm{hard}}(\mathcal{C}) \quad \Longleftrightarrow \quad \neg\exists O,\ O \in \mathcal{C} \wedge \mathsf{CVP}_{\mathrm{corr}}(O).$$

A CVP oracle receives B and t. The HCP procedures studied here receive (α, b); the operative Hodge operator and its kernel are withheld.

3.2 Presented Linear Images

Let R be a field. The field-linear image of B is a different object:

$$\mathcal{V}_B(R) = BR^n = \{Bx : x \in R^n\}.$$

Over a field this is a linear subspace, not the discrete lattice $B\mathbb{Z}^n$. The following comparison is therefore linear algebra; it is not a reduction from discrete CVP.

Let B present $\mathcal{V}_B(R)$. If a matrix Δ satisfies $\ker(\Delta) = \mathcal{V}_B(R)$, then any solver satisfying

$$\Delta S(\Delta, t) = 0$$

returns $S(\Delta, t) \in \mathcal{V}_B(R)$.

Proposition 3.1 (Kernel realization for explicit generated subspaces)**.** *Let $B \in R^{n\times n}$ be an explicit square generator matrix over a field and set $\mathcal{V}_B(R) = \{Bx : x \in R^n\}$. There exists a matrix Δ such that*

$$\ker(\Delta) = \mathcal{V}_B(R).$$

Consequently, any solver $S(\Delta, b)$ whose output is Δ-harmonic for every presented Δ returns a vector in the explicit generated subspace $\mathcal{V}_B(R)$ when run on this realized operator.

Proof. Let $B \in R^{n\times n}$ be an explicit generator matrix over a field R, set

$$\mathcal{V}_B(R) = \{Bx : x \in R^n\} \subseteq R^n,$$

and let $t \in R^n$ be the solver input. We construct a matrix Δ with

$$\ker(\Delta) = \mathcal{V}_B(R).$$

Put $V = \mathcal{V}_B(R)$. Since R^n is finite-dimensional over a field, choose a complementary subspace W with

$$V + W = R^n, \qquad V \cap W = 0.$$

Thus every $y \in R^n$ has a unique decomposition

$$y = v + w, \qquad v \in V, \quad w \in W.$$

Equivalently, there is a unique element $w_y \in W$ such that $y - w_y \in V$. Define

$$P(y) = w_y.$$

The uniqueness of the $V \oplus W$ decomposition gives linearity: for $y, z \in R^n$, the vector $P(y) + P(z)$ lies in W, and

$$(y + z) - (P(y) + P(z)) = (y - P(y)) + (z - P(z)) \in V,$$

so $P(y + z) = P(y) + P(z)$. Similarly, for $a \in R$, $aP(y) \in W$ and

$$ay - aP(y) = a(y - P(y)) \in V,$$

so $P(ay) = aP(y)$.

We now compute the kernel. If $y \in V$, then $0 \in W$ and $y - 0 \in V$, hence uniqueness gives $P(y) = 0$. Conversely, if $P(y) = 0$, then $y - P(y) = y \in V$. Therefore

$$\ker P = V = \mathcal{V}_B(R).$$

Let Δ be the matrix of the linear map P. Then, for every $y \in R^n$,

$$\Delta y = 0 \quad \Longleftrightarrow \quad y \in \ker P \quad \Longleftrightarrow \quad y \in \mathcal{V}_B(R) \quad \Longleftrightarrow \quad \exists x,\ Bx = y.$$

Let $S : R^{n\times n} \times R^n \to R^n$ be a presented-operator Hodge solver satisfying

$$\forall \Delta\, b, \qquad \Delta(S(\Delta, b)) = 0.$$

Applying this to the Δ constructed above and $b = t$ gives

$$\Delta(S(\Delta, t)) = 0.$$

By the kernel calculation, there exists x with

$$Bx = S(\Delta, t).$$

Hence $S(\Delta, t) \in \mathcal{V}_B(R)$. □

When $R = \mathbb{R}$, if a presented-operator solver additionally minimizes Euclidean distance among Δ-harmonic vectors, the same kernel equality says that it returns the continuous closest point of $\mathcal{V}_B(\mathbb{R})$. This is still not discrete CVP unless a separate lattice is supplied.

3.3 Explicit Harmonic-Lattice Bridge

The discrete bridge requires both kinds of data: a real harmonic subspace and an integer lattice contained in it. Let $W \subseteq \mathbb{R}^m$ be the operative harmonic subspace, let P_W be its orthogonal projection, and let $\Lambda_B = B\mathbb{Z}^n \subseteq W$ be an explicitly presented lattice. Set

$$\Delta_W = I - P_W.$$

The inclusion $\Lambda_B \subseteq W$ does not identify the discrete lattice with the real subspace.

Proposition 3.2 (Discrete CVP through harmonic projection)**.** *For $t \in \mathbb{R}^m$, put $t_W = P_W t$. Then:*

(i) t_W and every $\lambda \in \Lambda_B$ are Δ_W-harmonic;

(ii) for every $\lambda \in \Lambda_B$,

$$\|t - \lambda\|^2 = \|t - t_W\|^2 + \|t_W - \lambda\|^2;$$

(iii) a lattice vector λ is closest to t in Λ_B if and only if it is closest to t_W in Λ_B.

Proof. Since $t_W \in W$, every $\lambda \in \Lambda_B$ also lies in W, and $\ker(\Delta_W) = W$, the harmonicity claims follow. For the distance identity, write

$$t - \lambda = (t - t_W) + (t_W - \lambda).$$

Orthogonal projection gives $t - t_W \in W^\perp$, while $t_W - \lambda \in W$. The two summands are orthogonal, so the Pythagorean identity gives (ii). The term $\|t - t_W\|^2$ is independent of λ; consequently, for any $\lambda, \mu \in \Lambda_B$,

$$\|t - \lambda\|^2 \leq \|t - \mu\|^2 \quad \iff \quad \|t_W - \lambda\|^2 \leq \|t_W - \mu\|^2.$$

This is exactly (iii). □

The continuous projection $t_W = P_W t$ is the closest harmonic vector to t, but it need not lie in Λ_B. Thus projection transports the target to the harmonic subspace while preserving the discrete minimizers; it does not perform the remaining lattice search. The proposition also presumes that W and the inclusion $\Lambda_B \subseteq W$ have been supplied. It does not discover the operative hidden subspace from public class data.

3.4 Oracle Insufficiency

The oracle-insufficiency direction uses the typed realization from Definition 2.11. A public Hodge solver may call an explicit-lattice CVP oracle and receives the actual public observation (α, b), but it receives no hidden representative or operative Laplacian. Correctness is required only for representatives admitted by the realization, rather than for every matrix of the ambient size.

Definition 3.3 (Public-data Hodge solver contract)**.** *Let*

$$S : \mathcal{O}_{\mathrm{CVP}} \times (P \times \mathbb{R}^n) \longrightarrow \mathbb{R}^n,$$

where $\mathcal{O}_{\mathrm{CVP}}$ is the class of explicit-lattice CVP oracles. For a realization $x \mapsto (M_x, \Delta_x)$ and $O \in \mathcal{O}_{\mathrm{CVP}}$, define

$$\begin{aligned} \mathsf{H}_O(S) &\iff \forall x : A, \quad \forall b \in \mathbb{R}^n, \quad \Delta_x\big(S(O, (\pi(x), b))\big) = 0, \\ \mathsf{F}_O(S) &\iff \forall x : A, \quad \forall b \in \mathbb{R}^n, \quad \Delta_x b = 0 \Rightarrow S(O, (\pi(x), b)) = b. \end{aligned}$$

The public-data-only contract is

$$\exists S, \quad \forall O, \quad \mathsf{CVP}_{\mathrm{corr}}(O) \Rightarrow \big(\mathsf{H}_O(S) \wedge \mathsf{F}_O(S)\big).$$

Proposition 3.4 (Typed HCP ambiguity and CVP oracle insufficiency)**.** *Let $x, y \in A$ be representatives in a typed HCP semantic realization. Suppose that M_x and M_y are homotopy equivalent and that some $b \in \mathbb{R}^n$ satisfies*

$$\Delta_x b = 0, \qquad \Delta_y b \neq 0.$$

If at least one correct explicit-lattice CVP oracle exists, then

$$\neg\exists S, \quad \forall O, \quad \mathsf{CVP}_{\mathrm{corr}}(O) \Rightarrow (\mathsf{H}_O(S) \wedge \mathsf{F}_O(S)).$$

Hence a correct oracle for explicit known-lattice CVP does not by itself determine the operative Hodge–Laplacian kernel.

Proof. By Proposition 2.12, $\pi(x) = \pi(y)$. Suppose $\exists O, \mathsf{CVP}_{\mathrm{corr}}(O)$, and choose such an O. Suppose, for contradiction, that S satisfies the displayed public-data-only contract. Then

$$\mathsf{H}_O(S) \wedge \mathsf{F}_O(S).$$

Since $\Delta_x b = 0$, exactness at x gives

$$S(O, (\pi(x), b)) = b.$$

Soundness at y gives

$$\Delta_y S(O, (\pi(y), b)) = 0.$$

Replacing $\pi(y)$ by $\pi(x)$ and using the exactness equality yields $\Delta_y b = 0$, contradicting the separation hypothesis. □

The obstruction is kernel ambiguity: the same public observation may be compatible with multiple hidden operators whose harmonic kernels differ. A CVP oracle can solve a closest-vector problem after the lattice is presented. The bridge in Proposition 3.2 applies only after the operative harmonic subspace and the lattice inclusion have also been supplied; it does not determine which hidden kernel is compatible with the public data.

For every dimension at least two, consider the elementary matrix witness $L = 0$, $L' = \mathrm{diag}(1, 0, \ldots, 0)$, and $b = e_1$ under the constant projection to a one-point public type. This is a sanity example showing that the abstract ambiguity predicates are inhabited. It is not used as evidence that an arbitrary HCP realization admits the required semantic and Hodge extension witness. That witness remains an explicit hypothesis of Proposition 3.4; the following family constructs one for its stated semantic fragment.

3.5 A Constructed Integral Cellular Family

The preceding implication has a concrete instantiation in a stated homological fragment of the typed Helfer interface. Take one vertex, one edge and one face with incidence numbers $\partial_1 = 0$, $\partial_2 = 1$, and stalks $0, \mathbb{R}^2, \mathbb{R}$, respectively. This is the algebraic finite signed-incidence model of Section 2; no regular

CW or simplicial realization of this displayed base is asserted. Two cellular sheaves in that model have

$$\delta_{0,0} = \delta_{0,1} = 0, \qquad \delta_{1,0}(x_0, x_1) = x_0, \qquad \delta_{1,1}(x_0, x_1) = x_1.$$

Their true degree-one Hodge operators are

$$\Delta_0 = \operatorname{diag}(1, 0), \qquad \Delta_1 = \operatorname{diag}(0, 1).$$

Coordinate exchange is a degreewise chain isometry. Both operators have positive spectral gap 1. Standard integral stalk lattices give harmonic lattices $\mathbb{Z}e_1$ and $\mathbb{Z}e_0$, each with an explicit full-span presentation.

Interpret these actual complexes in the bounded-below real cochain Quillen model category. For this example the closed tests ask whether cohomology in an integer degree is nonzero. Their invariance is proved under every typed Helfer equivalence, using quasi-isomorphisms. The chain isometry therefore makes the two actual closed theories equal. This proves invariance for this homological test fragment; it does not formalize Helfer's full first-order formula syntax or general fibrational invariance theorem.

Proposition 3.5 (One observation, two nonzero integral harmonic targets)**.** *Let p be the common closed theory of these two presentations in the stated fragment, and let $b = e_0 + e_1$. There are structured Hodge samples with that same observation (p, b), harmonic messages e_1 and e_0, and zero exact components. Their operative targets are distinct and nonzero. For each presentation's explicit harmonic lattice, its message is also the unique closest lattice vector to b.*

Proof. In the first presentation use harmonic message e_1, exact opening zero and coexact opening 1, producing noise e_0. In the second use message e_0, exact opening zero and coexact opening 1, producing noise e_1. Both sums equal b, and both messages belong to their standard integral harmonic lattices. The actual Hodge projections recover those messages. Orthogonality gives the Pythagorean identity from Proposition 3.2; any other lattice point has strictly positive squared distance from the recovered message. Thus each message is the unique CVP answer in its presented lattice. □

For the same realization, the fixed coordinate e_1 is harmonic for Δ_0 and not for Δ_1. This constructs the separation witness used in Proposition 3.4. The existing no-uniform-recovery theorem therefore applies, and its explicit-CVP-oracle corollary applies under its oracle-existence premise. Equality of the public theory is derived from the actual semantic equivalence, rather

than imposed by a one-point classifier. The matrix-level public projection is extended from the two admitted operators; no semantic realization is asserted for other matrices.

The displayed pair uses coefficient 1 in each presentation's own harmonic-lattice basis. Its distinct ambient targets therefore do not alone assert distinct encoded integer plaintexts. A second constructed pair makes the encoding explicit: take $b = e_0 + 2e_1$, harmonic messages $2e_1$ and e_0, and complementary coexact noise e_0 and $2e_1$. Their integer coefficients in the same declared lattice presentations are 2 and 1. Both messages are nonzero, both exact components remain zero, and the public observation is again shared. No function of that observation can return the correct coefficient for both presentations. This is a finite exact-recovery obstruction for the specified integer encoding, not a distributional security experiment. Each message remains the unique CVP answer in its actual lattice.

This example fixes the mathematical observation to (p, b). Its equal zero exact components do not imply equality of complete storage records. A larger released view must be specified and shown to agree for both presentations before the same ambiguity argument applies. Transferring the target and CVP conclusions also requires agreement with the operative operator and classifier. No distributional anonymity or plaintext-security conclusion follows from this example.

4 Semantic Classifiers and the Homological Model

The ambiguity theorem uses equality of public class values. We now describe the semantic conditions that supply this equality, before examining what additional observations reveal.

4.1 Fibrational Semantics

The path-object and fibrational part of this semantic setting is adapted from Helfer's first-order homotopical logic [Hel25, Sections 2–7]. In particular, we use its replacement of diagonal equality by a path-space fibration, its Grothendieck-fibrational formulation of first-order semantics, and its homotopy-invariance theorem. We do not reproduce Helfer's full development of suitable model categories, Kan complexes, $h^{=}$-fibrations, or two-dimensional fibrations. Instead, we extract the semantic obligations consumed by HCP and add the project-specific public-classifier and observation boundary below. Helfer's external invariance theorem is cited as background. We retain the typed data needed to apply that result: a multi-sorted algebraic

signature, finite-product interpretations, homotopy homomorphisms coherent with every function symbol, and componentwise homotopy equivalence between cofibrant-fibrant interpretations. The closed-formula consequence of Helfer's theorem remains an explicit hypothesis, from which the HCP classifier bridge is proved in Proposition 2.12. We use the usual fibrational notation

$$p : E \longrightarrow B, \qquad E_b = p^{-1}(b)$$

for a total space of hidden data over a base of public or contextual data. When $x, y \in E_b$, equality in this setting is interpreted through a path object rather than by strict equality in the ambient presentation. We write $\mathcal{P}_X(x, y)$ for the path object from x to y in a space or type X, and set

$$x \simeq_b y \quad \Longleftrightarrow \quad \mathcal{P}_{E_b}(x, y) \neq \varnothing.$$

For a dependent family $F : E \to \mathsf{Type}$ equipped with the stated fibrational transport data, a path $\gamma \in \mathcal{P}_E(x, y)$ supplies the chosen map

$$\gamma_* : F_x \longrightarrow F_y.$$

Such transport is additional structure; equality of public classifier values alone supplies no transport map. Concrete observation and transport maps require their own compatibility data; these laws do not construct a byte-level encoding.

The typed interpretation assigns an object of a model category to each sort of an algebraic signature. Finite lists of sorts are interpreted by finite products, and function symbols by maps between those products. A homotopy homomorphism respects those operations up to the specified homotopies; the homotopy-equivalence data used by the classifier bridge also requires the stated componentwise homotopy-equivalence data. These conditions are separate from a relabelling of a presentation or an equality of matrix nullities.

4.2 Path-Object Semantics for Equality

Following Helfer's homotopical interpretation of intuitionistic first-order logic [Hel25, Section 2 and Definitions 6.3 and 6.6], let A be a Kan complex, or more generally an object in a suitable model category, and choose a path-object factorization

$$\Delta_A : A \xrightarrow{\sim} PA \twoheadrightarrow A \times A.$$

In the simplicial realization one may take $PA = A^I$, with the second map given by endpoint evaluation. For points $x, y \in A$, write

$$\mathcal{P}_A(x, y) = PA \times_{A\times A} \{(x, y)\}.$$

The interpretation of the atomic equality formula $x = y$ is this pullback. Its semantic inhabitation condition is therefore

$$x \simeq_A y \quad \Longleftrightarrow \quad \mathcal{P}_A(x, y) \neq \varnothing.$$

As an elementary local consequence, if the chosen path data also carry constant paths, reversal, and composition, then $\simeq_A$ is reflexive, symmetric, and transitive. This equivalence-relation observation is not being quoted as a separate theorem of Helfer.

Helfer's homotopy-invariance theorem applies under its stated categorical hypotheses. Let $M, N : \sigma \to \mathcal{C}_{\mathrm{f}}$ be base interpretations of an algebraic signature in a suitable model category, let $\widehat{M}, \widehat{N}$ be homotopical interpretations over them, and let $M \simeq N$ be a homotopy equivalence of the base interpretations. Then every formula-in-context has homotopy-equivalent interpretation objects over the induced context equivalence. In particular,

$$M \simeq N \quad \Longrightarrow \quad (M \models \varphi \Longleftrightarrow N \models \varphi)$$

for every closed first-order formula φ [Hel25, Definition 7.1 and Theorem 12.3]. We use this external theorem as semantic background; the general HCP comparison retains its closed-formula consequence as an explicit premise.

HCP uses this path-equality semantics as motivation for its hidden-representative model. The public classifier, the cryptographic hiding of a representative or path witness, and the verifier's evidence boundary are project-specific additions; they do not follow from Helfer's invariance theorem alone.

4.3 Public Classifier Fibers

Let A be a type of hidden representatives and let P be a type of public class data. A public classifier is a map

$$\pi : A \longrightarrow P.$$

It determines public fibers

$$A_\alpha = \pi^{-1}(\alpha) = \{x \in A : \pi(x) = \alpha\}, \qquad \alpha \in \mathrm{im}(\pi),$$

and a public equivalence relation

$$x \equiv_\pi y \quad \Longleftrightarrow \quad \pi(x) = \pi(y).$$

The classifier is path-respecting when

$$x \simeq_A y \Longrightarrow x \equiv_\pi y,$$

and nonfaithful when some public fiber contains distinct hidden representatives. A path $\gamma \in \mathcal{P}_A(x, y)$ is a hidden witness that x and y lie in the same path component; under path-respect, its public consequence is the equality $\pi(x) = \pi(y)$. At this stage the public datum is only the classifier value.

Path-respecting gives only the displayed forward implication. Unless a separate completeness condition is imposed, equality of classifier values need not imply the existence of a path; a public fiber A_α may be a coarser union of path components. Accordingly, α denotes the public classifier value and A_α its fiber, not a hidden path witness.

Nor do path-respect and nonfaithfulness prove that π hides x: nonfaithfulness supplies a collision, but it does not imply one-wayness, indistinguishability, or the absence of other private information from the output. Such privacy is a separate cryptographic property of the chosen public-view construction and its distributions.

The fibration projection and public classifier describe compatible but distinct levels. When the hidden representatives are the objects of E, a map $\kappa : B \to P$ on objects supplies the compatibility condition

$$\pi = \kappa \circ p.$$

Then $p(x)$ is the fibration-base point of x, while $\alpha = \pi(x) = \kappa(p(x))$ is its public class label. The special case $B = P$ and $\kappa = \mathrm{id}_B$ identifies the underlying object maps π and p. In general, κ may be lossy, and

$$A_\alpha = \bigcup_{\substack{b \in B \\ \kappa(b) = \alpha}} E_b.$$

This compatibility datum is additional structure; it is not implied merely by the requirement that π respect paths.

4.4 The Constructed Homological Fragment

The concrete family in Proposition 3.5 interprets its single complex sort in the bounded-below cochain model of real vector spaces. Its degree-zero-through-two terms use the actual incidence-defined cellular coboundaries. The closed

tests of the declared fragment are indexed by integers: the test in degree j asks whether H^j is nonzero. Quasi-isomorphisms preserve these tests, and the model's weak equivalences are quasi-isomorphisms. The development proves the required cofibrancy and fibrancy for these real complexes and obtains the corresponding closed-test invariance.

Consequently, the degreewise chain isometry exchanging the two coordinates of the constructed example gives equality of the two actual homological theories. This proves the shared-class premise used in the ambiguity argument. It does not identify equal public classes with all possible paths, or establish completeness of the classifier for every hidden representative. The full first-order syntax, equality objects and fibrational invariance statement of Helfer's general framework remain external background; the concrete example proves the named fragment rather than assuming the full first-order theorem.

4.5 Scope of the Semantic Model

The generic bridge in Proposition 2.12 retains its explicit invariance and separation hypotheses. The constructed fragment discharges its own invariance premise; it does not supply protocol authentication, a computational sampler or a security game.

5 Observation Boundaries and Recovery

The recovery problem fixes the public pair (α, b) from Definition 2.7. Changing the observation can change what is recoverable. We first examine observations of the exact component, then show how full projective data of the operative harmonic subspace determine the recovery target.

5.1 Exact Cochains and Full Hodge Samples

Fix one cellular Hodge system and an opening $a \in C^0$. Its exact one-cochain $c = \delta_0 a$ satisfies

$$P_H c = P_H \delta_0 a = 0.$$

Indeed, $\operatorname{im} \delta_0$ is orthogonal to the harmonic subspace. Thus this exact cochain is not the full sample $b = h + e$ when the harmonic message h is nonzero. An encoding modulo an integer, a digest of that encoding and a proof about its acceptance do not, by their types alone, supply the full b or its relation to the operative hidden operator.

There is also a distinction between the exact one-cochain and its opening. Linearity gives

$$\delta_0 a = \delta_0 a' \quad \Longleftrightarrow \quad a - a' \in \ker \delta_0.$$

Consequently the raw coboundary determines an opening only modulo $\ker \delta_0$. A unique degree-zero message encoding requires further application data. This elementary observation is independent of binding a specified exact C^1 payload cryptographically.

To connect a protocol artifact to the HCP observation, an application must supply a relation binding that artifact to the full sample, its operative operator and its classifier value. The artifact can retain an exact component and separately relate it to b; projecting such a related record is not an algorithm that extracts the full sample from residue bytes. The argument here uses only the resulting mathematical pair.

5.2 The Exact-Component Obstruction

The loss of information can be quantitative. Under the hypothesis of Proposition 2.6, a nonzero coexact direction gives samples with the same exact component and arbitrarily large full Hodge residual. Hence an observation depending only on that component need not preserve the full-sample residual or a positive far-radius condition. The proposition concerns the stated unrestricted Hodge-noise carrier; a restricted application profile requires its own comparison theorem.

This does not identify the distinct scores

$$\|P_{H^\perp} b\|, \qquad \operatorname{dist}(b, \operatorname{im} \delta_0), \qquad \text{a modular cochain or code distance.}$$

The first measures disagreement with the harmonic subspace, while the second measures distance to exactness. A modular distance requires its own carrier and normalization. No equality of these scores is assumed by the HCP/CVP comparison.

5.3 Additional Public Observations

The constructed ambiguity examples fix (α, b). If a larger released view $V(x, b)$ is used, the same obstruction applies only after proving that the two presentations also give equal values of that view. For example, a view factoring through (α, b) preserves their equality; arbitrary snapshot roots, full geometric coordinates or proof transcripts need not do so. No security conclusion for an unspecified larger record follows.

The full projective point of the operative harmonic subspace is a concrete example of consequential additional information. At the fixed ambient inner product, it determines that subspace's projector and therefore the HCP target from b. We prove this reconstruction next. A digest-only view remains a different observation and is not covered by the reconstruction theorem.

5.4 Frames and Projective Coordinates

Let $V = \mathbb{R}^n$ have its fixed Euclidean inner product, and let $w_1, \dots, w_r$ be an independent frame spanning $W \leq V$. Its exterior coordinate is

$$c = w_1 \wedge \cdots \wedge w_r \in \bigwedge^r V.$$

An independent frame has nonzero exterior product. A different basis of the same subspace changes c by the nonzero determinant of its change-of-basis matrix. The projective class therefore depends only on W:

$$c \sim c' \quad \Longleftrightarrow \quad \exists u \in \mathbb{R}^\times,\ c' = uc.$$

The formal raw carrier is the scalar-orbit quotient of the whole exterior power, including its zero orbit. A genuine frame determines a nonzero, decomposable orbit. The conclusions below use such frames; they do not assert that every point of the raw quotient is a Grassmannian point.

A related specialized reconstruction uses restricted Plücker coordinates for maximal isotropic subspaces [DK26]. The argument here uses the full projective point of an arbitrary real subspace and the fixed ambient metric; no orthogonal-matroid realization is assumed.

Proposition 5.1 (Projective Plücker invariance)**.** *Two independent frames spanning the same finite-dimensional subspace have equal projective exterior coordinates.*

Proof. Both exterior products are nonzero elements of the one-dimensional top exterior power of that subspace. They differ by a nonzero scalar and hence have the same orbit. □

5.5 Recovery from the Full Point

Proposition 5.2 (Recovery from the full projective point)**.** *Let $w_1, \dots, w_r$ be an independent frame for $W \subseteq \mathbb{R}^n$, and put $c = w_1 \wedge \cdots \wedge w_r$. Then*

$$W = \{x \in \mathbb{R}^n : x \wedge c = 0\}.$$

This reconstruction depends only on $[c]$. Consequently, two genuine rank-r frame witnesses have the same full projective point if and only if they present the same subspace. At the fixed ambient inner product, the full point determines P_W and $I - P_W$.

Proof. If $x \in W$, the frame with x adjoined is dependent and its exterior product vanishes. If $x \notin W$, the adjoined frame is independent and its exterior product is nonzero. Multiplying c by a nonzero scalar does not change this annihilator. The projector is the unique orthogonal projection onto the reconstructed subspace. □

In the raw quotient the zero orbit has the whole ambient space as its annihilator. The frame-indexed statement avoids treating that orbit as an arbitrary nonzero rank-r Plücker point. If $W = \ker \Delta_x$ is the operative harmonic subspace, full projective data together with b determine

$$h = P_W b.$$

The operative-kernel identification and the fixed inner product are essential. A coordinate for an unrelated subspace gives no such conclusion. The full point does not determine the positive spectrum of the original Δ_x. Nor does this exact-real reconstruction give an efficient finite byte algorithm or inversion of a digest.

6 Conclusion and Further Work

The hidden Hodge operator determines the recovery target. An explicitly presented harmonic lattice gives a precise discrete-CVP comparison, while the constructed common-input examples prevent uniform exact recovery from the specified public data. Exact-component observations and full projective observations expose different information, as the two observation results make precise.

6.1 Further Questions

The comparison suggests studying encoded HCP families with explicit distributions on hidden presentations and Hodge-structured noise. Their computational difficulty must be assessed within that specified model.

Discrete Morse reduction for cellular sheaf cohomology [CGN15] suggests a computational refinement. A chain-homotopy equivalence alone does not identify the original harmonic representative or preserve its distance. An

application to the original recovery target needs explicit retained lifts and a metric comparison.

The constructed classifier proves the named homological-test fragment in the real cochain model. Extending it to the full first-order fibrational semantics, constructing richer families with a declared topological realization, and analyzing transported public observations are separate mathematical tasks. The selected results remain the exact Hodge/CVP comparisons and observation boundaries of this manuscript.

A Statement–Lean Parity Table

Table 2 records the correspondence for this paper's six Hodge/CVP groups and two observation-boundary groups. The independent entry's configuration, `lean/Palomar/PaperOne/comparator.json`, selects 21 manuscript-facing and 25 supporting theorem declarations. Every declaration appears once below. These are coverage counts, not a count of independent research contributions. Definition rows name canonical implementation objects, not additional selected theorem targets. Main-result and support rows are proved under their stated premises; background, assumption and contract rows identify the separate scope boundaries.

Write `E` for `Hcrypt.Palomar.PaperOne`, `CS` for `E.CellularSheaf`, `HB` for `E.HCPBridge`, `AF` for `E.AxisFamily`, and `PL` for `E.Plucker`. The abbreviated anchors expand to the exact configured declaration names.

Table 2: Selected manuscript–Lean parity.

Statement, status and scope	**Corresponding formal declarations or boundary**
Definitions: HCP input and target. Section 2. The public pair contains a classifier value and observed cochain. A private representative selects the operative kernel and hence the orthogonal-projection target.	Canonical definitions: `Hcrypt.HCPBridge.Observation` `Hcrypt.HCPBridge.HiddenHodgeWitness` `Hcrypt.HCP.operativeHarmonicComponent` `Hcrypt.HCPBridge.operativeTarget`

Continued on the next page.

Table 2: Selected manuscript–Lean parity (continued).

Statement, status and scope	**Corresponding formal declarations or boundary**
Definitions: explicit-lattice CVP. Section 3.1. An injective real basis presents the lattice through integer coefficients. An instance adds a target; a solution is a closest discrete lattice point.	Canonical definitions: `CVP.ExplicitLattice` `CVP.Instance` `CVP.Solution`
Definitions: semantic realization. Sections 2 and 4. The public classifier factors through the specified closed theory. The operative Hodge operator is separate presentation-level data; equal classifier values need not identify it.	Canonical definitions: `Hcrypt.Axioms.PublicClassifier` `Hcrypt.Helfer.ClosedTheory` `Hcrypt.HCPBridge.Realization`
Definitions: Hodge sample and lattice. Sections 2–3. The sample combines an integral harmonic message with exact/coexact noise. A supplied harmonic-lattice presentation has full real span; it need not contain every intrinsic integral harmonic cochain.	Canonical definitions: `Hcrypt.Sheaf.CellularSheaf.HodgeEncryptedCochain` `Hcrypt.Sheaf.CellularSheaf.HarmonicLatticePresentation`
Main result: P1-S01. *Proved.* Proposition 2.5; private recovery in Sections 2–3. The complex equation and actual adjoint Hodge operator give componentwise unique harmonic, exact and coexact parts. Integer coefficient recovery uses the supplied harmonic-lattice presentation.	`E.Hodge_Decomposition_Theorem` `E.Hodge_Decomposition_unique` `CS.HodgeEncryptedCochain.harmonicOneProjection_observed` `CS.HarmonicLatticePresentation.decodeCoefficients_encrypt`

Continued on the next page.

Table 2: Selected manuscript–Lean parity (continued).

Statement, status and scope	Corresponding formal declarations or boundary
Main result: P1-S02. *Proved.* Proposition 3.1. A field-linear image of the displayed generator is realized as a kernel. The consequence concerns that image, not integer-lattice membership.	`E.exists_matrix_ker_eq_range` `E.Hodge_GeneratedSubspace_Reduction_Proof`
Main result: P1-S03. *Proved.* Proposition 3.2. The discrete lattice is explicitly supplied and lies in the projected subspace. The Pythagorean identity preserves exactly its closest-vector answers.	`E.squaredDistance_projection_decomposition` `E.solution_iff_projectedTarget`
Main result: P1-S04. *Proved.* Cellular specialization of Proposition 3.2. For the actual Hodge sample and supplied harmonic message lattice, the operative message is the unique closest lattice point.	`E.concreteSheafHCP_CVP_solution_iff_message` `E.concreteSheafHCP_CVP_existsUnique`
Main result: P1-S05. *Proved.* Propositions 3.4 and 3.5. Generic separation retains closed-test invariance and kernel separation; oracle corollaries also retain existence of a correct explicit-lattice CVP oracle. The constructed integral family has one public observation and distinct nonzero targets, ruling out uniformly exact public-data recovery.	`HB.operativeTargets_ne_of_kernelSeparation` `HB.cvpOracle_insufficient_of_kernelSeparation` `HB.cvpOracle_insufficient_for_operativeTarget` `AF.cellular_axis_ambiguity` `AF.cvp_oracle_insufficient`

Continued on the next page.

Table 2: Selected manuscript–Lean parity (continued).

Statement, status and scope	Corresponding formal declarations or boundary
Main result: P1-S06. *Proved.* Weighted example in Section 3.5. The common observation is $b = (1, 2)$, with private integer coefficients two and one. Each privately presented lattice has its own unique CVP answer.	`AF.weighted_axis_recovery_obstruction`
Main result: P1-B01. *Proved.* Proposition 2.6. An allowed nonzero coexact direction prevents the full Hodge residual from factoring through the exact component. The farness obstruction uses the unrestricted noise carrier and exact-component-only extraction.	`CS.HodgeEncryptedCochain.not_residual_norm_factors_exactComponent` `CS.HodgeEncryptedCochain.not_far_preserving_exactComponent`
Main result: P1-B02. *Proved.* Proposition 5.2. A genuine independent frame's full projective coordinates recover its subspace and fixed-metric projector. Operative-target recovery additionally identifies that subspace with the operative kernel. A digest is a different observation.	`PL.recoverSubspace_frame` `PL.recoverHarmonicProjector_frame` `PL.recover_eq_operativeHarmonicComponent`
Support: complexes and semantics. *Proved.* Sections 2–4. Actual coboundary composition, the constructed complex isomorphism and the corresponding three-term differential.	`CS.delta1_comp_delta0` `AF.cellular_complex_iso` `E.ThreeTermData.differential_comp` `AF.boundarySqZero`

Continued on the next page.

Table 2: Selected manuscript–Lean parity (continued).

Statement, status and scope	**Corresponding formal declarations or boundary**

Support: axis coordinates. *Proved.* Section 3.5. Coordinate vectors and the distinct complementary-axis choices in the examples.	`AF.unitCochain_apply`
	`AF.other_zero`
	`AF.other_one`
	`AF.other_ne`

Support: axis Hodge operators. *Proved.* Section 3.5. Both coboundaries, the adjoint, the degree-one Laplacian and its harmonicity criterion.	`AF.delta0_eq_zero`
	`AF.delta1_apply`
	`AF.delta1_adjoint_eq`
	`AF.degreeOneLaplacian_apply`
	`AF.harmonic_iff`

Support: integral lattice. *Proved.* Section 3.5. Restriction-compatible stalk integrality, harmonic basis vectors, encoding injectivity and membership in the chosen lattice.	`AF.standardStalkLattice_contains_iff`
	`AF.restriction_preserves`
	`AF.unitCochain_integral`
	`AF.other_unit_harmonic`
	`AF.harmonicBasis_injective`
	`AF.harmonicLatticeVector_eq`
	`AF.latticeVector_mem`

Support: projective quotient. *Proved.* Sections 5.4–5.5. Scalar-orbit equivalence laws, wedge-annihilator recovery and invariance under a nonzero scalar multiple.	`PL.ProjectivelyEquivalent.refl`
	`PL.ProjectivelyEquivalent.symm`
	`PL.ProjectivelyEquivalent.trans`
	`PL.mem_wedgeAnnihilator_iff`
	`PL.wedgeAnnihilator_eq_of_projectivelyEq uivalent`

External theorem and semantic premise. Section 4; distinct from the proved homological fragment.	Helfer's general fibrational/path-invariance theorem is cited background. Applying the generic bridge requires the declared invariant closed tests; full first-order invariance and a complete classifier for arbitrary hidden presentations are not proved by this entry.

Continued on the next page.

Table 2: Selected manuscript–Lean parity (continued).

Statement, status and scope	**Corresponding formal declarations or boundary**
Assumption: computational hardness. Section 3.1; distinct from the proved exact comparisons.	Known-lattice CVP hardness is an external computational interface. The selected algebraic comparisons and non-identifiability examples do not establish an asymptotic encoded-instance hardness reduction or a sampled encryption-security theorem.
Contract: protocol application. Section 5; distinct from the observation theorems.	A larger released view requires its own equality or factorization proof. Artifact binding, encoding, visibility and source-to-code metric comparisons are additional application conditions. No general full-HCP distance comparison follows from an exact-component extraction.

B Formal Objects and Proof Boundaries

Independent statements and canonical proofs. `Palomar.PaperOne.Challenge` gives ordinary transparent definitions using Mathlib-only imports. Its finite-product helpers `Hcrypt.Helfer.contextObject` and `Hcrypt.Helfer.contextMap` retain their canonical names. `Palomar.PaperOne.Solution` identifies the independent presentations with the canonical proof objects without importing Challenge. The 23 deliberate Challenge theorem placeholders are comparison targets; Solution has no proof or definition holes.

Source objects and mathematical scope. The finite cellular Hodge operators and integral message presentation are in the `Sheaf` modules. `CVP.lean`, `HCP.lean` and `Hardness.lean` supply the lattice and operative-target comparisons. `Sheaf/HCPAxisFamily.lean`, `HCP/AxisFamily.lean` and `Helfer/CochainModel.lean` construct the actual integral examples and homological-test interpretation. They use the algebraic finite signed-incidence model; no regular CW or simplicial realization of its base is asserted. Integer coefficient recovery is classical and noncomputable. The proved semantic fragment does not supply the general first-order theorem or arbitrary-presentation classifier.

The full-point reconstruction is owned by `Proximity/Concrete/GrassmannianPlucker/Reconstruction.lean`; `TCB/PluckerObservation.lean` identifies the operative target under explicit kernel agreement. The raw projective quotient contains the zero orbit. Recovery uses genuine independent frames, full exact-real coordinates and the fixed ambient metric; it supplies neither digest inversion nor an efficient finite-byte decoder.

Validation applies to exact snapshots. The permitted proof axioms are `propext`, `Quot.sound` and `Classical.choice`; the selected dependency audit reports only these axioms or subsets. The earlier public snapshot `66e1ad2` passed protected preflight. That result does not certify this revised manuscript; its eventual release requires its own exact-commit comparison and report. Mechanical checking is separate from editorial review, novelty assessment and registry registration. The release manifest records the proof/import closure and hashes; the parity table identifies the selected results, rather than every declaration in those supporting modules.

References

[CGN15] Justin Curry, Robert Ghrist, and Vidit Nanda. Discrete Morse theory for computing cellular sheaf cohomology, 2015. Version 2, 2015-04-08.

[DK26] Changxin Ding and Donggyu Kim. Grassmann–Plücker functions for orthogonal matroids, 2026. Version 2, 2026-02-01.

[Hel25] Joseph Helfer. First-order homotopical logic. *The Journal of Symbolic Logic*, 90(2):564–626, 2025.

[HG19] Jakob Hansen and Robert Ghrist. Toward a spectral theory of cellular sheaves. *Journal of Applied and Computational Topology*, 3:315–358, 2019.

[MG02] Daniele Micciancio and Shafi Goldwasser. *Complexity of Lattice Problems: A Cryptographic Perspective*. Springer, 2002.