CSCI317 Database Performance Tuning

Quantitative Analysis of Indexing

Dr Janusz R. Getta

School of Computing and Information Technology - University of Wollongong

1 of 18 25/6/22, 9:51 pm

Outline

Cost model? What is it?

Storage organization and models

Tables with randomly ordered rows

Tables with clustered B*-tree index

Tables with not clustered B*-tree index

TOP

Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

Cost model? What is it?

A model used for estimation of the cost of various database operations Notation

- **b** => the total number of fully packed blocks
- r => an average number of rows per block
- f => fanout of B*-tree index
- **k** => number of keys in an index

3/18

Outline

Cost model? What is it?

Storage organization and models

Tables with randomly ordered rows

Tables with clustered B*-tree index

Tables with not clustered B*-tree index

Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

25/6/22, 9:51 pm

Storage organizations and models

Tables with the randomly ordered rows

Tables with the clustered B*-tree indices

Tables with the unclustered B*-tree indices

TOP Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

Outline

Cost model? What is it?

Storage organization and models

Tables with randomly ordered rows


Tables with clustered B*-tree index

Tables with not clustered B*-tree index

TOP Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

Tables with randomly ordered rows


Full scan



Cost = **b** read block operations

Tables with randomly ordered rows

Full scan with an equality condition on a key




Cost = (1 + b)/2 read block operations

8/18

Tables with randomly ordered rows

Full scan with a range condition



Cost = **b** read block operations

9/18

Outline

Cost model? What is it?

Storage organization and models


Tables with randomly ordered rows

Tables with clustered B*-tree index

Tables with not clustered B*-tree index

TOP Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

Table with clustered B* tree index



Average number of blocks that contain all rows with the same value of index key = b/k


TOP Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

12/18

TOP

Table with clustered B* tree index

Full scan with an equality condition on a cluster key




Cost = $1 + \log_f k + b/k$ read block operations

Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

12 of 18 25/6/22, 9:51 pm

Table with clustered B* tree index

Full scan with a range condition on a cluster key where $\tt n$ is a number of cluster keys that satisfy the range condition



Cost = $1 + \log_f k + n * b/k$ read block operations

Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

13/18

13 of 18

TOP

Outline

Cost model? What is it?

Storage organization and models


Tables with randomly ordered rows

Tables with clustered B*-tree index

Tables with not clustered B*-tree index

TOP Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

Table with not clustered B* tree index



Total number of row identifiers per index key =

```
total number of rows / total number of keys = b*r/k

Average number of read block operations to read b*r/k rows = 

(the worst case+the best case)/2 = (b*r/k + (b*r/k)/r)/2


=(b*r/k + b/k)/2 = b*(r+1)/(2*k) \approx b*r/(2*k)

TOP Created by Janusz R. Getta, CSCJ317 Database Performance Tuning, SIM, Session 3, 2022 15/18
```

15 of 18 25/6/22, 9:51 pm

Table with not clustered B* tree index

Full scan with an equality condition on an index key




```
Cost = t_{traverse index} + t_{read data blocks} = 1 + log_f k + (b*r/k + b/k)/2
```

TOP Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

16/18

Table with not clustered B* tree index

Full scan with a range condition on an index key where $\tt n$ is a total number of index keys that satisfy a range condition



```
Cost = t_{traverse index} + t_{read data blocks} =
1+log<sub>f</sub>k + n*((b*r/k + b/k)/2)
```

TOP Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

17/18

References

Ramakrishnan R., J. Gehrke Database Management Systems, chapters 8.1-8.3

Lightstone, S., Teorey T., Nadeau T., Physical Database Design, The Database Professional's Guide to Exploiting Indexes, Views, Storage, and More, Morgan Kaufmann Publishers, 2007, chapter 4

Created by Janusz R. Getta, CSCI317 Database Performance Tuning, SIM, Session 3, 2022

18/18

TOP