
cisco
Lecture#7: Network Layer
Addressing : IPv4 Addressing
Introduction to Networks v7.0 (ITN) Module: 11

7.1.1 IPv4 Address Structure

IPv4 Address Structure

Network and Host Portions

- An IPv4 address is a 32-bit hierarchical address that is made up of a network portion and a host portion.
- When determining the network portion versus the host portion, you must look at the 32-bit stream.
- A subnet mask is used to determine the network and host portions.



IPv4 Address Structure

The Subnet Mask

- To identify the network and host portions of an IPv4 address, the subnet mask is compared to the IPv4 address bit for bit, from left to right.

- The actual process used to identify the network and host portions is called ANDing.



IPv4 Address Structure

The Prefix Length

- A prefix length is a less cumbersome method used to identify a subnet mask address.

- The prefix length is the number of bits set to 1 in the subnet mask.

- It is written in “slash notation” therefore, count the number of bits in the subnet mask and prepend it with a slash.

Subnet Mask	32-bit Address	Prefix Length
255.0.0.0	11111111.00000000.00000000.00000000	/8
255.255.0.0	11111111.11111111.00000000.00000000	/16
255.255.255.0	11111111.11111111.11111111.00000000	/24
255.255.255.192	11111111.11111111.11111111.11000000	/26
255.255.255.240	11111111.11111111.11111111.11110000	/28
255.255.255.248	11111111.11111111.11111111.11111000	/29
255.255.255.252	11111111.11111111.11111111.11111100	/30

Determining the Network: Logical AND

- A logical AND Boolean operation is used in determining the network address.
  - § Logical AND is the comparison of two bits where only a 1 AND 1 produces a 1 and any other combination results in a 0.
  - § 1 AND 1 = 1, 0 AND 1 = 0, 1 AND 0 = 0, 0 AND 0 = 0
  - § 1 = True and 0 = False

- To identify the network address, the host IPv4 address is logically ANDed, bit by bit, with the subnet mask to identify the network address.



IPv4 Address Structure

Video – Network, Host and Broadcast Addresses

This video will cover the following:

- Network address
- Broadcast Address
- First usable host
- Last usable host

IPv4 Address Structure

Network, Host, and Broadcast Addresses

- Within each network are three types of IP addresses:
  - Network address
  - Host addresses
  - Broadcast address



	Network Portion	Host Portion	Host Bits
SM : **255.255.255.**0 or **/24**	255 255 255 11111111 11111111 11111111	0 00000000	
NA : **192.168.10.**0 or **/24**	192 168 10 11000000 10100000 00001010	0 00000000	All 0s
FA : **192.168.10.**1 or **/24**	192 168 10 11000000 10100000 00001010	1 00000001	All 0s and a 1
LA : **192.168.10.**254 or **/24**	192 168 10 11000000 10100000 00001010	254 11111110	All 1s and a 0
BA : **192.168.10.**255 or **/24**	192 168 10 11000000 10100000 00001010	255 11111111	All 1s

7.1.2 Uni-, Broad-, and Multi-cast

Unicast

- Unicast transmission is sending a packet to one destination IP address.
- For example, the PC at 172.16.4.1 sends a unicast packet to the printer at 172.16.4.253.



Broadcast

- Broadcast transmission is sending a packet to all other destination IP addresses.
- For example, the PC at 172.16.4.1 sends a broadcast packet to all IPv4 hosts.



Multicast

- Multicast transmission is sending a packet to a multicast address group.
- For example, the PC at 172.16.4.1 sends a multicast packet to the multicast group address 224.10.10.5.

7.1.3 Types of IPv4 Addresses

Types of IPv4 Addresses

Public and Private IPv4 Addresses

- As defined in in RFC 1918, public IPv4 addresses are globally routed between internet service provider (ISP) routers.
- Private addresses are common blocks of addresses used by most organizations to assign IPv4 addresses to internal hosts.
- Private IPv4 addresses are not unique and can be used internally within any network.
- However, private addresses are not globally routable.

Network Address and Prefix	RFC 1918 Private Address Range
10.0.0.0/8	10.0.0.0 - 10.255.255.255
172.16.0.0/12	172.16.0.0 - 172.31.255.255
192.168.0.0/16	192.168.0.0 - 192.168.255.255

Types of IPv4 Addresses

Routing to the Internet

- Network Address Translation (NAT) translates private IPv4 addresses to public IPv4 addresses.
- NAT is typically enabled on the edge router connecting to the internet.
- It translates the internal private address to a public global IP address.



Special Use IPv4 Addresses

Loopback addresses

- 127.0.0.0 /8 (127.0.0.1 to 127.255.255.254)
- Commonly identified as only 127.0.0.1
- Used on a host to test if TCP/IP is operational.

```
C:\Users\NetAcad> ping 127.0.0.1
Pinging 127.0.0.1 with 32 bytes of data:
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
Reply from 127.0.0.1: bytes=32 time<1ms TTL=128
```

Link-Local addresses

- 169.254.0.0 /16 (169.254.0.1 to 169.254.255.254)
- Commonly known as the Automatic Private IP Addressing (APIPA) addresses or self-assigned addresses.
- Used by Windows DHCP clients to self-configure when no DHCP servers are available.

Legacy Classful Addressing

RFC 790 (1981) allocated IPv4 addresses in classes

- Class A (0.0.0.0/8 to 127.0.0.0/8)
- Class B (128.0.0.0 /16 – 191.255.0.0 /16)
- Class C (192.0.0.0 /24 – 223.255.255.0 /24)
- Class D (224.0.0.0 to 239.0.0.0)
- Class E (240.0.0.0 – 255.0.0.0)



- Classful addressing wasted many IPv4 addresses.

Classful address allocation was replaced with classless addressing which ignores the rules of classes (A, B, C).

Types of IPv4 Addresses

Assignment of IP Addresses

- The Internet Assigned Numbers Authority (IANA) manages and allocates blocks of IPv4 and IPv6 addresses to five Regional Internet Registries (RIRs).

- RIRs are responsible for allocating IP addresses to ISPs who provide IPv4 address blocks to smaller ISPs and organizations.



7.1.4 Network Segmentation

Network Segmentation

Broadcast Domains and Segmentation

- Many protocols use broadcasts or multicasts (e.g., ARP use broadcasts to locate other devices, hosts send DHCP discover broadcasts to locate a DHCP server.)
- Switches propagate broadcasts out all interfaces except the interface on which it was received.



- The only device that stops broadcasts is a router.
- Routers do not propagate broadcasts.
- Each router interface connects to a broadcast domain and broadcasts are only propagated within that specific broadcast domain.

Network Segmentation

Problems with Large Broadcast Domains

- A problem with a large broadcast domain is that these hosts can generate excessive broadcasts and negatively affect the network.
- The solution is to reduce the size of the network to create smaller broadcast domains in a process called subnetting.
- Dividing the network address 172.16.0.0 /16 into two subnets of 200 users each: 172.16.0.0 /24 and 172.16.1.0 /24.
- Broadcasts are only propagated within the smaller broadcast domains.



Network Segmentation

Reasons for Segmenting Networks

- Subnetting reduces overall network traffic and improves network performance.
- It can be used to implement security policies between subnets.
- Subnetting reduces the number of devices affected by abnormal broadcast traffic.

- Subnets are used for a variety of reasons including by:

Location



Group or



Device Type




Lecture#7: Network Layer
Addressing : IPv4 Subnetting
Introduction to Networks v7.0 (ITN) Module: 11

7.2.1 Subnet an IPv4 Network

Subnet an IPv4 Network

Subnet on an Octet Boundary

- Networks are most easily subnetted at the octet boundary of /8, /16, and /24.
- Notice that using longer prefix lengths decreases the number of hosts per subnet.

Prefix Length	Subnet Mask	Subnet Mask in Binary (n = network, h = host)	# of hosts
/8	**255**.0.0.0	**nnnnnnnn**.hhhhhhhh.hhhhhhhh.hhhhhhhh **11111111**.00000000.00000000.00000000	16,777,214
/16	**255.255**.0.0	**nnnnnnnn.nnnnnnnn**.hhhhhhhh.hhhhhhhh **11111111.11111111**.00000000.00000000	65,534
/24	**255.255.255**.0	**nnnnnnnn.nnnnnnnn.nnnnnnnn**.hhhhhhhh **11111111.11111111.11111111**.00000000	254

Subnet an IPv4 Network

Subnet on an Octet Boundary (Cont.)

- In the first table 10.0.0.0/8 is subnetted using /16 and in the second table, a /24 mask.

Subnet Address (256 Possible Subnets)	**Host Range** (65,534 possible hosts per subnet)	**Broadcast**
10.0.0.0/**16**	**10.0**.0.1 - **10.0**.255.254	**10.0**.255.255
10.1.0.0/**16**	**10.1**.0.1 - **10.1**.255.254	**10.1**.255.255
10.2.0.0/**16**	**10.2**.0.1 - **10.2**.255.254	**10.2**.255.255
10.3.0.0/**16**	**10.3**.0.1 - **10.3**.255.254	**10.3**.255.255
10.4.0.0/**16**	**10.4**.0.1 - **10.4**.255.254	**10.4**.255.255
10.5.0.0/**16**	**10.5**.0.1 - **10.5**.255.254	**10.5**.255.255
10.6.0.0/**16**	**10.6**.0.1 - **10.6**.255.254	**10.6**.255.255
10.7.0.0/**16**	**10.7**.0.1 - **10.7**.255.254	**10.7**.255.255
…	…	…
10.255.0.0/**16**	**10.255**.0.1 - **10.255**.255.254	**10.255**.255.255

Subnet Address (65,536 Possible Subnets)	**Host Range** (254 possible hosts per subnet)	**Broadcast**
10.0.0.0/**24**	**10.0.0**.1 - **10.0.0**.254	**10.0.0**.255
10.0.1.0/**24**	**10.0.1**.1 - **10.0.1**.254	**10.0.1**.255
10.0.2.0/**24**	**10.0.2**.1 - **10.0.2**.254	**10.0.2**.255
…	…	…
10.0.255.0/**24**	**10.0.255**.1 - **10.0.255**.254	**10.0.255**.255
10.1.0.0/**24**	**10.1.0**.1 - **10.1.0**.254	**10.1.0**.255
10.1.1.0/**24**	**10.1.1**.1 - **10.1.1**.254	**10.1.1**.255
10.1.2.0/**24**	**10.1.2**.1 - **10.1.2**.254	**10.1.2**.255
…	…	…
10.100.0.0/**24**	**10.100.0**.1 - **10.100.0**.254	**10.100.0**.255
…	…	…
10.255.255.0/**24**	**10.255.255**.1 - **10.2255.255**.254	**10.255.255**.255

Subnet an IPv4 Network

Subnet within an Octet Boundary

- Refer to the table to see six ways to subnet a /24 network.

Prefix Length	Subnet Mask	Subnet Mask in Binary (n = network, h = host)	# of subnets	# of hosts
/25	255.255.255.128	nnnnnnnn.nnnnnnnn.nnnnnnnn.**n**hhhhhhh 11111111.11111111.11111111.**1**0000000	**2**	126
/26	255.255.255.192	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nn**hhhhhh 11111111.11111111.11111111.**11**000000	**4**	62
/27	255.255.255.224	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nnn**hhhhh 11111111.11111111.11111111.**111**00000	**8**	30
/28	255.255.255.240	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nnnn**hhhh 11111111.11111111.11111111.**1111**0000	**16**	14
/29	255.255.255.248	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nnnnn**hhh 11111111.11111111.11111111.**11111**000	**32**	6
/30	255.255.255.252	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nnnnnn**hh 11111111.11111111.11111111.**111111**00	**64**	2

Subnet an IPv4 Network

Video – The Subnet Mask

- This video will demonstrate the process of subnetting.

Subnet an IPv4 Network

Video – Subnet with the Magic Number

- This video will demonstrate subnetting with the magic number.

7.2.2 Subnet a /16 and a /8 Prefix

Subnet a Slash 16 and a Slash 8 Prefix

Create Subnets with a Slash 16 prefix

- The table highlights all the possible scenarios for subnetting a /16 prefix.

Prefix Length	Subnet Mask	Network Address (n = network, h = host)	# of subnets	# of hosts
/17	255.255.**128**.0	nnnnnnnn.nnnnnnnn.**n**hhhhhhh.hhhhhhhh 11111111.11111111.**1**0000000.00000000	**2**	32766
/18	255.255.**192**.0	nnnnnnnn.nnnnnnnn.**nn**hhhhhh.hhhhhhhh 11111111.11111111.**11**000000.00000000	**4**	16382
/19	255.255.**224**.0	nnnnnnnn.nnnnnnnn.**nnn**hhhhh.hhhhhhhh 11111111.11111111.**111**00000.00000000	**8**	8190
/20	255.255.**240**.0	nnnnnnnn.nnnnnnnn.**nnnn**hhhh.hhhhhhhh 11111111.11111111.**1111**0000.00000000	**16**	4094
/21	255.255.**248**.0	nnnnnnnn.nnnnnnnn.**nnnnn**hhh.hhhhhhhh 11111111.11111111.**11111**000.00000000	**32**	2046
/22	255.255.**252**.0	nnnnnnnn.nnnnnnnn.**nnnnnn**hh.hhhhhhhh 11111111.11111111.**111111**00.00000000	**64**	1022
/23	255.255.**254**.0	nnnnnnnn.nnnnnnnn.**nnnnnnn**h.hhhhhhhh 11111111.11111111.**1111111**0.00000000	**128**	510
/24	255.255.**255.0**	nnnnnnnn.nnnnnnnn.**nnnnnnnn**.hhhhhhhh 11111111.11111111.**11111111**.00000000	**256**	254
/25	255.255.**255.128**	nnnnnnnn.nnnnnnnn.**nnnnnnnn.n**hhhhhhh 11111111.11111111.**11111111.1**0000000	**512**	126
/26	255.255.**255.192**	nnnnnnnn.nnnnnnnn.**nnnnnnnn.nn**hhhhhh 11111111.11111111.**11111111.11**000000	**1024**	62
/27	255.255.**255.224**	nnnnnnnn.nnnnnnnn.**nnnnnnnn.nnn**hhhhh 11111111.11111111.**11111111.111**00000	**2048**	30
/28	255.255.**255.240**	nnnnnnnn.nnnnnnnn.**nnnnnnnn.nnnn**hhhh 11111111.11111111.**11111111.1111**0000	**4096**	14
/29	255.255.**255.248**	nnnnnnnn.nnnnnnnn.**nnnnnnnn.nnnnn**hhh 11111111.11111111.**11111111.11111**000	**8192**	6
/30	255.255.**255.252**	nnnnnnnn.nnnnnnnn.**nnnnnnnn.nnnnnn**hh 11111111.11111111.**11111111.111111**00	**16384**	2

Subnet a Slash 16 and a Slash 8 Prefix

Create 100 Subnets with a Slash 16 prefix

Consider a large enterprise that requires at least 100 subnets and has chosen the private address 172.16.0.0/16 as its internal network address.

- The figure displays the number of subnets that can be created when borrowing bits from the third octet and the fourth octet.
- Notice there are now up to 14 host bits that can be borrowed (i.e., last two bits cannot be borrowed).



To satisfy the requirement of 100 subnets for the enterprise, 7 bits (i.e., $2^7 = 128$ subnets) would need to be borrowed (for a total of 128 subnets).

Subnet a Slash 16 and a Slash 8 Prefix

Create 1000 Subnets with a Slash 8 prefix

Consider a small ISP that requires 1000 subnets for its clients using network address 10.0.0.0/8 which means there are 8 bits in the network portion and 24 host bits available to borrow toward subnetting.

- The figure displays the number of subnets that can be created when borrowing bits from the second and third.
- Notice there are now up to 22 host bits that can be borrowed (i.e., last two bits cannot be borrowed).



To satisfy the requirement of 1000 subnets for the enterprise, 10 bits (i.e., 2^{10}=1024 subnets) would need to be borrowed (for a total of 128 subnets)

Subnet a Slash 16 and a Slash 8 Prefix

Video – Subnet Across Multiple Octets

This video will demonstrate creating subnets across multiple octets.

Subnet a Slash 16 and a Slash 8 Prefix

Lab – Calculate IPv4 Subnets

In this lab, you will complete the following objectives:

- Part 1: Determine IPv4 Address Subnetting
- Part 2: Calculate IPv4 Address Subnetting

7.2.3 Subnet to Meet Requirements

Subnet to Meet Requirements

Subnet Private versus Public IPv4 Address Space

Enterprise networks will have an:

- **Intranet** - A company's internal network typically using private IPv4 addresses.
- **DMZ** – A companies internet facing servers. Devices in the DMZ use public IPv4 addresses.

- A company could use the 10.0.0.0/8 and subnet on the /16 or /24 network boundary.

- The DMZ devices would have to be configured with public IP addresses.



Subnet to Meet Requirements
Minimize Unused Host IPv4 Addresses and Maximize Subnets

There are two considerations when planning subnets:

- The number of host addresses required for each network
- The number of individual subnets needed

Prefix Length	Subnet Mask	Subnet Mask in Binary (n = network, h = host)	# of subnets	# of hosts
/25	255.255.255.128	nnnnnnnn.nnnnnnnn.nnnnnnnn.**n**hhhhhhh 11111111.11111111.11111111.**1**0000000	**2**	126
/26	255.255.255.192	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nn**hhhhhh 11111111.11111111.11111111.**11**000000	**4**	62
/27	255.255.255.224	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nnn**hhhhh 11111111.11111111.11111111.**111**00000	**8**	30
/28	255.255.255.240	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nnnn**hhhh 11111111.11111111.11111111.**1111**0000	**16**	14
/29	255.255.255.248	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nnnnn**hhh 11111111.11111111.11111111.**11111**000	**32**	6
/30	255.255.255.252	nnnnnnnn.nnnnnnnn.nnnnnnnn.**nnnnnn**hh 11111111.11111111.11111111.**111111**00	**64**	2

Subnet to Meet Requirements

Example: Efficient IPv4 Subnetting

- In this example, corporate headquarters has been allocated a public network address of 172.16.0.0/22 (10 host bits) by its ISP providing 1,022 host addresses.



- There are five sites and therefore five internet connections which means the organization requires 10 subnets with the largest subnet requires 40 addresses.

- It allocated 10 subnets with a /26 (i.e., 255.255.255.192) subnet mask.



Subnet to Meet Requirements

Packet Tracer – Subnetting Scenario

In this Packet Tracer, you will do the following:

- Design an IP Addressing Scheme
- Assign IP Addresses to Network Devices and Verify Connectivity

7.2.4 VLSM

VLSM

Video – VLSM Basics

- This video will explain VLSM basics.

VLSM

Video – VLSM Example

- This video will demonstrate creating subnets specific to the needs of the network.

VLSM

IPv4 Address Conservation

Given the topology, 7 subnets are required (i.e, four LANs and three WAN links) and the largest number of host is in Building D with 28 hosts.

- A /27 mask would provide 8 subnets of 30 host IP addresses and therefore support this topology.



VLSM

IPv4 Address Conservation (Cont.)

However, the point-to-point WAN links only require two addresses and therefore waste 28 addresses each for a total of 84 unused addresses.



Host portion
2^5 – 2 = 30 host IP addresses per subnet

30 – 2 = 28
Each WAN subnet wastes 28 addresses

28 x 3 = 84
84 addresses are unused

- Applying a traditional subnetting scheme to this scenario is not very efficient and is wasteful.
- VLSM was developed to avoid wasting addresses by enabling us to subnet a subnet.

VLSM

- The left side displays the traditional subnetting scheme (i.e., the same subnet mask) while the right side illustrates how VLSM can be used to subnet a subnet and divided the last subnet into eight /30 subnets.
- When using VLSM, always begin by satisfying the host requirements of the largest subnet and continue subnetting until the host requirements of the smallest subnet are satisfied.
- The resulting topology with VLSM applied.



VLSM Topology Address Assignment

- Using VLSM subnets, the LAN and inter-router networks can be addressed without unnecessary waste as shown in the logical topology diagram.



7.2.5 Structured Design

Structured Design

IPv4 Network Address Planning

- IP network planning is crucial to develop a scalable solution to an enterprise network.
  - To develop an IPv4 network wide addressing scheme, you need to know how many subnets are needed, how many hosts a particular subnet requires, what devices are part of the subnet, which parts of your network use private addresses, and which use public, and many other determining factors.

- Examine the needs of an organization's network usage and how the subnets will be structured.
  - Perform a network requirement study by looking at the entire network to determining how each area will be segmented.
  - Determine how many subnets are needed and how many hosts per subnet.
  - Determine DHCP address pools and Layer 2 VLAN pools.

Structured Design

Device Address Assignment

- Within a network, there are different types of devices that require addresses:
  - **End user clients** – Most use DHCP to reduce errors and burden on network support staff. IPv6 clients can obtain address information using DHCPv6 or SLAAC.
  - **Servers and peripherals** – These should have a predictable static IP address.
  - **Servers that are accessible from the internet** – Servers must have a public IPv4 address, most often accessed using NAT.
  - **Intermediary devices** – Devices are assigned addresses for network management, monitoring, and security.
  - **Gateway** – Routers and firewall devices are gateway for the hosts in that network.
- When developing an IP addressing scheme, it is generally recommended that you have a set pattern of how addresses are allocated to each type of device.

Structured Design

Packet Tracer – VLSM Design and Implementation Practice

In this Packet Tracer, you will do the following:

- Examine the Network Requirements
- Design the VLSM Addressing Scheme
- Assign IP Addresses to Devices and Verify Connectivity


cisco
Lecture#7: Network Layer
Addressing : IPv4 Address Resolution
Introduction to Networks v7.0 (ITN) Module: 9

7.3.1 MAC and IP

MAC and IP

Destination on Same Network

There are two primary addresses assigned to a device on an Ethernet LAN:

- **Layer 2 physical (MAC) address** – Used for NIC to NIC communications on the same Ethernet network.
- **Layer 3 logical (IP) address** – Used to send the packet from the source device to the destination device.



Destination MAC	Source MAC	Source IPv4	Destination IPv4
55-55-55	aa-aa-aa	192.168.10.10	192.168.10.11

Layer 2 addresses are used to deliver frames from one NIC to another NIC on the same network. If a destination IP address is on the same network, the destination MAC address will be that of the destination device.

MAC and IP

Destination on Remote Network

When the destination IP address is on a remote network, the destination MAC address is that of the default gateway.

- ARP is used by IPv4 to associate the IPv4 address of a device with the MAC address of the device NIC.
- ICMPv6 is used by IPv6 to associate the IPv6 address of a device with the MAC address of the device NIC.

Destination MAC	Source MAC	Source IPv4	Destination IPv4
bb-bb-bb	aa-aa-aa	192.168.10.10	10.1.1.10

MAC and IP

Packet Tracer – Identify MAC and IP Addresses

In this Packet Tracer, you will complete the following objectives:

- Gather PDU Information for Local Network Communication
- Gather PDU Information for Remote Network Communication

7.3.2 ARP

ARP

ARP Overview

A device uses ARP to determine the destination MAC address of a local device when it knows its IPv4 address.

ARP provides two basic functions:

- Resolving IPv4 addresses to MAC addresses
- Maintaining an ARP table of IPv4 to MAC address mappings



ARP

ARP Functions

To send a frame, a device will search its ARP table for a destination IPv4 address and a corresponding MAC address.

- If the packet's destination IPv4 address is on the same network, the device will search the ARP table for the destination IPv4 address.
- If the destination IPv4 address is on a different network, the device will search the ARP table for the IPv4 address of the default gateway.
- If the device locates the IPv4 address, its corresponding MAC address is used as the destination MAC address in the frame.
- If there is no ARP table entry is found, then the device sends an ARP request.

ARP

Video - ARP Request

This video will cover an ARP request for a MAC address.

ARP

Video – ARP Operation - ARP Reply

This video will cover an ARP reply in response to an ARP request.

ARP

Video - ARP Role in Remote Communications

This video will cover how an ARP request will provide a host the MAC address of the default gateway.

ARP

Removing Entries from an ARP Table

- Entries in the ARP table are not permanent and are removed when an ARP cache timer expires after a specified period of time.
- The duration of the ARP cache timer differs depending on the operating system.
- ARP table entries can also be removed manually by the administrator.



ARP

ARP Tables on Networking Devices

- The **`show ip arp`** command displays the ARP table on a Cisco router.
- The **`arp –a`** command displays the ARP table on a Windows 10 PC.

```
R1# show ip arp
Protocol  Address          Age (min)  Hardware Addr   Type   Interface
Internet  192.168.10.1            -   a0e0.af0d.e140  ARPA   GigabitEthernet0/0/0
```

```
C:\Users\PC> arp -a

Interface: 192.168.1.124 --- 0x10
  Internet Address      Physical Address      Type
  192.168.1.1           c8-d7-19-cc-a0-86     dynamic
  192.168.1.101         08-3e-0c-f5-f7-77     dynamic
```

ARP Issues – ARP Broadcasting and ARP Spoofing

- ARP requests are received and processed by every device on the local network.

- Excessive ARP broadcasts can cause some reduction in performance.
- ARP replies can be spoofed by a threat actor to perform an ARP poisoning attack.
- Enterprise level switches include mitigation techniques to protect against ARP attacks.



ARP

Packet Tracer – Examine the ARP Table

In this Packet Tracer, you will complete the following objectives:

- Examine an ARP Request
- Examine a Switch MAC Address Table
- Examine the ARP Process in Remote Communications


CISCO