

Transactions

Outline

- Transaction Concept
- Transaction State
- Concurrent Executions
- Serializability
- Recoverability
- Implementation of Isolation
- Transaction Definition in SQL
- Testing for Serializability.

Transaction Concept

- A **transaction** is a *unit* of program execution that accesses and possibly updates various data items.
- E.g., transaction to transfer \$50 from account A to account B:
 1. **read**(A)
 2. $A := A - 50$
 3. **write**(A)
 4. **read**(B)
 5. $B := B + 50$
 6. **write**(B)
- Two main issues to deal with:
 - Failures of various kinds, such as hardware failures and system crashes
 - Concurrent execution of multiple transactions

Required Properties of a Transaction

- Consider a transaction to transfer \$50 from account A to account B:
 1. **read**(A)
 2. $A := A - 50$
 3. **write**(A)
 4. **read**(B)
 5. $B := B + 50$
 6. **write**(B)
- **Atomicity requirement**
 - If the transaction fails after step 3 and before step 6, money will be “lost” leading to an inconsistent database state
 - Failure could be due to software or hardware
 - The system should ensure that updates of a partially executed transaction are not reflected in the database
- **Durability requirement** — once the user has been notified that the transaction has completed (i.e., the transfer of the \$50 has taken place), the updates to the database by the transaction must persist even if there are software or hardware failures.

Required Properties of a Transaction (Cont.)

- **Consistency requirement** in above example:
 - The sum of A and B is unchanged by the execution of the transaction
- A transaction, when starting to execute, must see a consistent database.
- During transaction execution the database may be temporarily inconsistent.
- When the transaction completes successfully the database must be consistent
 - Erroneous transaction logic can lead to inconsistency

Required Properties of a Transaction (Cont.)

- **Isolation requirement** — if between steps 3 and 6 (of the fund transfer transaction) , another transaction **T2** is allowed to access the partially updated database, it will see an inconsistent database (the sum $A + B$ will be less than it should be).

T1	T2
1. read (A)	
2. $A := A - 50$	
3. write (A)	
	read(A), read(B), print(A+B)
4. read (B)	
5. $B := B + 50$	
6. write (B)	

- Isolation can be ensured trivially by running transactions **serially**
 - That is, one after the other.
- However, executing multiple transactions concurrently has significant benefits, as we will see later.

ACID Properties


A **transaction** is a unit of program execution that accesses and possibly updates various data items. To preserve the integrity of data the database system must ensure:

- **Atomicity**. Either all operations of the transaction are properly reflected in the database or none are.
- **Consistency**. Execution of a transaction in isolation preserves the consistency of the database.
- **Isolation**. Although multiple transactions may execute concurrently, each transaction must be unaware of other concurrently executing transactions. Intermediate transaction results must be hidden from other concurrently executed transactions.
 - That is, for every pair of transactions T_i and T_j , it appears to T_i that either T_j finished execution before T_i started, or T_j started execution after T_i finished.
- **Durability**. After a transaction completes successfully, the changes it has made to the database persist, even if there are system failures.

Transaction State

- **Active** – the initial state; the transaction stays in this state while it is executing
- **Partially committed** – after the final statement has been executed.
- **Failed** -- after the discovery that normal execution can no longer proceed.
- **Aborted** – after the transaction has been rolled back and the database restored to its state prior to the start of the transaction. Two options after it has been aborted:
 - Restart the transaction
 - can be done only if no internal logical error
 - Kill the transaction
- **Committed** – after successful completion.

Transaction State (Cont.)



Concurrent Executions

- Multiple transactions are allowed to run concurrently in the system.
Advantages are:
 - **Increased processor and disk utilization**, leading to better transaction *throughput*
 - E.g. one transaction can be using the CPU while another is reading from or writing to the disk
 - **Reduced average response time** for transactions: short transactions need not wait behind long ones.
- **Concurrency control schemes** – mechanisms to achieve isolation
 - That is, to control the interaction among the concurrent transactions in order to prevent them from destroying the consistency of the database

Schedules

- **Schedule** – a sequences of instructions that specify the chronological order in which instructions of concurrent transactions are executed
 - A schedule for a set of transactions must consist of all instructions of those transactions
 - Must preserve the order in which the instructions appear in each individual transaction.
- A transaction that successfully completes its execution will have a **commit** instructions as the last statement
 - By default transaction assumed to execute commit instruction as its last step
- A transaction that fails to successfully complete its execution will have an **abort** instruction as the last statement

Schedule 1

- Let T_1 transfer \$50 from A to B , and T_2 transfer 10% of the balance from A to B .
- An example of a **serial** schedule in which T_1 is followed by T_2 :

T_1	T_2
read (A) $A := A - 50$ write (A) read (B) $B := B + 50$ write (B) commit	read (A) $temp := A * 0.1$ $A := A - temp$ write (A) read (B) $B := B + temp$ write (B) commit

Schedule 2

- A **serial** schedule in which T_2 is followed by T_1 :

T_1	T_2
read (A) $A := A - 50$ write (A) read (B) $B := B + 50$ write (B) commit	read (A) $temp := A * 0.1$ $A := A - temp$ write (A) read (B) $B := B + temp$ write (B) commit

Schedule 3

- Let T_1 and T_2 be the transactions defined previously. The following schedule is not a serial schedule, but it is **equivalent** to Schedule 1.

T_1	T_2
read (A) $A := A - 50$ write (A)	
	read (A) $temp := A * 0.1$ $A := A - temp$ write (A)
read (B) $B := B + 50$ write (B) commit	
	read (B) $B := B + temp$ write (B) commit

Note -- In schedules 1, 2 and 3, the sum “A + B” is preserved.

Schedule 4

- The following concurrent schedule does not preserve the sum of “ $A + B$ ”

T_1	T_2
read (A) $A := A - 50$ write (A) read (B) $B := B + 50$ write (B) commit	read (A) $temp := A * 0.1$ $A := A - temp$ write (A) read (B) $B := B + temp$ write (B) commit

Serializability

- **Basic Assumption** – Each transaction preserves database consistency.
- Thus, serial execution of a set of transactions preserves database consistency.
- A (possibly concurrent) schedule is serializable if it is equivalent to a serial schedule. Different forms of schedule equivalence give rise to the notions of:
 1. **conflict serializability**
 2. **view serializability**

Simplified view of transactions

- We ignore operations other than **read** and **write** instructions
- We assume that transactions may perform arbitrary computations on data in local buffers in between reads and writes.
- Our simplified schedules consist of only **read** and **write** instructions.

Conflicting Instructions

- Let I_i and I_j be two Instructions of transactions T_i and T_j respectively. Instructions I_i and I_j **conflict** if and only if there exists some item Q accessed by both I_i and I_j , and at least one of these instructions wrote Q .
 1. $I_i = \text{read}(Q)$, $I_j = \text{read}(Q)$. I_i and I_j don't conflict.
 2. $I_i = \text{read}(Q)$, $I_j = \text{write}(Q)$. They conflict.
 3. $I_i = \text{write}(Q)$, $I_j = \text{read}(Q)$. They conflict
 4. $I_i = \text{write}(Q)$, $I_j = \text{write}(Q)$. They conflict
- Intuitively, a conflict between I_i and I_j forces a (logical) temporal order between them.
 - If I_i and I_j are consecutive in a schedule and they do not conflict, their results would remain the same even if they had been interchanged in the schedule.

Conflict Serializability

- If a schedule S can be transformed into a schedule S' by a series of swaps of non-conflicting instructions, we say that S and S' are **conflict equivalent**.
- We say that a schedule S is **conflict serializable** if it is conflict equivalent to a serial schedule

Conflict Serializability (Cont.)

- Schedule 3 can be transformed into Schedule 6 -- a serial schedule where T_2 follows T_1 , by a series of swaps of non-conflicting instructions. Therefore, Schedule 3 is conflict serializable.

T_1	T_2
read (A) write (A)	
	read (A) write (A)
read (B) write (B)	
	read (B) write (B)

Schedule 3

T_1	T_2
read (A) write (A) read (B) write (B)	
	read (A) write (A) read (B) write (B)

Schedule 6

Conflict Serializability (Cont.)


- Example of a schedule that is not conflict serializable:

T_3	T_4
read (Q)	write (Q)
write (Q)	

- We are unable to swap instructions in the above schedule to obtain either the serial schedule $\langle T_3, T_4 \rangle$, or the serial schedule $\langle T_4, T_3 \rangle$.




Precedence Graph

- Consider some schedule of a set of transactions T_1, T_2, \dots, T_n
- **Precedence graph** — a direct graph where the vertices are the transactions (names).
- We draw an arc from T_i to T_j if the two transaction conflict, and T_i accessed the data item on which the conflict arose earlier.
- We may label the arc by the item that was accessed.
- **Example**



Testing for Conflict Serializability

- A schedule is conflict serializable if and only if its precedence graph is acyclic.
- Cycle-detection algorithms exist which take order n^2 time, where n is the number of vertices in the graph.
 - (Better algorithms take order $n + e$ where e is the number of edges.)
- If precedence graph is acyclic, the serializability order can be obtained by a *topological sorting* of the graph.
 - That is, a linear order consistent with the partial order of the graph.
 - For example, a serializability order for the schedule (a) would be one of either (b) or (c)



Recoverable Schedules

- **Recoverable schedule** — if a transaction T_j reads a data item previously written by a transaction T_i , then the commit operation of T_i **must** appear before the commit operation of T_j .
- The following schedule is not recoverable if T_9 commits immediately after the read(A) operation.

T_8	T_9
read (A)	
write (A)	
	read (A)
	commit
read (B)	

- If T_8 should abort, T_9 would have read (and possibly shown to the user) an inconsistent database state. Hence, database must ensure that schedules are recoverable.

Cascading Rollbacks

- **Cascading rollback** – a single transaction failure leads to a series of transaction rollbacks. Consider the following schedule where none of the transactions has yet committed (so the schedule is recoverable)

T_{10}	T_{11}	T_{12}
read (A) read (B) write (A)	read (A) write (A)	read (A)
abort		

If T_{10} fails, T_{11} and T_{12} must also be rolled back.

- Can lead to the undoing of a significant amount of work

Cascadeless Schedules

- **Cascadeless schedules** — for each pair of transactions T_i and T_j such that T_j reads a data item previously written by T_i , the commit operation of T_i appears before the read operation of T_j .
- Every cascadeless schedule is also recoverable
- It is desirable to restrict the schedules to those that are cascadeless
- Example of a schedule that is NOT cascadeless

T_{10}	T_{11}	T_{12}
read (A) read (B) write (A)	read (A) write (A)	
abort		read (A)

Concurrency Control

- A database must provide a mechanism that will ensure that all possible schedules are both:
 - Conflict serializable.
 - Recoverable and preferably cascadeless
- A policy in which only one transaction can execute at a time generates serial schedules, but provides a poor degree of concurrency
- Concurrency-control schemes tradeoff between the amount of concurrency they allow and the amount of overhead that they incur
- Testing a schedule for serializability *after* it has executed is a little too late!
 - Tests for serializability help us understand why a concurrency control protocol is correct
- **Goal** – to develop concurrency control protocols that will assure serializability.

Weak Levels of Consistency

- Some applications are willing to live with weak levels of consistency, allowing schedules that are not serializable
 - E.g., a read-only transaction that wants to get an approximate total balance of all accounts
 - E.g., database statistics computed for query optimization can be approximate (why?)
 - Such transactions need not be serializable with respect to other transactions
- Tradeoff accuracy for performance