



AesthetiCal



A URL-Addressable Calendar for Aesthetic Computer

@jeffrey

Aesthetic.Computer

ORCID: 0009-0007-4460-4913

<https://aesthetic.computer/cal> · <https://aesthetic.computer>

Aesthetic Computer · June 2026 · v1 deployed

Abstract. This paper specifies *cal*, a calendar for Aesthetic.Computer (?): a single, URL-addressable piece (aesthetic.computer/cal) backed by a per-handle synced store and an interchange layer that speaks the standard iCalendar format (?). Time has been the one primitive the system never owned — pieces address space, color, sound, and identity, but never the day. *cal* adds it without adding a second app: the same piece runs on the website, inside the AC Native OS (?), and in a dedicated menu-bar icon hosted by the AC desktop app alongside the *nom games* (?). Appointments are stored server-side keyed by Auth0 *sub* and decorated with the author's *@handle* (?), mirroring the moods and paintings sync model already in production. Two front-ends share that store: the *cal* piece (month / week / day views, addressable as *cal:2026:6*, *cal:week*, *cal:day*), and *DateWizard* (*cal:wizard*), a Claude-poppable wizard in the family of RFA and WaveWizard whose week read-out you pop up to see the week and add, edit, or delete appointments. Each calendar's canonical, never-changing address is its owner's *permahandle* (the immutable *ac25...* code on the *users* record, e.g. */api/cal?code=ac25namuc*); the mutable *@handle* is a pretty alias over it. Calendars both export and import the standard *.ics* format (subscribable from, and ingestible into, Apple or Google Calendar), with CalDAV (?) reserved as a later phase. A v1 of this system — backend, piece, DateWizard, desktop tray, and *.ics* interchange — is deployed in production and in daily use; the contribution is not a new calendar but a demonstration that a creative-computing runtime can absorb time as just another addressable medium.

1. INTRODUCTION

Aesthetic.Computer is organized around a small set of primitives that every piece can reach: a screen to draw

on, a synth to sound, an input stream, a URL to be addressed by, and — since the handle system landed — a verified identity (?). What it has never had is *time*. A piece can ask what frame it is on; it cannot ask what day it is in any first-class way, and the system has no shared notion of an appointment, a deadline, or a recurring event. Calendars are among the oldest information structures humans maintain (?), and their absence has meant that scheduling around AC — shows, studio sessions, release dates, collaborative jams — happens in other people’s software.

This paper specifies `cal`: an attempt to add time to the system the same way every other capability was added, as a *piece* rather than an application. The design follows three commitments that recur throughout AC:

1. **One artifact, many surfaces.** The same `cal` piece runs in the browser, in the native OS, and framed inside a desktop menu-bar window. There is no separate “calendar app” — there is a piece, addressed by URL, wherever a piece can run.
2. **Addressable state.** A calendar view is a URL. `cal` shows today; `cal:2026:6` shows June 2026; `@jeffrey/cal` shows a handle’s public calendar. Time becomes navigable the way space already is.
3. **Standards at the edge, AC in the center.** Internally, events are plain documents in MongoDB. At the boundary they serialize to iCalendar (?) so that any conformant client can subscribe, and parse from .ics so that an existing calendar can be imported.

The name of the backing service is *aesthetical* — the calendar half of Aesthetic.Computer, the part that owns the almanac. The rest of the paper walks the feature from the user inward: the `cal` command and piece (§2), the DateWizard overlay (§3), the aesthetical backend and data model (§4), the iCalendar interchange layer (§5), per-handle sync and sharing (§6), the desktop menu-bar surface (§7), and a phased implementation plan (§8).

2. THE CAL PIECE

2.1 Command and routing

`cal` is registered the way every short verb in AC is: a one-line entry in the prompt command registry (`lib/prompt-commands.mjs`), which the prompt piece uses to build its help text and to validate input. Typing `cal` at the prompt resolves to the piece module `disks/cal.mjs`, loaded dynamically by BIOS. Colon parameters carry view state into `boot` through the `colon` array, exactly as `notepat` (?) and the `nom` games do:

- `cal` — today, in the default view (month).
- `cal:week` / `cal:day` — the current week or day view.
- `cal:wizard` — pop DateWizard open on the week read-out.
- `cal:add` — pop DateWizard straight into the add

form.

- `cal:2026:6` — June 2026.
- `@jeffrey/cal` — a handle’s public calendar (read-only unless it is yours; a pretty alias over the permahandle feed).

2.2 Lifecycle and rendering

The piece uses the standard AC lifecycle — `boot`, `paint`, `act`, `sim`, `leave` — documented in the disks authoring guide. There is no retained scene graph; `paint` redraws the grid every frame from immediate-mode primitives (`wipe`, `ink`, `box`, `line`, `write`). The reference template is `commits.mjs`, which already demonstrates the two patterns `cal` needs: a paginated fetch on `boot` and a scrollable, cached layout.

- **`boot`** ({ `colon`, `store`, `net`, `handle`, `user` }) — parse the view and date from `colon`; restore the last-used view from `store.retrieve("cal:view", "local")`; kick off a fetch of the visible range.
- **`paint`** — draw the month grid (a 7-column week lattice), week column, or day timeline; tint cells by event density; highlight today using the same time-of-day palette `notepat` uses for its background.
- **`act`** ({ `event` }) — tap a day to zoom in, swipe or arrow to page months, tap an event to open it, long-press an empty slot to create one.
- **`sim`** — advance a one-minute clock so “now” moves; no per-frame animation is required.

A shared engine, `lib/cal.mjs`, factors the grid math (first-weekday, days-in-month, week-of, event layout) out of the piece, following the `lib/nom.mjs` pattern where one engine backs several thin wrapper pieces. This lets `cal`, the DateWizard, and any future variant (a year view, a public-show feed) share one source of truth for date arithmetic.

2.3 Reading and writing events

Pieces never hold credentials; they call `net.userRequest(method, endpoint, body)`, which attaches the user’s Auth0 bearer token and issues the fetch. `cal` reads a range and writes appointments through the aesthetical endpoints (§4):

```
net.userRequest("GET",
  "/api/cal?from=...&to=...")
net.userRequest("POST", "/api/cal", {
  title, start, end, allDay, rrule, note
})
```

Unauthenticated visitors still get a calendar: `cal` falls back to `store.persist(..., "local")` so a logged-out user can keep a private, device-local calendar, which the first successful login can offer to migrate into *aesthetical*.

3. DATEWIZARD

3.1 What a Wizard is

A *Wizard* in AC is a guided, step-through helper that @jeffrey (or Claude on his behalf) can pop up to perform a focused task without leaving the current context. The established members of the family are RFA (`pop/bin/rfa.mjs`), a CLI that walks a vocal score note by note, and the native Swift wizards (WaveWizard, JukeWizard, ClipWizard) that step through a spec offering *keep / redo / skip* at each item. They are launched from the Slab menu-bar via an `osascript` bridge that opens a terminal or a native window. DateWizard joins this family as the *temporal* wizard.

3.2 Behavior

DateWizard is a thin overlay over the same *aesthetical* store the `cal` piece uses, optimized for a single guided question: *what does this week hold, and what should I change?* As shipped it opens on a **week read-out** — seven day rows, today highlighted, each listing that day’s events — and folds out into an add/edit form and back to the readout after any write, so the result is seen in context. It presents:

- a week read-out of existing appointments (the default pop-up), pageable by week, that doubles as the entry point for everything else;
- a step-through *add* flow — title, start, end, note, and a private/public visibility toggle — echoing the *keep/redo/skip* rhythm of the other wizards;
- *edit* and *delete* of an existing event by tapping its chip (recurring instances edit their master);
- natural-language entry (“lunch with Fia next Tuesday at 1”) parsed into a structured event before it is written;
- a confirmation step before any write, consistent with the house rule that outward or hard-to-reverse actions are confirmed first.

3.3 Two bodies, one wizard

DateWizard ships in the same two forms the other wizards already take:

1. **In-piece overlay.** Inside the `cal` piece, DateWizard is a modal layer drawn with the standard UI primitives (`ui.Button`, `ui.TextInput`). This is what a human taps “add” to get.
2. **Claude-poppable surface.** For Claude to “pop up” DateWizard the way it triggers RFA, the wizard is also reachable as a launchable target: a Slab/menu-bar action that opens `cal` focused on the add-flow, and an agent-facing path (an MCP-style tool over the same `/api/cal` endpoints) so Claude can read the day and draft appointments for approval. Because both bodies write through *aesthetical*, there is exactly one calendar regardless of who is driving.

4. THE AESTHETICAL BACKEND

4.1 Endpoint shape

Aesthetical is a backend function, `system/netlify/functions/cal.mjs` served by lith at `/api/cal`. It follows the canonical AC CRUD shape used by `store-kidlisp.mjs` and `mood.mjs`: `authorize`, `resolve the handle`, `connect`, `operate`, `disconnect`.

```
import { authorize, getHandleOrEmail }
  from "../../backend/authorization.mjs";
import { connect }
  from "../../backend/database.mjs";

export async function handler(event) {
  const user = await authorize(event.headers);
  const handle =
    await getHandleOrEmail(user.sub);
  const db = await connect();
  const cal = db.db.collection("calendar");
  // GET range / POST create / PUT edit / DELETE
  await db.disconnect();
}
```

Reads of a public calendar (`@handle/cal`) skip the `authorize` step and filter on the visibility flag; all writes require a valid token whose sub owns the event.

4.2 Data model

Events are keyed by Auth0 sub (the stable per-account id), with the `@handle` denormalized in for display and feed lookups — the same choice moods and paintings make. The `@handles` collection maps `sub` ↔ `handle`; *aesthetical* never trusts a handle supplied by the client.

Field	Meaning
<code>user</code>	Auth0 sub — owner, the key
<code>handle</code>	denormalized <code>@handle</code> for display
<code>uid</code>	stable event id (maps to iCal UID)
<code>title</code>	summary line
<code>start / end</code>	ISO instants (UTC)
<code>tz</code>	IANA zone the event was authored in
<code>allDay</code>	boolean
<code>rrule</code>	RFC 5545 recurrence rule, optional
<code>note</code>	free text / description
<code>visibility</code>	private public
<code>when</code>	server write timestamp
<code>seq</code>	revision counter for sync / ETag

Table 1: The calendar collection document.

4.3 Indexes and operations

A compound index `{ user: 1, start: 1 }` serves the dominant query — one owner’s events within a date range — and `{ user: 1, uid: 1 }` (unique) backs idempotent upsert by UID, which is what makes `.ics` import and CalDAV writes safe to retry. Table ?? lists the surface.

Optional, mirroring moods: emit a profile event on write so a handle’s public timeline can surface upcoming

Route	Purpose
GET /api/cal?from&to	events in the range for the caller (auth)
GET /api/cal?code=	public feed by permahandle (canonical)
GET /api/cal?handle=	public feed by @handle (alias)
...&format=ics	same, serialized as RFC 5545 .ics
POST /api/cal	create an event (auth)
PUT /api/cal	edit by uid (bumps seq, auth)
DELETE /api/cal?uid=	remove (auth)
POST /api/cal {import}	ingest an .ics URL or text (auth)

Table 2: Aesthetical endpoints.

public dates, and reserve an ATProto record type for later federation.

5. STANDARD-FORMAT INTERCHANGE

The system speaks iCalendar (?) at its edge so that cal is never a silo. The mapping is direct because the data model was chosen to match: uid → UID, title → SUMMARY, start/end → DTSTART/DTEND (with VALUE=DATE for all-day), rrule → RRULE, note → DESCRIPTION, seq → SEQUENCE.

- **Export (live).** GET /api/cal?code=<permahandle>&format=ics returns a VCALENDAR of that owner’s public events, subscribable read-only from Apple Calendar, Google Calendar, or any RFC 5545 client. The permahandle keys the feed so the subscription URL never breaks; ?handle= resolves the same feed by mutable alias.
- **Import (live).** POST /api/cal with an {import: {url}} body fetches an external .ics (e.g. a Google Calendar “secret address in iCal format” URL, webcal:// accepted) and upserts each VEVENT by UID (prefixed ics:), so re-importing edits rather than duplicates. This is the self-serve path for pulling an existing calendar in; an agent can also drive it directly through DateWizard.
- **CalDAV (later).** Two-way editing from native clients via CalDAV (?) — PROPFIND/REPORT/PUT/DELETE, ETags from seq, sync-tokens for deltas, .well-known discovery — is deferred to a dedicated phase because its surface dwarfs the rest of the feature. The uid/seq fields are in the schema from day one precisely so this phase needs no migration.

Both the serializer and the parser are hand-rolled in the backend (no ical.js/rrule.js dependency); the piece stays format-agnostic and talks JSON.

6. PER-HANDLE SYNC AND SHARING

Because every event is keyed by sub and stamped with a @handle, a calendar *is* a handle’s calendar. Sync across a user’s devices is automatic: any client that authenticates with the same Auth0 identity sees the same GET

/api/cal results. The canonical address of that calendar, though, is the owner’s *permahandle* — the immutable ac25... code on the users record, distinct from the renameable @handle — so a subscription URL survives any handle change. The sharing posture mirrors how moods and paintings already expose per-handle public feeds:

- **Private by default.** New events are visibility:private; only the owner’s authenticated requests return them. The DateWizard form carries a private/public toggle.
- **Opt-in public.** An event marked public appears in that owner’s permahandle feed (and its @handle alias) and in the .ics export — a read-only window others can view or subscribe to, never write.
- **Future: named calendars.** The schema’s room for a calendar label leaves the door open to @jeffrey/cal/shows versus .../studio without a breaking change.

7. DESKTOP MENU-BAR SURFACE

The AC desktop (Electron) app already runs a system-tray icon — the pink “pals” logo whose context menu launches the nom muncher games by navigating a webview to aesthetic.computer/<piece>. The app also carries a second, currently-disabled tray (createNotepadTray) that is the exact template for a dedicated calendar icon: its own Tray, its own template-image asset, its own context menu, opening its own framed window.

A createCalendarTray added beside it gives cal a first-class menu-bar home:

- a dedicated calendarTrayTemplate.png icon (monochrome template on macOS), distinct from the pals logo;
- a context menu — *Calendar*, *Add Appointment* (opens DateWizard’s add-flow), and *Day / Week / Month* items that navigate to cal:day | cal:week | cal:month;
- a left-click that opens a small framed window loading the cal piece via the existing flip-view renderer, exactly as the notepad window does.

On the menu bar, then, the calendar sits next to the nom games as a sibling: same launcher mechanics, same piece-over-webview loading, one more verb in the same instrument. The same cal piece is simultaneously the website calendar, the native-OS calendar, and the contents of this window — one artifact, three surfaces.

8. IMPLEMENTATION

The shipped system is small — one backend function, one piece, one shared engine, and a tray addition — because it borrows the rest (auth, DB, handles, the piece runtime, the desktop shell) from the platform. Table ?? is the whole of it.

The data path is one loop: the piece calls net.userRequest → functions/cal.mjs authorizes the bearer, resolves the sub, and reads or writes the calendar collection → the

Component	Role
functions/cal.mjs	the <i>aesthetical</i> backend: CRUD, range/public reads, .ics export serializer + import parser
disks/cal.mjs	the piece: month/week/day views + DateWizard (week readout, add/edit/delete, import)
lib/cal.mjs	dependency-free engine: grids, week/day layout, expandRecurrences
ac-electron	createCalendarTray + template icon
calendar (Mongo)	the event store, keyed {user,uid}
prompt-commands	registers the cal verb

Table 3: The whole implementation. Everything else (Auth0, MongoDB, the @handles/permahandle resolvers, net.userRequest, the piece lifecycle, the Electron tray runtime) is reused unchanged.

response is laid out by lib/cal.mjs and drawn by the piece. Public reads and the .ics feed branch off the same function by permahandle. The Electron tray and the AC Native OS surface are not separate clients — they load the same disks/cal.mjs over a webview, so there is exactly one piece behind all three faces.

The work decomposed into phases that each left something usable; phases 1–5 are deployed, the last is the open stretch:

1. **Store & piece (v1).** (*shipped*) calendar collection + GET/POST on /api/cal; disks/cal.mjs with a month view and local-only fallback; cal registered as a command.
2. **Edit & views.** (*shipped*) PUT/DELETE; week and day views; the shared lib/cal.mjs engine; recurrence expansion (rrule) for display.
3. **DateWizard.** (*shipped*) week read-out $\nrightarrow$ add/edit overlay; the Claude-poppable launch path and an agent-facing path over /api/cal.
4. **iCalendar edge.** (*shipped*) .ics export feed keyed by permahandle + .ics URL import; public-visibility toggle.
5. **Desktop & native.** (*shipped*) createCalendarTray in the Electron app; the same piece serves the website, the native OS, and the tray window.
6. **CalDAV (stretch).** (*open*) two-way sync for native clients, built on the uid/seq fields already present; a Google Calendar API bridge for live bidirectional sync is the sibling open item.

9. NEXT PHASE: EVENTS, INVITES, AND AESTHETICKS

Today an AesthetiCal entry is a private appointment. The next phase generalizes it into a public, bookable *show*: an event with a host, a venue, a capacity, and a guest list, so that a space or collective can post an open slot, an artist can book it, and an audience can be invited and ticketed — all addressable by URL like everything

else in the system.

The schema already leans this way. A show is just an event with `visibility:public` plus a few fields — `kind: "show"`, `host` (a handle), `venue`, `capacity` — and two new relations layered on the existing store:

- **Invites / RSVP.** An invited @handle sees the show appear on *their* AesthetiCal as a tentative entry (a cross-handle write, the same broadcast mechanism moods and paintings already use to fan out to a profile feed), and can accept or decline. The host’s guest list is the set of accepted handles. An .ics VEVENT carries the same invite to anyone outside AC, so an invitation is just a calendar URL.
- **Booking.** A venue handle publishes an open slot (a show with no host yet); an artist claims it. Because slots are events, the whole booking calendar of a space — e.g. a room like the one at laklok — is a subscribable public feed, and double-booking is a uniqueness constraint, not a workflow.

This is where **Aestheticks** enters — the ticketing surface to AesthetiCal’s almanac. AesthetiCal owns the *when* and *where*; Aestheticks owns *who holds a ticket*. A ticket is a per-handle record granting entry to a show; the guest list is the set of ticket holders, capped at `capacity`. Free shows issue RSVP tickets; paid or limited shows can mint tickets on Tezos, reusing the platform’s existing minting path, so a ticket is a real on-chain (or off-chain) object a holder owns rather than a row in someone else’s database. Entry is verified the way AC already verifies everything: a handle, a signature, a QR code from `share`. Nothing here is a new app — a show is a calendar event, an invite is a URL, a ticket is a record, and the venue’s season is an .ics feed.

10. CONCLUSION

cal treats time the way Aesthetic.Computer treats everything else: not as an application to be bolted on but as a medium to be addressed. A day is a URL, an appointment is a document keyed to a handle, and a calendar is a piece that happens to run on a website, on bare metal, and inside a menu-bar window without being rewritten for any of them. The standards live at the edge — iCalendar out, iCalendar in, CalDAV when it earns its keep — while the center stays plain JSON that the rest of the system already knows how to sync. DateWizard makes the same store conversational, so that adding “next Tuesday at 1” is a step-through the human taps or the agent drafts. The bet is modest and consistent with the rest of the platform: if the system can own the day the way it owns the screen and the synth, scheduling around the work can finally happen *inside* the work.

References

- Cyrus Daboo, Bernard Desruisseaux, and Lisa Dusseault. Calendaring extensions to webdav (caldav). Technical

Report RFC 4791, Internet Engineering Task Force, 2007. URL <https://www.rfc-editor.org/rfc/rfc4791>.

Bernard Desruisseaux. Internet calendaring and scheduling core object specification (icalendar). Technical Report RFC 5545, Internet Engineering Task Force, 2009. URL <https://www.rfc-editor.org/rfc/rfc5545>.

Jeffrey Alan Scudder. Aesthetic computer, 2026a. URL <https://aesthetic.computer>. A mobile-first runtime and social network for creative computing.

Jeffrey Alan Scudder. Handle identity on the at protocol, 2026b. Aesthetic Computer working paper.

Jeffrey Alan Scudder. Ac native os, 2026c. Aesthetic Computer working paper.

Jeffrey Alan Scudder. The nom games, 2026d. Aesthetic Computer working paper.

Jeffrey Alan Scudder. notepat.com: From keyboard toy to system front door, 2026e. Aesthetic Computer working paper.

Eviatar Zerubavel. *The Seven Day Circle: The History and Meaning of the Week*. Free Press, New York, 1985.