



KidLisp Language Reference

@jeffrey · Aesthetic.Computer · ORCID [0009-0007-4460-4913](https://orcid.org/0009-0007-4460-4913)

working draft — not for citation

Dansk · Español · 中文 · 日本語

March 2026 · [8fe6526fd](#)

Index

1. Syntax	4
2. The 12 Categories	5
2.1 Graphics (9 functions)	5
2.2 Transformations (11 functions)	6
2.3 Math (14 functions)	6
2.4 Color (19+ named colors)	7
2.5 System & Display (9 functions)	8
2.6 Control Flow (7 functions)	8
2.7 Timing	9
2.8 Text (4 functions)	10
2.9 Input (3 functions)	10
2.10 Audio (6 functions)	11
2.11 3D Graphics (8 functions)	11
2.12 Composition via \$-Codes	12

3. Evaluation Model	14
3.1 Deterministic Randomness	14
3.2 Chaos Mode	15
4. Design by Omission	16
5. Complete Built-in Index	18
6. Example: Complete Program	19

1. Syntax

KidLisp uses S-expression syntax McCarthy, 1960 . Every expression is either an atom (number, string, symbol) or a list enclosed in parentheses:

```
; Atoms  
42 ; number  
"hello" ; string  
red ; symbol (color name)  
  
; Lists (function application)  
(wipe "navy") ; clear screen navy  
(ink "red") ; set drawing color  
(box 10 10 50 50) ; draw rectangle  
(circle 64 64 30) ; draw circle
```

There are no operators, no infix notation, no special syntax beyond parentheses, strings, numbers, and symbols. Arithmetic uses prefix notation:

```
(+ 1 2) ; => 3  
(* 3 (+ 1 2)) ; => 9  
(- 10 3) ; => 7  
(/ 100 4) ; => 25  
(% 17 5) ; => 2 (modulo)
```



```

; Conditional
(if (> frame 60)
  (ink "red")
  (ink "blue"))

; Loop
(repeat 10 i
  (circle (* i 12) 64 5))

; Execute once (not every frame)
(once (wipe "black"))

; Local binding
(let ((cx 64) (cy 64))
  (circle cx cy 30))

```

The `repeat` loop binds its counter variable (`i` above) from 0 to $n - 1$. Nested repeats use different variable names:

```

(repeat 8 i
  (repeat 8 j
    (box (* i 16) (* j 16) 14 14)))
; 8x8 grid of squares

```

2.7 Timing

KidLisp's timing system uses *inline scheduling* rather than callbacks. Timing expressions wrap

code blocks:

```
; Frame-based timing
(0 (wipe "black")) ; every frame
(1 (spin 5)) ; every 2nd frame
(30f (ink "red")) ; after 30 frames

; Second-based timing
(1s (wipe "red")) ; after 1 second
(2.5s (ink "gold")) ; after 2.5 seconds
(1s! (write "!" 10 10)) ; fire once at 1s

; Repeating intervals
(0.5s... (spin 45)) ; every 0.5 seconds
(1s... (scroll 1 0)) ; every second
```

This eliminates the need for `setTimeout`, `setInterval`, or animation frame callbacks. Time is a *property of the expression*, not a function called on it.

2.8 Text (4 functions)

```
(write "hello" 10 20) ; text at position
(write "centered" ; centered text
  (/ width 2) (/ height 2))
(type "typed" 10 10) ; typewriter effect
```

2.9 Input (3 functions)

```

; Pen/mouse position and state
(if pen
  (circle pen.x pen.y 5))

; Touch input
(if hand
  (line hand.x hand.y 64 64))

```

2.10 Audio (6 functions)

```

; Microphone input
(def vol (mic)) ; amplitude 0-255
(circle 64 64 vol) ; sound-reactive

; Melody playback
(melody "C4 E4 G4 C5")

; Overtone harmonics
(overtone 440 3) ; 3rd harmonic of A4

```

2.11 3D Graphics (8 functions)

```

(cube "mycube") ; create 3D cube
(form "mycube"
  (move 0 0 -5) ; position
  (scale 2) ; size
  (spin (* frame 0.5) 1 1 0)) ; rotate

```

2.12 Composition via $\$$ -Codes

The most distinctive feature of KidLisp is its composition system. Instead of user-defined functions, programs reference other programs by their short code:

```
; Embed another program as a layer  
($cow) ; execute program "cow"  
($nece 10 20) ; pass parameters  
  
; Multi-layer composition  
(wipe "black")  
($cow) ; background layer  
($faim) ; foreground layer  
  
; Chain multiple programs  
(resolution 64 64)  
($zobi)  
(spin 1)  
($grel)
```

Programs are fetched from MongoDB, cached in RAM and IndexedDB, and content-addressed via SHA-256. The $\$$ -code system replaces user-defined functions, modules, and libraries with a single social mechanism: *find a program someone made, reference it by code, compose with it.*

The most-referenced programs are simple visual primitives that serve as building blocks. The system produces a social dependency graph: program A embeds program B, which embeds program C, up to 7 layers deep in observed usage.

3. Evaluation Model

KidLisp re-evaluates its **entire AST every frame**. There is no retained state beyond explicitly defined variables. The frame and time variables increment automatically. Transformations like `zoom`, `scroll`, and `spin` accumulate in the framebuffer.

This model eliminates the `setup()/draw()` split familiar from Processing (?). Every line of a KidLisp program executes every frame. Animation emerges from frame-dependent expressions:

```
(wipe "black")
(ink "white")
; Circle orbits center using sin/cos
(circle
  (+ 64 (* 30 (cos (* frame 0.03))))
  (+ 64 (* 30 (sin (* frame 0.03))))
  8)
  3.
```

3.0

5. Complete Built-in Index

Category	Count
Graphics	9
Transformations	11
Math	14
Color	19
System/Display	9
Control Flow	7
Text/Output	4
Input	3
Audio	6
3D Graphics	8
Composition	4
Data	4
Total	118

Table 1: All 118 built-in functions by category.

6. Example: Complete Program

A complete KidLisp program that draws a sound-reactive particle field with orbital motion:

```
"black"
(def vol (+ 5 (* (mic) 0.2)))
(repeat 50 i
  (def angle (* i 0.1256))
  (def r (+ 20 (* vol (sin (+ (* frame 0.02) angle)))))
  ↪ )
  (def cx (+ 64 (* r (cos (+ angle (* frame 0.01))))))
  (def cy (+ 64 (* r (sin (+ angle (* frame 0.01))))))
  (ink (+ 100 (* i 3)) 50 (+ 150 (* i 2)))
  (circle cx cy (+ 1 (random 3)))
(blur 1)
(zoom 1.002)
```

This program: sets a black background, reads microphone amplitude, draws 50 particles in orbital paths modulated by sound, colors them with a computed gradient, applies a slight blur, and slowly zooms in. It runs at 60 FPS. It is 12 lines long. It requires no imports, no setup function, no animation loop, and no event listeners.

ORCID: 0009-0007-4460-4913

References

Kate Compton and Michael Mateas. Casual creators. In *Proceedings of the International Conference on Computational Creativity*, 2015.

John McCarthy. Recursive functions of symbolic expressions and their computation by machine, part i. *Communications of the ACM*, 3(4):184–195, 1960.

Seymour Papert. *Mindstorms: Children, Computers, and Powerful Ideas*. Basic Books, 1980.

Casey Reas and Ben Fry. *Processing: A Programming Handbook for Visual Designers and Artists*. MIT Press, 2007.