



KidLisp Language Reference



118 Built-ins in 12 Categories for Generative Art

Syntax, Semantics, Timing, Color, and the \$-Code Composition System

@jeffrey

Aesthetic.Computer

ORCID: 0009-0007-4460-4913

<https://aesthetic.computer>

[working draft — not for citation]

Abstract. KidLisp is a minimal Lisp dialect for generative art with 118 built-in functions across 12 categories, no user-defined functions, no recursion, no file I/O, and no networking. It is safe by construction: a KidLisp program cannot break out of its sandbox, crash its host, or access resources beyond its canvas. This paper serves as a complete language reference, documenting every built-in function with syntax-highlighted examples, the timing system (frame-based and second-based scheduling without callbacks), the color model (named colors, RGB, gradients, patterns), the \$-code composition system (embedding programs by reference as the primary abstraction mechanism), and the evaluation model (full AST re-evaluation every frame with deterministic PRNG). We present KidLisp as a language designed around *omission*: what it cannot do is as deliberate as what it can, and the constraints produce a creative space that 59 authors have used to write 16,634 programs.

1. SYNTAX

KidLisp uses S-expression syntax (?). Every expression is either an atom (number, string, symbol) or a list enclosed in parentheses:

```
; Atoms
42                ; number
"hello"           ; string
red               ; symbol (color name)
```

```
; Lists (function application)
(wipe "navy")      ; clear screen navy
(ink "red")        ; set drawing color
(box 10 10 50 50)  ; draw rectangle
(circle 64 64 30)  ; draw circle
```

There are no operators, no infix notation, no special syntax beyond parentheses, strings, numbers, and symbols. Arithmetic uses prefix notation:

```
(+ 1 2)      ; => 3
(* 3 (+ 1 2)) ; => 9
(- 10 3)     ; => 7
(/ 100 4)    ; => 25
(% 17 5)     ; => 2 (modulo)
```

2. THE 12 CATEGORIES

2.1 Graphics (9 functions)

Drawing primitives operate in immediate mode—each call renders directly to the framebuffer.

```
(wipe "black")      ; clear canvas
(ink "cyan")        ; set color
(line 0 0 128 128)  ; diagonal line
(box 10 10 40 40)   ; rectangle
(circle 64 64 20)   ; circle at center
(tri 32 10 10 54 54 54) ; triangle
(plot 64 64)        ; single pixel
(flood 64 64)       ; flood fill
(shape 10 10 50 10 30 50) ; polygon
```

fill and outline control whether shapes are solid or stroked (Processing-compatible):

```
(fill)      ; filled shapes
(ink "red")
(circle 64 64 30) ; solid red circle

(outline)   ; outlined shapes
(ink "white")
(circle 64 64 30) ; white ring
```

2.2 Transformations (11 functions)

Pixel-level transformations operate on the framebuffer after drawing:

```
(scroll 1 0)      ; shift pixels right
(zoom 1.01)       ; slow zoom in
(spin 1)          ; rotate 1 degree
(blur 2)          ; gaussian blur
(contrast 1.2)    ; increase contrast
(suck 0.5)        ; radial displacement
(sort)           ; sort pixels by brightness
```

Transformations *accumulate* across frames, producing animation without explicit state management:

```
(wipe "black")
(ink "white")
(circle 64 64 10) ; draw circle
```

```
(spin 2)      ; rotate 2 deg/frame
(zoom 1.005)   ; grow slightly/frame
; Result: spiraling, growing circle
```

2.3 Math (14 functions)

```
(sin (* frame 0.05)) ; sine wave
(cos (* frame 0.03)) ; cosine wave
(random)              ; 0-255
(random 10)           ; 0-9
(random 5 15)         ; 5-14
(wiggle 10)           ; random +/-5
(floor 3.7)           ; => 3
(abs -5)              ; => 5
(sqrt 16)             ; => 4
(min 3 7 1)           ; => 1
(max 3 7 1)           ; => 7
```

random uses a seeded PRNG initialized from the program's short code, making all generative output **deterministic**: the same program always produces the same visual.

2.4 Color (19+ named colors)

Colors can be specified as names, RGB values, or gradient strings:

```
(ink "red")      ; named color
(ink 255 0 0)    ; RGB
(ink 255 0 0 128) ; RGBA (semi-transparent)
(ink "fade:red-blue") ; horizontal gradient
(ink (fade "cyan" "magenta" "vertical"))
(ink "rainbow")  ; repeating rainbow
(ink "zebra")    ; striped pattern
```

Available color names include all CSS named colors: red, green, blue, yellow, orange, purple, pink, cyan, magenta, black, white, gray, brown, lime, navy, teal, gold, coral, salmon, crimson, lavender, indigo, violet, turquoise, tomato, and more.

A bare color name on the first line sets the background:

```
"navy"
(ink "gold")
(circle 64 64 30)
; Navy background, gold circle
```

2.5 System & Display (9 functions)

```
(def w width)      ; screen width
(def h height)     ; screen height
frame              ; current frame number
time               ; seconds elapsed

(resolution "half") ; half-resolution
(resolution 64 64)  ; explicit 64x64
(fps 30)            ; set frame rate
```

2.6 Control Flow (7 functions)

```

; Variable definition
(def x 50)
(def y (+ 10 (* frame 0.5)))

; Conditional
(if (> frame 60)
  (ink "red")
  (ink "blue"))

; Loop
(repeat 10 i
  (circle (* i 12) 64 5))

; Execute once (not every frame)
(once (wipe "black"))

; Local binding
(let ((cx 64) (cy 64))
  (circle cx cy 30))

```

The repeat loop binds its counter variable (*i* above) from 0 to $n - 1$. Nested repeats use different variable names:

```

(repeat 8 i
  (repeat 8 j
    (box (* i 16) (* j 16) 14 14)))
; 8x8 grid of squares

```

2.7 Timing

KidLisp's timing system uses *inline scheduling* rather than callbacks. Timing expressions wrap code blocks:

```

; Frame-based timing
(0 (wipe "black")) ; every frame
(1 (spin 5)) ; every 2nd frame
(30f (ink "red")) ; after 30 frames

; Second-based timing
(1s (wipe "red")) ; after 1 second
(2.5s (ink "gold")) ; after 2.5 seconds
(1s! (write "!" 10 10)) ; fire once at 1s

; Repeating intervals
(0.5s... (spin 45)) ; every 0.5 seconds
(1s... (scroll 1 0)) ; every second

```

This eliminates the need for `setTimeout`, `setInterval`, or animation frame callbacks. Time is a *property of the expression*, not a function called on it.

2.8 Text (4 functions)

```

(write "hello" 10 20) ; text at position
(write "centered" ; centered text
  (/ width 2) (/ height 2))
(type "typed" 10 10) ; typewriter effect

```

2.9 Input (3 functions)

```

; Pen/mouse position and state
(if pen
  (circle pen.x pen.y 5))

; Touch input
(if hand
  (line hand.x hand.y 64 64))

```

2.10 Audio (6 functions)

```

; Microphone input
(def vol (mic)) ; amplitude 0-255
(circle 64 64 vol) ; sound-reactive

; Melody playback
(melody "C4 E4 G4 C5")

; Overtone harmonics
(overtone 440 3) ; 3rd harmonic of A4

```

2.11 3D Graphics (8 functions)

```

(cube "mycube") ; create 3D cube
(form "mycube"
  (move 0 0 -5) ; position
  (scale 2) ; size
  (spin (* frame 0.5) 1 1 0)) ; rotate

```

2.12 Composition via \$-Codes

The most distinctive feature of KidLisp is its composition system. Instead of user-defined functions, programs reference other programs by their short code:

```

; Embed another program as a layer
($cow) ; execute program "cow"
($nece 10 20) ; pass parameters

; Multi-layer composition
(wipe "black")
($cow) ; background layer
($faim) ; foreground layer

; Chain multiple programs
(resolution 64 64)
($zobi)
(spin 1)
($grel)

```

Programs are fetched from MongoDB, cached in RAM and IndexedDB, and content-addressed via SHA-256. The \$-code system replaces user-defined functions, modules, and libraries with a single social mechanism: *find a program someone made, reference it by code, compose with it*.

The most-referenced programs are simple visual primitives that serve as building blocks. The system produces a social dependency graph: program A embeds program B, which embeds program C, up to 7 layers deep in observed usage.

3. EVALUATION MODEL

KidLisp re-evaluates its **entire AST every frame**. There is no retained state beyond explicitly defined variables. The `frame` and `time` variables increment automatically. Transformations like `zoom`, `scroll`, and `spin` accumulate in the framebuffer.

This model eliminates the `setup()/draw()` split familiar from Processing (?). Every line of a KidLisp program executes every frame. Animation emerges from frame-dependent expressions:

```
(wipe "black")
(ink "white")
; Circle orbits center using sin/cos
(circle
  (+ 64 (* 30 (cos (* frame 0.03))))
  (+ 64 (* 30 (sin (* frame 0.03))))
  8)
```

3.1 Deterministic Randomness

`random` is seeded from the program's short code. The same program produces identical output on every device, every time. This makes KidLisp programs *reproducible generative art*: the code *is* the artwork, not just the instructions for generating it.

3.2 Chaos Mode

Invalid input—gibberish, unbalanced parentheses, random characters—does not produce error messages. Instead, KidLisp detects low recognition ratios (< 30% known words) and high special character ratios (> 50%) and renders artistic visual output. The user never sees "SyntaxError." They see colors.

4. DESIGN BY OMISSION

KidLisp deliberately lacks:

- **User-defined functions:** replaced by `$`-code composition
- **Recursion:** prevents infinite loops and stack overflows
- **File I/O:** the canvas is the only output
- **Networking:** programs cannot fetch external data
- **String manipulation:** no `concat`, `split`, `replace`
- **Error messages:** replaced by chaos mode
- **Import/require:** replaced by `$`-codes
- **Objects/classes:** data is numbers, strings, and lists

Each omission is a design decision. The absence of user-defined functions forces composition through the social layer. The absence of error messages means beginners never encounter a wall of red text. The absence of networking means every program is self-contained and safe to run.

This follows the principle that a language's constraints define its creative space more than its features (?).

KidLisp is not a general-purpose language that happens to do art. It is an art language that *cannot* do anything else.

5. COMPLETE BUILT-IN INDEX

Category	Count	Core Functions
Graphics	9	wipe, ink, line, box, circle
Transformations	11	scroll, zoom, spin, blur, suck
Math	14	+, -, *, /, random, sin, cos
Color	19+	red, blue, fade, rainbow, zebra
System/Display	9	width, height, frame, time
Control Flow	7	def, if, repeat, once, let
Text/Output	4	write, type, paste, print
Input	3	pen, hand, gamepad
Audio	6	mic, melody, overtone, sound
3D Graphics	8	cube, form, trans, move, scale
Composition	4	\$code, layer, bake, embed
Data	4	list, get, set, let
Total	118	

Table 1: All 118 built-in functions by category.

6. EXAMPLE: COMPLETE PROGRAM

A complete KidLisp program that draws a sound-reactive particle field with orbital motion:

```
"black"
(def vol (+ 5 (* (mic) 0.2)))
(repeat 50 i
  (def angle (* i 0.1256))
  (def r (+ 20 (* vol (sin (+ (* frame 0.02) angle)
    ))))
  (def cx (+ 64 (* r (cos (+ angle (* frame 0.01)
    ))))
  (def cy (+ 64 (* r (sin (+ angle (* frame 0.01)
    ))))
  (ink (+ 100 (* i 3)) 50 (+ 150 (* i 2)))
  (circle cx cy (+ 1 (random 3)))
  (blur 1)
  (zoom 1.002)
```

This program: sets a black background, reads microphone amplitude, draws 50 particles in orbital paths modulated by sound, colors them with a computed gradient, applies a slight blur, and slowly zooms in. It runs at 60 FPS. It is 12 lines long. It requires no imports, no `setup` function, no animation loop, and no event listeners.

ORCID: 0009-0007-4460-4913

References

Kate Compton and Michael Mateas. Casual creators. In *Proceedings of the International Conference on Computational Creativity*, 2015.

John McCarthy. Recursive functions of symbolic expressions and their computation by machine, part i. *Communications of the ACM*, 3(4):184–195, 1960.

Seymour Papert. *Mindstorms: Children, Computers, and Powerful Ideas*. Basic Books, 1980.

Casey Reas and Ben Fry. *Processing: A Programming Handbook for Visual Designers and Artists*. MIT Press, 2007.

WORKING DRAFT