



KidLisp Cards

@jeffrey

Aesthetic.Computer

ORCID: 0009-0007-4460-4913

working draft — not for citation

March 2026 · b3a48ec6a

Dansk · Español · 中文 · 日本語

Index

1. Introduction	5
2. The Card Format	7
2.1 Card Dimensions	7
2.2 What Makes a Good Card	8
3. Offline Rendering Pipeline	10
3.1 The Python Interpreter	10
3.2 Jupyter Notebook Workflow	11
3.3 Two Interpreters, One Language	12
4. The Card Catalog	13
4.1 Lines	13
4.2 Circles	15
4.3 Boxes & Composition	15
4.4 Math & Curves	15
4.5 Color & Gradients	15

4.6 Turtle Graphics	18
4.7 Minimal Koans	18
5. Layouts	22
5.1 Vertical (Screen / Print)	22
5.2 Horizontal (Deck / Landscape)	22
5.3 Postcard (Mail Art)	24
5.4 Deck Arrangements	24
6. Cards in the Wild	27
6.1 What Real Pieces Add	27
6.2 The Card as Snapshot	28
7. What Cards Could Be	31
7.1 Trading Cards	31
7.2 Pedagogical Sequences	31
7.3 Printed Scores	32
7.4 Postal Art	32
7.5 Generative Stationery	33
7.6 Constraint as Generative Principle	33

8. Related Work	35
9. Conclusion	37

1. Introduction

Most programming languages produce programs that are too long to print on an index card. This is a consequence of abstraction: general-purpose languages encourage decomposition into functions, classes, modules, and files. The program is distributed across a codebase. No single artifact captures the whole.

KidLisp is different. Its programs are typically 1–6 lines long. A complete animated scene, a geometric pattern, a recursive fractal, or a moiré interference pattern fits in a few S-expressions. This is not a limitation but a design choice: KidLisp omits user-defined functions, recursion (except through `later`), mutable data structures, and imports. Programs are flat sequences of drawing commands, loops, and conditionals.

This flatness creates an opportunity. If the source code of a program fits on a card, and the visual output of that program fits on the same card, then the card becomes a self-contained artifact: a program you can hold, pass to someone, pin to a wall, or mail. The card is both documen-

tation and executable. It is a *score*—instructions for producing a visual event.

This paper describes the KidLisp Cards format (§2), the offline rendering pipeline (§3), the current card catalog (§4), layout variations and their social and physical affordances (§5), and speculative futures for the format (§7).

2. The Card Format

A KidLisp Card has three elements:

1. **Title.** A short name that evokes the visual output: “Starburst,” “Honeycomb,” “Spiral Walk.”
2. **Rendered output.** A pixel-art image (160×120 default resolution, upscaled 3× with nearest-neighbor interpolation to preserve hard edges).
3. **Source code.** The complete KidLisp program, typically 1–4 lines, displayed in monospace below the image.

The card is self-contained: anyone who reads the source code can reproduce the image exactly, in any KidLisp interpreter. There are no external dependencies, no imports, no configuration. The program *is* the card.

2.1 Card Dimensions

The rendered image occupies a 160×120 pixel canvas (4:3 ratio), matching the default KidLisp resolution. At 3× upscale, this produces a

480×360 pixel image suitable for screen display. For print, cards are sized at 4×6 inches (standard index card / postcard), with the image occupying the upper portion and the source code below.

2.2 What Makes a Good Card

Not every KidLisp program makes a good card. The best cards share properties:

- **Brevity.** 1–4 lines. If the source code doesn't fit comfortably below the image, the program is too long for the format.
- **Surprise.** The output should be more complex or beautiful than the source code suggests. A three-line program that produces a moiré pattern rewards inspection.
- **Legibility.** A reader should be able to trace from source to output without running the program. The connection between code and image should be discernible, even if not immediately obvious.
- **Independence.** No `$code` embeds, no external state. The card must work in isolation.




Figure 1: Two program cards rendered by the Python interpreter: “Starburst” (72 radial lines, 3 lines of code) and “Moiré” (overlapping concentric circles, 3 lines). These are trivial examples—they demonstrate the card format’s structure but do not represent the expressive range of the language or the ambitions of the format.

3. Offline Rendering Pipeline

KidLisp Cards are rendered using a Python interpreter that runs outside the browser. This enables batch rendering, print production, and notebook-based curation without requiring the full Aesthetic Computer runtime.

3.1 The Python Interpreter

The interpreter (`notebooks/ac.py`, 452 lines) implements a subset of KidLisp sufficient for static card rendering:

- **Drawing:** wipe, ink, line, box, circle, tri, plot, shape, flood
- **Turtle:** crawl, left, right, goto, face, up, down
- **Control:** repeat, if, def, later, do
- **Math:** full arithmetic, trigonometry, abs, sqrt, min, max
- **Canvas:** resolution, fill, outline, stroke

The interpreter uses PIL (Pillow) for rendering. Each card is drawn on an RGBA canvas, up-scaled with nearest-neighbor interpolation, and exported as PNG. The Python implementation

is intentionally simpler than the browser evaluator (15,161 lines)—it omits animation, audio, embedding, and timing syntax, focusing only on the subset needed for static visual output.

3.2 Jupyter Notebook Workflow

The primary curation tool is a Jupyter notebook (notebooks/kidlisp-cards.ipynb). The `show_card()` function renders a program and displays it inline as an HTML card:

```
show_card("Starburst", """(wipe_black)
(ink_white)
(repeat_72_i
  (line_80_60
    (uuu(+_80_(*_55_(cos_(*_i_0.087))))
    (uuu(+_60_(*_55_(sin_(*_i_0.087))))))""")
```

Each call produces a dark-background card with the title, rendered image, and source code displayed inline. The notebook serves as both a development environment and a gallery—scrolling through the notebook is like flipping through a deck of cards.

3.3 Two Interpreters, One Language

The existence of two independent interpreters (JavaScript in the browser, Python in the notebook) serves as a cross-validation mechanism. If a program renders identically in both, its behavior is determined entirely by the language semantics rather than implementation details. Programs that rely on browser-specific features (animation, audio, embedded layers) are excluded from the card format by construction—they simply won't render in the Python interpreter.

4. The Card Catalog

The current notebook contains 28 cards organized into seven categories. Each category explores a different aspect of the language through minimal examples. These programs are deliberately trivial—drawing exercises, mathematical illustrations, turtle walks. They establish the card format’s structure but do not represent its expressive potential. The interesting cards have not been made yet. The format’s value will emerge from programs that use brevity to say something worth saying, not from geometric demos.

4.1 Lines

Line cards demonstrate `repeat` and trigonometry. A starburst radiates 72 lines from center. A crosshatch overlays horizontal and vertical grids at low opacity.

```
; Starburst -72 radial lines  
(wipe black)  
(ink white)  
(repeat 72 i  
  (line 80 60  
    (+ 80 (* 55 (cos (* i 0.087))))))
```




Figure 2: “Starburst” and “Crosshatch” — line cards.

```
(+ 60 (* 55 (sin (* i 0.087)))))
```

4.2 Circles

Circle cards use `outline` mode and nested `repeat` loops. “Ripple” draws 30 concentric circles with blue-shifting color.

4.3 Boxes & Composition

“Mondrian” recreates the primary-color grid with four colored rectangles. “Nest” draws 10 inset rectangles with shifting hues.

4.4 Math & Curves

These cards use `plot` with mathematical functions. “Lissajous” draws a Lissajous figure with 600 points. “Spiral” plots a polar spiral.

4.5 Color & Gradients

“Sierpinski” uses bitwise AND to generate the Sierpinski triangle: `(if (= 0 (& x y)) (plot (+ 16 x) y))`. “Sunflower” plots 500 points along a golden-angle spiral with cycling colors.




Figure 3: “Ripple” (circles) and “Mondrian” (boxes).




Figure 4: “Lissajous” (math curves) and “Sierpinski” (bitwise AND fractal).

4.6 Turtle Graphics

Turtle cards use `crawl`, `left`, `right`, and `face`. A five-pointed star uses `(right 144)`. A tree uses `later` for recursive branching. A snowflake nests Koch-curve segments.

```
; Star -5 sides, 144-degree turns  
(wipe navy)  
(ink yellow)  
(repeat 5 i (crawl 50) (right 144))
```

4.7 Minimal Koans

The shortest cards in the deck. “Horizon” is three lines: dark sky, gold earth. “Pip” is a single red dot on black. These cards approach the minimum viable program—the smallest amount of code that produces a recognizable image.

```
; Pip -the minimum card  
(wipe black)  
(ink red)  
(circle 80 60 4)
```




Figure 5: “Star” and “Tree” — turtle graphics cards.





Figure 6: “Horizon” and “Pip” — minimal koans (2–3 lines each).

Boxes


Nest



```
(wipe black)
(repeat 10 i
  (ink (* i 25) 100
    (- 255 (* i 25)))
  (box (* i 7) (* i 5)
    (- 160 (* i 14))
    (- 120 (* i 10))))
```

Patterns

Sunflower



```
(wipe black)
(repeat 500 i
  (ink (* (% i 8) 32)
    (+ 100 (% (* i 7) 155))
    (* (% i 5) 50))
  (plot
    (+ 80 (* (* i 0.1)
      (cos (* i 2.4)))))
    (+ 60 (* (* i 0.1)
      (sin (* i 2.4)))))
```

Turtle

Snowflake



5. Layouts

The card format has no fixed layout. How the three elements (title, output, source) are arranged determines what the card affords—what you can do with it physically and socially. This section explores layout variations and their consequences.

5.1 Vertical (Screen / Print)


The default layout stacks title, image, and source top-to-bottom. This is the notebook layout—it scrolls naturally on a phone or in a Jupyter notebook. For print, it maps to a 4×6 inch card in portrait orientation. The reader’s eye moves downward from name to image to code, tracing the relationship between the program and its output.

5.2 Horizontal (Deck / Landscape)

A landscape layout places the rendered image on the left and the source code on the right. This works for fanning cards across a table, for slide decks, and for side-by-side comparison. Two

Card Layouts

Vertical
(screen / print)



Horizontal
(landscape / deck)



Postcard
(mail art / postal)



Figure 8: Three layout strategies. **Vertical:** title / image / source stacked top-to-bottom, optimized for phone screens and portrait printing. **Horizontal:** image on the left, title and source on the right, suited for landscape cards and side-by-side deck browsing. **Postcard:** rendered output on the front, source code and metadata on the back—a mailable card where the program is hidden until you flip it over.

cards placed next to each other create a diptych—the viewer can compare programs and outputs simultaneously.

5.3 Postcard (Mail Art)

The postcard layout separates front from back. The front shows only the rendered image, full-bleed, no text. The back shows the source code, the author's handle, the short code (\$xyz), and a stamp area. The recipient sees the image first—a visual artifact. Flipping the card reveals the program: the instructions that produced it. The card is both art object and executable score, depending on which side you read.

5.4 Deck Arrangements

Cards are not single objects. They form decks, and the arrangement of a deck creates meaning. A *pedagogical sequence* orders cards by concept: boxes first (coordinates), then lines (trigonometry), then circles (radius), then math curves, then turtle graphics, then minimal koans. A *gallery grid* arranges cards spatially on a wall, inviting comparison across categories. A *shuffled deck* randomizes the order, producing unexpected juxtapositions between a fractal and a horizon, between a tree and a dot.

Social & Physical Affordances





Figure 9: Social and physical affordances of the card format. Each affordance follows from the card's materiality: it can be **shared** hand-to-hand, **mailed** as a postcard, **traded** and collected, **taught from** in pedagogical sequences, **performed** as a graphic score, or **pinned** to a gallery wall.

Deck Arrangements



Gallery Grid

pedagogical
sequence □



Figure 10: Deck arrangements. Left: cards fanned by category (Lines, Circles, Boxes, Math, Turtle, Koans) with multiple cards stacked per category. Right: a gallery grid where cards are arranged spatially for browsing.

6. Cards in the Wild

The notebook cards are exercises. The real KidLisp corpus—16,000+ programs created by 59 authors—contains pieces that use the full runtime: animation, audio, embedded layers, gradient fades, random placement, and timing syntax. These pieces are short enough for the card format but far more expressive than the notebook examples. Their preview images are rendered by the oven service (Puppeteer-based screenshot capture) and served via CDN.

6.1 What Real Pieces Add

The notebook cards use a static subset of KidLisp. Real pieces on `kidlisp.com` use the full runtime:

- **Animation.** Programs re-evaluate every frame. `frame` and `time` change automatically. A single-frame screenshot captures one moment of a living piece.
- **Randomness.** The `?` operator produces a random value from a list each frame. (`ink (? red blue green)`) flickers between colors.

- **Gradient fades.** `fade:red-blue-black` interpolates a multi-stop gradient across the canvas, driven by frame count. One expression replaces pages of manual color math.
- **Embedding.** `($cow)` fetches piece `cow` from MongoDB, evaluates it in an offscreen buffer, and composites the result. Pieces build on pieces.
- **Timing.** `1s... (zoom 0.5)` applies a zoom every second. No explicit animation loop.

These features keep programs short while dramatically expanding what they can express. `$bop`—the most-played piece at 12,188 views—is four lines: a purple background, rainbow-flickering ink, a random line, and a blur. On a card, it looks like a frozen moment of a kinetic painting. In the browser, it is one.

6.2 The Card as Snapshot


A card of an animated piece is necessarily incomplete. It captures one frame of a temporal process. This incompleteness is part of the format: the card invites you to type the code and see what it actually does. The static image is

a promise. The source code is the fulfillment. The short code (`$bop`) is the bridge—type it into `kidlisp.com` and the card comes alive.

\$bop

@jeffrey • 12,188 plays

bop



```
purple
ink (? rainbow white 0) (ls... 24 64)
line
blur 5
```

\$roz

@jeffrey • 7,064 plays

roz



```
fader:red-blue-black-blue-red
ink (? rainbow white 0) (ls... 24 64)
line w/2 0 w/2 h
```

30

7. What Cards Could Be

The card format is young. The current notebook is a proof of concept—28 programs rendered offline. But the correspondence between short programs and physical cards suggests several directions.

7.1 Trading Cards

A KidLisp Card is collectible in a way that most software is not. Each card has a name, a visual identity, a short code ($\$xyz$), and an author. Cards could be printed, numbered, and traded. Rare cards might use obscure language features or produce unexpectedly complex output from minimal code. The “rarity” of a card is its information density: how much visual complexity emerges from how few characters.

7.2 Pedagogical Sequences

The seven categories in the current notebook suggest a teaching order: start with boxes (simple coordinates), move to lines (trigonometry), circles (radius and repetition), math curves (plot

and sine), turtle graphics (relative motion), and finally koans (minimal expression). Each card teaches one concept. A teacher could hand students a physical deck and ask them to reproduce each card, modify it, or create a new card in the same category.

7.3 Printed Scores

In music, a score is instructions for producing a temporal event. A KidLisp Card is instructions for producing a visual event. Cards could function as graphic scores in the tradition of Cornelius Cardew, John Cage, and the Fluxus event scores. A performer receives a card, interprets the code (by typing it into `kidlisp.com`, by reading it aloud, by drawing it by hand), and produces an event. The card is the score. The rendering is one possible realization.

7.4 Postal Art

At 4×6 inches, a KidLisp Card is a postcard. The front shows the rendered image. The back shows the source code, the author's handle, and the short code for looking it up online. Mail art

with executable content—the recipient can type the code and see the image regenerate on their screen. The physical card and the digital program are the same work in two media.

7.5 Generative Stationery

Because the Python interpreter is deterministic and standalone, cards can be batch-rendered for print production without network access. A set of cards could be printed as a booklet, a zine, or a boxed set. The `cards-convert.mjs` pipeline already produces 4×6 inch PDF cards from the paper format; extending this to include rendered program output alongside source code is a natural next step.

7.6 Constraint as Generative Principle

The most interesting consequence of the card format is how it feeds back into the language. Programs that don't fit on a card suggest missing abstractions—or suggest that the program is doing too much. The card constraint encourages economy: find the three-line program that produces the most interesting image. This is a gen-

erative constraint in the tradition of Oulipo—
arbitrary formal restrictions that produce unexpected creative results.

8. Related Work

Printed code. The demoscene tradition of “sizecoding” (programs under 256 bytes) shares the aesthetic of minimal programs producing maximal output. KidLisp Cards are closer to the “code poem” tradition, where the source code itself is read as text alongside its output.

Graphic scores. Cardew’s *Treatise* (1967) and Cage’s *Notations* (1969) established that visual notation can serve as performance instructions without prescribing a specific realization. KidLisp Cards differ in that they are fully executable—the rendering is deterministic, not open to interpretation. But the card-as-score framing invites reinterpretation: what if you “play” the card differently each time?

Trading card games. Games like *Magic: The Gathering* (1993) demonstrated that cards with structured metadata (name, type, rules text, art) create rich combinatorial spaces. KidLisp Cards have natural metadata (title, category, function count, line count, output complexity) that could support similar game mechanics.

Computational notebooks. Jupyter notebooks already combine code and output. The KidLisp Cards notebook is a Jupyter notebook, but with a specific constraint: each cell is a self-contained card rather than a step in a longer computation. The notebook is a gallery, not a narrative.

9. Conclusion

KidLisp Cards emerge from a simple observation: when programs are short enough, they fit on cards. The card format—title, image, source—makes programs into physical artifacts that can be printed, mailed, collected, taught from, and performed. The Python rendering pipeline enables offline batch production. The seven-category catalog provides a curated entry point into the language.

The format is a work in progress. The current deck of 28 cards is a starting point, not a finished collection. The question is not how many cards to make but which programs deserve to be cards—which three-line compositions produce images worth holding in your hand.

The notebook, interpreter, and card catalog are available at <https://github.com/whistlegraph/aesthetic-computer>. Programs can be created and shared at <https://kidlisp.com>.

ORCID: 0009-0007-4460-4913

References