



aESTHETIC.CoMPUTeR '26

A Mobile-First Runtime for Creative Computing

@jeffrey · Aesthetic.Computer · ORCID 0009-0007-4460-4913

working draft — not for citation

Dansk · Español · 中文 · 日本語

March 2026 · 8fe6526fd

Index

1. Introduction	5
2. Design Principles	7
3. Architecture	9
3.1 Boot Loader	9
3.2 BIOS	9
3.3 Disk API	10
3.4 Module Loader	10
4. The Piece Model	12
5. Multi-Language Runtime	14
6. The Prompt	16
6.1 URL Routing	16
6.2 Command Categories	16
7. Social Infrastructure	18
7.1 Identity	18

7.2 Real-Time Communication	18
7.3 Moods	18
7.4 Live Profiles	19
8. Publishing and Distribution	20
8.1 Publish and Source	20
8.2 Pack System	20
8.3 Custom Domains	20
8.4 Media Export	21
9. Development History	22
9.1 Origins: No Paint (2020–2021)	22
9.2 Foundation (2022–2023)	22
9.3 Expansion (2024)	23
9.4 Platform Integration (2025–2026)	23
10. Evaluation	25
10.1 Observations	25
10.2 Limitations	26

11. Related Work	27
12. Conclusion	29

1. Introduction

Creative coding platforms have steadily lowered the barrier to computational expression. Processing [Reas and Fry, 2007] introduced the sketchbook metaphor; p5.js [McCarthy, 2015] brought it to the browser; Scratch [Resnick et al., 2009] made programming accessible to children through block-based visual programming. Yet these tools share a common assumption: the user interacts with an *editor*—a code editor, a block canvas, an IDE.

Aesthetic.Computer starts from a different premise. The primary interface is a **text prompt**—a command line into which users type short, memorable names to launch interactive programs. There is no file browser, no project panel, no menu bar. The experience is closer to a musical instrument than a development environment: users discover commands through exploration, build muscle memory through repetition, and eventually improvise by recombining pieces fluently.

The platform originated from observations dur-

ing the development of No Paint (2020), a pixel art tool whose community of non-technical users began contributing custom brushes and stamps. The manual integration process—hours or days per contribution—motivated building a system where anyone could publish interactive programs instantly. Development began in 2021, with the current repository spanning 11,045 commits from December 2022 to March 2026.

This paper describes the design principles (§2), system architecture (§3), piece model (§4), multi-language runtime (§5), prompt interface (§6), social infrastructure (§7), publishing and distribution (§8), development history (§9), and adoption (§10). The companion paper [jeffrey, 2026] covers the KidLisp language in detail.

2. Design Principles

1. **Instrument, not IDE.** The interface is designed to function like a musical instrument, on which users discover their own memorable paths through the network of commands and published pieces. This echoes Nelson's vision of personal computing as creative liberation [Nelson, 1974]: the computer as an expressive medium, not a bureaucratic tool. As literacy grows through play, users improvise, recombine, and expand their repertoire.
2. **Mobile-first.** Every interaction targets touch input on phones and tablets. Desktop support follows naturally; the reverse does not hold.
3. **URL-addressable.** Every piece, every parameter combination, every user's work is a URL. Sharing is navigation; navigation is sharing. McLuhan's observation that the medium shapes the message [McLuhan, 1964] applies literally: the URL *is* the instrument, and its memorability shapes what gets made and shared.
4. **Single-file programs.** Following Process-

ing's sketchbook model and Unix's philosophy of small composable programs, each piece is one file—no project structure, no build step, no dependencies.

5. **Social by default.** User handles, chat, moods, and profiles are part of the runtime, not bolted-on services.

3. Architecture

The system comprises four major components: the boot loader, the BIOS runtime, the Disk API, and the module loader.

3.1 Boot Loader

The boot loader (`boot.mjs`, 1,948 lines) initializes three subsystems in parallel: a WebSocket connection to the session server (800ms timeout with HTTP fallback), a Service Worker for persistent module caching, and an IndexedDB store for offline module storage. Boot telemetry logs browser, device type, screen resolution, and performance timings to `/api/boot-log`.

3.2 BIOS

The BIOS (`bios.mjs`, 20,935 lines) is the runtime orchestrator. It manages the 60fps rendering loop, routes input events (keyboard, touch, mouse, gamepad, MIDI), coordinates piece lifecycle transitions, and maintains the WebGL compositing layer (“glaze”) for post-processing effects. The BIOS also manages the tape recording

system for capturing piece performances as frame sequences with synchronized audio.

3.3 Disk API

The Disk (`disk.mjs`, 15,879 lines) provides the complete API surface that pieces use. It manages piece loading, lifecycle dispatch, and exposes drawing primitives, audio, input, networking, and UI components. All graphics operations are immediate-mode—there is no retained scene graph. Kittler argued that software obscures the material reality of computation [Kittler, 1995]; AC’s immediate-mode model resists this by making the relationship between code and screen explicit—every pixel is drawn every frame, with nothing hidden behind abstraction layers.

3.4 Module Loader

The module loader streams JavaScript modules over WebSocket from the session server, bypassing the HTTP proxy chain for faster loading. On first load, modules are cached in IndexedDB. Subsequent visits load from cache, falling back to HTTP if the session server is unavailable. This

produces near-instant piece loading on repeat visits.

4. The Piece Model

A piece is a single .mjs (JavaScript) or .lisp (KidLisp) file that exports up to five lifecycle functions:

```
function boot({ wipe, screen, params }) {  
  // Runs once when piece loads  
}  
  
function paint({ wipe, ink, line, circle }) {  
  wipe("navy")  
  ink("pink")  
  circle(screen.width / 2,  
         screen.height / 2, 50)  
}  
  
function act({ event: e }) {  
  if (e.is("keyboard:down:space")) { }  
}  
  
function sim() { } // Per-frame logic  
  
export { boot, paint, act, sim };
```

The API object passed to each function provides: Pieces follow Processing's sketchbook model—one source file per explorable idea—combined

Category	Functions
Graphics	wipe, ink, line, box, circle, poly, paste, plot
Text	write, form, TextInput
Input	event, pen, hand, gamepad
Audio	sound, speaker, microphone, melody
UI	ui.Button, ui.TextInput, cursor
System	screen, jump, store, net, send

Table 1: Piece API categories.

with Unix’s philosophy of user-level composability across small, single-purpose programs.

5. Multi-Language Runtime

AC supports two programming languages: JavaScript (ES modules, `.mjs`) and KidLisp (a minimal Lisp dialect, `.lisp`). The system currently includes 336 JavaScript pieces and 18 KidLisp pieces.

JavaScript pieces have full access to Web APIs and the Disk API surface. KidLisp pieces use a 15,161-line tree-walking evaluator [Jeffrey, 2026] that provides 118 built-in functions for drawing, color, transformation, math, animation, and audio—with no file I/O, networking, or string manipulation, making arbitrary user-submitted code safe to execute.

KidLisp programs can also be entered directly as URLs. The expression `(wipe blue)` is URL-encoded and executable at `aesthetic.computer/(%28wipe%20blue%29)`. Short codes (`$cow`, `$7z`) resolve to stored programs via MongoDB lookup.

The architecture supports additional language backends. Any language that can target the piece lifecycle (boot/paint/act/sim/leave) and call the

Disk API can be integrated as a new evaluator.

6. The Prompt

The prompt (`prompt.mjs`, 9,386 lines) is itself a piece—the most complex one in the system. It serves as the primary navigation interface, implementing over 60 commands.

6.1 URL Routing

Every piece is URL-addressable through a parser (`parse.mjs`) that supports multiple parameter conventions:

- **Simple:** `aesthetic.computer/notepat`
- **Colon params:** `tone:440:sine`
- **Space params:** `notepat 180 major` (encoded as tildes in URLs)
- **User pieces:** `@bash/hub`
- **KidLisp codes:** `$cow`
- **Shortcodes:** `!abc` (video), `*bako` (clock melody)

6.2 Command Categories

The prompt implements commands for navigation (`list`, `back`), creation (`publish`, `source`, `pack`),

social interaction (chat, mood, profile), identity (handle, login), recording (tape, share), and piece sequencing (merry, which chains pieces with timing).

7. Social Infrastructure

Unlike platforms where social features are external services (GitHub, Discord), AC integrates social infrastructure directly into the runtime.

7.1 Identity

Users register `@handles` through the prompt. Handles resolve to MongoDB user records and serve as namespaces for published pieces (`@handle/piece-name`). As of March 2026, 2,801 handles are registered.

7.2 Real-Time Communication

The session server provides WebSocket-based real-time features: public chat (18,020 messages), presence tracking (which piece each user is currently viewing), and multiplayer state synchronization for collaborative pieces.

7.3 Moods

Users post short text updates (“moods”) visible on their profiles. Moods are dual-written to MongoDB and ATPROTO (the protocol underlying

Bluesky), enabling federation with the broader social web.

7.4 Live Profiles

The profile piece displays a real-time scorecard: online/offline status, current piece, WebSocket latency, and counts of paintings, published pieces, KidLisp programs, chat messages, and moods—all updated live via WebSocket streaming.

8. Publishing and Distribution

8.1 Publish and Source

The `publish` command uploads a piece to DigitalOcean Spaces and registers it in MongoDB under the user's handle. The `source` command downloads any piece's source code as a template for forking.

8.2 Pack System

The `pack` command bundles a piece into a self-contained HTML file via the oven service. The output includes the piece code, all runtime dependencies, and embedded fonts—a single file that works offline with no server. This enables distribution via email, USB drives, blockchain minting (Tezos/Teia), and archival.

8.3 Custom Domains

Pieces can be served as standalone applications on custom domains. `notepat.com` routes to the `notepat` music sequencer piece; `kidlisp.com` serves the KidLisp IDE. Netlify edge functions

detect the hostname and rewrite routing accordingly, including custom Open Graph meta tags for social sharing.

8.4 Media Export

The oven service (`oven.aesthetic.computer`) converts recorded sessions into MP4 video via FFmpeg, generates Open Graph preview images for social sharing, and serves QR codes for piece URLs. Tape recordings capture frame sequences with per-frame timing data and optional audio.

9. Development History

The following timeline is reconstructed from the git history of the Aesthetic Computer repository (11,045 commits between December 2022 and March 2026). The project’s conceptual origins trace to 2020 with No Paint.

9.1 Origins: No Paint (2020–2021)

No Paint, a pixel art tool released in 2020, built a community of non-technical users who contributed custom brushes and stamps. The manual integration bottleneck—each contribution required developer intervention—motivated building a platform where anyone could publish interactive programs instantly.

9.2 Foundation (2022–2023)

The current repository begins in December 2022. Through 2023 (3,766 commits), the core runtime took shape: the BIOS rendering loop, Disk API, prompt interface, piece lifecycle, and initial set of built-in pieces. September 2023 saw peak early activity (542 commits) as the multiplayer session

server and real-time chat were integrated.

9.3 Expansion (2024)

The year 2024 (2,698 commits) saw the addition of KidLisp (April), the painting system, handle registration, mood posts, and the tape recording infrastructure. Activity peaked in April (379 commits) and October (336 commits).

9.4 Platform Integration (2025–2026)

Development accelerated dramatically in late 2025: October saw 700 commits, November 663, December 525. The KidLisp IDE launched at kidlisp.com (November 2025), ATPProto/Bluesky federation was added, the pack system matured, and the oven service began generating social preview images. January 2026 was the single busiest month (1,095 commits), driven by KidLisp refinement, chaos mode, 3D primitives, and stage mode for live performance.

The project is primarily single-author: @jeffrey accounts for approximately 98% of commits, with contributions from 14 additional collabora-

Period	Commits	Milestone
2020–2021	—	No Paint; AC conception
Dec 2022	47	Repository begins
2023	3,766	Core runtime, prompt, multiplayer
2024	2,698	KidLisp, painting, handles, moods
Jan–May 2025	318	Maintenance period
Jun–Dec 2025	2,962	IDE, pack, oven, federation
Jan–Mar 2026	2,149	Chaos mode, 3D, stage mode
Total	11,045	

Table 2: Development activity by period.

tors. The AestheticAnts system—an automated maintenance agent that runs pre-commit checks, score enforcement, and platter synchronization—embodies the platform’s treatment of maintenance as a first-class creative act, following Ukeles’s argument that care and upkeep are inseparable from the work itself [Ukeles, 1969].

10. Evaluation

Adoption metrics as of March 2026 are shown in Table 3.

Metric	Value
Built-in pieces	354 (336 JS + 18 KidLisp)
User-published pieces	265
API endpoints	78
Registered handles	2,801
Paintings created	4,404
KidLisp programs	16,244
Chat messages	18,020
Core runtime (lines)	~63,300

Table 3: Platform metrics (March 2026).

10.1 Observations

Prompt as discovery mechanism. Users report discovering pieces by typing guesses into the prompt—trying words like *piano*, *draw*, *chat*—and finding what exists. This accidental discovery is a deliberate design outcome of the flat namespace.

Mobile engagement. The mobile-first design means users interact with AC on phones during

commutes, in waiting rooms, and in classrooms— contexts where desktop creative coding tools are inaccessible.

Social fabric drives retention. The integration of chat, moods, and profiles creates a social context that keeps users returning. Users check moods, respond in chat, and discover new pieces through social activity rather than search.

10.2 Limitations

The single-file piece model limits program complexity. Pieces cannot import shared libraries or split across multiple modules (though they can embed KidLisp programs via `$code` references). The prompt interface, while powerful for experienced users, presents a steep discovery curve for newcomers who expect visual affordances.

11. Related Work

Creative coding. Processing [Reas and Fry, 2007] and p5.js [McCarthy, 2015] established the sketchbook paradigm. AC inherits the single-file model but replaces the editor with a prompt and adds social infrastructure.

Social coding. Scratch [Resnick et al., 2009] demonstrated that social sharing drives engagement in educational programming. OpenProcessing [Baran, 2009] and Glitch [Fog Creek Software, 2017] provide web-based sharing for creative code. AC differs by making social features part of the runtime itself, not a surrounding website.

Live coding. Hydra [Jack, 2019] provides browser-based live visual coding. Strudel [Roos and McLean, 2023] brings TidalCycles-style pattern live coding to the browser with no installation. Sonic Pi [Aaron, 2016] targets music education with a live-coding REPL. AC’s stage mode (transparent editor over full-screen canvas) enables similar live performance contexts.

Mobile creative tools. Most creative cod-

ing tools assume desktop use. AC’s mobile-first design—touch input, prompt navigation, phone-sized canvases—targets contexts where desktop tools cannot reach.

Procedural and generative traditions. The *10 PRINT* project [Montfort et al., 2012] demonstrated that a single line of BASIC could be the basis for serious study of computational aesthetics. AC’s piece model shares this commitment to minimal, complete programs as creative units—each piece is a self-contained generative artifact that can be studied, shared, and varied.

12. Conclusion

Aesthetic.Computer demonstrates that a creative computing platform can be organized around a text prompt rather than a graphical IDE, that social infrastructure integrated directly into the runtime produces different engagement patterns than external social layers, and that a mobile-first browser-native approach makes creative coding accessible in contexts desktop tools cannot reach.

The platform's 354 built-in pieces, 265 user-published works, and 16,244 KidLisp programs constitute a growing corpus of creative computing artifacts—what Staunæs [2021], reading Stiegler, would call a collective *idiotext*: an externalized memory woven through technical prostheses, irreducibly shaped by its community of authors. The prompt-as-instrument metaphor—where users build fluency through memorization and improvisation rather than menu navigation—offers an alternative model for how people might relate to creative software.

AC is open source under the ISC license at [https](https://papers.aesthetic.computer/aesthetic-computer-26-arkiv-cards.pdf#page=29):

[//github.com/digitpain/aesthetic.computer.](https://github.com/digitpain/aesthetic.computer)

ORCID: 0009-0007-4460-4913

References

Samuel Aaron. Sonic pi – performance in education, technology and art. In *Proceedings of the International Conference on Live Coding*, 2016.

Sinan Ascioglu Baran. Openprocessing, 2009. URL <https://openprocessing.org>. A community platform for sharing Processing and p5.js sketches.

Fog Creek Software. Glitch, 2017. URL <https://glitch.com>. A collaborative web development platform.

Olivia Jack. Hydra: Live coding networked visuals, 2019. URL <https://hydra.ojack.xyz>.

@jeffrey. Kidlisp '26: A minimal lisp for generative art, 2026. Companion paper describing the KidLisp language in detail.

Friedrich A. Kittler. There is no software. *CTheory*, 1995. Article a032.

Lauren McCarthy. p5.js, 2015. URL <https://p5js.org>.

[//p5js.org](http://p5js.org). A JavaScript library for creative coding.

Marshall McLuhan. *Understanding Media: The Extensions of Man*. McGraw-Hill, New York, 1964.

Nick Montfort, Patsy Baudoin, John Bell, Ian Bogost, Jeremy Douglass, Mark C. Marino, Michael Mateas, Casey Reas, Mark Sample, and Noah Vawter. *10 PRINT CHR\$(205.5+RND(1)); : GOTO 10*. MIT Press, 2012.

Theodor H. Nelson. *Computer Lib / Dream Machines*. Self-published, 1974. Revised edition, Microsoft Press, 1987.

Casey Reas and Ben Fry. *Processing: A Programming Handbook for Visual Designers and Artists*. MIT Press, Cambridge, MA, 2007.

Mitchel Resnick, John Maloney, Andrés Monroy-Hernández, Natalie Rusk, Evelyn Eastmond, Karen Brennan, Amon Millner, Eric Rosenbaum, Jay Silver, Brian Silverman, and Yasmin Kafai. *Scratch: Programming for all*.

Communications of the ACM, 52(11):60–67, 2009.

Felix Roos and Alex McLean. Strudel: Live coding patterns on the web. In *Proceedings of the International Conference on Live Coding (ICLC)*, 2023.

Asker Bryld Staunæs. Stiegler’s concept of idio-text. *Stiegler Studies*, 1(1), 2021.

Mierle Laderman Ukeles. Manifesto for maintenance art 1969! 1969. Proposal for an exhibition “Care”.