

Timed Trace Alignment with Metric Temporal Logic over Finite Traces

Giuseppe Perelli*

Sapienza University of Rome, Italy

Trace alignment (Aalst, van der 2013) is a prominent problem in Declarative Process Mining, which consists in minimally modifying, or *repairing*, a *log trace* to make it compliant with an input temporal specification. In its simplest formulation, traces are finite sequences of *events*, corresponding to the logs stored by a system under execution, and specifications capture properties that involve the mutual ordering of events, specified using the DECLARE language (van der Aalst, Pesic, and Schonenberg 2009), which is a fragment of the Linear-time Temporal Logic interpreted over finite traces LTL_f (De Giacomo and Vardi 2013).

While the Business Process Management (BPM) community has devoted many efforts to this problem –see, e.g., promtools.org, (de Leoni, Maggi, and van der Aalst 2012), and (de Leoni, Maggi, and van der Aalst 2015), the best solution technique currently available comes from AI (De Giacomo et al. 2017) and is based on an automata-theoretic approach that takes advantage of the cost-optimal planning technology, e.g., (Helmert 2006; Torralba et al. 2014) to efficiently perform the search. Notably, such a technique is able to deal with any specification expressed in LTL_f , not only those allowed by DECLARE (which are defined in terms of LTL_f), a commonly adopted language in the BPM context.

A more sophisticated variant of the problem is *timed trace alignment*. In this variant, each event in a log trace is paired with a timestamp and the specifications can be expressed in a variety of forms, from pre-defined patterns (Lanz, Weber, and Reichert 2014), to formulas of more structured logics, such as the multi-perspective version of DECLARE, i.e., MP-DECLARE (Burattin, Maggi, and Sperduti 2016). MP-DECLARE is a fragment of Metric First-order Temporal Logic (Chomicki 1995) (MFOTL), a language that combines First-order Logic (FOL) and Metric Temporal Logic (Koymans 1990), both interpreted over finite traces, to express properties that concern event attributes and timestamps. Interestingly, for the timed version of trace alignment with specifications expressed in a rich language such as MP-DECLARE, a solution technique is not available yet, not even for the case where propositional formulas only are allowed in place of FO. Even more, it is not even known whether the existence of a solution is decidable.

In this talk, we present the timed version of trace alignment, introduced in (De Giacomo et al. 2021), with specifi-

cations expressed in metric temporal logic over finite traces (MTL_f), which is essentially a superlanguage of LTL_f . Importantly, MTL_f is a strictly more expressive language than the propositional version of MP-DECLARE thus, from the temporal perspective, we are addressing the problem in its entire generality. In this setting, trace alignment requires to repair a trace not only by adding or removing events from a finite alphabet but, crucially, by also adding timestamps from the infinite, uncountable, real space. This results in a substantially more challenging setting than that of the basic variant (De Giacomo et al. 2017), as the presence of time makes the structures involved in the search (uncountably) infinite-state, which requires a more sophisticated technical machinery, based on alternating timed automata, as opposed to the standard finite-state automata sufficient for the untimed version.

The contribution is threefold. Firstly, it proposes an automata-based formalization of timed trace alignment which reduces the problem of finding a minimal-cost solution (in terms of changes made to the input trace) to the search for an accepting path in an alternating timed automaton. Secondly, based on the above formulation, it shows that the problem is solvable. Thirdly, by proving solvability in a constructive way, the work devises the first technique for actually computing a solution in the timed setting.

Technically, to achieve these results, we build on two works, namely (Ouaknine and Worrell 2007) and (Finkel and Schnoebelen 2001). The former proves decidability of MTL_f by reducing the problem to non-emptiness of alternating timed automata and showing that this corresponds to the search for an accepting path in a *well-structured* transition system, while the latter provides the theoretical results on such transition systems to make the search effective. Broadly speaking, we generalize the approach described in (Ouaknine and Worrell 2007), which is aimed at showing the existence of a solution, to actually perform a search in the space of the solutions, and take advantage of the results from (Finkel and Schnoebelen 2001) to obtain termination of our technique.

We observe that, while the obtained technique is quite demanding from the complexity point of view, it solves the problem in its entire generality, as far as temporal aspects only are concerned, thus can serve as a reference for practical approaches that typically deal with less expressive fragments of MTL_f , such as the propositional fragment of MP-DECLARE.

*Joint work with Giuseppe De Giacomo, Fabio Patrizi, and Aniello Murano

Acknowledgements

Work partially supported by the ERC Advanced Grant WhiteMech (No. 834228), the EU ICT-48 2020 project TAILOR (No. 952215), and the Sapienza Project DRAPE: Data-aware Automatic Process Execution.

References

- Aalst, van der, W. M. 2013. Business Process Management: a Comprehensive Survey. *ISRN Software Engineering*.
- Burattin, A.; Maggi, F.; and Sperduti, A. 2016. Conformance Checking Based on Multi-perspective Declarative Process Models. *Expert Syst. Appl.* 65:194–211.
- Chomicki, J. 1995. Efficient Checking of Temporal Integrity Constraints Using Bounded History Encoding. *ACM Trans. Database Syst.* 20(2):149–186.
- De Giacomo, G., and Vardi, M. Y. 2013. Linear temporal logic and linear dynamic logic on finite traces. In *IJCAI*, 854–860.
- De Giacomo, G.; Maggi, F. M.; Marrella, A.; and Patrizi, F. 2017. On the Disruptive Effectiveness of Automated Planning for LTL_f-Based Trace Alignment. In *AAAI*, 3555–3561.
- De Giacomo, G.; Murano, A.; Patrizi, F.; and Perelli, G. 2021. Timed trace alignment with metric temporal logic over finite traces. In *KR’21*, 227–236.
- de Leoni, M.; Maggi, F. M.; and van der Aalst, W. M. P. 2012. Aligning Event Logs and Declarative Process Models for Conformance Checking. In *BPM*.
- de Leoni, M.; Maggi, F.; and van der Aalst, W. 2015. An Alignment-Based Framework to Check the Conformance of Declarative Process Models and to Preprocess Event-log Data. *Inf. Syst.* 47:258–277.
- Finkel, A., and Schnoebelen, P. 2001. Well-Structured Transition Systems Everywhere! *Theor. Comput. Sci.* 256(1-2):63–92.
- Helmert, M. 2006. The Fast Downward Planning System. *J. Artif. Intell. Res.(JAIR)* 26:191–246.
- Koymans, R. 1990. Specifying Real-Time Properties with Metric Temporal Logic. *Real Time Syst.* 2(4):255–299.
- Lanz, A.; Weber, B.; and Reichert, M. 2014. Time Patterns for Process-aware Information Systems. *Requir. Eng.* 19(2):113–141.
- Ouaknine, J., and Worrell, J. 2007. On the Decidability and Complexity of Metric Temporal Logic over Finite Words. *Log. Methods Comput. Sci.* 3(1).
- Torralba, A.; Alcazar, V.; Borrajo, D.; Kissmann, P.; and Edelkamp, S. 2014. Symba: A Symbolic Bidirectional A* Planner. In *International Planning Competition*, 105–108.
- van der Aalst, W.; Pesic, M.; and Schonenberg, H. 2009. Declarative Workflows: Balancing Between Flexibility and Support. *Computer Science - R&D* 23(2):99–113.