

# TILT TABLES



Beech **LOAD REDI™** Tilt Tables are designed for multiple applications enabling the work to be positioned up to 45 degrees, decreasing the need for workers to stretch, lift and bend.

- Capacities 750 to 6000 lbs.
- Internally mounted power unit
- 1/2 HP Motor (115/1/60) is standard on RTL Series
- 1 HP Motor (115/1/60) is standard on RMT Series
- Hand controls and a 10 foot cord are standard.
- 8" lip is standard
- Velocity fuse equipped cylinders



## Popular Options:

- 30 and 60 degrees tilt is available (consult factory)
- Floor stands are available (consult factory)
- Lift table mounted units (lift and tilt)
- Foot controls with cover
- 90 degree upender
- Lip to 24"
- Accordion skirt

RTL-Series 7 <sup>1</sup> / <sub>2</sub> " Lowered Height														
24"W x 36 <sup>5</sup> / <sub>8</sub> " L Platform					36"W x 36 <sup>5</sup> / <sub>8</sub> " L Platform					48"W x 48 <sup>5</sup> / <sub>8</sub> " L Platform				
Model No.	Tilt Capacity	Tilt Degree	Raise Time	Wt. (lbs.)*	Model No.	Tilt Capacity	Tilt Degree	Raise Time	Wt. (lbs.)*	Model No.	Tilt Capacity	Tilt Degree	Raise Time	Wt. (lbs.)*
RTL 45 - 7.5 - 2W	750	45	20 sec.	180	RTL 45 - 7.5 - 3W	750	45	20 sec.	220	RTL 45 - 7.5 - 4W	750	45	20 sec.	260
RTL 45 - 10 - 2W	1000	45	21 sec.	190	RTL 45 - 10 - 3W	1000	45	21 sec.	240	RTL 45 - 10 - 4W	1000	45	21 sec.	280
RTL 45 - 15 - 2W	1500	45	23 sec.	220	RTL 45 - 15 - 3W	1500	45	23 sec.	260	RTL 45 - 15 - 4W	1500	45	23 sec.	300

RMT-Series 7 <sup>1</sup> / <sub>2</sub> " Lowered Height														
24"W x 36 <sup>5</sup> / <sub>8</sub> " L Platform					36"W x 36 <sup>5</sup> / <sub>8</sub> " L Platform					48"W x 48 <sup>5</sup> / <sub>8</sub> " L Platform				
Model No.	Tilt Capacity	Tilt Degree	Raise Time	Wt. (lbs.)*	Model No.	Tilt Capacity	Tilt Degree	Raise Time	Wt. (lbs.)*	Model No.	Tilt Capacity	Tilt Degree	Raise Time	Wt. (lbs.)*
RMT 45 - 20 - 2W	2000	45	18 sec.	380	RMT 45 - 20 - 3W	2000	45	18 sec.	400	RMT 45 - 20 - 4W	2000	45	18 sec.	420
RMT 45 - 40 - 2W	4000	45	20 sec.	400	RMT 45 - 40 - 3W	4000	45	20 sec.	420	RMT 45 - 40 - 4W	4000	45	20 sec.	440
RMT 45 - 60 - 2W	6000	45	22 sec.	410	RMT 45 - 60 - 3W	6000	45	22 sec.	430	RMT 45 - 60 - 4W	6000	45	22 sec.	460

\* All weights are approximate

Beech is not responsible for printed errors. Design changes may occur without notice. Call Beech for more information.