

LIGHT DUTY SCISSOR LIFTS



LOAD REDI™ Light Duty scissor lifts are designed for lifting and work applications in (3) standard platform sizes. Rugged construction combined with quality electrical and mechanical components provide years of safe and reliable performance.



- Capacities 750 to 1500 lbs.
- Standard base is 24" wide. (36" and 48" platform models have 6" and 12" stability legs.)
- 1/3 HP Motor (115/230 volt, 1 phase, 60 cycle.)
Power up and down are standard.
- Hand controls and a 10 foot cord are standard.
- Velocity fuse equipped cylinders.
- Listed capacities are based on uniform loads.
(Consult factory for side/end capacities.)

RL-24 Series 24" Travel, 30¹/₄" Raised Height x 6¹/₄" Lowered Height											
24"W x 36⁵/₈" L Platform				36"W x 36⁵/₈" L Platform				48"W x 48⁵/₈" L Platform			
Model No.	Capacity	Raise Time	Weight*	Model No.	Capacity	Raise Time	Weight*	Model No.	Capacity	Raise Time	Weight*
RL 24-7.5-2W	750	15 sec.	260 lbs.	RL 24-7.5-3W	750	15 sec.	280 lbs.	RL 24-7.5-4W	750	15 sec.	300 lbs.
RL 24-10-2W	1000	17 sec.	270 lbs.	RL 24-10-3W	1000	17 sec.	290 lbs.	RL 24-10-4W	1000	17 sec.	310 lbs.
RL 24-15-2W	1500	21 sec.	280 lbs.	RL 24-15-3W	1500	21 sec.	300 lbs.	RL 24-15-4W	1500	21 sec.	320 lbs.

RL-36 Series 36" Travel, 42¹/₄" Raised Height x 6¹/₄" Lowered Height											
24"W x 36⁵/₈" L Platform				36"W x 36⁵/₈" L Platform				48"W x 48⁵/₈" L Platform			
Model No.	Capacity	Raise Time	Weight*	Model No.	Capacity	Raise Time	Weight*	Model No.	Capacity	Raise Time	Weight*
RL 36-7.5-2W	750	19 sec.	320 lbs.	RL 36-7.5-3W	750	19 sec.	340 lbs.	RL 36-7.5-4W	750	19 sec.	360 lbs.
RL 36-10-2W	1000	24 sec.	330 lbs.	RL 36-10-3W	1000	24 sec.	350 lbs.	RL 36-10-4W	1000	24 sec.	370 lbs.
RL 36-15-2W	1500	42 sec.	340 lbs.	RL 36-15-3W	1500	42 sec.	360 lbs.	RL 36-15-4W	1500	42 sec.	380 lbs.

* All weights are approximate

Beech is not responsible for printed errors. Design changes may occur without notice. Call Beech for more information.