

TOSHIBA



Through our commitment to world-class **efficiency**, versatile **scalability** and leading **quality**, Toshiba Air Conditioning advances leading-edge technologies to find the most forward-thinking solutions possible for your world.

TOTALINE



TOSHIBA SERVICE HELPLINE
1800 3000 3545
1800 1021 421

For more details, please contact our sales office:

Corporate & Registered Office: Carrier Airconditioning & Refrigeration Ltd, Kherki Daula Post, Narsingpur, Gurgaon 122004, Tel: 0124-4825500
Sales Offices:— Ahmedabad: 079-44820400/401 **Ghaziabad:** 0120-4183260 **Bangalore:** 080-43442000 **Bhubaneswar:** 9778030033 **Chandigarh:** 0172-5007549/50 **Chennai:** 044-66448888 **Cochin:** 0484-4029000/001, **Coimbatore:** 7397444250 **Daryaganj:** 011-23244491, 9810973264 **Delhi/NCR:** 0124-4873200 **Goa:** 9987868667 **Guwahati:** 9831079624 **Hyderabad:** 040-4181 2222 **Indore:** 0731-2445200 **Jaipur:** 0141-4921737 / 738 **Kolkata:** 033-40592000/3000 **Lucknow:** 0522-4158701/704 **Navi Mumbai/Thane:** 9167788252 **Mumbai:** 022-61700700 **Nagpur:** 9881714903 **Patna:** 7070621177 **Pune:** 020-48571000 **Raipur:** 9752542882 **Surat:** 7433920332



Notice : Toshiba is committed to continuously improving its products to ensure the highest quality and reliability standards, and to meet local regulations and market requirements. All features and specifications are subject to change without prior notice.

TOSHIBA

TOSHIBA AIR CONDITIONING INDOOR UNITS




WIDE CHOICE INDOOR UNITS

> LARGE INDOOR UNIT LINE-UP

The wide choice of indoor unit models increases design flexibility and reduces costs to the building's owner by ensuring the most appropriate system is installed.

- 18 different types of indoor units
- Capacity from 0.8 HP to 20 HP
- For heating, cooling and fresh air production



> SUPERIOR AIR COMFORT


Cool comfort with soft cooling mode

The development of the soft cooling mode provides a new level for cool to personalize the air flow intensity, angle and direct directly from the remote control and enjoy the indoor environment at the right temperature without being directly exposed to the cold draft.




Special coated for FCU heat exchanger

The Toshiba FCU provide odorless and fresh air always, thanks to special coated heat exchanger. This special coating is able to release dust which is attached on heat exchanger with condensed water.



Optimised heating operations

The Toshiba VRF allows continuous heating, even during external defrost operations, thanks to the Kobetsu and Renkei functions integrated in SMMS-u. Indoor units will now operate continually, with only a minimal reduction in capacity output. This results in an uninterrupted flow of warm air, ensuring maximum comfort to the end user.



Low consumption for low operation cost

Premium comfort doesn't mean high power consumption. By using DC motor, large air discharge surface and resin coating system, Toshiba reduces the indoor unit power consumption drastically.

No compromise on air quality

All indoor units are equipped with air suction filters. A symbol on the remote warns the user when filters need to be cleaned.




Example for Compact 4-Way Cassette (0.8HP)



	PCB	FAN	DRAIN	TOTAL
Low fan speed	4 W	6 W	3 W	13 W
Medium fan speed	4 W	7 W	3 W	14 W
High fan speed	4 W	9 W	3 W	16 W

CHOOSE YOUR ADAPTED SYSTEM SOLUTION

2021
NEW
indoor
units



1-Way Cassette

Compact chassis
Smart operation
Advanced filtration



Fresh Air Intake Duct

Light and compact chassis
Wide air flow range



High Wall

Expanding capacity
Up to 4HP big air flow volume
Low noise

Model	(HP)	0.8	1.0	1.25	1.7	2.0	2.5	3.0	3.2	4.0	5.0	6.0	8.0	10.0	12.0	14.0	16.0	18.0	20.0
	(kW)	2.2	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2	14.0	16.0	22.4	28.0	34.0	40.0	45.0	50.4	56.0
4-way Cassette MMU-UP_1HP-E																			
Compact 4-way Cassette MMU-UP_1MH-E																			
2-way Cassette MMU-UP_1WH-E																			
1-way Cassette MMU-UP_1YHP-E																			
Slim Duct MMD-UP_1SPHY-E																			
Concealed Duct MMD-UP_1BHP-E																			
HSP Concealed Duct MMD-UP_1HP-E																			
Fresh Air Intake Duct MMD-UP_1HFP-E																			
Ceiling MMC-UP_1HP-E																			
High Wall MMK-UP_1HP-E																			
Console MML-UP_1NHP-E																			
Floor Standing Concealed MML-UP_1BH-E																			
Floor Standing Cabinet MML-UP_1H-E																			
Floor Standing MMF-UP_1H-E																			
Dx-coil controller & Dx-valve kit TCB-IFD_1E & RBM-A_1VAE																			

Model	Air flow in m3/h	500	600	700	800	900	1000	1100	1200	1300
Air-to-Air Heat Exchanger with DX-coil MMD-VN_2HEX1E										

MMU-UP_1HP-E
4-WAY CASSETTE



The 4-Way Cassette is designed to provide uniform air distribution and total user comfort making this unit the ideal solution for small commercial applications.



LOCAL CONTROLS

RBC-AXU31-E
RBC-AXU31U-E

RBC-AMSU51-EN/ES

RBC-AMTU31-E

RBC-ASCU11-E


Features

Model name		MMU-	UP0091HP-E	UP0121HP-E	UP0151HP-E	UP0181HP-E	UP0241HP-E	UP0271HP-E	UP0301HP-E	UP0361HP-E	UP0481HP-E	UP0561HP-E
Cooling code		HP	1.0	1.25	1.7	2.0	2.5	3.0	3.2	4.0	5.0	6.0
Cooling capacity		kW	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2	14.0	16.0
Heating capacity		kW	3.2	4.0	5.0	6.3	8.0	9.0	10.0	12.5	16.0	18.0
Electrical characteristics	Power supply		1-phase 230V (220-240V) 50Hz / 1-phase 220V (208-230V) 60Hz									
	Running current (50Hz)	A	0.23		0.28	0.29	0.38	0.38	0.43	0.73	0.88	
	Power consumption (50Hz)	kW	0.021		0.023	0.026	0.036		0.043	0.088	0.112	
Appearance	Main unit		Heat-insulating material attached - Zinc hot dipping steel plate									
	Ceiling panel name		RBC-U32PGP-E									
	Panel color		White (Munsell: 2.5GY9.0/0.5)									
Outer dimensions	Main unit (HxWxD)	mm	256x840x840							319x840x840		
	Ceiling panel (HxWxD)	mm	30x950x950									
Total weight	Main unit	kg	18		20					25		
	Ceiling panel	kg	4									
Heat exchanger			Finned tube									
Soundproof / Heat-insulating material			Non-flammable insulation									
Fan unit	Fan		Turbo fan									
	Standard air flow (H/M/L)	m³/h	800/730/680		930/830/790	1050/920/800	1290/920/800		1320/1100/850	1970/1430/1070	2130/1430/1130	2130/1520/1230
	Motor output	W	14				20			68		72
Sound pressure level (H/M/L)		dB(A)	30/29/27		31/29/27	32/29/27	35/31/28		38/33/30	43/38/32	46/38/33	46/40/33
Air filter			Standard filter supplied (Long life filter)									
Controller (Optional)			Wired or infrared remote controller									
Connecting pipe	Gas side	mm	9.5	9.5	12.7	12.7	15.9	15.9	15.9	15.9	15.9	15.9
	Liquid side	mm	6.4	6.4	6.4	6.4	9.5	9.5	9.5	9.5	9.5	9.5
	Drain port (nominal dia)	mm	25 (Polyvinyl chloride tube)									

Drawings

MMU-UP0091HP-E to MMU-UP0301HP-E


MMU-UP0361HP-E to MMU-UP0561HP-E



4-WAY CASSETTE


Air diffusion

Unit : m/s



Accessories


No.	Part name	Model name	Remarks
1	Ceiling Panel (Wide-flow louver)	RBC-U32PGP-E	White (Munsell: 2.5GY9.0/0.5)
2	Spacer for height adjustment	TCB-SP1602UE	50 mm
3	Fresh air chamber	TCB-GFC1602UE	Use with TCB-GB1602U
4	Fresh air intake box	TCB-GB1602UE	Connection=Dia.100 mm fresh air intake ratio: Up to 20%
5	Air discharge direction kit	TCB-BC1602UE	6-direction patterns
6	Auxiliary fresh air flange	TCB-FF101URE2	Connection=Dia.100 mm fresh air intake ratio: Up to 5%




MMU-UP_1MH-E COMPACT 4-WAY CASSETTE



The Compact 4-Way Cassette is especially designed for business office applications, where a compact and efficient solution is required.



LOCAL CONTROLS




Features

Model name		MMU-	UP0071MH-E	UP0091MH-E	UP0121MH-E	UP0151MH-E	UP0181MH-E	
Cooling code		HP	0.8	1.0	1.25	1.7	2.0	
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	
Heating capacity		kW	2.5	3.2	4.0	5.0	6.3	
Electrical characteristics	Power supply		1-phase 230V (220-240V) 50Hz / 1-phase 220V (208-230V) 60Hz					
	Running current (50Hz)		A	0.23	0.24	0.25	0.28	0.4
	Power consumption (50Hz)		kW	0.023	0.025	0.027	0.030	0.052
Appearance	Main unit		Zinc hot dipping steel plate (Heat-insulating material attached only to upper plate)					
	Ceiling panel name		RBC-UM21PG(W)-E					
	Panel color		Gran White (Mansell 5PB9/1)					
Outer dimensions	Main unit (HxWxD)		mm	256x575x575				
	Ceiling panel (HxWxD)		mm	12x620x620				
Total weight	Main unit		kg	15				
	Ceiling panel		kg	2.5				
Heat exchanger			Finned tube					
Soundproof / Heat-insulating material			Non-flammable insulation					
Fan unit	Fan		Turbo fan					
	Standard air flow (H/M/L)		m³/h	552/462/378	570/468/378	594/504/402	660/552/468	840/642/522
	Motor output		W	60				
Sound pressure level (H/M/L)		dB(A)	37/33/29	38/33/29	38/34/30	40/35/31	47/39/34	
Air filter			Standard filter supplied (Long life filter)					
Controller (Optional)			Wired or infrared remote controller					
Connecting pipe	Gas side		mm	9.5	9.5	9.5	12.7	12.7
	Liquid side		mm	6.4	6.4	6.4	6.4	6.4
	Drain port (nominal dia)		mm	VP20 (Polyvinyl chloride tube)				

Drawings

All models

Unit : mm




COMPACT 4-WAY CASSETTE


Air diffusion

Unit : m/s


MMU-UP0071MH-E




MMU-UP0091MH-E




MMU-UP0121MH-E



MMU-UP0151MH-E



MMU-UP0181MH-E



Accessories

Part name	Model name	Applied model	Remarks
Ceiling panel	RBC-UM21PG(W)-E	MMU-UP_1MH-E	Required accessory
Auxiliary fresh air flange	TCB-FF101URE2		For easy fresh air intake by using the knockout hole of indoor unit (dia=100 mm)
Wireless Remote Control kit	RBC-AXU31UM-E		Wireless remote control kit and occupancy sensor cannot be used on the same indoor unit"
Occupancy sensor	TCB-SIR41UM-E		



MMU-UP_1WH-E 2-WAY CASSETTE



Slim, compact and lightweight, the 2-Way Cassette has been designed to fit easily and discreetly into any room interior.

CAPACITY




0.8 HP ~ 6 HP

SOUND PRESSURE LEVEL



30 dB(A)

LOCAL CONTROLS



Features


Model name		MMU-	UP0071WH-E	UP0091WH-E	UP0121WH-E	UP0151WH-E	UP0181WH-E	UP0241WH-E	UP0271WH-E	UP0301WH-E	UP0361WH-E	UP0481WH-E	UP0561WH-E
Cooling code		HP	0.8	1.0	1.25	1.7	2.0	2.5	3.0	3.2	4.0	5.0	6.0
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2	14.0	16.0
Heating capacity		kW	2.5	3.2	4.0	5.0	6.3	8.0	9.0	10.0	12.5	16.0	18.0
Electrical characteristics	Power supply		1-phase 230V (220-240V) 50Hz / 1-phase 220V (208-230V) 60Hz										
	Running current (50Hz)	A	0.21			0.21	0.28	0.37		0.43	0.50	0.57	0.77
	Power consumption (50Hz)	kW	0.024			0.026	0.034	0.045		0.055	0.081	0.091	0.131
Appearance	Main unit		Heat-insulating material attached - Zinc hot dipping steel plate										
	Ceiling panel name		RBC-UW283PG(W)-E				RBC-UW803PG(W)-E				RBC-UW1403PG(W)-E		
	Panel color		Moon white_(Munsell 2.5GY9.0/0.5)										
Outer dimensions	Main unit (HxWxD)	mm	295x815x570				345x1180x570				345x1600x570		
	Ceiling panel (HxWxD)	mm	20x1050x680				20x1415x680				20x1835x680		
Total weight	Main unit	kg	18				26				35		
	Ceiling panel	kg	10				14				14		
Heat exchanger			Finned tube										
Soundproof / Heat-insulating material			Non-flammable insulation										
Fan unit	Fan		Turbo fan					Centrifugal fan					
	Standard air flow (H/M/L)	m³/h	558/498/450			600/534/450	900/750/618	1050/840/738		1260/900/780	1740/1434/1182	1800/1482/1230	2040/1578/1320
	Motor output	W	60				94				139		
Sound pressure level (H/M/L)		dB(A)	34/32/30			35/33/30		38/35/33		40/37/34	42/39/36	43/40/37	46/42/39
Air filter			Standard filter supplied (Long life filter)										
Controller (Optional)			Wired or infrared remote controller										
Connecting pipe	Gas side	mm	9.5	9.5	9.5	12.7	12.7	15.9	15.9	15.9	15.9	15.9	15.9
	Liquid side	mm	6.4	6.4	6.4	6.4	6.4	9.5	9.5	9.5	9.5	9.5	9.5
	Drain port (nominal dia)	mm	25 (Polyvinyl chloride tube)										

Drawings

MMU-UP0071WH-E to MMU-UP0151WH-E

MMU-UP0181WH-E to MMU-UP0301WH-E

Unit : mm




8 | TOSHIBA

2-WAY CASSETTE


Air diffusion

Unit : m/s


MMU-UP0071WH-E, MMU-UP0091WH-E, MMU-UP0121WH-E, MMU-UP0151WH-E




MMU-UP0181WH-E




MMU-UP0241WH-E, MMU-UP0271WH-E




MMU-UP0301WH-E



MMU-UP0361WH-E, MMU-UP0481WH-E




MMU-UP0561WH-E



Accessories

No.	Part name	Model name	Applied model	Notes	Remarks
1	Ceiling Panel	RBC-UW283PG(W)-E	MMU-UP0071 to 0151WH	Required accessory	
		RBC-UW803PG(W)-E	MMU-UP0181 to 0301WH		
		RBC-UW1403PG(W)-E	MMU-UP0361 to 0561WH		
2	Super long life filter	TBC-LF283UW-E	MMU-UP0071 to 0151WH	Dust collecting effect: 50% (Weight method)	Use with TBC-FC283UW-E
		TBC-LF803UW-E	MMU-UP0181 to 0301WH		Use with TBC-FC803UW-E
		TBC-LF1403UW-E	MMU-UP0361 to 0561WH		Use with TBC-FC1403UW-E
3	Filter chamber	TBC-FC283UW-E	MMU-UP0071 to 0151WH	For super long life filter	
		TBC-FC803UW-E	MMU-UP0181 to 0301WH		
		TBC-FC1403UW-E	MMU-UP0361 to 0561WH		
4	Auxiliary fresh air flange	TBC-FF151US-E	MMU-UP0071 to 0561WH	For fresh air intake by using the knockout hole of indoor unit.	





MMU-UP_1YHP-E/SH-E
1-WAY CASSETTE

NEW



Toshiba's innovative slim-line 1-Way Cassette is simple to install and suitable for small areas, such as hotels, offices and reception rooms.




Features

Model name		MMU-	UP0071YHP-E	UP0091YHP-E	UP0121YHP-E	UP0151YHP-E	UP0181YHP-E	UP0241YHP-E	UP0271YHP-E
Cooling code		HP	0.8	1.0	1.25	1.7	2.0	2.5	3.0
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	7.1	8.0
Heating capacity		kW	2.5	3.2	4.0	5.0	6.3	8.0	9.0
Electrical characteristics	Power supply		1-phase 230V (220-240V) 50Hz / 1-phase 220V (208-230V) 60Hz						
	Running current (50Hz)	A	0.17	0.18	0.19	0.24	0.26	0.34	0.41
	Power consumption (50Hz)	kW	0.017	0.018	0.019	0.025	0.027	0.042	0.050
Appearance	Main unit		Heat-insulating material attached - Zinc hot dipping steel plate						
	Ceiling panel name		RBC-UY32P-E			RBC-UY42P-E			
	Panel color		Moon white_(Munsell 2.5GY9.0/0.5)						
Outer dimensions	Main unit (HxWxD)	mm	150x990x450			150x1180x450			
	Ceiling panel (HxWxD)	mm	30x1220x530			30x1410x530			
Total weight	Main unit	kg	14			15		16	
	Ceiling panel	kg	4			6			
Heat exchanger			Finned tube						
Soundproof / Heat-insulating material			Non-flammable insulation						
Fan unit	Fan		Centrifugal fan			Cross Flow Fan			
	Standard air flow (H/M/L)	m³/h	500/390/270	520/410/290	540/420/290	750/630/500	800/650/500	940/760/600	1000/860/720
	Motor output	W	30			42		59	
Sound pressure level (H/M/L)		dB(A)	38/34/25	39/35/26	40/36/26	54/51/48	55/52/48	61/57/52	62/59/56
Air filter			Standard filter supplied (Long life filter) / Air purifier available as option						
Controller (Optional)			Wired or infrared remote controller						
Connecting pipe	Gas side	mm	9.5	9.5	9.5	12.7		15.9	
	Liquid side	mm	6.4	6.4	6.4	6.4		9.5	
	Drain port (nominal dia)	mm	25 (Polyvinyl chloride tube)						


1-WAY CASSETTE

Air diffusion


MMU-UP0071YHP-E



MMU-UP0091YHP-E




MMU-UP0121YHP-E



Unit : m/s


Accessories

No.	Part name	Model name	Applied model	Notes	Remarks
1	Ceiling Panel	RBC-UY32P-E	MMU-UP_1YHP-E	1-Way cassette panel without receiver	Required accessory
		RBC-UY42P-E			Required accessory
2	Air purifier kit	TCB-EAPC1UYHP-E	MMU-UP-1YHP-E	Set of Plasma Air Purifier, Dust sensor, Air quality indicator, Wireless receiver and Wireless RC	
3	Occupancy sensor	TCB-SIR41UYP-E	MMU-UP-1YHP-E	Occupancy sensor	Cannot match with Wireless receiver Kit
4	Wireless receiver kit	RBC-AX33UYP-E	MMU-UP-1YHP-E	Wireless RC kit	Cannot match with Occupancy sensor




Drawings

MMU-UP0071YHP-E to MMU-UP0121YHP-E



MMU-UP0151SH-E to MMU-UP0241SH-E



MMD-UP_1SPHY-E
SLIM DUCT



Whatever installed in a ceiling void or in a false ceiling, Toshiba Slim Duct offers the ultimate technology, with exceptional energy saving, high performance and easy installation.



LOCAL CONTROLS

Features

Model name		MMD-	UP0071SPHY-E	UP0091SPHY-E	UP0121SPHY-E	UP0151SPHY-E	UP0181SPHY-E	UP0241SPHY-E	UP0271SPHY-E
Cooling code		HP	0.8	1.0	1.25	1.7	2.0	2.5	3.0
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	7.1	8.0
Heating capacity		kW	2.5	3.2	4.0	5.0	6.3	8.0	9.0
Electrical characteristics	Power supply		1-phase 50Hz 220-240V / 1-phase 60Hz 208-230V						
	Running current (50Hz)	A	0.40	0.42	0.44	0.47	0.53	0.69	0.74
	Power consumption (50Hz)	kW	0.026	0.029	0.031	0.035	0.044	0.067	0.072
Appearance			Zinc hot dipping steel plate						
Outer dimensions (HxWxD)		mm	210x700x450			210x900x450		210x1110x450	
Total weight		kg	15			19		22	
Heat exchanger			Finned tube						
Soundproof / Heat-insulating material			Polyethylene foam + Polyurethane foam						
Fan unit	Fan		Centrifugal fan (sirocco fan)						
	Standard air flow (H/M/L)	m³/h	540/460/400	570/500/420	600/520/440	690/640/550	780/730/650	1080/950/860	1140/980/910
	Motor output	W	50			94			
	External static pressure (Factory setting)	Pa	10						
	External static pressure	Pa	10-20-30-40-50 (5 Steps)						
Sound pressure level (H/M/L)	Under air intake	dB(A)	41/39/35	42/40/36	44/40/37	42/39/37	44/42/39	47/44/41	48/45/43
	Back air intake	dB(A)	31/29/26	32/29/26	33/30/27	33/30/28	34/32/29	36/33/30	37/34/32
Air filter			Standard filter supplied (Long life filter)						
Controller (Optional)			Wired or infrared remote controller						
Connecting pipe	Gas side	mm	9.5	9.5	9.5	12.7	12.7	15.9	15.9
	Liquid side	mm	6.4	6.4	6.4	6.4	6.4	9.5	9.5
	Drain port (nominal dia)	mm	25 (Polyvinyl chloride tube : External dia.32 Internal dia.25)						


SLIM DUCT

Accessories

Part name	Model name	Applied model	Remarks
Auxiliary fresh air flange	TCB-FF101URE2	MMD-UP_1SPHY-E	For fresh air intake by using the knockout hole of indoor unit (dia.=100 mm)

Installation flexibility

Change from under air intake to back air intake



Drawings

MMD-UP0071SPHY-E to MMD-UP0271SPHY-E

MMD-UP***1SPHY-E	007-012	015-018	024-027
A	650	850	1050
B	700	900	1100
C	770	970	1170
D	5	7	9
E	500	700	900
F	655	855	1055
G	6.4	9.5	9.5
H	9.5	12.7	15.9

Unit : mm

MMD-UP_1BHP-E STANDARD DUCT



Whatever the shape of the room, this flexible model ensures a uniform temperature and air distribution for optimal end user comfort.

CAPACITY



0.8 HP ~ 6 HP

SOUND PRESSURE LEVEL



23 dB(A)

LOCAL CONTROLS



RBC-AXU31-E



RBC-AMSU51-EN/ES



RBC-AMTU31-E



RBC-ASCU11-E


STANDARD DUCT

Accessories

Part name	Model name	Applied model	Appearance	Remarks
Spigot shaped flange	TCB-SF56C6BE	MMD-UP0071/0091/0121/0151/0181BHP-E		263x694x175mm / Spigot diameter 200mm
	TCB-SF80C6BE	MMD-UP0241/0271/0301BHP-E		263x994x175mm / Spigot diameter 200mm
	TCB-SF160C6BE	MMD-UP0361/0481/0561BHP-E		263x1394x175mm / Spigot diameter 200mm

Installation flexibility

Changing from back air intake to under air intake




Features

Model name		MMD-	UP0071BHP-E	UP0091BHP-E	UP0121BHP-E	UP0151BHP-E	UP0181BHP-E	UP0241BHP-E	UP0271BHP-E	UP0301BHP-E	UP0361BHP-E	UP0481BHP-E	UP0561BHP-E		
Cooling code		HP	0.8	1.0	1.25	1.7	2.0	2.5	3.0	3.2	4.0	5.0	6.0		
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2	14.0	16.0		
Heating capacity		kW	2.5	3.2	4.0	5.0	6.3	8.0	9.0	10.0	12.5	16.0	18.0		
Electrical characteristics	Power supply		1-phase 50Hz 220-240V / 1-phase 60Hz 208-230V												
	Running current (50Hz)	A	0.35	0.38		0.70		0.80		0.95	1.29	1.70			
	Power consumption (50Hz)	kW	0.055	0.060		0.110		0.135		0.160	0.220	0.290			
Appearance			Zinc hot dipping steel plate												
Dimensions (HxWxD)		mm	275x700x750					275x1000x750			275x1400x750				
Total weight		kg	23					30			40				
Heat exchanger			Finned tube												
Soundproof / Heat-insulating material			Polyethylene foam												
Fan unit	Fan		Centrifugal fan												
	Standard air flow (H/M/L)	m³/h	540/450/360	570/480/390		920/660/540		1320/1090/870		1450/1200/960	1920/1620/1380	2350/1920/1500	2350/1090/1500		
	Motor output	W	150								250				
	External static pressure (Factory setting)	Pa	30					40			50				
	External static pressure	Pa	30-40-50-65-80-100-150 (7 Steps)												
Sound pressure level (H/M/L)		dB(A)	29/26/23	30/26/23	30/26/23	33/29/25	33/29/25	33/30/27	33/30/27	36/31/27	36/34/31	40/36/33	40/36/33		
Air filter			Standard filter supplied (Long life filter)												
Controller (Optional)			Wired or infrared remote controller												
Connecting pipe	Gas side	mm	9.5	9.5	9.5	12.7	12.7	15.9	15.9	15.9	15.9	15.9	15.9		
	Liquid side	mm	6.4	6.4	6.4	6.4	6.4	9.5	9.5	9.5	9.5	9.5	9.5		
	Drain port (nominal dia)	mm	25 (Polyvinyl chloride tube)												


Drawings

Unit : mm


MMD-UP0071BHP-E to MMD-UP0181BHP-E




MMD-UP0241BHP-E to MMD-UP0301BHP-E





MMD-UP0361BHP-E to MMD-UP0561BHP-E



MMD-UP_1HP-E HIGH STATIC PRESSURE DUCT



This is Toshiba's most powerful ducted unit delivering air flows up to 4,800 m³/h with an external static pressure up to 250 Pa.




Features

Model name		MMD-	UP0181HP-E	UP0241HP-E	UP0271HP-E	UP0361HP-E	UP0481HP-E	UP0561HP-E	UP0721HP-E1	UP0961HP-E1
Cooling code		HP	2.0	2.5	3.0	4.0	5.0	6.0	8.0	10.0
Cooling capacity		kW	5.6	7.1	8.0	11.2	14.0	16.0	22.4	28.0
Heating capacity		kW	6.3	8.0	9.0	12.5	16.0	18.0	25.0	31.5
Electrical characteristics	Power supply		1-phase 50Hz 220-240V / 1-phase 60Hz 208-230V							
	Running current (50Hz)	A	0.82	0.92	1.16	1.39	1.81	2.48	2.83	3.77
	Power consumption (50Hz)	kW	0.125	0.140	0.190	0.230	0.300	0.400	0.540	0.790
Appearance			Zinc hot dipping steel plate							
Dimensions (HxWxD)		mm	298x1000x750			298x1400x750			448x1400x900	
Total weight		kg	34			43			97	
Heat exchanger			Finned tube							
Soundproof / Heat-insulating material			Polyethylene foam							
Fan unit	Fan		Centrifugal fan							
	Standard air flow (H/M/L)	m³/h	1100/990/900	1200/1050/960	1500/1350/1200	1920/1560/1340	2340/1980/1695	2760/2340/1920	3800/3200/2500	4800/4200/3500
	Motor output	W	250			350			250	
	External static pressure (Factory setting)	Pa	100						150	
	External static pressure	Pa	50-75-125-100-150-175-200 (7steps)						50-83-117-150-183-217-250 (7steps)	
Sound pressure level (H/M/L)		dB(A)	37/33/31	38/34/31	43/41/38	41/37/34	44/44/38	46/44/41	44/40/36	46/42/38
Air filter			Sold separately (TCB-LK801D-E)			Sold separately (TCB-LK1401D-E)			Sold separately (TCB-LK2801D-E)	
Controller (Optional)			Wired or infrared remote controller							
Connecting pipe	Gas side	mm	12.7	15.9	15.9	15.9	15.9	15.9	22.2	22.2
	Liquid side	mm	6.4	9.5	9.5	9.5	9.5	9.5	12.7	12.7
	Drain port (nominal dia)	mm	25 (Polyvinyl chloride tube)							

Drawings


MMD-UP0181HP-E to MMD-UP0561HP-E



HIGH STATIC PRESSURE DUCT

Drawings

MMD-UP0721HP-E1 & MMD-UP0961HP-E1



Accessories


Part name	Model name	Applied model	Appearance	Remarks
Spigot shaped flange	TCB-SF80C6BE	MMD-UP0181/0241/0271HP-E		263x994x175mm / Spigot diameter 200mm
	TCB-SF160C6BE	MMD-UP0361/0481/0561HP-E		263x1394x175mm / Spigot diameter 200mm
Long life filter kit	TCB-LK801D-E	MMD-UP0181/0241/0271HP-E		Flange shaped Mount chassis directly Upside down mounting possible Left and right removable
	TCB-LK1401D-E	MMD-UP0361/0481/0561HP-E		
	TCB-LK2801DP-E	MMD-UP0721/0961HP-E		
Auxiliary fresh air flange	TCB-FF151US-E	MMD-UP0181/0241/0271/0361/ 0481/0561HP-E		
Drain pump kit	TCB-DP40DPE	MMD-UP0721/0961HP-E		

FRESH AIR INTAKE

MMD-UP_1HFP-E
FRESH AIR INTAKE



This indoor unit has been specifically designed to manage and treat fresh air before its distribution into the building.



Features


Model name		MMD-	UP0481HFP-E	UP0721HFP-E1	UP0961HFP-E1	
Cooling code		HP	5.0	8.0	10.0	
Cooling capacity (*) (Note 1)		kW	14.0	22.4	28.0	
Heating capacity (*) (Note 2)		kW	8.9	13.9	17.4	
Electrical characteristics	Power supply		1-phase 50Hz 220-240V / 1-phase 60Hz 208-230V			
	Running current (50Hz)	A	0.77	0.86	1.07	
	Power consumption (50Hz)	kW	0.108	0.153	0.198	
Dimensions (HxWxD)		mm	327x1430x750	477x1430x900		
Total weight		kg	44	99		
Heat exchanger			Finned tube			
Soundproof / Heat-insulating material			Non-flammable insulation			
Fan unit	Fan		Centrifugal fan			
	Standard air flow (H/M/L)	m³/h	1080/930/760	1680/1440/1200	2100/1800/1470	
	Motor output	W	350	1000		
	External static pressure (Factory setting)		Pa	100		
	External static pressure		Pa	50-75-100-125-150-175-200 (7 Steps)		
	Air flow limit	Lower limit	m³/h	600	960	1320
		Upper limit	m³/h	1320	2040	2520
Sound pressure level (H/M/L)		dB(A)	38/35/31	38/36/33	39/36/33	
Air filter			Option or field supply			
Controller (Optional)			Wired or infrared remote controller			
Connecting pipe	Gas / Liquid side	mm	15.9 / 9.5	22.2 / 12.7		
	Drain port (nominal dia)	mm	25 (Polyvinyl chloride tube)			

* The setting temperature is 13 ~ 25°C (standard FCU: 18 ~ 30 °C).
* Height difference between Fresh Air Intake Indoor units must be within 5 m.


Note 1: Rated conditions
Cooling: Outdoor air temperature 33°C DB/28°C WB setting temperature 18°C
Heating: Outdoor air temperature 0°C DB/-2.9°C WB setting temperature 25°C
Note 2: When supply air temperature is "setting temperature + 3°C" or less, Fresh Air Intake unit operates as FAN mode
Note 3: When supply air temperature is "setting temperature -3°C" or over, Fresh Air Intake unit operates as FAN mode
Note 4: 45-52°C is also available but temporary operable
In case of connecting with SMMS-e for all Fresh Air Intake unit, it can use down to -5°C in heating mode

Drawings

MMD-UP0481HFP-E



MMD-UP0721HFP-E1 to MMD-UP0961HFP-E1



FRESH AIR INTAKE

Accessories

Part name	Model name	Description	Applied model	Appearance
Air filtration	TCB-UFM0481D-E	High-efficiency filter 65	MMD-UP0481HF-E	
	TCB-UFM1281D-E	High-efficiency filter 65	MMD-UP0721HF-E to MMD-UP1281HF-E	
	TCB-UFH0481D-E	High-efficiency filter 90	MMD-UP0481HF-E	
	TCB-UFH1281D-E	High-efficiency filter 90	MMD-UP0721HF-E to MMD-UP1281HF-E	
	TCK-LK1401D-E	Stand alone long life prefilter	MMD-UP0481HF-E	
	TCK-LK2801DP-E	Stand alone long life prefilter	MMD-UP0721HF-E to MMD-UP1281HF-E	
	TCK-LK1401D-E (*2)	High efficiency long life prefilter	MMD-UP0481HF-E	
	TCK-PF1281DF-E	High efficiency long life prefilter	MMD-UP0721HF-E to MMD-UP1281HF-E	
	TCB-FC0481DF-E	Filter chamber	MMD-UP0481HF-E	
Drain pump kit	TCB-FC1281DF-E	Filter chamber	MMD-UP0721HF-E to MMD-UP1281HF-E	
	TCB-DP40DFP-E	Drain pump kit	All models	

MMC-UP_1HP-E
UNDER CEILING



The simple yet elegant design helps to create a pleasant and relaxing environment, quickly conditioning the room air to the desired temperature.



LOCAL CONTROLS

RBC-AXU31-E
RBC-AXU31C-E

RBC-AMSU51-EN/ES

RBC-AMTU31-E


RBC-ASCU11-E

Features

Model name		MMC-	UP0151HP-E	UP0181HP-E	UP0241HP-E	UP0127HP-E	UP0361HP-E	UP0481HP-E	UP0561HP-E
Cooling code		HP	1.7	2.0	2.5	3.0	4.0	5.0	6.0
Cooling capacity		kW	4.5	5.6	7.1	8.0	11.2	14.0	16.0
Heating capacity		kW	5.0	6.3	8.0	9.0	12.5	16.0	18.0
Electrical characteristics	Power supply		1 phase 50Hz 230V (220-240V) / 1 phase 60Hz 220V						
	Running current (50Hz)	A	0.35	0.36	0.64	0.65	0.77	0.77	0.99
	Power consumption (50Hz)	kW	0.033	0.034	0.067	0.067	0.083	0.083	0.111
Appearance			Pure White (Munsell N9.1)						
Dimensions (HxWxD)		mm	235x950x690		235x1270x690			235x1586x690	
Total weight		kg	24		30			39	
Heat exchanger			Finned tube						
Soundproof / Heat-insulating material			Polyethylene foam						
Fan unit	Fan		Centrifugal fan (Sirocco fan)						
	Standard air flow (H/M/L)	m³/h	840/690/540	960/720/540	1440/1020/750	1440/1020/750	1860/1350/1020	1860/1530/1200	2040/1650/1260
	Motor output	W	94				139		
Sound pressure level (H/M/L)		dB(A)	36/34/28	37/35/28	41/36/29	41/36/29	44/38/32	44/41/35	46/42/36
Air filter			Standard filter supplied (Long life filter)						
Controller (Optional)			Wired or infrared remote controller						
Connecting pipe	Gas side	mm	12.7	12.7	15.9	15.9	15.9	15.9	15.9
	Liquid side	mm	6.4	6.4	9.5	9.5	9.5	9.5	9.5
	Drain port (nominal dia)	mm	20 (Polyvinyl chloride tube)						

Drawings


Unit : mm



UNDER CEILING


Air diffusion

Unit : m/s




Accessories

No.	Part name	Model name	Applied model	Notes	Remarks
1	Wireless Remote Controller kit	RBC-AXU31C-E	MMC-UP_1HP-E		
2	Drain pump kit	TCB-DP31CE		Antibacterial glass is built into drain pump kit	
3	Elbow piping kit	TCB-KP14CPE TCB-KP24CPE		It is necessary for installation of drain pump kit	Use with TCB-DP31CE
4	Option connecting kit	TCB-PCUC2E		For external I/O signal without local relay preparation	



MMK-UP_1HP-E
HIGH-WALL

NEW



Particularly compact, this high-wall is perfect for limited spaces, such as offices or small shops.

CAPACITY




0.8 HP ~ 4 HP

SOUND PRESSURE LEVEL



25 dB(A)

LOCAL CONTROLS



Features

Model name		MMK-	UP0071HP-E	UP0091HP-E	UP0121HP-E	UP0151HP-E	UP0181HP-E	UP0241HP-E	UP0271HP-E	UP0301HP-E	UP0361HP-E
Cooling code		HP	0.8	1.0	1.25	1.7	2.0	2.5	3.0	3.2	4.0
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6	7.1	8.0	9.0	11.2
Heating capacity		kW	2.5	3.2	4.0	5.0	6.3	8.0	9.0	10.0	12.5
Electrical characteristics	Power supply	1 phase 50Hz 230V (220-240V) / 1 phase 60Hz 220V									
	Running current (50Hz)	A	0.15	0.16	0.17	0.25	0.28	0.40	0.28	0.44	0.52
	Power consumption (50Hz)	kW	0.015	0.016	0.017	0.028	0.032	0.050	0.034	0.054	0.066
Dimensions (HxWxD)		mm	293x798x230			320x1050x250			348x1200x280		
Total weight		kg	11			16			21		
Heat exchanger		Finned tube									
Soundproof / Heat-insulating material		Non-flammable insulation									
Fan unit	Fan	Cross Flow Fan									
	Standard air flow (H/M/L)	m³/h	480/385/270	510/395/270	540/410/270	840/690/550	900/720/550	1200/900/600	1200/1000/800	1500/1300/1100	1650/1350/1250
Sound pressure level (H/M/L)		dB(A)	35/30/25	36/31/25	37/32/25	40/36/32	41/37/32	45/39/33	44/41/39	48/44/41	50/45/43
Air filter		Standard filter supplied (Long life filter)									
Controller (Packed with unit)		Wireless remote controller									
Connecting pipe	Gas side	mm	12.7	12.7	12.7	12.7	12.7	15.9	15.9	15.9	15.9
	Liquid side	mm	6.4	6.4	6.4	6.4	6.4	9.5	9.5	9.5	9.5
	Drain port (nominal dia)	mm	16 (Polyvinyl chloride tube)								


Drawings

Unit : mm

MMK-UP0071HP-E to MMK-UP0121HP-E


MMK-UP0151HP-E to MMU-UP0241HP-E

MMK-UP0271HP-E to MMU-UP0361HP-E



Air diffusion

Unit : m/s



MML-UP_1NHP-E
BI-FLOW CONSOLE



BI-FLOW CONSOLE

Innovative and compact unit to be installed on the floor and in low wall applications, fits perfectly under the window sills or in a low ceiling attic.




Features

Model name		MML-	UP0071NHP-E	UP0091NHP-E	UP0121NHP-E	UP0151NHP-E	UP0181NHP-E
Cooling code		HP	0.8	1.0	1.25	1.7	2.0
Cooling capacity		kW	2.2	2.8	3.6	4.5	5.6
Heating capacity		kW	2.5	3.2	4.0	5.0	6.3
Electrical characteristics	Power supply		1 phase 50Hz 230V (220-240V) / 1 phase 60Hz 220V				
	Running current (50Hz)	A	0.20	0.20	0.23	0.29	0.42
	Power consumption (50Hz)	kW	0.021	0.021	0.025	0.034	0.052
Appearance	Air intake grille and side panel		Moon white (Munsell : 2.5GY 9.0/0.5)				
	Discharge-grille		Moon white (Munsell : 2.5GY 9.0/0.5)				
	Bottom surface		Moon white (Munsell : 2.5GY 9.0/0.5)				
Dimensions (HxWxD)		mm	600x700x220				
Total weight		kg	17				
Heat exchanger			Finned tube				
Soundproof / Heat-insulating material			Foamed polystyrene / Polyethylene				
Fan unit	Fan		Turbo fan				
	Standard air flow (H/M/L)	m³/h	510/366/282	510/366/282	552/408/324	624/468/384	726/528/426
	Motor output	W	41				
Sound pressure level (H/M/L)		dB(A)	38/32/26	38/32/26	40/34/29	43/37/31	47/40/34
Air filter			Standard filter supplied (Long life filter)				
Controller (Packed with indoor unit)			Wireless remote controller				
Connecting pipe	Gas side	mm	9.5	9.5	9.5	12.7	12.7
	Liquid side	mm	6.4	6.4	6.4	6.4	6.4
	Drain port (nominal dia)	mm	16 (Polypropylene tube)				

Drawings


All models

Unit : mm




Air diffusion


MML-UP0071NH-E, UP0091NH-E




MML-UP0121NH-E



MML-UP0151NH-E




MML-UP0181NH-E




Air diffusion


MML-UP0071H-E, MML-UP0091H-E



MML-UP0121H-E, MML-UP151H-E



MML-UP0181H-E, MML-UP241H-E



Unit : m/s



FLOOR STANDING

MMF-UP_1H-E
FLOOR STANDING

This system is particularly suitable to large rooms air condition like shops, showrooms, and with low ceiling rooms like restaurants.

CAPACITY

↑

1.7 HP ~ 6 H

SOUND PRESSURE LEVEL




38 dB(A)

FLOOR STANDING


Air diffusion

Unit : m/s


MMF-UP0151H-E, MMF-UP0181H-E




MML-UP0151BH-E, MML-UP0271BH-E



MMF-UP0361H-E



MML-UP0481BH-E, MML-UP0561BH-E



↑ IDU

AIR-TO-AIR HEAT EXCHANGER

MMD-VN AIR-TO-AIR HEAT EXCHANGER WITH DX COIL



TOSHIBA

MMD-VN ventilation products are using exhaust air + DX coil to pre-condition the incoming air, thus reducing the cooling or heating load and the overall size of the required air conditioning system.

CAPACITY



4.1 kW ~ 8.25 kW

AIR FLOW



Up to 500m³/h ~ 950m³/h

SOUND PRESSURE LEVEL



34.5 dB(A)

LOCAL CONTROLS



NRC-01HE
RBC-AMTU31E

Features

Model name			MMD-	Without humidifier				
				VN502HEX1E		VN802HEX1E	VN1002HEX1E	VN1002HEX1E2
Cooling capacity			kW	4.10(1.30)		6.56(2.06)	8.25(2.32)	8.25(2.32)
Heating capacity			kW	5.53(2.33)		8.61(3.61)	10.92(4.32)	10.92(4.32)
Power supply				1 phase 50Hz 230V (220-240V) / 1 phase 60Hz 220V			1 phase 50Hz 230V(220V-240V)	1 phase 60Hz 220V
Temperature exchange efficiency	Extra high/High/Low		%	70.5/71.5/72.0		70.5/72.5/73.0	65.5/67.5/68.0	65.5/67.5/68.0
Enthalpy exchange efficiency (%)	Cooling (Extra high/High/Low)		%	56.5/57.5/58.0		56.0/59.0/59.5	52.0/54.0/55.0	52.0/54.0/55.0
	Heating (Extra high/High/Low)		%	68.5/69.0/69.0		70.0/73.0/73.5	66.0/68.5/69.0	66.0/68.5/69.0
Power input (Heat exchange mode)	Extra high		kw	0.300/0.365		0.505/0.595	0.550	0.720
	High		kw	0.280/0.350		0.465/0.555	0.545	0.665
	Low		kw	0.235/0.250		0.335/0.390	0.485	0.530
Running current	Extra high		A	1.30/1.65		2.25/2.77	2.46	3.38
	High		A	1.21/1.62		2.07/2.59	2.43	3.11
	Low		A	1.01/1.14		1.46/1.79	2.16	2.45
Fan unit	Standard air flow	Extra high	m³/h	500/-		800/-	950	950
		High	m³/h	500/-		800/-	950	950
		Low	m³/h	440/410		640/600	820	800
	External static pressure	Extra high	Pa	120/200		120/190	135	195
		High	Pa	105/170		100/155	120	160
		Low	Pa	115/150		100/130	105	130
	Air flow limit	Lower limit	m³/h	330		480	640	640
		Upper limit	m³/h	600		960	1140	1140
Humidifier	System			-		-	-	-
	Amount			-		-	-	-
	Feed water pressure			-		-	-	-
Sound pressure level	Extra high		dB(A)	37.5/40		41/43	43	43.5
	High		dB(A)	36.5/38		40/42	42	42
	Low		dB(A)	34.5/36.5		38/37	40	40
Appearance				Zinc hot dipping steel plate				
Dimensions (HxWxD)			mm	430x1140x1690		430x1189x1739	430x1189x1789	430x1189x1789
Weight			kg	84		100	101	101
Heat exchanger / Heat-insulating material				Finned tube / Flexible urethane foam				
Air filter				Standard filter & High efficiency filter				
Controller				Remote controller (Separately sold parts)				
Connecting pipe	Gas side / Liquid side		mm	9.5 / 6.4		12.7 / 6.4	12.7 / 6.4	12.7 / 6.4
	Drain port (nominal dia)		mm	25 (Polyvinyl chloride tube)				

Cooling and heating capacities are based on the following conditions:
Cooling capacities are based on: Indoor temperature: 27°C DB/19°C WB, Outdoor temperature: 35°C DB
Heating capacities are based on: Indoor temperature: 20°C DB, Outdoor temperature: 7°C DB/6°C WB.
The figures in () indicate the heat reclaimed from the heat recovery ventilator.


VN-M_HE
AIR-TO-AIR HEAT EXCHANGER



AIR-TO-AIR HEAT EXCHANGER WITH DX COIL

Drawings

Unit : mm




➤ IDU

Accessories

Part name	Model name	Description	Appearance	Remarks
Control	NRC-01HE	Dedicated remote controller for air-to-air heat exchanger		Integrated functions : fan speed, freecooling, air balance volume rate, temperature management and timer.
	NRB-1HE	On/off optional PCB for air-to-air heat exchanger		
Condensates	TCB-DP31HEXE	Drain pump kit		

Other information



Toshiba's VN model uses exhaust air to pre-condition the incoming air, thus reducing the cooling or heating load on the system. This allows the overall capacity size of the system to be reduced.



AIR FLOW
150m3/h ~ 2,000m3/h



SOUND PRESSURE LEVEL
20 dB(A)

LOCAL CONTROLS



NRC-01HE
RBC-AMTU31E

Features


Model name			VN-M150HE	VN-M250HE	VN-M350HE	VN-M500HE	VN-M650HE	VN-M800HE	VN-M1000HE1	VN-M1500HE1	VN-M2000HE1
Air volume (Extra high/High/Low)		m³/h	150/150/110	250/250/155	350/350/210	500/500/390	650/650/520	800/800/700	1000/1000/700	1500/1500/1200	2000/2000/1400
Power consumption	Extra high	W	68-78	123-138	165-182	214-238	262-290	360-383	390	640	780
	High	W	59-67	99-111	135-145	176-192	240-258	339-353	340	570	680
	Low	W	42-47	52-69	82-88	128-142	178-191	286-300	190	320	380
External static pressure	Extra high	Pa	82-102	80-98	114-125	134-150	91-107	142-158	105	140	105
	High	Pa	52-78	34-65	56-83	69-99	58-82	102-132	80	110	80
	Low	Pa	47-64	28-40	65-94	62-92	61-96	76-112	70	80	70
Sound pressure level	Extra high	dB(A)	26-28	29.5-30	34-35	32.5-34	34-36	37-38.5	38.0	41.0	41.5
	High	dB(A)	24-25.5	25-27	30-32	29.5-31	33-34	35.5-37	37.0	40.0	40.5
	Low	dB(A)	20-22	21-22	27-29	26-29	31-32.5	33.5-35	33.0	36.0	36.5
Sound power level (Extra high)		dB(A)	41-43	44.5-45	49-50	47.5-49	49-51	52-53.5	53.0	56.0	56.5
Temperature exchange efficiency (%)	Extra high		81.5	78	74.5	76.5	75	76.5	73.5	76.5	73.5
	High		81.5	78	74.5	76.5	75	76.5	73.5	76.5	73.5
	Low		83	81.5	79.5	78	76.5	77.5	77.0	79.0	77.5
Enthalpy exchange efficiency (%)	Extra high	Heating	74.5	70	65	72	69.5	71	68.5	71.0	68.5
	High	Heating	74.5	70	65	72	69.5	71	68.5	71.0	68.5
	Low	Heating	76	74	71.5	73.5	71.5	71.5	71.5	73.5	72.0
	Extra high	Cooling	69.5	65	60.5	64.5	61.5	64	60.5	64.0	60.5
	High	Cooling	69.5	65	60.5	64.5	61.5	64	60.5	64.0	60.5
	Low	Cooling	71	69	67	66.5	64	65.5	64.5	67.0	65.5
Power supply			220V-240V / 50Hz								
Dimensions (HxWxD)		mm	900x900x290			1140x1140x350		1189x1189x400		1189x1189x810	
Weight		kg	36	36	38	53	53	70	70	126	126

* Air volume can be changed over to high (Extra high) mode or low mode at both heat exchange and normal ventilation modes.
* Sound pressure level is measured 1.5 m below the center of the unit, and the value which was measured at the acoustic room.
* Sound pressure levels usually become higher than above values by the influence of actual installation condition such as reflected sound and peripheral noise.

* Sound power level is the value of casing.
*1) When the temperature of the outdoor air is below -10°C, the unit runs cold operation mode (intermittent operation of the ventilation for air supply). The unit cannot be used at -15°C or less. The ventilator for air supply stops, and the ventilator for air exhaust also can be stopped by the setting.

Drawings

Unit : mm




AIR-TO-AIR HEAT EXCHANGER

Accessories

Part name	Model name	Description	Appearance	Remarks
Control	NRC-01HE	All air-to-air heat exchangers Dedicated remote control		Integrated functions: fan speed, freecooling, air balance volume rate, temperature management and timer.
	NRB-1HE	All air-to-air heat exchangers On/Off additional PCB		On/off optional PCB for air-to-air heat exchanger

➤ IDU

Other information



WIRELESS
SOLUTIONS
KEEP
CONTROL

WIRELESS SOLUTIONS KEEP CONTROL




In addition to the high quality of the air conditioners, the controls also play a significant part in the ease-of-use and efficiency of the units. Optimized settings create the perfect climate. Along with local control options, Toshiba also offers a broad selection of central control systems or the option to integrate these in the building control system.

> ONE CONTROL FOR EVERY USAGE



Local controls

Cable remote controls (max. cable length 500 m) or wireless infrared remote controls are used to control individual units or groups of up to 8 indoor units. Additional modules allow units to be controlled from any location via apps or the Internet.



Central controls

VRF systems can be controlled from a preferred central location, such as the reception or plant room. Cable lengths can be max. 2,000 m and up to 512 indoor units can be controlled.



Building control systems

Toshiba air conditioners can be interlinked with all conventional building control systems. This makes air conditioning an integral part of the central control of a building.

> WHEREVER YOU ARE



On the cloud with Toshiba AC control app

Locally with standard remote control

Using Toshiba WebBrowser for all your facilities

> TRUST TOSHIBA TU2C LINK

All control devices are connected to the air conditioner side using Toshiba's dedicated central control network, also called the TU2C LINK. It can be used to directly connect all equipment.


Wiring: 2-core, non-polarity
Type: Shield wire
Size/length:
• 1 to 1.5 mm² / Up to 1,000 m
• 2 mm² / Up to 2,000 m

INDIVIDUAL REMOTE CONTROLLER


TYPE		INFRARED							WIRED			
Part number		RBC-AXU31-E	RBC-AXU41U-E	RBC-AXU31U-E	RBC-AXU31UM-E	RBC-AXU31UW-E	RBC-AXU31C-E	RBC-AX33UYP-E	RBC-ASCU11-E	RBC-AMTU31-E	RBC-AMSU51-ENES	NRG-01HE
Picture												
Dimensions (HxWxD) in mm	Remote	157x56x19	157x56x19	157x56x19	157x56x19	157x56x19	157x56x19	157x56x19	86x86x16	120x120x16	120x120x20	120x120x16
	Infrared receiver	120x70x18	204x204x24	163x163x24	163x163x24	71x162x39	130x65	140x113x12				
Compatibility		All indoor units	Smart 4 way cassette	4 way cassette	Compact 4 way cassette	2 way cassette	Ceiling, 1 way cassette (SH)	1 way cassette (YHP)	All indoor units	All indoor units	All indoor units	Air to air heat exchanger
Connectivity		1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:16	1:16	1:16	1:8
Standard functions	On/Off	•	•	•	•	•	•	•	•	•	•	•
	Mode (heat, cool, ventilation, dry, auto)	•	•	•	•	•	•	•	•	•	•	•
	Temperature setting	• / 17°C-30°C	• / 17°C-30°C	• / 17°C-30°C	• / 17°C-30°C	• / 17°C-30°C	• / 17°C-30°C	• / 17°C-30°C	• / 18°C-29°C	• / 18°C-29°C	• / 18°C-29°C	• / 18°C-29°C
	Fan speed (auto, manual 5 speed)	•	•	•	•	•	•	•	•	•	•	•
	Air direction (swing mode or manual orientation)	•	•	•	•	•	•	•	•	•	•	•
Scheduling	Timer function	•	•	•	•	•	•	•	•	•	•	•
	Schedule function								•	•	•	•
	Return back										•	•
Advanced functions	Dual set point										•	•
	Soft cooling										•	•
	Night operation										•	•
	Energy save function									•	•	•
	Frost protection									•	•	•
	Lock function										•	•
	Summer time										•	•
	Room naming										•	•
Installation & maintenance	Filter dirty indication								•	•	•	•
	Error display	•	•	•	•	•	•	•	•	•	•	•
	System settings								•	•	•	•
	Indoor unit serial number										•	•
Outputs	Error output								•	•	•	•
	External ventilation control									•	•	•
Display & Interface	Interface	Icon	Icon	Icon	Icon	Icon	Icon	Icon	Icon	Icon	Menu	Icon
	Multilanguage										•	•
	Luminous buttons										•	•
	Backlight display										•	•
Other	Temperature sensor								•	•	•	•
Communication protocol									TU2C link	TU2C link	TU2C link	TCC link

Installation drawings

Individual controls



Group controls




TOUCH SCREEN SOLUTIONS

CLOUD SOLUTION

TYPE		WIRED	
Part number		TCB-SC640U-E	BMS-SM1281ETLE - Smart Manager
Picture			
Dimensions (HxWxD) in mm		120x120x16	180x120x90
Compatibility		all systems	all systems
Connectivity		1:64	1:128
Standard functions	On/Off	•	•
	Mode (heat, cool, ventilation, dry, auto)	•	•
	Temperature setting	•	•
	Fan speed (auto, manual 5 speed)	•	•
	Air direction (swing mode or manual orientation)	•	•
Scheduling	Timer function		•
	Schedule function	•	•
	Return back		•
Advanced functions	Dual set point		•
	Soft cooling		•
	Energy save function		
	Energy monitoring		• (If power meter, BMS-IFWH5E interface relay needed)
Central control	Permit/prohibit function	•	•
	Group control	•	•
Installation & maintenance	Filter dirty indication	•	•
	Error display	•	•
	Error transfer by Email		•
	System settings	•	V
Display & Interface	Interface	Menu	Icon
	Multilanguage	•	•
	Luminous buttons	•	
	Backlight display	•	
Other	Digital Input/output		• (BMS-IFDD03E interface needed)
	Web connection		•
Communication protocol		TU2C Link	TCC Link

Drawings




Focus on Web Browser

The Smart Manager can be remotely connected via a computer and all functions can be controlled via web browser:
Standard operation - Advanced scheduling - Dual set point management - Up to 64 zones - Permit/Prohibit function - Energy saving - Return back




Focus on Data Analyzer

With or without power meter, the Data Analyzer software allows facility manager to manage system energy consumption. Through graphics on different periods, different indoor units, different energy consumption zones can be compared to optimize global efficiency. Set point, ambient temperature and outdoor temperature are monitored.



Part number		BMS-IWF0320E - Smart Device control interface	
App name		Toshiba AC control	
Picture			
Dimensions (HxWxD) in mm		140x90x45	
Compatibility		All indoor units (except hot water module, DX kit, fresh air, A2A heat exchanger)	
Connectivity		1:32	
Standard functions	On/Off	•	
	Mode (heat, cool, ventilation, dry, auto)	•	
	Temperature setting	•	
	Fan speed (auto, manual 5 speed)	•	
	Air direction (swing mode or manual orientation)	•	
Scheduling	Timer function	•	
	Schedule function	•	
	Return back	•	
Advanced functions	Energy save function	•	
	Eco temperature shift	•	
	Soft cooling	•	
	Customize room/floor/building name	•	
Central control	Permit/prohibit function	•	
	Group control	•	
Display & Interface	Interface	App	
	Multilanguage	•	
	App compatibility	Android & IOS	
	Devices compatibility	Smartphone and Phablet	
Installation & maintenance	Filter dirty indication	•	
	Error display	•	
	Error transfer by Email	•	
Users	User acces	Login & Password	
	Max user	1 admin / 32 users	
Communication protocol		TCC Link	

Drawings



Level function	Administrator	User
Air conditioner's display	•	•*1
Air conditioner's settings	•	•*1, *2
User settings	•	-
Alarm	•	-*3
Schedule	•	-
Air conditioner's various settings	•	-*4
Clock settings	• (via intranet acces only)	-
Operation mode restriction	• (via intranet acces only)	-

*1: Only the air conditioners in the "Access Area" can be displayed.
*2: If the locking setting is enabled, you cannot do any settings.
*3: The alarm settings for "Access Area" can only be displayed.
*4: The settings can only be displayed.

Toshiba AC control



Designed for commercial applications, the Toshiba AC Control App is your one-stop solution for managing up to 32 indoor units via an Android or iOS smartphone, with all main functions accessible in a single touch.




TOUCH SCREEN SOLUTIONS


Part number	Touch Screen Smart Manager	BMS-CT2560U-E	BMS-CT5121E
Picture			
Dimensions (HxWxD) in mm		205x136x90	255x323x49
Compatibility		All indoor units (except hot water module, DX kit, fresh air, A2A heat exchanger)	All indoor units. TCS-NET relay interface needed (BMS-IFLSV4E)
Connectivity		1:256	1:512
Screen	Type / Dimension	Capacitive color touch screen / 7"	Capacitive color touch screen / 12.1"
Standard functions	On/Off	•	•
	Mode (heat, cool, ventilation, dry, auto)	•	•
	Temperature setting	•	•
	Fan speed (auto, manual 5 speed)	•	•
	Air direction (swing mode or manual orientation)	•	•
Scheduling	Timer function	•	•
	Schedule function	•	•
	Return back	•	•
Advanced functions	Dual set point	•	•
	Soft cooling	•	•
	Energy save function	•	•
	Energy monitoring	•	• (If power meter,BMS-IFWH5E interface relay needed)
	Rooms naming		
Central control	Permit/prohibit function		
	Group control	•	•
Installation & maintenance	Filter dirty indication	•	•
	Error display	•	•
	Error transfer by Email	•	•
	System settings	•	•
Outputs	Digital Input/output	•	• (Digital I/O BMS-IFDD03E needed)
	Web connection	•	•
Display & Interface	Interface	Menu	Menu
	Multilanguage	•	•
	Backlight display	•	•
Communication protocol		TU2C Link	TCC Link

Installation drawings

BMS-CT2560U-E



BMS-CT5121E



ADDITIONAL PCB


Additional PCB for outdoor units

Model name	Power peak-cut control board			External master ON/OFF control board			Output control board		
									
	TCB-PCDM4E			TCB-PCMO4E			TCB-PCIN4E		
System	SMMSe/SMMSu	SHRMe	MINi SMMSe	SMMSe/SMMSu	SHRMe	MINi SMMSe	SMMSe/SMMSu	SHRMe	MINi SMMSe
Power peak cut control	•	•	•						
Power peak cut extend	•	•	•						
Snowfall fan control				•	•				
External master ON/OFF control				•	•	•			
Night operation (Sound reduction) control				•	•	•			
Operation mode selection control				•	•	•			
Error/Operation output control							•	•	•
Compressor operation output							•	•	•
Operation rate display							•	•	•
Max number installed	1	1	1	4	4	2	2	2	1
Kind of digital input / output	2/1			6/-			-/8		

Additional PCB for Indoor units

Windows switch sensor TCB-IFCB5PE

Function	Mode / Description	Dip Switch setting
Remote On/Off control application	Remote On-Off signal has full priority	All Bits OFF
	Priority is given to the remote ON signal	Bit 1 ON
	Priority is given to the remote OFF signal	Bit 2 ON
	Last touch priority	Bit 1 & 2 ON
Window switch application	With return back to previous operation	Bit 3 ON
	With no return back function	Bit 4 ON




Optional connection kit TCB-PCUC2-E

SIGNAL

OUTPUT TERMINAL TB1


Signal outputs (Mode, fans status, alarm, defrost,...) are extracted from "OUT1", "OUT2", and "OUT3".



EXTERNAL

DIGITAL INPUT TERMINAL TB2


Stop air conditioner or lock local remote by inputting signal.



EXTERNAL

ANALOG INPUT TERMINAL TB3

Change the indoor unit's operation mode (AN1), set temperature (AN2), and blower setting (AN3) by connecting a variable resistor to the analog input terminal.



Features

Part number		BMS-IFMB0TLR-E	TCB-IFMB641TLE	BMS-IFKX0TLR-E	TCB-IFLN642TLE	BMS-IFBN640TLE	TCB-IFCB640TLE
Langage		Modbus		KNX	LonWorks	Bacnet	Analogue and digital inputs
Picture							
Dimensions (HxWxD) in mm		53x86	170x200x66	92x82x33	193x246x66	90x140x45	66x170x200
Compatibility		All indoor units	All indoor units (HWM, A2A heat exchanger excluded)	All indoor units (HWM, A2A heat exchanger excluded)	All indoor units (HWM, A2A heat exchanger excluded)	All indoor units (HWM excluded)	All indoor units
Connectivity	Max number of indoor units	8	64	8	64	64	64
	Max number of outdoor units		16		16		
	Max number of gateways	63	15		10	1	
Command	On/Off	R/W	R/W	R/W	R/W	R/W	R/W
	Accumulated operation time		R/W				
	Mode (heat, cool, ventilation, dry, auto)	R/W	R/W	R/W	R/W	R/W	R/W
	Temperature setting	R/W (Dual set point supported)	R/W	R/W (Dual set point supported)	R/W	R/W	R/W
	Fan speed (auto, manual 5 speed)	R/W	R/W	R/W	R/W	R/W	R/W
	Air direction (swing mode or manual orientation)	R/W	R/W	R/W	R/W	R/W	R/W
	Soft cooling	R/W					
	Save operation	R/W					
	Filter dirty indication	R/W	R/W	R/W	R/W	R/W	
	Room temperature	R	R	R	R	R	
	Permit/Prohibit local operation	R/W	R/W	R/W	R/W	R/W	
	Temperature setting range limitation		R/W				
	Error status	R	R	R	R	R	R
	Error code	R	R	R	R		
	Error address	R		R			
	Model name		R				
	Serial number		R				
	Indoor unit capacity		R				
	Indoor unit type		R				
Protocol		Modbus RTU	Modbus RTU	EIB bus	Lontalk communication	Bacnet IP	Voltage signal
Infrastructure		RS-485	RS-485	KNX TP1	Twisted pair shield cable	LAN cable (higher than Category 5, UTP)	
Requirements (Locally supplied)			Modbus master device	KNX power unit	Lonworks control system		
			Modbus master device	ETS4 or ETS5 tool	Lonworks Network Card for PC Control		
Toshiba communication protocol		TCC Link	TCC Link	TCC Link	TCC Link	TCC Link	TCC Link


Refrigerant accessories

Model name		Specification	Picture	Total capacity codes
Compatible SMMSu	Compatible SHRM-e			
RBM-BY55E	RBM-BY55FE	Branching joint		under 6.4 HP
RBM-BY105E	RBM-BY105FE			from 6.4 to 14.2 HP
RBM-BY205E	RBM-BY205FE			from 14.2 to 25.2 HP
RBM-BY305E	RBM-BY305FE			from 25.2 to 61.2 HP
RBM-BY405E				61.2 HP or more
RBM-HY1043E	RBM-HY1043FE	Headers branching four-way		< 14.2 HP
RBM-HY2043E	RBM-HY2043FE			< 14.2 - 25.2 HP
RBM-HY1083E	RBM-HY1083FE	Headers branching eight-way		< 14.2 HP
RBM-HY2083E	RBM-HY2083FE			< 14.2 - 25.2 HP
RBM-BT14E	RBM-BT14FE	Joints for connection of outdoor units		< 26 HP system capacity
RBM-BT24E	RBM-BT24FE			> 26 < 62 HP system capacity
RBM-BT34E				> 62 HP system capacity

TECHNICAL GUIDEBOOK


SOFTWARE

SYSTEM RESTRICTION



CAUTION FOR INSTALLATION

Be careful of the connecting arrangement of the header unit and follower units. Set the outdoor units in order of capacity from the one with the largest capacity.



FREE BRANCHING SYSTEM

Line branching system	
Header branching system	
Header branching system after line branching	
Line branching system after header branching	
Header branching system after header branching	

SELECTION TOOL



Software main screen

Toshiba Selection software has been fully designed, with a user-friendly interface allowing novice and expert users alike to create simple yet detailed VRF system schematics. It is highly versatile, allowing the level of detail to be tailored to suit customer requirements. The software also allows the user to specify pricing strategy and create additional interim reports including any diagrams and schematics required. Final detailed reports can then be produced and sent to customers in PDF format or in more complex files such as AutoCAD DXF, allowing simple integration into their existing software packages.

Project fully customizable



Complete report



NOTES

This image shows a single sheet of white paper with horizontal ruling lines. The lines are evenly spaced and run across the width of the page. There are no margins, text, or other markings on the paper.