

MATH 4070 R Session 6: Stationary Processes

Whitney

Contents

Examples realizations of white noise processes	1
MA(1) processes	7
AR(1) processes	10
Random walk	12
Gaussian process	15
Different covaraince functions (kernels)	15
Generate one sample from each Gaussian Process with different kernels	16
Mean Estimation and Inference	17


Examples realizations of white noise processes

If Z_t is a *white noise* process, then its mean and variance are constants and uncorrelated in time


Note: here we do not require the sequence follow the same distribution.

```
T = 100
t <- 1:T
WN1 <- rnorm(n = T, mean = 2, sd = 2)

par(las = 1, mgp = c(2, 0.5, 0), mar = c(3.6, 3.6, 0.8, 0.6))
plot(t, WN1, type = "l", xlab = "Time", ylab = "i.i.d. N(2, 4) noise")
abline(h = 2, col = "gray")
```




```
acf(WN1)
points(0:20, c(1, rep(0, 20)), pch = 16, col = "blue")
```




```
WN2 <- rchisq(n = T, df = 2)


plot(t, WN2, type = "l", xlab = "Time", ylab = expression(paste("i.i.d. ", chi[2], " noise")))
abline(h = 2, col = "gray")
```




```
acf(WN2)
points(0:20, c(1, rep(0, 20)), pch = 16, col = "blue")
```



```
WN3 <- c(WN1, WN2)[sample(1:200)]  
plot(1:200, WN3, type = "l", xlab = "Time", ylab = expression(paste("White noise")))  
abline(h = 2, col = "gray")
```



```
acf(WN3)
points(0:23, c(1, rep(0, 23)), pch = 16, col = "blue")
```







MA(1) processes





$$\eta_t = Z_t + \theta Z_{t-1},$$

where $Z \sim \text{WN}(0, \sigma^2)$.



```
T = 100
t <- 1:T
z <- rnorm(110)
theta <- c(0.25, 1, -1, -0.25)

par(las = 1, mgp = c(2, 0.5, 0), mar = c(3.6, 3.6, 0.8, 0.6), mfrow = c(2, 1))
for (i in 1:4){
  MA1 <- filter(z, sides = 1, c(1, theta[i]))[-(1:10)]
  plot(t, MA1, type = "l", xlab = "Time", ylab = "MA(1)")
  abline(h = 0, col = "gray")
  legend("topleft", legend = theta[i], title = expression(theta),
        bty = "n")
  acf(MA1)
  points(0:20, c(1, theta[i] / (1 + theta[i]^2)), rep(0, 19)),
        pch = 16, col = "blue")
}
```





```
##another way to simulate MA(1)
MA1 <- arima.sim(n = 100, list(ma = c(0.5)))
plot(MA1)
acf(MA1)
```







AR(1) processes



$$\eta_t = \phi\eta_{t-1} + Z_t,$$

where $|\phi| < 1$ is a constant and η_s and Z_t are uncorrelated for all $s < t \Rightarrow$ future noise is uncorrelated with the current value.

```
phi <- c(0.25, 0.9, -0.5)

par(las = 1, mgp = c(2, 0.5, 0), mar = c(3.6, 3.6, 0.8, 0.6), mfrow = c(2, 1))
for (i in 1:3){
  AR1 <- arima.sim(n = 100, list(ar = c(phi[i])))
  plot(t, AR1, type = "l", xlab = "Time",
       ylab = paste("AR(1), rho = ", phi[i]))
  abline(h = 0, col = "gray")
  acf(AR1)
  points(0:20, phi[i]^(0:20), pch = 16, col = "blue")
}
```










Random walk

$$\eta_t = \sum_{s=1}^t Z_s.$$

```
par(las = 1, mgp = c(2, 0.5, 0), mar = c(3.6, 3.6, 0.8, 0.6))
for (i in 1:5){
  z <- rnorm(500)
  plot(1:500, cumsum(z), type = "l", xlab = "Time",
       ylab = "Random Walk")
  abline(h = 0, col = "gray")
}
```








Gaussian process

Different covariance functions (kernels)

```
library(fields)
# Commonly used covariance functions
cov.exp <- function(h, pars) pars[1] * exp(-h / pars[2])
cov.doubleExp <- function(h, pars) pars[1] * exp(-(h / pars[2])^2)
cov.Matern <- function(h, pars) Matern(h, phi = pars[1], range = pars[2], smoothness = pars[3])

xg <- seq(0, 5, 0.01)
c_exp <- cov.exp(xg, c(1, 0.75))
c_doubleExp <- cov.doubleExp(xg, c(1, 1))
c_Matern <- cov.Matern(xg, c(1, 0.4, 1.5))


plot(xg, c_exp, type = "l", ylab = "Covariance", xlab = "Distance in time", las = 1)
lines(xg, c_doubleExp, col = "red")
lines(xg, c_Matern, col = "blue")
legend("topright", legend = c("Exp", "Gau", "Matern 3/2"),
      col = c("black", "red", "blue"), lty = 1, bty = "n")
```



Generate one sample from each Gaussian Process with different kernels

```
Sigma_exp <- cov.exp(rdist(xg), c(1, 0.75))
Sigma_doubleExp <- cov.doubleExp(rdist(xg), c(1, 1))
Sigma_Matern <- cov.Matern(rdist(xg), c(1, 0.4, 1.5))
library(MASS)
set.seed(123)
sim_exp_1d <- mvrnorm(n = 1, rep(0, 501), Sigma_exp)
sim_doubleExp_1d <- mvrnorm(n = 1, rep(0, 501), Sigma_doubleExp)
sim_Matern_1d <- mvrnorm(n = 1, rep(0, 501), Sigma_Matern)

plot(xg, sim_exp_1d, type = "l", ylim = range(sim_exp_1d, sim_doubleExp_1d,
                                              sim_Matern_1d), ylab = "y", las = 1)
lines(xg, sim_doubleExp_1d, col = "red")
lines(xg, sim_Matern_1d, col = "blue")
legend("topleft", legend = c("Exp", "Gau", "Matern 3/2"),
      col = c("black", "red", "blue"), lty = 1, bty = "n")
```

Mean Estimation and Inference


Given a stationary process $\{\eta_t\}_{t=1}^T$, the point estimator is $\bar{\eta} = \frac{1}{T} \sum_{t=1}^T \eta_t$. The variance of this estimator is

$$\nu_T = \text{Var}(\bar{\eta}) = \text{Var}\left(\frac{1}{T} \sum_{t=1}^T \eta_t\right) = \frac{1}{T} \sum_{h=-(T-1)}^{T-1} \left(1 - \frac{|h|}{T}\right) \gamma(h)$$

```
# Monte Carlo approximation
M = 1000; T = 200; phi = 0.9
set.seed(123)
sim <- replicate(M, arima.sim(n = T, list(ar = c(phi))))
eta_bar <- apply(sim, 2, mean)
hist(eta_bar, 40, col = "lightblue", border = "gray", las = 1, prob = T, main = "")
(nu_T_hat <- var(eta_bar))
```

```
## [1] 0.4659671
```

```
# Theoretical sampling dist
mu = 0
h <- -(T-1):(T-1)
nu_T <- (1 / T) * sum((1 - (abs(h) / T)) * (phi^(abs(h)) / (1 - phi^2)))
## Superimpose the true density curve
xg <- seq(-2.5, 2.5, 0.01)
abline(v = mu, lty = 2)
lines(xg, dnorm(xg, sd = sqrt(nu_T)), col = "red")
```



```
## Compare nu_T and nu
(nu_T <- (1 / T) * sum((1 - (abs(h) / T)) * (phi^(abs(h)) / (1 - phi^2))))
```

```
## [1] 0.4763158
```

```
(nu <- (1 / T) * (1 / (1 - phi)^2))
```

```
## [1] 0.5
```