

DSA 8020 R Session 11: Time Series Analysis

Whitney

April 01, 2023

Contents


Time Series Data	1
Lake Huron Time Series	1
CO ₂ Concentration	2
U.S. monthly unemployment rates	3
Time Series Models	5
ARMA: Autocovariance Function (ACF)	5
ARMA: Partial Autocorrelation Function (PACF)	6
Lake Huron Case Study	7
Plot the time series data	7
Estimate the linear trend	8
ARMA model fitting, selection, and diagnostics	10
AR(2)	13
ARMA(2, 1)	14
Model selection using AIC	16
AR(2) Fitting and Forecasting	16

Time Series Data

Lake Huron Time Series

Annual measurements of the level of Lake Huron in feet


```
par(mar = c(3.2, 3.2, 0.5, 0.5), mgp = c(2, 0.5, 0), bty = "L")
data(LakeHuron)
plot(LakeHuron, ylab = "Depth in feet", xlab = "Year", las = 1)
points(LakeHuron, pch = 16, col = "blue")
grid()
```




CO₂ Concentration

Atmospheric concentrations of CO₂ are expressed in parts per million (ppm) and reported in the preliminary 1997 SIO manometric mole fraction scale.

```
data(co2)
par(mar = c(3.8, 4, 0.8, 0.6))
plot(co2, las = 1, xlab = "", ylab = "")
points(co2, pch = 16, col = "blue", cex = 0.5)
mtext("Time (year)", side = 1, line = 2)
mtext(expression(paste("CO"[2], " Concentration (ppm)")), side = 2, line = 2.5)
grid()
```



```
# Seasonal and Trend decomposition using Loess (STL)
par(mar = c(4, 3.6, 0.8, 0.6))
stl <- stl(co2, s.window = "periodic")
plot(stl, las = 1)
```



U.S. monthly unemployment rates

```
library(quantmod)
getSymbols("UNRATE", src = "FRED")
```


```
## [1] "UNRATE"
```

```
head(UNRATE); tail(UNRATE)
```

```
##          UNRATE
## 1948-01-01    3.4
## 1948-02-01    3.8
## 1948-03-01    4.0
## 1948-04-01    3.9
## 1948-05-01    3.5
## 1948-06-01    3.6
```

```
##          UNRATE
## 2022-09-01    3.5
## 2022-10-01    3.7
## 2022-11-01    3.6
## 2022-12-01    3.5
## 2023-01-01    3.4
## 2023-02-01    3.6
```


```
chartSeries(UNRATE)
```



Time Series Models


ARMA: Autocovariance Function (ACF)

```
set.seed(123)
n = 200
WN <- rnorm(n)
par(mfrow = c(4, 2), mar = c(3.6, 3.6, 1.2, 0.6))
plot(1:n, WN, type = "l", las = 1, xlab = "", ylab = "")
mtext("WN")
acf(WN, xlab = "", ylab = "", main = "", las = 1)
mtext("ACF")
# AR(1) phi = 0.8
set.seed(123)
AR <- arima.sim(n = n, model = list(ar = 0.8))
plot(1:n, AR, type = "l", las = 1, xlab = "", ylab = "")
mtext("AR(1)")
acf(AR, xlab = "", ylab = "", main = "", las = 1)
# MA(1) theta = 0.5
set.seed(123)
MA <- arima.sim(n = n, model = list(ma = 0.5))
plot(1:n, MA, type = "l", las = 1, xlab = "", ylab = "")
mtext("MA(1)")
acf(MA, xlab = "", ylab = "", main = "", las = 1)
# ARMA(1, 1) phi = 0.8, theta = 0.5
set.seed(123)
ARMA <- arima.sim(n = n, model = list(ar = 0.8, ma = 0.5))
plot(1:n, ARMA, type = "l", las = 1, xlab = "", ylab = "")
mtext("ARMA(1,1)")
mtext("Time", side = 1, line = 2)
acf(ARMA, xlab = "", ylab = "", main = "", las = 1)
mtext("Lag", side = 1, line = 2)
```



ARMA: Partial Autocorrelation Function (PACF)


```
par(mfrow = c(4, 2), mar = c(3.6, 3.6, 1.2, 0.6))
plot(1:n, WN, type = "l", las = 1, xlab = "", ylab = "")
mtext("WN")
pacf(WN, xlab = "", ylab = "", main = "", las = 1)
mtext("PACF")
# AR(1) phi = 0.8
set.seed(123)
AR <- arima.sim(n = n, model = list(ar = 0.8))
plot(1:n, AR, type = "l", las = 1, xlab = "", ylab = "")
mtext("AR(1)")
pacf(AR, xlab = "", ylab = "", main = "", las = 1)
# MA(1) theta = 0.5
set.seed(123)
MA <- arima.sim(n = n, model = list(ma = 0.5))
plot(1:n, MA, type = "l", las = 1, xlab = "", ylab = "")
mtext("MA(1)")
pacf(MA, xlab = "", ylab = "", main = "", las = 1)
# ARMA(1, 1) phi = 0.8, theta = 0.5
set.seed(123)
ARMA <- arima.sim(n = n, model = list(ar = 0.8, ma = 0.5))
plot(1:n, ARMA, type = "l", las = 1, xlab = "", ylab = "")
mtext("ARMA(1,1)")
mtext("Time", side = 1, line = 2)
pacf(ARMA, xlab = "", ylab = "", main = "", las = 1)
mtext("Lag", side = 1, line = 2)
```



Lake Huron Case Study

Plot the time series data



```
## Let us create a 'years' variable.
years <- time(LakeHuron)
## Plot time series
plot(LakeHuron, ylab = "Depth (ft)", xlab = "Year", las = 1)
points(LakeHuron, col = "blue", pch = 16, cex = 0.8)
grid()
```



Calcu-

late ACF and PACF

```
par(mfrow = c(2, 1), mar = c(4, 4, 1, 1), las = 1)
acf(LakeHuron, xlab="Lag in years", ylab = "sample ACF", main = "")
pacf(LakeHuron, xlab="Lag in years", ylab = "sample PACF", main = "")
```



Estimate the linear trend


```
lm <- lm(LakeHuron ~ years)
par(mfrow = c(2, 1), mar = c(3.5, 3.5, 1, 0.6))
```



```

plot(LakeHuron, ylab = "", xlab = "", las = 1); grid()
abline(lm, col = "blue", lty = 2)
mtext("Depth (ft)", 2, line = 2.4)
deTrend <- resid(lm)
plot(1875:1972, deTrend, type = "l", ylab = "", xlab = "", las = 1); grid()
abline(h = 0, col = "blue", lty = 2)
mtext("Year", 1, line = 2)
mtext("Depth (ft)", 2, line = 2.4)

```





##

Recompute ACF and PACF for the detrended time series

```

par(mfrow = c(1, 2), mar = c(4, 4, 1, 1), las = 1)
acf(deTrend, xlab = "Lag in years", ylab = "sample ACF", main = "")
pacf(deTrend, xlab = "Lag in years", ylab = "sample PACF", main = "")



```



Histogram and QQ plot

```
hist(deTrend, 15, main = "", xlab = "", las = 1)
```

```
qqnorm(deTrend, main = "", pch = 16, cex = 0.8); qqline(deTrend, col = "blue")
```




ARMA model fitting, selection, and diagnostics

```
(ar1.model <- arima(deTrend, order = c(1, 0, 0)))
```



AR(1)

```
##  
## Call:  
## arima(x = deTrend, order = c(1, 0, 0))  
##  
## Coefficients:  
##          ar1  intercept  
##      0.7829    0.0797  
## s.e. 0.0634    0.3178  
##  
## sigma^2 estimated as 0.4972:  log likelihood = -105.29,  aic = 216.58
```

```
ar1.resids <- resid(ar1.model)  
plot(1875:1972, ar1.resids, type = "l", xlab = "year", ylab = "AR1 residuals")
```




```
## Sample ACF and PACF of the residuals  
par(mfrow = c(1, 2))  
acf(ar1.resids, ylab = "sample ACF", xlab = "lag (year)")  
pacf(ar1.resids, ylab = "sample PACF", xlab = "lag (year)")
```



```
## Normal Q-Q plot for the residuals
qqnorm(ar1.resids, main = ""); qqline(ar1.resids, col = "blue")
## Test for time dependence for the residuals
Box.test(ar1.resids, type = "Ljung-Box")
```

```
##
## Box-Ljung test
##
## data: ar1.resids
## X-squared = 4.93, df = 1, p-value = 0.02639
```




```
(ar2.model <- arima(deTrend, order = c(2, 0, 0)))
```

AR(2)

```
##
## Call:
## arima(x = deTrend, order = c(2, 0, 0))
##
## Coefficients:
##          ar1          ar2  intercept
##          1.0047      -0.2919       0.0196
## s.e.  0.0977      0.1004       0.2351
##
## sigma^2 estimated as 0.4571:  log likelihood = -101.25,  aic = 210.5
```


```
## calculate the residuals
ar2.resids <- resid(ar2.model)
## Sample ACF and PACF of the residuals
par(mfrow = c(1, 2))
acf(ar2.resids, ylab = "sample ACF", xlab = "lag (year)")
pacf(ar2.resids, ylab = "sample PACF", xlab = "lag (year)")
```



```
## Test for time dependence for the residuals
Box.test(ar2.resids, type = "Ljung-Box")
```

```
##
## Box-Ljung test
##
## data:  ar2.resids
## X-squared = 0.029966, df = 1, p-value = 0.8626
```

```
## Normal Q-Q plot for the residuals
qqnorm(ar2.resids, main = ""); qqline(ar2.resids, col = "blue")
```




```
(arma21.model <- arima(deTrend, order = c(2, 0, 1)))
```

ARMA(2, 1)


```
##
## Call:
## arima(x = deTrend, order = c(2, 0, 1))
##
## Coefficients:
##      ar1      ar2      ma1  intercept
##    0.8374 -0.1622  0.1846    0.0245
## s.e.  0.3180   0.2621  0.3180    0.2452
##
## sigma^2 estimated as 0.4556:  log likelihood = -101.09,  aic = 212.18
```

```
## calculate the residuals
arma21.resids <- resid(arma21.model)
## Sample ACF and PACF of the residuals
par(mfrow=c(1,2))
acf(arma21.resids, ylab = "sample ACF", xlab = "lag (year)")
pacf(arma21.resids, ylab = "sample PACF", xlab = "lag (year)")
```

Series arma21.resids




Series arma21.resids



```
## Normal Q-Q plot for the residuals
qqnorm(arma21.resids, main = ""); qqline(arma21.resids, col = "blue")
## Test
Box.test(arma21.resids, type = "Ljung-Box")
```

```
##
## Box-Ljung test
##
## data: arma21.resids
## X-squared = 5.5105e-05, df = 1, p-value = 0.9941
```



```
AIC(ar1.model); AIC(ar2.model); AIC(arma21.model)
```

Model selection using AIC

```
## [1] 216.5835
```

```
## [1] 210.5032
```


```
## [1] 212.1784
```

AR(2) Fitting and Forecasting

```
library(forecast)
(fit <- Arima(LakeHuron, order = c(2, 0, 0), include.drift = T))
```

```
## Series: LakeHuron
## ARIMA(2,0,0) with drift
##
## Coefficients:
##          ar1      ar2 intercept    drift
##          1.0048 -0.2913  580.0915 -0.0216
## s.e.  0.0976   0.1004    0.4636  0.0081
##
## sigma^2 = 0.476: log likelihood = -101.2
## AIC=212.4   AICc=213.05   BIC=225.32
```

```
par(mfrow = c(2, 2), mar = c(4.1, 4, 1, 0.8), las = 1)
res <- fit$residuals
plot(res, type = "l", xlab = "year", ylab = "AR(2) residuals", las = 1)
abline(h = 0, col = "blue")
qqnorm(res, main = ""); qqline(res, col = "blue")
acf(res, ylab = "sample ACF", xlab = "lag (year)")
pacf(res, ylab = "sample PACF", xlab = "lag (year)")
```

```
# 10-year-ahead forecasts
autoplot(forecast(fit, h = 10, level = c(50, 95)))
```

