

MATH 8090: Autoregressive Integrated Moving Average (ARIMA) Models and Seasonal ARIMA Models

Whitney Huang, Clemson University

10/7-10/9/2025

Contents


ARIMA	1
Monthly Price of Oil: January 1986–January 2006	1
An explosive AR model	2
Seasonal Autoregressive Integrated Moving Average (SARIMA)	4
Stochastic and Deterministic Trends	4
SARIMA Simulation	5
Simulating a Seasonal AR Model	6
Simulating a Seasonal MA Model	7
Simulating a SARIMA Model	8
Monthly International Airline Passenger Data	9
Read the data	9
Plot the time series	10
Plot sample ACF/PACF	11
Trying Different Orders of Differencing	12
Plot ACF and PACF	12
Show the ACF and PACF for the $d = 1, D = 0$ case.	14
A useful function for the model diagnostics (courtesy of Peter Craigmile)	14
Fitting the SARIMA(1, 1, 0) \times (1, 0, 0) model	15
Fitting the SARIMA(0, 1, 0) \times (1, 0, 0) model	16
Forecasting 1971 Data	17
Evaluating Forecast Performance	20

ARIMA

Monthly Price of Oil: January 1986–January 2006

```
library(TSA)
data(oil.price)

par(las = 1, mgp = c(2, 1, 0), mar = c(3.5, 3.5, 0.8, 0.6))
plot(oil.price, ylab = 'Price per Barrel', type = 'l')
points(oil.price, pch = 16, cex = 0.5)
grid()
```




A stationary model does not seem to be reasonable. However, it is also not clear which (deterministic) trend model is appropriate

An explosive AR model


$$\eta_t = 1.1\eta_{t-1} + Z_t$$

```
n <- 50; phi <- 1.1
set.seed(128)
z <- rnorm(n)
eta <- c()
eta[1] <- z[1]
for (i in 2:n) eta[i] <- phi * eta[i - 1] + z[i]
plot(1:n, eta, las = 1, type = "l")
grid()
```



```
acf(eta)
```

Series eta



Seasonal Autoregressive Integrated Moving Average (SARIMA)

Stochastic and Deterministic Trends


```
library(astsa)
set.seed(1234)
n = 200
t <- 1:n
sim1 <- arima.sim(list(order = c(1, 1, 0), ar = 0.6), n = n)[-1]

par(las = 1, mar = c(3.5, 3.5, 1, 0.5))
tsplot(sim1)
# Fit a deterministic trend
library(mgcv)
```

```
## Loading required package: nlme
```

```
## This is mgcv 1.9-1. For overview type 'help("mgcv-package")'.
```

```
dFit <- gam(sim1 ~ s(t, k = 10))
lines(t, predict(dFit), col = "red")
# Fit a stochastic trend
sFit <- arima(sim1, order = c(1, 1, 0))
lines(t, sFit$residuals + sim1, col = "blue")
legend("top", legend = c("Deterministic", "Stochastic"),
      col = c("red", "blue"), lty = 1, bty = "n")
```



SARIMA Simulation


```
n = 120
t <- 1:n
# Deterministic seasonality
season_d <- 2 * cos(2 * pi * (t / 12)) + 1 * cos(2 * pi * (t / 6)) + 0.5 * cos(2 * pi * (t / 3))
set.seed(123)
y1 = season_d + rnorm(n, sd = 0.5)
# Convert to a time series with monthly frequency
y1 <- ts(y1, frequency = 12, start = 1)

par(las = 1, mfrow = c(2, 2))
tsplot(y1)
library(forecast)
(sarma_model <- Arima(y1, order = c(1, 0, 1), seasonal = c(1, 0, 0)))
```

```
## Series: y1
## ARIMA(1,0,1)(1,0,0)[12] with non-zero mean
##
## Coefficients:
##          ar1      ma1      sar1      mean
##      -0.8183  1.0000  0.9135  0.0027
## s.e.    0.0554  0.0124  0.0289  0.4161
##
## sigma^2 = 0.4135: log likelihood = -125.5
## AIC=261   AICc=261.53   BIC=274.94
```


```
set.seed(12)
# Stochastic seasonality
m <- list(order = c(1, 0, 1),
          seasonal = list(order = c(1, 0, 0), period = 12),
          ar = c(0.8), ma = c(0.95), sar = c(0.9))
# Simulate the SARIMA model
y2 <- arima.sim(model = m, n = n, sd = 0.75)
# Convert to a time series with monthly frequency
y2 <- ts(y2, frequency = 12, start = 1)
tsplot(y2)

acf(y1, lag.max = 4)
acf(y2, lag.max = 4)
```




Simulating a Seasonal AR Model

```
n = 120; Phi = 0.9
set.seed(1234)
sAR = sarima.sim(sar = Phi, S = 12, n = n)
sAR <- ts(sAR, frequency = 1, start = 1)
par(las = 1, mar = c(3.5, 3.5, 1, 0.5), mgp = c(2.5, 1, 0), mfrow = c(3, 1))
tsplot(sAR, xlab = "Time")
stats::acf(sAR, lag.max = 48, ylim = c(-0.5, 1))
trueACF <- ARMAacf(ar = c(rep(0, 11), Phi), lag.max = 48)
points(1:48, trueACF[2:49], col = "red")
abline(v = 12 * (1:4), col = "pink", lty = 2)
stats::pacf(sAR, lag.max = 48, ylim = c(-0.5, 1))
truePACF <- ARMAacf(ar = c(rep(0, 11), Phi), lag.max = 48, pacf = T)
points(1:48, truePACF, col = "red")
abline(v = 12, col = "pink", lty = 2)
```




Simulating a Seasonal MA Model

```
n = 100; Theta = 0.75
set.seed(1234)
sMA = sarima.sim(sma = Theta, S = 4, n = n)
sMA <- ts(sMA, frequency = 1, start = 1)
par(las = 1, mar = c(3.5, 3.5, 1, 0.5), mgp = c(2.5, 1, 0), mfrow = c(3, 1))
tsplot(sMA, xlab = "Time")
stats::acf(sMA, lag.max = 20, ylim = c(-0.5, 1))
trueACF <- ARMAacf(ma = c(rep(0, 3), Theta), lag.max = 20)
points(1:20, trueACF[2:21], col = "red")
abline(v = 4, col = "pink", lty = 2)
stats::pacf(sMA, lag.max = 20, ylim = c(-0.5, 1))
truePACF <- ARMAacf(ma = c(rep(0, 3), Theta), lag.max = 20, pacf = T)
points(1:20, truePACF, col = "red")
abline(v = 4 * (1:5), col = "pink", lty = 2)
```



Simulating a SARIMA Model


```
par(las = 1, mar = c(3.5, 3.5, 1, 0.5), mgp = c(2.5, 1, 0), mfrow = c(3, 1))
set.seed(123)
sarima <- sarima.sim(d = 1, ar = -.25, sar = .9, D = 1, sma = 0.75, S = 12, n = 200)
sarima <- ts(sarima, frequency = 1, start = 1)
tsplot(sarima, ylab = "")
acf(sarima, lag.max = 60)
pacf(sarima, lag.max = 60)
```

Monthly International Airline Passenger Data



Read the data

```
library(TSA)
data(airpass)
plot(airpass)
```




Plot the time series

```
par(bty = "L", mar = c(3.6, 3.5, 0.8, 0.6), mgp = c(2.4, 1, 0), las = 1, mfrow = c(2, 1))  
## plot the time series.  
plot(airpass, xlab = "Year", ylab = "Monthly total (1000s)")  
grid()  
## take a log (to the base 10) of the air passenger data.  
log.airpass <- log10(airpass)  
plot(log.airpass, type = "l", xlab = "Year", ylab = "log10(monthly total)")  
grid()
```



Plot sample ACF/PACF

```
yr <- time(airpass)
log.shortair <- log.airpass[1:132]
shortyears <- yr[1:132]
par(bty = "L", mar = c(3.6, 3.5, 0.8, 0.6), mgp = c(2.4, 1, 0), las = 1, mfrow = c(1, 2))
acf(log.shortair, ylab = "sample ACF", main = "", lag.max = 48, xaxt = "n")
abline(v = 12 * (1:4), col = "pink", lty = 2)
axis(side = 1, at = seq(0, 48, 12))
pacf(log.shortair, ylab = "sample PACF", main = "", lag.max = 48, xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))
```



Trying Different Orders of Differencing

```
## take the differences  $Y_t = (1-B) X_t$ 
diff.1.0 <- diff(log.shortair)
## take the seasonal differences  $Y_t = (1-B^{(12)}) X_t$ 
diff.0.1 <- diff(log.shortair, lag = 12, diff = 1)
## take the differences  $Y_t = (1-B^{(12)}) (1-B) X_t$ 
diff.1.1 <- diff(diff(log.shortair, lag = 12, diff = 1))
```

Plot ACF and PACF

```
par(bty = "L", mar = c(3.6, 3.5, 1, 0.6), mgp = c(2.4, 1, 0), las = 1)
layout.matrix <- matrix(c(1, 1, 2, 3, 4, 4, 5, 6, 7, 7, 8, 9), nrow = 3, ncol = 4, byrow = T)
layout(mat = layout.matrix)
plot(shortyears[-1], diff.1.0, xlab = "", ylab = "d=1, D=0",
     type = "l", ylim = c(-0.1, 0.1), xlim = range(shortyears))

stats::acf(diff.1.0, lag.max = 48, ylab = "", xlab = "", main = "", ylim = c(-0.6, 1), xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))
mtext("Sample ACF", side = 3, line = 0, cex = 0.8)

stats::pacf(diff.1.0, lag.max = 48, ylab = "", xlab = "", main = "", ylim = c(-0.6, 1), xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))
```

```

mtext("Sample PACF", side = 3, line = 0, cex = 0.8)

plot(shortyears[-c(1:12)], diff.0.1, xlab = "", ylab = "d=0, D=1",
     type = "l", ylim = c(-0.1, 0.1), xlim = range(shortyears))

stats::acf(diff.0.1, lag.max = 48, ylab = "", xlab = "", main = "", ylim = c(-0.6, 1), xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))


stats::pacf(diff.0.1, lag.max = 48, ylab = "", xlab = "", main = "", ylim = c(-0.6, 1), xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))

plot(shortyears[-c(1:13)], diff.1.1, xlab = "", ylab = "d=1, D=1",
     type = "l", ylim = c(-0.1, 0.1), xlim = range(shortyears))
mtext("Year", side = 1, line = 1.8, cex = 0.8)

stats::acf(diff.1.1, lag.max = 48, ylab = "", xlab = "", main = "", ylim = c(-0.6, 1), xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))
mtext("lag", side = 1, line = 1.8, cex = 0.8)

stats::pacf(diff.1.1, lag.max = 48, ylab = "", xlab = "", main = "", ylim = c(-0.6, 1), xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))
mtext("lag", side = 1, line = 1.8, cex = 0.8)


```



Show the ACF and PACF for the $d = 1, D = 0$ case.

```
par(mfrow = c(1, 2), cex = 0.8, bty = "L", mar = c(3.6, 3, 1, 0.6), mgp = c(2.4, 1, 0), las = 1)
stats::acf(diff.1.0, lag.max = 48, ylab = "", xlab = "", main = "", ylim = c(-0.6, 1), xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))
mtext("Sample ACF", side = 3, cex = 0.8)

stats::pacf(diff.1.0, lag.max = 48, ylab = "", xlab = "", main = "", ylim = c(-0.6, 1), xaxt = "n")
axis(side = 1, at = seq(0, 48, 12))
mtext("Sample PACF", side = 3, cex = 0.8)
```



A useful function for the model diagnostics (courtesy of Peter Craigmire)

```
plot.residuals <- function(x, y = NULL, lag.max = NULL, mean.line = TRUE,
                           acf.ylim = c(-0.25, 1), mfrow = c(2, 2),
                           lags = NULL, ...){
  if (!is.null(mfrow))
    par(mfrow = mfrow)
  if (is.null(y)){
    y <- x
    x <- seq(length(y))
  } else {
    x <- as.numeric(x)
    y <- as.numeric(y)
  }
  if (lag.max == NULL)
    lag.max <- length(x)
  acf <- acf(y, lag.max = lag.max, main = "", ylab = "", xlab = "",
             ylim = acf.ylim, xaxt = "n", yaxp = 1, bty = "n",
             las = 1, cex = 0.8, mar = c(3.6, 3, 1, 0.6), mgp = c(2.4, 1, 0))
  pacf <- pacf(y, lag.max = lag.max, main = "", ylab = "", xlab = "",
              ylim = acf.ylim, xaxt = "n", yaxp = 1, bty = "n",
              las = 1, cex = 0.8, mar = c(3.6, 3, 1, 0.6), mgp = c(2.4, 1, 0))
  if (mean.line)
    lines(x, y, lty = 1, col = "black", lwd = 1)
  if (lags)
    lines(x, lags, lty = 1, col = "black", lwd = 1)
  plot(x, y, lty = 1, col = "black", lwd = 1, yaxp = 1, bty = "n",
       las = 1, cex = 0.8, mar = c(3.6, 3, 1, 0.6), mgp = c(2.4, 1, 0))
  plot(x, pacf, lty = 1, col = "black", lwd = 1, yaxp = 1, bty = "n",
       las = 1, cex = 0.8, mar = c(3.6, 3, 1, 0.6), mgp = c(2.4, 1, 0))
  if (lags)
    lines(x, lags, lty = 1, col = "black", lwd = 1)
```

```

}

if (is.null(lag.max)) {
  lag.max <- floor(10 * log10(length(x)))
}
plot(x, y, type = "l", ...)
if (mean.line) abline(h = 0, lty = 2)
qqnorm(y, main = "", las = 1); qqline(y)
if (is.null(lags)) {
  stats::acf(y, main = "", lag.max = lag.max, xlim = c(0, lag.max), ylim = acf.ylim,
    ylab = "sample ACF", las = 1)

  stats::pacf(y, main = "", lag.max = lag.max, xlim = c(0, lag.max), ylim = acf.ylim,
    ylab = "sample PACF", las = 1)
}
else {
  stats::acf(y, main = "", lag.max = lag.max, xlim = c(0, lag.max), ylim = acf.ylim,
    ylab = "sample ACF", xaxt = "n", las = 1)
  axis(side = 1, at = lags)

  stats::pacf(y, main = "", lag.max = lag.max, xlim = c(0, lag.max), ylim = acf.ylim,
    ylab = "sample PACF", xaxt = "n", las = 1)
  axis(side = 1, at = lags)
}
Box.test(y, lag.max, type = "Ljung-Box")
}

```

Fitting the SARIMA(1,1,0) × (1,0,0) model

```

(fit1 <- arima(diff.1.0, order = c(1, 0, 0), seasonal = list(order = c(1, 0, 0), period = 12)))


##
## Call:
## arima(x = diff.1.0, order = c(1, 0, 0), seasonal = list(order = c(1, 0, 0),
##   period = 12))
##
## Coefficients:
##      ar1      sar1  intercept
##    -0.2667  0.9291    0.0039
## s.e.    0.0865  0.0235    0.0096
##
## sigma^2 estimated as 0.0003298:  log likelihood = 327.27,  aic = -648.54

Box.test(fit1$residuals, lag = 48, type = "Ljung-Box")

##
## Box-Ljung test
##
## data:  fit1$residuals
## X-squared = 55.372, df = 48, p-value = 0.2164

```

```
par(mfrow = c(2, 2), cex = 0.8, bty = "L", mar = c(3.6, 4, 0.8, 0.6),
    mgp = c(2.8, 1, 0), las = 1)
plot.residuals(shortyears[-1], resid(fit1), lag.max = 48,
               ylab = "SARIMA residuals", xlab = "Year", lags = seq(0, 48, 12))
```



```
##
## Box-Ljung test
##
## data: y
## X-squared = 55.372, df = 48, p-value = 0.2164
```

Fitting the SARIMA(0,1,0) × (1,0,0) model

```
(fit2 <- arima(diff.1.0, seasonal = list(order = c(1, 0, 0), period = 12)))
```

```
##
## Call:
## arima(x = diff.1.0, seasonal = list(order = c(1, 0, 0), period = 12))
##
## Coefficients:
##          sar1  intercept
##          0.9081    0.0040
## s.e.  0.0278    0.0108
```







```
##
## sigma^2 estimated as 0.0003616: log likelihood = 322.75, aic = -641.51
```

```
Box.test(fit2$residuals, lag = 48, type = "Ljung-Box")
```

```
##
## Box-Ljung test
##
## data: fit2$residuals
## X-squared = 80.641, df = 48, p-value = 0.002209
```

```
par(mfrow = c(2, 2), cex = 0.8, bty = "L", mar = c(3.6, 4, 0.8, 0.6),
    mgp = c(2.8, 1, 0), las = 1)
plot.residuals(shortyears[-1], resid(fit2), lag.max = 48,
               ylab = "SARIMA residuals", xlab = "Year", lags = seq(0, 48, 12))
```



```
##
## Box-Ljung test
##
## data: y
## X-squared = 80.641, df = 48, p-value = 0.002209
```

Forecasting 1971 Data

Fit the SARIMA(1,1,0) × (1,0,0) Model

```
(fit1 <- arima(log.shortair, order = c(1, 1, 0),
              seasonal = list(order = c(1, 0, 0), period = 12)))
```

```
##
## Call:
## arima(x = log.shortair, order = c(1, 1, 0), seasonal = list(order = c(1, 0,
##      0), period = 12))
##
## Coefficients:
##          ar1      sar1
##      -0.2665  0.9298
## s.e.   0.0866  0.0233
##
## sigma^2 estimated as 0.0003299:  log likelihood = 327.19,  aic = -650.38
```

Fit the SARIMA(0,1,0) \times (1,0,0) Model

```
(fit2 <- arima(log.shortair, order = c(0, 1, 0),
              seasonal = list(order = c(1, 0, 0), period = 12)))
```

```
##
## Call:
## arima(x = log.shortair, order = c(0, 1, 0), seasonal = list(order = c(1, 0,
##      0), period = 12))
##
## Coefficients:
##          sar1
##      0.9088
## s.e.  0.0276
##
## sigma^2 estimated as 0.0003617:  log likelihood = 322.69,  aic = -643.38
```

```
AIC.to.AICC <- function(aic, n, npars){ aic - 2 * npars * (1 - n / (n - 1 - npars)) }
```

Define the forecasting time points

```
fyears <- yr[133:144]
```

Calculate the predictions and prediction intervals for both models

```
preds1 <- predict(fit1, 12)
forecast1 <- preds1$pred
flimits1 <- qnorm(0.975) * preds1$se

preds2 <- predict(fit2, 12)
forecast2 <- preds2$pred
flimits2 <- qnorm(0.975) * preds2$se
```

```





par(mfrow = c(2, 2), cex = 0.8, bty = "L", mar = c(3.6, 4, 1, 0.6),
    mgp = c(2.4, 1, 0), las = 1)
plot(shortyears, log.shortair, type = "l", xlab = "Year",
     ylab = "log10(passenger numbers)", xlim = range(yr), ylim = c(2, 2.9))
mtext("SARIMA(1,1,0) x (1,0,0)")
## plots the forecasts
lines(fyears, forecast1, lwd = 2, col = "blue")
## plot the 95% prediction intervals.
lines(fyears, forecast1 + flimits1, col = "blue")
lines(fyears, forecast1 - flimits1, col = "blue")

plot(shortyears, log.shortair, type = "l", xlab = "Year",
     ylab = "log10(passenger numbers)", xlim = range(yr), ylim = c(2, 2.9))
mtext("SARIMA(0,1,0) x (1,0,0)")
## plots the forecasts
lines(fyears, forecast2, lwd = 2, col = "red")
## plot the 95% prediction intervals.
lines(fyears, forecast2 + flimits2, col = "red")
lines(fyears, forecast2 - flimits2, col = "red")

plot(shortyears, 10^log.shortair, type = "l", xlab = "Year",
     ylab="1000s of airline passengers", xlim = range(yr), ylim = c(100, 800))
lines(fyears, 10^forecast1, lwd = 2, col = "blue")
lines(fyears, 10^(forecast1 + flimits1), col = "blue")
lines(fyears, 10^(forecast1 - flimits1), col = "blue")

plot(shortyears, 10^log.shortair, type = "l", xlab = "Year",
     ylab="1000s of airline passengers", xlim = range(yr), ylim = c(100, 800))
lines(fyears, 10^forecast2, lwd = 2, col = "red")
lines(fyears, 10^(forecast2 + flimits2), col = "red")
lines(fyears, 10^(forecast2 - flimits2), col = "red")

```



Evaluating Forecast Performance

Root mean square error (RMSE)

```
sqrt(mean((10^forecast1 - 10^log.airpass[133:144])^2))
```

```
## [1] 30.36384
```

```
sqrt(mean((10^forecast2 - 10^log.airpass[133:144])^2))
```

```
## [1] 31.32376
```

Mean relative prediction error

```
mean((10^forecast1 - 10^log.airpass[133:144]) / 10^log.airpass[133:144])
```

```
## [1] 0.05671086
```

```
mean((10^forecast2 - 10^log.airpass[133:144]) / 10^log.airpass[133:144])
```

```
## [1] 0.05951677
```

Empirical coverage rate

```

CI_fit1 <- cbind(as.numeric(10^(forecast1 + flimits1)),
                 as.numeric(10^(forecast1 - flimits1)))
out <- CI_fit1 - 10^log.airpass[133:144]
hits <- apply(out, 1, function(x) prod(x) < 0)

sum(hits) / length(10^log.airpass[133:144])

```

```
## [1] 0.9166667
```

```

CI_fit2 <- cbind(as.numeric(10^(forecast2 + flimits2)),
                 as.numeric(10^(forecast2 - flimits2)))
out <- CI_fit2 - 10^log.airpass[133:144]
hits <- apply(out, 1, function(x) prod(x) < 0)

sum(hits) / length(10^log.airpass[133:144])

```

```
## [1] 1
```