

DSA 8020 R Session 13: Spatial Interpolation I

Whitney

April 01, 2023

Contents

Toy Examples	1
Create spatial locations	1
Case 1: No spatial pattern	1
Case 2: A smooth spatial image	3
Using Variogram Cloud and (Binned) Variogram to Examine the Spatial Dependence	3
Gaussian Processes: Covariance functions and their realizations	4
Simulate 1D realizations	4
Simulate 2D realizations	6
Spatial interpolation	7
Predicting one location	7
Predicting multiple locations	8

Toy Examples

Create spatial locations

```
N = 30
xg <- yg <- seq(0, 1, length = N)
locs <- expand.grid(xg, yg)
```

Case 1: No spatial pattern

```
par(mar = c(2, 2, 1, 0.6), mgp = c(2.4, 1, 0), las = 1)
set.seed(123)
y1 <- array(rnorm(n = N^2), dim = c(N, N))
y1[N / 2, N / 2] <- NA
which(is.na(y1) == 1)
```

```
## [1] 435
```

```
library(fields)
```

```
## Loading required package: spam
```

```
## Spam version 2.8-0 (2022-01-05) is loaded.
```

```
## Type 'help( Spam)' or 'demo( spam)' for a short introduction  
## and overview of this package.
```

```
## Help for individual functions is also obtained by adding the  
## suffix '.spam' to the function name, e.g. 'help( chol.spam)'.
```

```
##
```

```
## Attaching package: 'spam'
```

```
## The following objects are masked from 'package:base':
```

```
##
```

```
##      backsolve, forwardsolve
```


```
## Loading required package: viridis
```

```
## Loading required package: viridisLite
```

```
##
```

```
## Try help(fields) to get started.
```

```
image.plot(xg, yg, y1, xlab = "", ylab = "", xaxt = "n", yaxt = "n")  
text(xg[N / 2], yg[N / 2], "?")
```




Case 2: A smooth spatial image

```
library(MASS)
cov.Matern <- function(h, pars) Matern(h, phi = pars[1], range = pars[2], smoothness = pars[3])
dist <- rdist(locs)
Sigma_Matern <- cov.Matern(dist, c(1, 0.1, 1.5))
set.seed(123)
y2 <- array(mvrnorm(n = 1, rep(0, N^2), Sigma_Matern), dim = c(N, N))
y2[N / 2, N / 2] <- NA
which(is.na(y2) == 1)
```

```
## [1] 435
```

```
image.plot(xg, yg, y2, xlab = "", ylab = "", xaxt = "n", yaxt = "n")
text(xg[N / 2], yg[N / 2], "?")
```



Using Variogram Cloud and (Binned) Variogram to Examine the Spatial Dependence

```
gamma1 <- array(dim = c(N^2, N^2))
system.time(for (i in 1:N^2){
  for (j in 1:N^2){
    gamma1[i, j] <- (c(y1)[i] - c(y1)[j])^2
  }
})
system.time(gamma1 <- outer(c(y1), c(y1), FUN = "-")^2)
gamma2 <- outer(c(y2), c(y2), FUN = "-")^2

par(mfrow = c(2, 2), mar = c(3.6, 3.6, 1, 0.6),
```

```

    mgp = c(2.4, 1, 0), las = 1)
plot(dist, gamma1, cex = 0.2, xlab = "Distance", ylab = expression(gamma))
abline(h = 2 * 1, col = "blue")
mtext("Variogram Cloud")

plot(dist, gamma2, cex = 0.2, xlab = "Distance", ylab = expression(gamma))
dgrid <- seq(0, sqrt(2), 0.001)
lines(dgrid, 2 * (1 - cov.Matern(dgrid, c(1, 0.1, 1.5))),
      col = "blue")
mtext("Variogram Cloud")

vargram1 <- vgram(locs, c(y1), N = 30)
plot(vargram1, ylim = c(0, 1.3), main = "Binned Variogram")
abline(h = 1, col = "blue")

vargram2 <- vgram(locs, c(y2), N = 30)
plot(vargram2, ylim = c(0, 1.1), main = "Binned Variogram")
lines(dgrid, 1 - cov.Matern(dgrid, c(1, 0.1, 1.5)), col = "blue")

```

Gaussian Processes: Covariance functions and their realizations

Simulate 1D realizations


```

# Commonly used covariance functions
cov.exp <- function(h, pars) pars[1] * exp(-h / pars[2])
cov.doubleExp <- function(h, pars) pars[1] * exp(-(h / pars[2])^2)

xg <- seq(0, 5, 0.01)
c_exp <- cov.exp(xg, c(1, 0.75))
c_doubleExp <- cov.doubleExp(xg, c(1, 1))
c_Matern <- cov.Matern(xg, c(1, 0.4, 1.5))

plot(xg, c_exp, type = "l", ylab = "Covariance", xlab = "Distance", las = 1)
lines(xg, c_doubleExp, col = "red")
lines(xg, c_Matern, col = "blue")
legend("topright", legend = c("Exp", "Gau", "Matern 3/2"),
      col = c("black", "red", "blue"), lty = 1, bty = "n")

```




```

Sigma_exp <- cov.exp(rdist(xg), c(1, 0.75))
Sigma_doubleExp <- cov.doubleExp(rdist(xg), c(1, 1))
Sigma_Matern <- cov.Matern(rdist(xg), c(1, 0.4, 1.5))
library(MASS)
set.seed(123)
sim_exp_1d <- mvrnorm(n = 1, rep(0, 501), Sigma_exp)
set.seed(123)
sim_doubleExp_1d <- mvrnorm(n = 1, rep(0, 501), Sigma_doubleExp)
set.seed(123)
sim_Matern_1d <- mvrnorm(n = 1, rep(0, 501), Sigma_Matern)

plot(xg, sim_exp_1d, type = "l", ylim = range(sim_exp_1d, sim_doubleExp_1d,
                                              sim_Matern_1d),
     ylab = "y", las = 1)
lines(xg, sim_doubleExp_1d, col = "red")
lines(xg, sim_Matern_1d, col = "blue")
legend("topleft", legend = c("Exp", "Gau", "Matern 3/2"),
     col = c("black", "red", "blue"), lty = 1, bty = "n")

```




Simulate 2D realizations

```
grid <- list(x = seq(0, 20, len = 200), y = seq(0, 20, len = 200))
nu <- c(0.5, 1, 2.5, 5)
obj <- list()
for (i in 1:4) obj[[i]] <- matern.image.cov(grid = grid, theta = 0.5,
                                           smoothness = nu[i], setup = TRUE)

set.seed(2021)
sim <- lapply(obj, sim.rf)
set.panel(2, 2)
```

plot window will lay out plots in a 2 by 2 matrix

```
par(mar = c(2.6, 3.1, 3.1, 0.6), las = 1)
for (i in 1:4){
  image.plot(grid$x, grid$y, sim[[i]], zlim = c(-4.25, 4.25), xlab = "", ylab = "")
}
```



Spatial interpolation

Here we assume $m(s) = 0 \quad \forall s \in \mathcal{S}$

Predicting one location

$$\hat{y}_0 = k^T \Sigma^{-1} \mathbf{y}$$

$$\text{Var}(\hat{y}_0) = \sigma^2 - k^T \Sigma^{-1} k$$

```

Sigma_Matern <- cov.Matern(dist, c(1, 0.1, 1.5))
set.seed(123)
y2 <- array(mvrnorm(n = 1, rep(0, N^2), Sigma_Matern), dim = c(N, N))
y2[N / 2, N / 2] <- NA
# k vector
k <- Sigma_Matern[435, -435]
# Sigma matrix
Sigma <- Sigma_Matern[-435, -435]
# y vector
y <- y2[-435]
## prediction
system.time(y0_hat <- t(k) %*% solve(Sigma) %*% y)

```

```

##    user  system elapsed
##  0.322   0.002   0.325

```

```
system.time(y0_hat_faster <- t(k) %*% solve(Sigma, y))
```

```
##      user  system elapsed
## 0.099   0.001   0.100
```

```
## prediction uncertainty
```


```
system.time(var_y0_hat <- Sigma_Matern[435, 435] - t(k) %*% solve(Sigma) %*% k)
```

```
##      user  system elapsed
## 0.318   0.000   0.319
```

```
system.time(Sigma_Matern[435, 435] - t(k) %*% solve(Sigma, k))
```

```
##      user  system elapsed
## 0.100   0.000   0.101
```

```
w <- t(k) %*% solve(Sigma)
weight_map <- array(c(w[1, 1:434], NA, w[1, 435:899]),
                    dim = c(30, 30))
xg <- yg <- seq(0, 1, length = N)
image.plot(xg, yg, weight_map)
```



Predicting multiple locations


```

N = 30
xg <- yg <- seq(0, 1, length = N)
locs <- expand.grid(xg, yg); dist <- rdist(locs)
Sigma_Matern <- cov.Matern(dist, c(1, 0.1, 1.5))
set.seed(123)
y2 <- array(mvrnorm(n = 1, rep(0, N^2), Sigma_Matern), dim = c(N, N))
y2_vec <- c(y2)
set.seed(123)
rm <- sample(1:(N^2), 0.5 * N^2)
y2_vec[rm] <- NA
y2_rm <- array(y2_vec, dim = c(N, N))

# k matrix
k <- Sigma_Matern[-rm, rm]
# Sigma matrix
Sigma <- Sigma_Matern[-rm, -rm]
# y vector
y <- y2_rm[-rm]
## prediction
system.time(y0_hat <- t(k) %*% solve(Sigma) %*% y)

##      user      system elapsed
##    0.079      0.000      0.080

system.time(y0_hat_faster <- t(k) %*% solve(Sigma, y))

##      user      system elapsed
##    0.015      0.000      0.015

## prediction uncertainty
system.time(var_y0_hat <- Sigma_Matern[rm, rm] - t(k) %*% solve(Sigma) %*% k)

##      user      system elapsed
##    0.115      0.000      0.116

system.time(Sigma_Matern[rm, rm] - t(k) %*% solve(Sigma, k))

##      user      system elapsed
##    0.092      0.000      0.093

par(mfrow = c(1, 3), mar = c(0, 1.6, 1.2, 0),
    mgp = c(2.4, 1, 0), las = 1)
image.plot(xg, yg, y2_rm, xlab = "", ylab = "", xaxt = "n", yaxt = "n",
           horizontal = T, legend.width = 0.8, legend.line = 1)
mtext("Observed")

y2_pred <- y2_rm
y2_pred[rm] <- y0_hat[, 1]
image.plot(xg, yg, y2_pred, xlab = "", ylab = "", xaxt = "n", yaxt = "n",
           horizontal = T, legend.width = 0.8, legend.line = 1)

```

```

mtext("Predicted")

con_sd <- sqrt(diag(var_y0_hat))
condSD <- array(0, dim = c(N, N))
temp <- c(condSD); temp[rm] <- con_sd
condSD <- array(temp, dim = c(N, N))

image.plot(xg, yg, matrix(condSD, N, N), xlab = "", ylab = "", xaxt = "n", yaxt = "n",
           horizontal = T, legend.width = 0.8, legend.line = 1)
mtext("Predicted Sd")

```

