



## CYBERSECURITY FOUNDATION V2

### Lab 4: Configuring Authentication

Document Version: **2022-12-22**

Copyright © 2022 Network Development Group, Inc.  
[www.netdevgroup.com](http://www.netdevgroup.com)

NETLAB+ is a registered trademark of Network Development Group, Inc.

Palo Alto Networks and the Palo Alto Networks logo are trademarks or registered trademarks of Palo Alto Networks, Inc.

## Contents

Introduction .....	3
Objective .....	3
Lab Topology.....	4
Lab Settings.....	5
1   Configuring Authentication.....	6
1.0   Load Lab Configuration .....	6
1.1   Configure a Local User Account and Authentication Profile.....	11
1.2   Enable the Authentication Portal and Enable Web-Form based Logins .....	15
1.3   Create an Authentication Policy.....	19
1.4   Commit and Test Authentication Policy.....	22

## Introduction


In this lab, you will configure the Firewall to use a Captive Portal to authenticate users by using a local user account and Authentication Policy.

## Objective

In this lab, you will perform the following tasks:

- Configure a Local User Account and Authentication Profile
- Enable the Captive Portal and Enable Web-Form based Logins
- Create an Authentication Policy
- Commit and Test Authentication Policy

## Lab Topology



## Lab Settings

The information in the table below will be needed in order to complete the lab. The task sections below provide details on the use of this information.

Virtual Machine	IP Address	Account (if needed)	Password (if needed)
Client	192.168.1.20	lab-user	PaloAlt0!
DMZ	192.168.50.10	root	PaloAlt0!
Firewall	192.168.1.254	admin	PaloAlt0!

## 1 Configuring Authentication


### 1.0 Load Lab Configuration

In this section, you will load the Firewall configuration file.


1. Click on the **Client** tab to access the Client PC.




2. Log in to the Client PC as username `lab-user`, password `PaloAlt0!`.
3. Double-click the **Chromium Web Browser** icon located on the Desktop.



4. In the *Chromium* address field, type `https://192.168.1.254` and press **Enter**.




5. You will see a “*Your connection is not private*” message. Click on the **ADVANCED** link.



If you experience the “Unable to connect” or “502 Bad Gateway” message while attempting to connect to the specified IP above, please wait an additional 1-3 minutes for the Firewall to fully initialize. Refresh the page to continue.


6. Click on **Proceed to 192.168.1.254 (unsafe)**.




7. Log in to the Firewall web interface as username admin, password PaloAlt0!.




8. In the web interface, navigate to **Device > Setup > Operations** and click on **Load named configuration snapshot** underneath the *Configuration Management* section.



9. In the *Load Named Configuration* window, select **pan-cf-lab-04.xml** from the *Name* dropdown box and click **OK**.




10. In the Loading Configuration window, a message will show *Configuration is being loaded. Please check the Task Manager for its status. You should reload the page when the task is completed.* Click **Close** to continue.



11. Click the **Tasks** icon located at the bottom-right of the web interface.



12. In the *Task Manager – All Tasks* window, verify the *Load* type has successfully completed. Click **Close**.




TYPE	STATUS	START TIME	MESSAGES	ACTION
Load	Completed	08/13/22 22:42:30		
EDLRefresh	Completed	08/13/22 22:40:42		
EDLFetch	Completed	08/13/22 22:40:41		
Report	Completed	08/13/22 22:35:53		
EDLFetch	Completed	08/13/22 22:35:40		
Auto Commit	Completed	08/13/22 22:34:58		


13. Click the **Commit** link located at the top-right of the web interface.



14. In the **Commit** window, click **Commit** to proceed with committing the changes.



15. When the commit operation successfully completes, click **Close** to continue.






The commit process takes changes made to the Firewall and copies them to the running configuration, which will activate all configuration changes since the last commit.

## 1.1 Configure a Local User Account and Authentication Profile

In this section, you will configure a local user account. Then, you will create a local authentication profile, which will later be assigned to a security policy.


1. Navigate to **Network > Zones**, and click on the **inside** zone.



The screenshot shows the PA-VM management interface. The top navigation bar includes links for DASHBOARD, ACC, MONITOR, POLICIES, OBJECTS, NETWORK (which is highlighted with a red box), and DEVICE. On the left, a sidebar lists various network components: Interfaces, Zones (which is also highlighted with a red box), VLANs, Virtual Wires, Virtual Routers, IPSec Tunnels, GRE Tunnels, DHCP, DNS Proxy, GlobalProtect, Portals, and Gateways. The main content area displays a table of zones. The columns are: NAME, TYPE, INTERFACES / VIRTUAL SYSTEMS, ZONE PROTECTION PROFILE, PACKET BUFFER PROTECTION, LOG SETTING, and ENABLED. The rows show five zones: danger (virtual-wire, interfaces: ethernet1/4, ethernet1/5), dmz (layer3, interfaces: ethernet1/3), inside (layer3, interfaces: ethernet1/2), and outside (layer3, interfaces: ethernet1/1). The 'inside' zone is highlighted with a red box in both the sidebar and the table.


NAME	TYPE	INTERFACES / VIRTUAL SYSTEMS	ZONE PROTECTION PROFILE	PACKET BUFFER PROTECTION	LOG SETTING	ENABLED
danger	virtual-wire	ethernet1/4 ethernet1/5		<input checked="" type="checkbox"/>		<input type="checkbox"/>
dmz	layer3	ethernet1/3		<input checked="" type="checkbox"/>		<input type="checkbox"/>
inside	layer3	ethernet1/2		<input checked="" type="checkbox"/>		<input type="checkbox"/>
outside	layer3	ethernet1/1		<input checked="" type="checkbox"/>		<input type="checkbox"/>

2. In the Zone window, click the **Enable User Identification** checkbox under the **User Identification ACL**. Then, click the **OK** button.




This will enable the inside zone to use a Username for authentication.


3. Navigate to **Device > Local User Database > Users > Add**. You may need to scroll down on the left pane.



4. In the *Local User* window, type lab-web in the *Name* field. Then, type Pal0Alt0 in the *Password* and *Confirm Password* fields. Finally, click the **OK** button.




5. Navigate to **Device > Authentication Profile > Add**. You may need to scroll up on the left pane.



6. In the *Authentication Profile* window, type Local-Auth-Profile in the *Name* field. Then, select **Local Database** from the *Type* dropdown.

The screenshot shows the 'Authentication Profile' configuration dialog box. The 'Name' field contains 'Local-Auth-Profile' with a red box around it. The 'Type' dropdown is set to 'Local Database' with a red box around it. The 'User Domain' and 'Username Modifier' fields are also visible. At the bottom are 'OK' and 'Cancel' buttons.

7. In the **Authentication Profile** window, click on the **Advanced** tab. Then, click on the **Add** button. Next, select **all** from the dropdown in the *Allow List* column. Finally, click the **OK** button.



## 1.2 Enable the Authentication Portal and Enable Web-Form based Logins

In this section, you will enable a captive portal. In that captive portal, you will use a web-form for login.

1. Navigate to **Device > User Identification > Authentication Portal Settings**, and click on the gear icon.


The screenshot shows the PA-VM interface with the following details:

- Navigation Bar:** DASHBOARD, ACC, MONITOR, POLICIES, OBJECTS, NETWORK, DEVICE (highlighted).
- Left Sidebar:** Setup, High Availability, Config Audit, Password Profiles, Administrators, Admin Roles, Authentication Profile (highlighted), Authentication Sequence, User Identification (highlighted), Data Redistribution, Device Quarantine, VM Information Sources, Troubleshooting.
- Top Header:** User Mapping, Connection Security, Terminal Server Agents, Group Mapping Settings, Authentication Portal Settings (highlighted).
- Authentication Portal Section:**
  - Enable Authentication Portal:
  - Timer (min): 60
  - Idle Timer (min): 15
  - SSL/TLS Service Profile
  - Authentication Profile
  - GlobalProtect Network Port for Inbound Authentication Prompts (UDP): 4501
  - Certificate Profile
  - Mode: transparent



Authentication Portal may also be identified as Captive Portal, which was the name used in versions prior to PAN-OS 10.

2. In the *Authentication Portal* window, click the **Enable Authentication Portal** checkbox. Then, select **Local-Auth-Profile** from the *Authentication Profile* dropdown. Finally, click the **OK** button.




This will turn on the Authentication Portal for web-form logins and associate it with the **Local-Auth-Profile** you created earlier.

3. Navigate to **Objects > Authentication**. You may need to scroll down on the left pane.

NAME	LOCATION	AUTHENT
default-web-form	Predefined	web-form
default-browser-challenge	Predefined	browser-cl
default-no-captive-portal	Predefined	no-captive


4. Click the checkbox beside the **default-web-form** and click **Clone**.




	NAME	LOCATION
<input checked="" type="checkbox"/>	default-web-form	Predefined
<input type="checkbox"/>	default-browser-challenge	Predefined
<input type="checkbox"/>	default-no-captive-portal	Predefined

+ Add - Delete **Clone** PDF/CSV

5. In the *Clone* window, click the **OK** button to confirm the clone.




6. You will notice a new entry named **default-web-form-1** has been created; click on **default-web-form-1**.



	NAME	LOCATION
<input checked="" type="checkbox"/>	default-web-form	Predefined
<input type="checkbox"/>	default-browser-challenge	Predefined
<input type="checkbox"/>	default-no-captive-portal	Predefined
<input type="checkbox"/>	default-web-form-1	


7. In the *Authentication Enforcement* window, type local-web-form-auth in the *Name* field. Then, select **Local-Auth-Profile** in the *Authentication Profile* dropdown. Next, click the **OK** button.



### 1.3 Create an Authentication Policy


In this section, you will enable a captive portal. A captive portal redirects web requests that match the authentication policy and forces the user to use a login to continue. This is typically seen in corporate guest networks, hotels, and Wi-Fi hotspots. In this captive portal, you will use a web-form for login.

1. Navigate to **Policies > Authentication > Add**.




The screenshot shows the PA-VM management interface. The top navigation bar includes DASHBOARD, ACC, MONITOR, POLICIES (which is highlighted with a red box), OBJECTS, NETWORK, and DEVICE. On the left, a sidebar menu lists various policy types: Security, NAT, QoS, Policy Based Forwarding, Decryption, Tunnel Inspection, Application Override, Authentication (which is highlighted with a red box), and DoS Protection. Below the sidebar is a 'Policy Optimizer' section with a 'Rule Usage' tree view showing counts for 'Unused in 30 days', 'Unused in 90 days', and 'Unused'. The main content area has a table header with columns: NAME, TAGS, ZONE, ADDRESS, USER, and DEVICE. At the bottom of the table area, there is a toolbar with buttons: Object : Addresses, + (highlighted with a red box), Delete, Clone, Enable, Disable, Move, PDF/CSV, and Highlight Unused Rules.


2. In the *Authentication Policy Rule* window, type `web-form-policy` in the **Name** field.




3. In the *Authentication Policy Rule* window, click on the **Source** tab. Then, click the **Add** button in the *Source Zone* section. Next, select **inside**.




4. In the *Authentication Policy Rule* window, click on the **Destination** tab. Then, click the **Add** button in the *Destination Zone* section. Next, select **outside**.



5. In the *Authentication Policy Rule* window, click on the **Service/URL Category** tab. Then, click on the **Add** button in the *Service* section. Next, select **service-https**.




6. In the *Authentication Policy Rule* window, click on the **Actions** tab. Then, select **local-web-form-auth** from the *Authentication Enforcement* dropdown. Then, click the **OK** button.




## 1.4 Commit and Test Authentication Policy

In this section, you will commit your changes and test the authentication policy with the captive portal.


1. Click the **Commit** link located at the top-right of the web interface.



2. In the **Commit** window, click **Commit** to proceed with committing the changes.



3. When the commit operation successfully completes, click **Close** to continue.




4. Open a second **Chromium Web Browser** from the taskbar.



5. In the *Chromium* address field, type `http://www.facebook.com` and press **Enter**.




6. You will see a "*Your connection is not private*" message. Click on the **ADVANCED** Link, and then click **Proceed to www.facebook.com (unsafe)**.



You are seeing this error because the Firewall is intercepting traffic coming from the inside zone to the outside zone. The Firewall serves as a man-in-the-middle until authenticated.

7. You will see a web-form login, type lab-web as the username. Then, type Pal0Alt0 as the password. Finally, click the **Login** button.




The resource you are trying to access requires proper user identification.  
Please enter your credentials.

lab-web

\*\*\*\*\*

Login

8. You will then see Facebook after you successfully authenticate to the Firewall as **lab-web**.



Email or phone number

Password

Log In

Forgot password?

Create new account



If the tab does not immediately load the Facebook page, wait and try again, or open a new tab in Chromium and enter <http://www.facebook.com> in the address bar, then press **Enter**.

9. Click the X in the upper-right to close **Chromium**.



10. Navigate to **Monitor > Logs > Traffic**.

11. In the logs, you will see that the entries to **facebook-base** are associated with the **lab-web** user. You may need to manually refresh logs or check additional pages at the bottom.

	RECEIVE TIME	TYPE	FROM ZONE	TO ZONE	SOURCE	SOURCE USER	DESTINATION	TO PORT	APPLICATION	ACTION
	08/17 17:01:00	end	dmz	outside	192.168.50.10		1.1.1.1	53	dns-base	allow
	08/17 17:31:30	end	dmz	outside	192.168.50.10		1.1.1.1	53	dns-base	allow
	08/17 17:31:30	end	dmz	outside	192.168.50.10		1.1.1.1	53	dns-base	allow
	08/17 17:31:30	end	dmz	outside	192.168.50.10		1.1.1.1	53	dns-base	allow
	08/17 17:31:28	end	inside	outside	192.168.1.20	lab-web	17.253.2.123	123	ntp-base	allow
	08/17 17:31:28	end	inside	outside	192.168.1.20	lab-web	176.9.157.155	123	ntp-base	allow
	08/17 17:31:23	end	inside	outside	192.168.1.20	lab-web	8.8.8.8	53	dns-base	allow
	08/17 17:31:22	end	inside	outside	192.168.1.20	lab-web	8.8.8.8	53	dns-base	allow
	08/17 17:31:21	end	inside	outside	192.168.1.20	lab-web	8.8.8.8	53	dns-base	allow
	08/17 17:31:21	end	inside	outside	192.168.1.20	lab-web	8.8.8.8	53	dns-base	allow
	08/17 17:31:21	end	inside	outside	192.168.1.20		8.8.8.8	53	dns-base	allow
	08/17 17:31:08	end	inside	outside	192.168.1.20	lab-web	157.240.229.1	443	facebook-base	allow
	08/17 17:31:08	end	inside	outside	192.168.1.20	lab-web	157.240.229.1	443	facebook-base	allow
	08/17 17:30:21	end	inside	outside	192.168.1.20		17.253.2.123	123	ntp-base	allow

12. The lab is now complete; you may end the reservation.