

CHAMELEON - A Deep Learning Meta-Architecture for News Recommender Systems

Gabriel de Souza Pereira Moreira

CI&T

Brazilian Aeronautics Institute of Technology - ITA

São José dos Campos, SP, Brazil

gabrielpm@ciandt.com

ABSTRACT

News recommender systems are aimed to personalize users experiences and help them discover relevant articles from a large and dynamic search space. Therefore, news domain is a challenging scenario for recommendations, due to its sparse user profiling, fast growing number of items, accelerated item's value decay, and users preferences dynamic shift.

Deep Learning (DL) have achieved a great success in complex domains, such as computer vision, Natural Language Processing (NLP), machine translation, speech recognition, and reinforcement learning. Therefore, it became a mainstream approach in Recommender Systems research only since 2016.

The main objective of this research is the investigation, design, implementation and evaluation of a Meta-Architecture for personalized news recommendations using deep neural networks.

As information about users' past interactions is scarce in such cold-start scenario, user context and session information are explicitly modeled, as well as past user sessions, when available. Users' past behaviors and item features are both considered in an hybrid session-aware recommendation approach. The recommendation task addressed in this work is next-item prediction for user sessions: "what is the next most likely article a user might read in a session?"

This paper presents the research methodology for this Doctoral research, the proposed Meta-Architecture and some preliminary results, as well as the next research challenges.

CCS CONCEPTS

• **Information systems** → **Recommender systems**; • **Computing methodologies** → **Neural networks**;

KEYWORDS

Recommender Systems; Deep Learning; News Recommendation; Session-Based Recommendation; Context-Based Recommendation; Meta-Architecture; Recurrent Neural Networks

1 INTRODUCTION

Recommender Systems (RS) have been increasingly popular in assisting users with their choices, thus enhancing their engagement

and overall satisfaction with online services [32]. They are an important part of information and e-commerce systems, enabling users to filter through large information and product spaces.

Recommender systems have been researched and applied in online services from different domains, like music [10] [60] [64] (e.g., Spotify, Pandora, Last.fm), videos (e.g. YouTube [14]), people [2] (e.g., Facebook), jobs [4] (e.g., LinkedIn [33], Xing [44]), and research papers [62] [5] (e.g., Docear [6]), among others.

1.1 News Recommender Systems

Popular news portals, such as Google News [13], Yahoo! News [58], The New York Times [57], Washington Post [47] [9], among others, have gained increasing attention from a massive amount of online news readers.

Online news recommendations have also been addressed by researchers in the last years, either using Content-Based Filtering [36] [11] [49] [30] [45], Collaborative Filtering [13] [15], and Hybrid approaches [12] [39] [36] [48] [38] [37] [59] [18].

1.2 Deep Learning on Recommender Systems

Deep Learning (DL) [27] [28] [8] [7] is a hot area in machine learning communities. The uptake of deep learning by RS community was relatively slow, as the topic became popular only in 2016, with the first Deep Learning for Recommender Systems workshop at the ACM RecSys 2016 [25].

Early pioneer work applying used neural networks to RS was done in [52], where a two-layer Restricted Boltzmann Machine (RBM) slightly outperformed Matrix Factorization.

After a winter on RS research using neural networks, Deep Collaborative Filtering was addressed by [63] and [66] using denoising auto-encoders [61]. Deep neural networks have also been used to learn item features from unstructured data, like text [3], music [60] [64], and images [43] [21].

Recurrent Neural Networks (RNN) possess several properties that make them attractive for sequence modeling of user sessions. In particular, they are capable of incorporating input from past consumption events, allowing to derive a wide range of sequence-to-sequence mappings [16]. Recent work has explored the usage of RNNs for session-aware/based recommendations [24] [54].

According to [22], the main approaches using Deep Learning in Recommender Systems can be grouped as: (a) **Item Embeddings and 2vec Models**, (b) **Deep Collaborative Filtering**, (c) **Deep Session-Based/Aware RS**, and (d) **Deep Feature Extraction from Heterogeneous Data** [22]. This research focuses on approaches (c) and (d), due to some challenges of news recommendation and architecture requirements discussed in next sections.

Permission to make digital or hard copies of part or all of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. Copyrights for third-party components of this work must be honored. For all other uses, contact the owner/author(s).

RecSys '18, October 2–7, 2018, Vancouver, BC, Canada

© 2018 Copyright held by the owner/author(s).

ACM ISBN 978-1-4503-5901-6/18/10...\$15.00

<https://doi.org/10.1145/3240323.3240331>

2 RESEARCH

2.1 Problem

The news domain poses some challenges for Recommender Systems, summarized below:

- **Sparse user profiling** – the majority of readers are anonymous, and they actually read only few stories from the entire repository. This results in extreme levels of sparsity in the user-item matrix, and users usually have tracked very few information about past behaviour, if any [36] [38] [15];
- **Fast growing number of items** – hundreds of new stories are added daily in a news portal (e.g., over 300 in New York Times [57]). This intensifies the cold-start problem, as for fresh items you cannot count on lots of interactions before starting to recommend them [15]. For news aggregators, scalability problems may arise, as a high volume of news articles overload the web within limited time span [45];
- **Accelerated item's value decay** – information value decays over time. This is specially true in the news domain, as most users are interested in fresh information. Thus, each item is expected to have a short shelf life [13]; and
- **Users preferences shift** – users interests on news are not as stable as in the entertainment domain. Some user interests shift over time, while other long-term interests remain stable [15]. User's current interest in a session may be affected by his context (e.g., location, access time) [15] or by global context (e.g., breaking news or important events) [18].

2.2 Objective

The main objective of this research is to investigate, design, implement, and evaluate a deep learning meta-architecture for news recommendation, in order to improve the accuracy of recommendations provided by news portals, satisfying readers' dynamic information needs in such a challenging recommendation scenario.

2.3 Research Scope and Methodology

The recommendation task addressed in this work is the next-item prediction for user sessions [55] (e.g., "what is the next most likely news article a user might read in a session?"). Models are trained using past user interactions on news portals to predict future article reads.

The Research Requirements are presented as follows:

- **RRQ1** - To investigate state-of-art methods for news recommendations;
- **RRQ2** - To investigate state-of-art Deep Learning architectures applied for recommender systems;
- **RRQ3** - To elaborate a Deep Learning meta-architecture for news recommendations;
- **RRQ4** - To implement and evaluate instantiations of the proposed meta-architecture; and
- **RRQ5** - To test stated hypotheses based on evaluation results.

2.4 Research Hypotheses

This research aims to evaluate the following hypotheses, related to the proposed meta-architecture for news recommendation:

- **HY1** - Is it possible to improve news recommendation accuracy by usage of Deep Learning architectures to learn articles' feature representations directly from their textual content, when compared to feature extraction based on using statistical Natural Language Processing (NLP) techniques or other unsupervised learning methods (e.g. Doc2Vec)?
- **HY2** - Can news recommendations accuracy be improved, by modeling with RNNs users' short-term (session) interests and context, when compared to other session-based recommenders?
- **HY3** - Can news recommendations accuracy be improved, by modeling with RNNs users' long-term interests (past sessions), when compared to other session-aware recommenders?
- **HY4** - Can Deep Learning architectures automatically learn how to leverage news dynamic attributes (popularity and recency) and users contextual attributes (location, time, device) to improve recommendations accuracy, when compared to other context-aware recommenders?

3 CHAMELEON - A DEEP LEARNING META-ARCHITECTURE FOR NEWS RECOMMENDER SYSTEMS

The main contribution of this research is to propose the first Deep Learning meta-architecture for news recommendation.

For the purpose of this thesis, a meta-architecture is a reference architecture that collects together decisions relating to an architecture strategy. A meta-architecture might be instantiated as different architectures with similar characteristics that fulfill a common task, in this case, news recommendations.

3.1 Conceptual Model of News Relevance Factors

Many factors may influence the relevance of news article for users. In this research, a Conceptual Model of News Relevance Factors was conceptualized and is presented in Figure 1.




Figure 1: The Conceptual Model of News Relevance Factors

News articles have some **static properties** regarding its content, like title, text, **topics**, and mentioned **entities** (e.g., people, places) [36] [51]. The **publisher** reputation may also add trust or discredit to an article [41] [19].

News articles also have **dynamic properties**, that change over time, like **popularity** [12] [42] and **recency** [59] [19].

Global factors that might affect the article **popularity** are usually related to **breaking events** (e.g., natural disasters, or a real family member birth). There are also **popular topics**, that might be continuously interesting for users (e.g., sports) or may follow some **seasonality** (e.g., soccer during the World Cup, politics during a presidential election, etc.) [12] [19] [42].

The current **user context**, like **location**, **device**, and **time** is also important to define his **short-term interests** [45] [51], as they may differ during and off business hours, for example.

The HTTP **referrer** URL brings some knowledge about the origin of the user request and may also be useful as a predictive contextual information, as shown in the Yahoo! experiments reported on [59].

Users' **long-term interests** on news usually remain stable over time [15]. These interests may be specific personal preferences (e.g., chess playing) or influenced by popular global topics (e.g., tech).

The proposed Meta-Architecture leverages those factors to improve the quality of provided recommendations.

3.2 Requirements

To conceptualize the CHAMELEON Meta-Architecture, some requirements were first devised, based on the news recommender systems challenges described in Section 2.1 and also on the capabilities provided by Deep Learning. The CHAMELEON Meta-Architecture should be able:

- **RQ1** - to provide personalized news recommendations in extreme cold-start scenarios, as most news are fresh and most users cannot be identified;
- **RQ2** - to use Deep Learning to automatically learn news representations from textual content and news metadata, minimizing the need of manual feature engineering;
- **RQ3** - to leverage the user session information, as the sequence of interacted news may indicate user's short-term preferences for session-based recommendations;
- **RQ4** - to leverage users' past sessions information, when available, to model long-term interests for session-aware recommendations;
- **RQ5** - to leverage users' contextual information as a rich data source, in such information scarcity about the user;
- **RQ6** - to model explicitly contextual news properties – popularity and recency – as those are important factors on news interest life cycle;
- **RQ7** - to support an increasing number of new items and users by incremental model retraining (online learning), without the need to retrain on the whole historical dataset; and
- **RQ8** - to provide a modular structure for news recommendation, allowing its modules to be instantiated by different and increasingly advanced neural network architectures.

3.3 The Proposed Meta-Architecture

The CHAMELEON Meta-Architecture presented in Figure 2 was designed based on the Conceptual Model of News Relevance Factors (Section 3.1) and also on requirements described in Section 3.2. It

is based on neural networks, which support incremental online learning from mini-batches (RQ7).

The CHAMELEON Meta-Architecture was structured to support changes. It defines inputs, outputs, modules, sub-modules, and their interactions. Modules and sub-modules can be instantiated by different neural architectures, which might be evaluated and compared.




Figure 2: CHAMELEON - A Deep Learning Meta-Architecture for News Recommender Systems

The CHAMELEON is composed of two modules (RQ8) with independent life cycles for training and inference: the Article Content Representation (ACR) and the Next-Article Recommendation (NAR).

The ACR module is responsible for learning distributed representations (embeddings) for news' contents. For scalability reasons, those embeddings are not directly trained for recommendation task, but for a side task of news metadata (e.g. category) classification.

The Next-Article Recommendation (NAR) module is responsible to provide news articles recommendations for active user sessions.

Traditional CF and Hybrid RS trust in user and item identifications to learn similarities and provide recommendations. In the dynamic scenario of news recommendation (RQ1), the proposed hybrid meta-architecture does not count on item IDs when modeling users preferences on news. Instead, Article Content Embeddings, pre-trained in by ACR module, and stored in a repository, are used to represent the content of items.

User IDs are not directly used by the neural network as well – only users' contextual information, interactions in the session, and past sessions information, when available.

The inputs for the NAR module are: (1) the pre-trained Article Content Embedding of the last interacted article; (2) the contextual properties of the article (popularity and recency); and (3) the user context (time, location, and device).

3.4 Comparisons with Related Work

To the best of the knowledge from this research so far, the only works presenting a deep learning architecture for news recommendation were [56] and [35]. The CHAMELEON is positioned in a higher level of abstraction, for being a Meta-Architecture.

One of the main inspirations for CHAMELEON was the GRU4Rec [24], the seminal work on the usage of Recurrent Neural Networks

(RNN) on session-based recommendations, and subsequent work [26] [23]. Since then, a research line has emerged on the usage of RNN on session-based [65] [40] [55] and session-aware [16] [46] [50] recommendations.

The aforementioned works on the RNN session-based/aware architectures mostly trust on static user IDs and item IDs to provide recommendations, which does not meet the RQ7. The CHAMELEON uses articles content and context embeddings to represent items and also user context to represent users, dealing smoothly with the incoming stream of new articles and users interactions.

Other main inspirations came from the Multi-View Deep Neural Network (MV-DNN) [17], which adapted Deep Structured Semantic Model (DSSM) [29] for the recommendation task.

The MV-DNN maps users and items to a latent space, where the cosine similarity between users and their preferred items is maximized. That approach makes it possible to keep the neural network architecture static, rather than adding new units into the output layer for each new item (e.g., published article), as required in [24] (softmax loss function).

The MV-DNN was adapted for News recommendation by [56] Temporal DSSM (TDSSM) and [35] Recurrent Attention DSSM (RA-DSSM). Differently from CHAMELEON, TDSSM [56] did not model user sessions explicitly, and items and users representations are not directly learned from news content and users behaviours.

The RA-DSSM [35] ignores past user sessions information, whilst CHAMELEON provides session-aware news recommendations. Furthermore, whilst RA-DSSM represents articles content by using Doc2Vec embeddings (unsupervised training), CHAMELEON trains news content embeddings to predict news metadata by using multi-task supervised learning. Finally, the RA-DSSM does not use any contextual information about the user and articles, which may limit its accuracy in a extreme cold-start scenario like news RS.

4 INITIAL EXPERIMENTS

Based on the Research Methodology presented in Section 2.3, the student has completed **RRQ1**, **RRQ2**, **RRQ3**, and is currently working on **RRQ4**, by designing concrete architecture instantiations for ACR and NAR modules and implementing on TensorFlow [1].

For the first evaluation of ACR module, an architecture based on Convolutional Neural Networks (CNN) was proposed, as shown in Figure 3. CNNs have been widely used in Deep NLP research as a fast and powerful method for feature extraction from textual data.

The inputs for the ACR module are (1) article metadata attributes (e.g., publisher), and (2) article textual content, represented as a sequence of word embeddings (e.g., Word2Vec, GloVe). The Article Content Embeddings are trained to a side task – classifying the articles' categories.

Architecture instantiations of the NAR module are also being designed and implemented, based on RNNs, and evaluated by usage of Top-N accuracy metrics: Recall@N and NDCG@N [31]).

The Research Hypotheses stated in Section 2.4 will be tested (**RRQ5**) by offline evaluation on CHAMELEON instantiations, trained on news portals datasets described in Table 1.




Figure 3: The CNN-based instantiation of the ACR module

Table 1: News portal datasets used by this research

| | G1 | GE ¹ | CLEF ² | Adressa ³ | Life.ru ⁴ |
|-------------------|---------|-----------------|-------------------|----------------------|----------------------|
| Language | Portug. | Portug. | German | Norweg. | Russian |
| Period (months) | 5 | 5 | 1 | 3 | 1 |
| clicks (million) | 124 | 196 | 1.5 | 2.7 | 30 |
| articles (thous.) | 391 | 156 | 6 | 1 | 140 |
| users (thous.) | 1,030 | 957 | 600 | 15 | - |
| user con-text | Yes | Yes | Yes | Yes | No |

5 CONCLUSIONS

The main contribution of this research is to propose the first Deep Learning meta-architecture for news recommendation - the CHAMELEON. Its instantiations and implementations will be evaluated on real news portals datasets, in order to test stated hypotheses.

This Doctoral student intends to make this research code available open-source as soon as main results are obtained, to allow reproducibility and to foster advances in Deep Recommender Systems.

REFERENCES

- [1] Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, et al. 2016. Tensorflow: Large-scale machine learning on heterogeneous distributed systems. *arXiv preprint arXiv:1603.04467* (2016).
- [2] Hernan Badenes, Mateo N Bengualid, Jilin Chen, Liang Gou, Eben Haber, Jalal Mahmud, Jeffrey W Nichols, Aditya Pal, Jerald Schoudt, Barton A Smith, et al. 2014. System U: automatically deriving personality traits from social media for people

¹G1 and Globo Esporte (GE) are news portals from Globo.com (among the most popular in Brazil). These large dataset were provided exclusively for this research.

²The CLEF-NewsREEL dataset (German) [34]: <http://www.clef-newsreel.org>

³The Adressa Dataset (Norwegian) [20]: <http://reclab.idi.ntnu.no/dataset>

⁴Russian news portal dataset [53]: <http://life.ru>

- recommendation. In *Proceedings of the 8th ACM Conference on Recommender systems*. ACM, 373–374.
- [3] Trapit Bansal, David Belanger, and Andrew McCallum. 2016. Ask the gru: Multi-task learning for deep text recommendations. In *Proceedings of the 10th ACM Conference on Recommender Systems*. ACM, 107–114.
 - [4] Mathieu Bastian, Matthew Hayes, William Vaughan, Sam Shah, Peter Skomoroch, Hyungjin Kim, Sal Uryasev, and Christopher Lloyd. 2014. LinkedIn skills: large-scale topic extraction and inference. In *Proceedings of the 8th ACM Conference on Recommender systems*. ACM, 1–8.
 - [5] Joeran Beel, Stefan Langer, Marcel Genzmehr, Bela Gipp, Corinna Breiteringer, and Andreas Nürnberger. 2013. Research paper recommender system evaluation: A quantitative literature survey. In *Proceedings of the International Workshop on Reproducibility and Replication in Recommender Systems Evaluation*. ACM, 15–22.
 - [6] Joeran Beel, Stefan Langer, Marcel Genzmehr, and Andreas Nürnberger. 2013. Introducing Docear's research paper recommender system. In *Proceedings of the 13th ACM/IEEE-CS joint conference on Digital libraries*. ACM, 459–460.
 - [7] Yoshua Bengio et al. 2009. Learning deep architectures for AI. *Foundations and trends® in Machine Learning* 2, 1 (2009), 1–127.
 - [8] Yoshua Bengio, Yann LeCun, et al. 2007. Scaling learning algorithms towards AI. *Large-scale kernel machines* 34, 5 (2007), 1–41.
 - [9] R. Bilton. 2016. The Washington Post tests personalized "pop-up" newsletters to promote its big stories. <http://www.niemanlab.org/2016/05/the-washington-post-tests-personalized-pop-up-newsletters-to-promote-its-big-stories/> (May 2016).
 - [10] Jiajun Bu, Shulong Tan, Chun Chen, Can Wang, Hao Wu, Lijun Zhang, and Xiaofei He. 2010. Music recommendation by unified hypergraph: combining social media information and music content. In *Proceedings of the international conference on Multimedia*. ACM, 391–400.
 - [11] Michel Capelle, Flavius Frasinicar, Marnix Moerland, and Frederik Hogenboom. 2012. Semantics-based news recommendation. In *Proceedings of the 2nd international conference on web intelligence, mining and semantics*. ACM, 27.
 - [12] Wei Chu and Seung-Taek Park. 2009. Personalized recommendation on dynamic content using predictive bilinear models. In *Proceedings of the 18th international conference on World wide web*. ACM, 691–700.
 - [13] Abhinandan S Das, Mayur Datar, Ashutosh Garg, and Shyam Rajaram. 2007. Google news personalization: scalable online collaborative filtering. In *Proceedings of the 16th international conference on World Wide Web*. ACM, 271–280.
 - [14] James Davidson, Benjamin Liebald, Junling Liu, Palash Nandy, Taylor Van Vleet, Ullas Gargi, Sujoy Gupta, Yu He, Mike Lambert, Blake Livingston, et al. 2010. The YouTube video recommendation system. In *Proceedings of the fourth ACM conference on Recommender systems*. ACM, 293–296.
 - [15] Jorge Díez Peláez, David Martínez Rego, Amparo Alonso Betanzos, Óscar Luaces Rodríguez, and Antonio Bahamonde Rionda. 2016. Metrical Representation of Readers and Articles in a Digital Newspaper. In *10th ACM Conference on Recommender Systems (RecSys 2016)*. ACM.
 - [16] Tim Donkers, Benedikt Loepp, and Jürgen Ziegler. 2017. Sequential User-based Recurrent Neural Network Recommendations. In *Proceedings of the Eleventh ACM Conference on Recommender Systems*. ACM, 152–160.
 - [17] Ali Mamdouh Elkahky, Yang Song, and Xiaodong He. 2015. A multi-view deep learning approach for cross domain user modeling in recommendation systems. In *Proceedings of the 24th International Conference on World Wide Web*. International World Wide Web Conferences Steering Committee, 278–288.
 - [18] Elena Viorica Epure, Benjamin Kille, Jon Espen Ingvaldsen, Rebecca Deneckere, Camille Salinesi, and Sahin Albayrak. 2017. Recommending Personalized News in Short User Sessions. In *Proceedings of the Eleventh ACM Conference on Recommender Systems*. ACM, 121–129.
 - [19] Jon Atle Gulla, Cristina Marco, Arne Dag Fidjestøl, Jon Espen Ingvaldsen, and Özlem Özgöbek. 2016. The Intricacies of Time in News Recommendation.. In *UMAP (Extended Proceedings)*.
 - [20] Jon Atle Gulla, Lemei Zhang, Peng Liu, Özlem Özgöbek, and Xiaomeng Su. 2017. The Adressa dataset for news recommendation. In *Proceedings of the International Conference on Web Intelligence*. ACM, 1042–1048.
 - [21] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. 2016. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*. 770–778.
 - [22] Balázs Hidasi. 2017. Deep Learning for Recommender Systems. <http://pro.unibz.it/projects/schoolrecsys17/DeepLearning.pdf>. (August 2017).
 - [23] Balázs Hidasi and Alexandros Karatzoglou. 2017. Recurrent Neural Networks with Top-k Gains for Session-based Recommendations. *arXiv preprint arXiv:1706.03847* (2017).
 - [24] Balázs Hidasi, Alexandros Karatzoglou, Linas Baltrunas, and Domonkos Tikk. 2016. Session-based recommendations with recurrent neural networks. In *Proceedings of Forth International Conference on Learning Representations*.
 - [25] Balázs Hidasi, Alexandros Karatzoglou, Oren Sar-Shalom, Sander Dieleman, Bracha Shapira, and Domonkos Tikk. 2017. DLRS 2017-Second Workshop on Deep Learning for Recommender Systems. In *Proceedings of the 2st Workshop on Deep Learning for Recommender Systems*. ACM, Vol. 29, 34.
 - [26] Balázs Hidasi, Massimo Quadana, Alexandros Karatzoglou, and Domonkos Tikk. 2016. Parallel recurrent neural network architectures for feature-rich session-based recommendations. In *Proceedings of the 10th ACM Conference on Recommender Systems*. ACM, 241–248.
 - [27] Geoffrey E Hinton, Simon Osindero, and Yee-Whye Teh. 2006. A fast learning algorithm for deep belief nets. *Neural computation* 18, 7 (2006), 1527–1554.
 - [28] Geoffrey E Hinton and Ruslan R Salakhutdinov. 2006. Reducing the dimensionality of data with neural networks. *science* 313, 5786 (2006), 504–507.
 - [29] Po-Sen Huang, Xiaodong He, Jianfeng Gao, Li Deng, Alex Acero, and Larry Heck. 2013. Learning deep structured semantic models for web search using clickthrough data. In *Proceedings of the 22nd ACM international conference on Conference on information & knowledge management*. ACM, 2333–2338.
 - [30] Ilija Ilievski and Sujoy Roy. 2013. Personalized news recommendation based on implicit feedback. In *Proceedings of the 2013 international news recommender systems workshop and challenge*. ACM, 10–15.
 - [31] Kalervo Järvelin and Jaana Kekäläinen. 2002. Cumulated gain-based evaluation of IR techniques. *ACM Transactions on Information Systems (TOIS)* 20, 4 (2002), 422–446.
 - [32] Gawesh Jawaheer, Peter Weller, and Patty Kostkova. 2014. Modeling user preferences in recommender systems: A classification framework for explicit and implicit user feedback. *ACM Transactions on Interactive Intelligent Systems (TiIS)* 4, 2 (2014), 8.
 - [33] Krishnaram Kenthapadi, Benjamin Le, and Ganesh Venkataraman. 2017. Personalized Job Recommendation System at LinkedIn: Practical Challenges and Lessons Learned. In *Proceedings of the Eleventh ACM Conference on Recommender Systems*. ACM, 346–347.
 - [34] Benjamin Kille, Andreas Lommatzsch, Frank Hopfgartner, Martha Larson, and Torben Brodt. 2017. CLEF 2017 NewsREEL Overview: Offline and Online Evaluation of Stream-based News Recommender Systems. (2017).
 - [35] Vaibhav Kumar, Dhruv Khattar, Shashank Gupta, Manish Gupta, and Vasudeva Varma. 2017. Deep Neural Architecture for News Recommendation. In *Working Notes of the 8th International Conference of the CLEF Initiative, Dublin, Ireland. CEUR Workshop Proceedings*.
 - [36] Lei Li, Dingding Wang, Tao Li, Daniel Knox, and Balaji Padmanabhan. 2011. SCENE: a scalable two-stage personalized news recommendation system. In *Proceedings of the 34th international ACM SIGIR conference on Research and development in Information Retrieval*. ACM, 125–134.
 - [37] Lei Li, Li Zheng, Fan Yang, and Tao Li. 2014. Modeling and broadening temporal user interest in personalized news recommendation. *Expert Systems with Applications* 41, 7 (2014), 3168–3177.
 - [38] Chen Lin, Runquan Xie, Xinjun Guan, Lei Li, and Tao Li. 2014. Personalized news recommendation via implicit social experts. *Information Sciences* 254 (2014), 1–18.
 - [39] Jiahui Liu, Peter Dolan, and Elin Rønby Pedersen. 2010. Personalized news recommendation based on click behavior. In *Proceedings of the 15th international conference on Intelligent user interfaces*. ACM, 31–40.
 - [40] Qiang Liu, Shu Wu, Diyi Wang, Zhaokang Li, and Liang Wang. 2016. Context-aware sequential recommendation. In *Data Mining (ICDM), 2016 IEEE 16th International Conference on*. IEEE, 1053–1058.
 - [41] Andreas Lommatzsch. 2014. Real-Time News Recommendation Using Context-Aware Ensembles.. In *ECIR*, Vol. 14. Springer, 51–62.
 - [42] Andreas Lommatzsch, Benjamin Kille, and Sahin Albayrak. 2017. Incorporating context and trends in news recommender systems. In *Proceedings of the International Conference on Web Intelligence*. ACM, 1062–1068.
 - [43] Julian McAuley, Christopher Targett, Qinfeng Shi, and Anton Van Den Hengel. 2015. Image-based recommendations on styles and substitutes. In *Proceedings of the 38th International ACM SIGIR Conference on Research and Development in Information Retrieval*. ACM, 43–52.
 - [44] Sonu K Mishra and Manoj Reddy. 2016. A bottom-up approach to job recommendation system. In *Proceedings of the Recommender Systems Challenge*. ACM, 4.
 - [45] Itishree Mohallick and Özlem Özgöbek. 2017. Exploring privacy concerns in news recommender systems. In *Proceedings of the International Conference on Web Intelligence*. ACM, 1054–1061.
 - [46] Massimo Quadana, Alexandros Karatzoglou, Balázs Hidasi, and Paolo Cremonesi. 2017. Personalizing Session-based Recommendations with Hierarchical Recurrent Neural Networks. In *Proceedings of the 11th ACM Conference on Recommender Systems*.
 - [47] Graff. R. 2015. How the Washington Post used data and natural language processing to get people to read more news. <https://knightlab.northwestern.edu/2015/06/03/how-the-washington-posts-clavis-tool-helps-to-make-news-personal/>. (June 2015).
 - [48] Junyang Rao, Aixia Jia, Yansong Feng, and Dongyan Zhao. 2013. Personalized news recommendation using ontologies harvested from the web. In *International Conference on Web-Age Information Management*. Springer, 781–787.
 - [49] Hongda Ren and Wei Feng. 2013. Concert: A concept-centric web news recommendation system. In *International Conference on Web-Age Information Management*. Springer, 796–798.

- [50] Massimiliano Ruocco, Ole Steinar Lillestøl Skrede, and Helge Langseth. 2017. Inter-Session Modeling for Session-Based Recommendation. In *Proceedings of the 2nd Workshop on Deep Learning for Recommender Systems*. ACM, 24–31.
- [51] Alan Said, Jimmy Lin, Alejandro Bellogin, and Arjen de Vries. 2013. A month in the life of a production news recommender system. In *Proceedings of the 2013 workshop on Living labs for information retrieval evaluation*. ACM, 7–10.
- [52] Ruslan Salakhutdinov, Andriy Mnih, and Geoffrey Hinton. 2007. Restricted Boltzmann machines for collaborative filtering. In *Proceedings of the 24th international conference on Machine learning*. ACM, 791–798.
- [53] Pavel Shashkin and Nikolay Karpov. 2017. Learning to rank for personalized news recommendation. In *Proceedings of the International Conference on Web Intelligence*. ACM, 1069–1071.
- [54] Ole Steinar Lillestøl Skrede. 2017. *Inter-/Intra-session Recurrent Neural Network for Session-based Recommender Systems*. Master's thesis. NTNU.
- [55] Elena Smirnova and Flavian Vasile. 2017. Contextual Sequence Modeling for Recommendation with Recurrent Neural Networks. In *Proceedings of the 11th ACM Conference on Recommender Systems*.
- [56] Yang Song, Ali Mamdouh Elkahky, and Xiaodong He. 2016. Multi-rate deep learning for temporal recommendation. In *Proceedings of the 39th International ACM SIGIR conference on Research and Development in Information Retrieval*. ACM, 909–912.
- [57] A. Spangher. 2015. Building the Next New York Times Recommendation Engine. <https://open.blogs.nytimes.com/2015/08/11/building-the-next-new-york-times-recommendation-engine/>. (Aug 2015).
- [58] Michele Trevisiol, Luca Maria Aiello, Rossano Schifanella, and Alejandro Jaimes. 2014. Cold-start news recommendation with domain-dependent browse graph. In *Proceedings of the ACM Recommender System conference, RecSys*, Vol. 14.
- [59] Michele Trevisiol, Luca Maria Aiello, Rossano Schifanella, and Alejandro Jaimes. 2014. Cold-start news recommendation with domain-dependent browse graph. In *Proceedings of the 8th ACM Conference on Recommender systems*. ACM, 81–88.
- [60] Aaron Van den Oord, Sander Dieleman, and Benjamin Schrauwen. 2013. Deep content-based music recommendation. In *Advances in neural information processing systems*. 2643–2651.
- [61] Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. 2008. Extracting and composing robust features with denoising autoencoders. In *Proceedings of the 25th international conference on Machine learning*. ACM, 1096–1103.
- [62] Chong Wang and David M Blei. 2011. Collaborative topic modeling for recommending scientific articles. In *Proceedings of the 17th ACM SIGKDD international conference on Knowledge discovery and data mining*. ACM, 448–456.
- [63] Hao Wang, Naiyan Wang, and Dit-Yan Yeung. 2015. Collaborative deep learning for recommender systems. In *Proceedings of the 21th ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*. ACM, 1235–1244.
- [64] Xinxin Wang and Ye Wang. 2014. Improving content-based and hybrid music recommendation using deep learning. In *Proceedings of the 22nd ACM international conference on Multimedia*. ACM, 627–636.
- [65] Caihua Wu, Junwei Wang, Juntao Liu, and Wenyu Liu. 2016. Recurrent neural network based recommendation for time heterogeneous feedback. *Knowledge-Based Systems* 109 (2016), 90–103.
- [66] Yao Wu, Christopher DuBois, Alice X Zheng, and Martin Ester. 2016. Collaborative denoising auto-encoders for top-n recommender systems. In *Proceedings of the Ninth ACM International Conference on Web Search and Data Mining*. ACM, 153–162.