

1. Screenshots (label each clearly)

- Output of `sts get-caller-identity` showing your operating identity.

```
(melon@melon)-[~]
$ # Configure dummy credentials (LocalStack accepts any value)
aws configure set aws_access_key_id test
aws configure set aws_secret_access_key test
aws configure set region us-east-1

# Test: this talks to LocalStack, NOT real AWS
aws --endpoint-url=http://localhost:4566 sts get-caller-identity

{
  "UserId": "AKIAIOSFODNN7EXAMPLE",
  "Account": "000000000000",
  "Arn": "arn:aws:iam::000000000000:root"
}
```

- `get-group Admins` output showing your CloudAdmin user as a member.

```
(melon@melon)-[~]
$ aws $EP iam get-group --group-name Admins
{
  "Users": [
    {
      "Path": "/",
      "UserName": "CloudAdmin_MELON",
      "UserId": "AIDAQAAAAAAKMHYMNYP",
      "Arn": "arn:aws:iam::000000000000:user/CloudAdmin_MELON",
      "CreateDate": "2026-07-29T11:34:42.256631+00:00"
    }
  ],
  "Group": {
    "Path": "/",
    "GroupName": "Admins",
    "GroupId": "AGPAQAAAAAAJ5BKYZFA4",
    "Arn": "arn:aws:iam::000000000000:group/Admins",
    "CreateDate": "2026-07-29T11:33:45.712778+00:00"
  }
}
```

- list-attached-user-policies for the Analyst showing only the read-only policy.

```
(melon@melon)-[~]  
$ aws $EP iam list-attached-user-policies --user-name Analyst_MANGO  
{  
  "AttachedPolicies": [  
    {  
      "PolicyName": "AmazonS3ReadOnlyAccess",  
      "PolicyArn": "arn:aws:iam::aws:policy/AmazonS3ReadOnlyAccess"  
    }  
  ]  
}
```

- The three kubectl auth can-i results (YES / NO / NO).

```
(melon@melon)-[~]  
$ SA=system:serviceaccount:dev:dev-user  
  
# Should be YES - reading pods in dev is allowed  
kubectl auth can-i list pods -n dev --as=$SA  
  
yes
```

```
(melon@melon)-[~]  
$ # Should be NO - deleting pods is not granted  
kubectl auth can-i delete pods -n dev --as=$SA  
  
no
```

```
(melon@melon)-[~]  
$ # Should be NO - the role does not extend to prod  
kubectl auth can-i list pods -n prod --as=$SA  
  
no
```