

More detailed



C程序设计

T15



位处理

厦门大学信息学院软件工程系

黄炜 副教授

二进制数、位和字节

- 人表示数：十根手指，十进制

$$- 2157 = 2 * 10^3 + 1 * 10^2 + 5 * 10^1 + 7 * 10^0$$

- 计算机表示数：高低电平，二进制

$$- 100001101101 = 1 * 2^{11} + 1 * 2^6 + 1 * 2^5 + 1 * 2^3 + 1 * 2^2 + 1 * 2^0$$

- 回顾二进制整数、有符号整数、浮点数



其它基数

- 八进制 (**Octal**)
- 十六进制 (**Hexadecimal**)
 - 0 ~ 9 仍对应 0 ~ 9
 - A ~ F 对应 10 ~ 15



C的位运算符

- 位逻辑运算符

- 二进制反码或按位取反： \sim

- 二进制： $\sim(10011010) \rightarrow 01100101$

- 用法：

```
newval = ~val;
printf("%d", val);
val = ~val;
```

- 按位与（and）： $\&$

- $(10010011) \& (00111101) \rightarrow (00010001)$

- 用法：

```
val &= 0377;
val = val & 0377;
```



C的位运算符

- 位逻辑运算符

- 按位或 (**or**) : |

- $(10010011) \mid (00111101) \rightarrow (10111111)$

- 用法 :

```
val |= 0377;  
val = val | 0377;
```

- 按位异或 (**exclusive or**) : ^

- $(10010011) \wedge (00111101) \rightarrow (10101110)$

- 用法 :

```
val ^= 0377;  
val = val ^ 0377;
```



C的位运算符

- 位逻辑运算符

- 掩码 (mask) : &

- $(10010011) \& (00000010) \rightarrow (00000010)$

- 用法：

```
flags &= MASK;  
ch &= 0xff; /* or ch &= 0377; */
```

- 打开位 (setting bit) : |

- $(10000000) | (00000101) \rightarrow (10000101)$

- 用法：

```
flags = flags | MASK;  
flags | MASK
```



C的位运算符

- 位逻辑运算符

- 关闭位 (clearing bit) : $\& \sim$

- $(00001111) \& \sim (10110110) \rightarrow (00001001)$

- 用法 : `flags &= ~MASK;`

- 转置位 (toggling bit) : \wedge

- $(00001111) \wedge (10110110) \rightarrow (10111001)$

- 用法 : `flags ^= MASK;`



C的位运算符

- 位逻辑运算符

- 查看一位的值 (**checking the value of a bit**) : **&**

- 用法： `if ((flags & MASK) == MASK)`

- 左移 (**left shift**) : **<<**

- $(10001010) \ll 2 \rightarrow (00101000)$

- 用法： `onkoo = stonk << 2;`
`stonk <<= 2;`



C的位运算符

- 位逻辑运算符

- 右移 (right shift) : `>>`

- $(01001010) \gg 2 \rightarrow (00010010)$

- 用法：

```
onkoo = stonk >> 2;  
stonk >>= 2;
```

- 注意：右移时，对于无符号整数，新位置补0。对于有符号整数，一部分系统补0，另一部分系统补“最高位”。



位移公式

```
/* binbit.c - using bit operations to display binary */
#include <stdio.h>
#include <limits.h> // for CHAR_BIT, # of bits per char
char * itobs(int, char *);
void show_bstr(const char *);
int main(void)
{
    char bin_str[CHAR_BIT * sizeof(int) + 1];
    int number;
    puts("Enter integers and see them in binary.");
    puts("Non-numeric input terminates program.");
    while (scanf("%d", &number) == 1)
    {
        itobs(number, bin_str);
        printf("%d is ", number);
        show_bstr(bin_str);
        putchar('\n');
    }
    puts("Bye!");
}
```



```

    return 0;
}

char * itobs(int n, char * ps)
{
    int i;
    const static int size = CHAR_BIT * sizeof(int);
    for (i = size - 1; i >= 0; i--, n >>= 1)
        ps[i] = (01 & n) + '0';
    ps[size] = '\\0';
    return ps;
}

/* show binary string in blocks of 4 */
void show_bstr(const char * str)
{
    int i = 0;
    while (str[i]) /* not the null character */

```



```

{
    putchar(str[i]);
    if(++i % 4 == 0 && str[i])
        putchar(' ');
}
}

```

Non-numeric input terminates program.

32↓

32 is 0000 0000 0000 0000 0000 0000 0010 0000

95↓

95 is 0000 0000 0000 0000 0000 0000 0101 1111

168654341↓

168654341 is 0000 1010 0000 1101 0111 0110 0000
0101

1↓

1 is 0000 0000 0000 0000 0000 0000 0000 0001

-1↓

-1 is 1111 1111 1111 1111 1111 1111 1111 1111

0↓

0 is 0000 0000 0000 0000 0000 0000 0000 0000

q↓

Bye!



```

/* invert4.c -- using bit operations to display binary */
#include <stdio.h>
#include <limits.h>
char * itobs(int, char *);
void show_bstr(const char *);
int invert_end(int num, int bits);

int main(void)
{
    char bin_str[CHAR_BIT * sizeof(int) + 1];

    int number;

    puts("Enter integers and see them in binary.");
    puts("Non-numeric input terminates program.");
    while (scanf("%d", &number) == 1)
    {
        itobs(number, bin_str);
    }
}

```



```

    printf("%d is\n", number);
    show_bstr(bin_str);
    putchar('\n');
    number = invert_end(number, 4);
    printf("Inverting the last 4 bits gives\n");
    show_bstr(itobs(number, bin_str));
    putchar('\n');
}
puts("Bye!");

return 0;
}

char * itobs(int n, char * ps)
{
    int i;
    const static int size = CHAR_BIT * sizeof(int);

```



```

    for (i = size - 1; i >= 0; i--, n >>= 1)
        ps[i] = (01 & n) + '0';
    ps[size] = '\0';

    return ps;
}

/* show binary string in blocks of 4 */
void show_bstr(const char * str)
{
    int i = 0;

    while (str[i]) /* not the null character */
    {
        putchar(str[i]);
        if(++i % 4 == 0 && str[i])
            putchar(' ');
    }
}

```




```

int invert_end(int num, int bits)
{
    int mask = 0;
    int bitval = 1;

    while (bits-- > 0)
    {
        mask |= bitval;
        bitval <<= 1;
    }

    return num ^ mask;
}

```

Enter integers and see them in binary.
Non-numeric input terminates program.

95↵

95 is

0000 0000 0000 0000 0000 0000 0101 1111

Inverting the last 4 bits gives

0000 0000 0000 0000 0000 0000 0101 0000

168654341↵

168654341 is

0000 1010 0000 1101 0111 0110 0000 0101

Inverting the last 4 bits gives

0000 1010 0000 1101 0111 0110 0000 1010

1↵

1 is

0000 0000 0000 0000 0000 0000 0000 0001

Inverting the last 4 bits gives

0000 0000 0000 0000 0000 0000 0000 1110

q↵

Bye!



位字段

- 位字段是有符号或无符号整型中一组相邻的位

```
struct box_props {  
    bool opaque                : 1;    // or unsigned int (pre C99)  
    unsigned int fill_color    : 3;  
    unsigned int               : 4;  
    bool show_border           : 1;    // or unsigned int (pre C99)  
    unsigned int border_color   : 3;  
    unsigned int border_style   : 2;  
    unsigned int               : 2;  
};
```

- 在内存里如何存储？

— 自低向高、不跨边界、尽量无缝连接、允许省略变量名



```

/* fields.c -- define and use fields */
#include <stdio.h>
#include <stdbool.h>    //C99, defines bool, true, false

/* line styles      */
#define SOLID      0
#define DOTTED    1
#define DASHED    2
/* primary colors   */
#define BLUE      4
#define GREEN     2
#define RED       1
/* mixed colors     */
#define BLACK     0
#define YELLOW    (RED | GREEN)
#define MAGENTA   (RED | BLUE)
#define CYAN      (GREEN | BLUE)
#define WHITE     (RED | GREEN | BLUE)

```



```

const char * colors[8] = {"black", "red", "green", "yellow",
    "blue", "magenta", "cyan", "white"};
struct box_props {
    bool opaque                : 1;    // or unsigned int (pre
C99)
    unsigned int fill_color    : 3;
    unsigned int               : 4;
    bool show_border          : 1;    // or unsigned int (pre
C99)
    unsigned int border_color  : 3;
    unsigned int border_style  : 2;
    unsigned int               : 2;
};

void show_settings(const struct box_props * pb);

int main(void)
{

```



```
/* create and initialize box_props structure */
struct box_props box = {true, YELLOW , true, GREEN,
DASHED};
printf("Original box settings:\n");
show_settings(&box);
box.opaque = false;
box.fill_color = WHITE;
box.border_color = MAGENTA;
box.border_style = SOLID;
printf("\nModified box settings:\n");
show_settings(&box);

return 0;
}

void show_settings(const struct box_props * pb)
{
```



```
printf("Box is %s.\n", pb->opaque == true ? "opaque":  
"transparent");  
printf("The fill color is %s.\n", colors[pb->fill_color]);  
printf("Border %s.\n", pb->show_border == true ? "shown" :  
"not shown");  
printf("The border color is %s.\n", colors[pb-  
>border_color]);  
printf ("The border style is ");  
switch(pb->border_style)  
{  
    case SOLID    : printf("solid.\n"); break;  
    case DOTTED   : printf("dotted.\n"); break;  
    case DASHED   : printf("dashed.\n"); break;  
    default       : printf("unknown type.\n");  
}  
}
```



Original box settings:

Box is opaque.

The fill color is yellow.

Border shown.

The border color is green.

The border style is dashed.

Modified box settings:

Box is transparent.

The fill color is white.

Border shown.

The border color is magenta.

The border style is solid.



位字段与联合

- 见下方实例


```
struct box_props {
    bool opaque                : 1;
    unsigned int fill_color    : 3;
    unsigned int               : 4;
    bool show_border          : 1;
    unsigned int border_color  : 3;
    unsigned int border_style  : 2;
    unsigned int               : 2;
};

union Views /* look at data as struct or as unsigned short */
{
    struct box_props st_view;
    unsigned short us_view;
};
```



位字段与联合

- 例题：整数与结构的联合



```
/* dualview.c -- bit fields and bitwise operators */
#include <stdio.h>
#include <stdbool.h>
#include <limits.h>
/* BIT-FIELD CONSTANTS */
/* line styles */
#define SOLID 0
#define DOTTED 1
#define DASHED 2
/* primary colors */
#define BLUE 4
#define GREEN 2
#define RED 1
/* mixed colors */
#define BLACK 0
#define YELLOW (RED | GREEN)
#define MAGENTA (RED | BLUE)
#define CYAN (GREEN | BLUE)
#define WHITE (RED | GREEN | BLUE)
```



```
/* BITWISE CONSTANTS */
#define OPAQUE          0x1
#define FILL_BLUE      0x8
#define FILL_GREEN     0x4
#define FILL_RED       0x2
#define FILL_MASK      0xE
#define BORDER         0x100
#define BORDER_BLUE    0x800
#define BORDER_GREEN   0x400
#define BORDER_RED     0x200
#define BORDER_MASK    0xE00
#define B_SOLID        0
#define B_DOTTED       0x1000
#define B_DASHED       0x2000
#define STYLE_MASK     0x3000

const char * colors[8] = {"black", "red", "green", "yellow",
    "blue", "magenta", "cyan", "white"};
```



```

struct box_props {

    bool opaque                : 1;
    unsigned int fill_color    : 3;
    unsigned int               : 4;
    bool show_border          : 1;
    unsigned int border_color  : 3;
    unsigned int border_style  : 2;
    unsigned int               : 2;
};

union Views      /* look at data as struct or as unsigned short */
{
    struct box_props st_view;
    unsigned short us_view;
};

void show_settings(const struct box_props * pb);
void show_settings1(unsigned short);
char * itobs(int n, char * ps);

```



```

int main(void)
{
    /* create Views object, initialize struct box view */
    union Views box = {{true, YELLOW, true, GREEN, DASHED}};
    char bin_str[8 * sizeof(unsigned int) + 1];

    printf("Original box settings:\n");
    show_settings(&box.st_view);
    printf("\nBox settings using unsigned int view:\n");
    show_settings1(box.us_view);

    printf("bits are %s\n",
           itobs(box.us_view, bin_str));
    box.us_view &= ~FILL_MASK;           /* clear fill bits */
    box.us_view |= (FILL_BLUE | FILL_GREEN); /* reset fill */
    box.us_view ^= OPAQUE;               /* toggle opacity */
    box.us_view |= BORDER_RED;           /* wrong approach */
    box.us_view &= ~STYLE_MASK;          /* clear style bits */
    box.us_view |= B_DOTTED;             /* set style to dotted */
}

```



```

printf("\nModified box settings:\n");
show_settings(&box.st_view);
printf("\nBox settings using unsigned int view:\n");
show_settings1(box.us_view);
printf("bits are %s\n", itobs(box.us_view, bin_str));
return 0;
}

void show_settings(const struct box_props * pb)
{
    printf("Box is %s.\n", pb->opaque == true ? "opaque":
"transparent");
    printf("The fill color is %s.\n", colors[pb->fill_color]);
    printf("Border %s.\n", pb->show_border == true ? "shown" :
"not shown");
    printf("The border color is %s.\n", colors[pb-
>border_color]);
    printf ("The border style is ");

```



```

switch(pb->border_style)
{
    case SOLID    : printf("solid.\n"); break;
    case DOTTED   : printf("dotted.\n"); break;
    case DASHED   : printf("dashed.\n"); break;
    default       : printf("unknown type.\n");
}
}

void show_settings1(unsigned short us)
{
    printf("box is %s.\n",
        (us & OPAQUE) == OPAQUE? "opaque": "transparent");
    printf("The fill color is %s.\n",
        colors[(us >> 1) & 07]);
    printf("Border %s.\n",
        (us & BORDER) == BORDER? "shown" : "not shown");
    printf ("The border style is ");
}

```



```

switch(us & STYLE_MASK)
{
    case B_SOLID    : printf("solid.\n"); break;
    case B_DOTTED   : printf("dotted.\n"); break;
    case B_DASHED   : printf("dashed.\n"); break;
    default         : printf("unknown type.\n");
}
printf("The border color is %s.\n",
       colors[(us >> 9) & 07]);
}

char * itobs(int n, char * ps)
{
    int i;
    const static int size = CHAR_BIT * sizeof(int);

    for (i = size - 1; i >= 0; i--, n >>= 1)
        ps[i] = (01 & n) + '0';
}

```




```
ps[size] = '\\0';  
  
return ps;  
}
```

Original box settings:
Box is opaque.
The fill color is yellow.
Border shown.
The border color is green.
The border style is dashed.

Box settings using unsigned int view:
box is opaque.
The fill color is black.
Border not shown.
The border style is solid.
The border color is black.
bits are 00000000000000000000000000000001

Modified box settings:
Box is transparent.
The fill color is yellow.
Border shown.
The border color is green.
The border style is dashed.

Box settings using unsigned int view:
box is transparent.
The fill color is cyan.
Border not shown.
The border style is dotted.
The border color is red.
bits are 000000000000000000001001000001100



位字段与联合

- 位字段和按位视图的区别在于后者需要记住位置信息
- 警告：位字段和位的位置之间的对应关系是依赖于实现的。
 - 大端（尾）序和小端序
 - 例如：对于long型数据0x12345678，
按书写习惯0x12最大，0x78最小，
大端序：最大的存在尾部（内存地址较低处），小端反之
 - 3000H : 0x12 ; 3001H : 0x34 ; 3002H : 0x56 ; 3003H : 0x78



```
// align.c -- using _Alignof and Alignas (C11)
```

```
#include <stdio.h>
```

```
int main(void)
```

```
{
```

```
    double dx;
```

```
    char ca;
```

```
    char cx;
```

```
    double dz;
```

```
    char cb;
```

```
    char _Alignas(double) cz;
```

```
    printf("char alignment:   %zd\n", _Alignof(char));
```

```
    printf("double alignment: %zd\n", _Alignof(double));
```

```
    printf("&dx: %p\n", &dx);
```

```
    printf("&ca: %p\n", &ca);
```

```
    printf("&cx: %p\n", &cx);
```

```
    printf("&dz: %p\n", &dz);
```

```
    printf("&cb: %p\n", &cb);
```

```
    printf("&cz: %p\n", &cz);
```

```
    return 0;
```

```
char alignment:   1
```

```
double alignment: 8
```

```
&dx: 0028FEE8
```

```
&ca: 0028FEE7
```

```
&cx: 0028FEE6
```

```
&dz: 0028FED8
```

```
&cb: 0028FED7
```

```
&cz: 0028FED0
```



C程序设计

T15



谢谢

厦门大学信息学院软件工程系

黄炜 副教授