

代码阅读

TINYHTTPD 0.1.0

附加课程



廈門大學
XIAMEN UNIVERSITY



信息学院
(国家示范性软件学院)
School of Informatics

黃 煒
博士, 副教授
Dr. Wei Huang

文件列表

- `.\tinyhttpd-0.1.0\httpd.c`
- `.\tinyhttpd-0.1.0\Makefile`
- `.\tinyhttpd-0.1.0\README`
- `.\tinyhttpd-0.1.0\simpleclient.c`
- `.\tinyhttpd-0.1.0\htdocs`
 - `.\tinyhttpd-0.1.0\htdocs\check.cgi`
 - `.\tinyhttpd-0.1.0\htdocs\color.cgi`
 - `.\tinyhttpd-0.1.0\htdocs\index.html`
 - `.\tinyhttpd-0.1.0\htdocs\README`

[.\tinyhttpd-0.1.0\README]

This software is copyright 1999 by J. David Blackstone. Permission is granted to redistribute and modify this software under the terms of the GNU General Public License, available at <http://www.gnu.org/> .

If you use this software or examine the code, I would appreciate knowing and would be overjoyed to hear about it at jdavidb@sourceforge.net .

This software is not production quality. It comes with no warranty of any kind, not even an implied warranty of fitness for a particular purpose. I am not responsible for the damage that will likely result if you use this software on your computer system.

I wrote this webserver for an assignment in my networking class in 1999. We were told that at a bare minimum the server had to serve pages, and told that we would get extra credit for doing "extras."

Perl had introduced me to a whole lot of UNIX functionality (I learned sockets and fork from Perl!), and O'Reilly's lion book on UNIX system calls plus O'Reilly's books on CGI and writing web clients in Perl got

me thinking and I realized I could make my webserver support CGI with little trouble.

Now, if you're a member of the Apache core group, you might not be impressed. But my professor was blown over. Try the color.cgi sample script and type in "chartreuse." Made me seem smarter than I am, at any rate. :)

Apache it's not. But I do hope that this program is a good educational tool for those interested in http/socket programming, as well as UNIX system calls. (There's some textbook uses of pipes, environment variables, forks, and so on.)

One last thing: if you look at my webserver or (are you out of mind?!?) use it, I would just be overjoyed to hear about it. Please email me. I probably won't really be releasing major updates, but if I help you learn something, I'd love to know!

Happy hacking!

J. David Blackstone

```
[.\tinyhttpd-0.1.0\Makefile]
```

```
all: httpd
```

```
httpd: httpd.c
```

```
gcc -W -Wall -pthread -o httpd httpd.c
```

```
clean:
```

```
rm httpd
```

[.\tinyhttpd-0.1.0\htdocs\README]

These are sample CGI scripts and webpages for tinyhttpd.
They can
be redistributed under the terms of the GPL.

The most impressive demonstration I gave of tinyhttpd to my professor and my classmates was to load color.cgi with a value of "chartreuse." :) It's actually a very simple script, guys.

jdb

```
[.\tinyhttpd-0.1.0\htdocs\index.html]
```

```
<HTML>
```

```
<TITLE>Index</TITLE>
```

```
<BODY>
```

```
<P>Welcome to J. David's webserver.
```

```
<H1>CGI demo
```

```
<FORM ACTION="color.cgi" METHOD="POST">
```

```
Enter a color: <INPUT TYPE="text" NAME="color">
```

```
<INPUT TYPE="submit">
```

```
</FORM>
```

```
</BODY>
```

```
</HTML>
```

```
[.\tinyhttpd-0.1.0\htdocs\color.cgi]
```

```
#!/usr/bin/perl -Tw
```

```
use strict;
```

```
use CGI;
```

```
my($cgi) = new CGI;
```

```
print $cgi->header;
```

```
my($color) = "blue";
```

```
$color = $cgi->param('color') if defined $cgi->param('color');
```

```
print $cgi->start_html(-title => uc($color),  
                      -BGCOLOR => $color);
```

```
print $cgi->h1("This is $color");
```

```
print $cgi->end_html;
```



```
[.\tinyhttpd-0.1.0\htdocs\check.cgi]
```

```
#!/usr/bin/perl -Tw
```

```
use strict;
```

```
use CGI;
```

```
my($cgi) = new CGI;
```

```
print $cgi->header('text/html');
```

```
print $cgi->start_html(-title => "Example CGI script",  
                      -BGCOLOR => 'red');
```

```
print $cgi->h1("CGI Example");
```

```
print $cgi->p, "This is an example of CGI\n";
```

```
print $cgi->p, "Parameters given to this script:\n";
```

```
print "<UL>\n";
```

```
foreach my $param ($cgi->param)
```

```
{
```

```
print "<LI>", "$param ", $cgi->param($param), "\n";  
}  
print "</UL>";  
print $cgi->end_html, "\n";
```

[.\tinyhttpd-0.1.0\simpleclient.c]

```
#include <stdio.h>
#include <sys/types.h>
#include <sys/socket.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <unistd.h>
```

```
int main(int argc, char *argv[])
{
```

```
    int sockfd;
    int len;
    struct sockaddr_in address;
    int result;
    char ch = 'A';
```

```
    sockfd = socket(AF_INET, SOCK_STREAM, 0);
```

```
address.sin_family = AF_INET;
address.sin_addr.s_addr = inet_addr("127.0.0.1");
address.sin_port = htons(8080);
len = sizeof(address);
result = connect(sockfd, (struct sockaddr *)&address, len);

if (result == -1)
{
    perror("oops: client1");
    exit(1);
}
write(sockfd, &ch, 1);
read(sockfd, &ch, 1);
printf("char from server = %c\n", ch);
close(sockfd);
exit(0);
}
```

```
[.\tinyhttpd-0.1.0\httpd.c]
```

```
/* J. David's webserver */
/* This is a simple webserver.
 * Created November 1999 by J. David Blackstone.
 * CSE 4344 (Network concepts), Prof. Zeigler
 * University of Texas at Arlington
 */
/* This program compiles for Sparc Solaris 2.6.
 * To compile for Linux:
 * 1) Comment out the #include <pthread.h> line.
 * 2) Comment out the line that defines the variable newthread.
 * 3) Comment out the two lines that run pthread_create().
 * 4) Uncomment the line that runs accept_request().
 * 5) Remove -lsocket from the Makefile.
 */
#include <stdio.h>
#include <sys/socket.h>
```

```
#include <sys/types.h>
#include <netinet/in.h>
#include <arpa/inet.h>
#include <unistd.h>
#include <ctype.h>
#include <strings.h>
#include <string.h>
#include <sys/stat.h>
#include <pthread.h>
#include <sys/wait.h>
#include <stdlib.h>

#define ISspace(x) isspace((int)(x))

#define SERVER_STRING "Server: jdbhttpd/0.1.0\r\n"

void *accept_request(void *);
void bad_request(int);
```

```

void cat(int, FILE *);
void cannot_execute(int);
void error_die(const char *);
void execute_cgi(int, const char *, const char *, const char *);
int get_line(int, char *, int);
void headers(int, const char *);
void not_found(int);
void serve_file(int, const char *);
int startup(u_short *);
void unimplemented(int);

/*****
/* A request has caused a call to accept() on the server port to
* return. Process the request appropriately.
* Parameters: the socket connected to the client */
*****/
void *accept_request(void *args)
{

```

```

char buf[1024];
int numchars;
char method[255];
char url[255];
char path[512];
size_t i, j;
struct stat st;
int cgi = 0;          /* becomes true if server decides this is a CGI
                       * program */
char *query_string = NULL;
int client = ((int *)args)[0];
numchars = get_line(client, buf, sizeof(buf));
i = 0; j = 0;
while (!isspace(buf[j]) && (i < sizeof(method) - 1))
{
    method[i] = buf[j];
    i++; j++;
}

```



```

method[i] = '\0';

if (strcasecmp(method, "GET") && strcasecmp(method, "POST"))
{
    unimplemented(client);
    return NULL;
}

if (strcasecmp(method, "POST") == 0)
    cgi = 1;

i = 0;
while (isspace(buf[j]) && (j < sizeof(buf)))
    j++;
while (!isspace(buf[j]) && (i < sizeof(url) - 1) && (j <
sizeof(buf)))
{
    url[i] = buf[j];

```

```
        i++; j++;
    }
    url[i] = '\0';

    if (strcasecmp(method, "GET") == 0)
    {
        query_string = url;
        while ((*query_string != '?') && (*query_string != '\0'))
            query_string++;
        if (*query_string == '?')
        {
            cgi = 1;
            *query_string = '\0';
            query_string++;
        }
    }

    sprintf(path, "htdocs%s", url);
```

```

if (path[strlen(path) - 1] == '/')
    strcat(path, "index.html");
if (stat(path, &st) == -1) {
    while ((numchars > 0) && strcmp("\n", buf)) /* read
& discard headers */
        numchars = get_line(client, buf, sizeof(buf));
    not_found(client);
}
else
{
    if ((st.st_mode & S_IFMT) == S_IFDIR)
        strcat(path, "/index.html");
    if ((st.st_mode & S_IXUSR) ||
        (st.st_mode & S_IXGRP) ||
        (st.st_mode & S_IXOTH))
        cgi = 1;
    if (!cgi)
        serve_file(client, path);
}

```

```

        else
            execute_cgi(client, path, method, query_string);
    }

    close(client);
    return NULL;
}

/*****
/* Inform the client that a request it has made has a problem.
* Parameters: client socket */
*****/

void bad_request(int client)
{
    char buf[1024];

    sprintf(buf, "HTTP/1.0 400 BAD REQUEST\r\n");
    send(client, buf, sizeof(buf), 0);
}

```

```

    sprintf(buf, "Content-type: text/html\r\n");
    send(client, buf, sizeof(buf), 0);
    sprintf(buf, "\r\n");
    send(client, buf, sizeof(buf), 0);
    sprintf(buf, "<P>Your browser sent a bad request, ");
    send(client, buf, sizeof(buf), 0);
    sprintf(buf, "such as a POST without a Content-
Length.\r\n");
    send(client, buf, sizeof(buf), 0);
}

/*****
/* Put the entire contents of a file out on a socket. This function
* is named after the UNIX "cat" command, because it might have been
* easier just to do something like pipe, fork, and exec("cat").
* Parameters: the client socket descriptor
*             FILE pointer for the file to cat */
*****/
void cat(int client, FILE *resource)

```

```

{
    char buf[1024];

    fgets(buf, sizeof(buf), resource);
    while (!feof(resource))
    {
        send(client, buf, strlen(buf), 0);
        fgets(buf, sizeof(buf), resource);
    }
}

/*****
/* Inform the client that a CGI script could not be executed.
* Parameter: the client socket descriptor. */
*****/
void cannot_execute(int client)
{
    char buf[1024];

```

```

    sprintf(buf, "HTTP/1.0 500 Internal Server Error\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "Content-type: text/html\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "<P>Error prohibited CGI execution.\r\n");
    send(client, buf, strlen(buf), 0);
}

/*****
/* Print out an error message with perror() (for system errors; based
* on value of errno, which indicates system call errors) and exit the
* program indicating an error. */
*****/

void error_die(const char *sc)
{
    perror(sc);

```

```

    exit(1);
}

/*****
/* Execute a CGI script. Will need to set environment variables as
* appropriate.
* Parameters: client socket descriptor
*             path to the CGI script */
*****/
void execute_cgi(int client, const char *path,
                 const char *method, const char *query_string)
{
    char buf[1024];
    int cgi_output[2];
    int cgi_input[2];
    pid_t pid;
    int status;
    int i;

```



```

char c;
int numchars = 1;
int content_length = -1;

buf[0] = 'A'; buf[1] = '\0';
if (strcasecmp(method, "GET") == 0)
    while ((numchars > 0) && strcmp("\n", buf)) /* read
& discard headers */
        numchars = get_line(client, buf, sizeof(buf));
else /* POST */
{
    numchars = get_line(client, buf, sizeof(buf));
    while ((numchars > 0) && strcmp("\n", buf))
    {
        buf[15] = '\0';
        if (strcasecmp(buf, "Content-Length:") == 0)
            content_length = atoi(&(buf[16]));
        numchars = get_line(client, buf, sizeof(buf));
    }
}

```

```

    }
    if (content_length == -1) {
        bad_request(client);
        return;
    }
}

sprintf(buf, "HTTP/1.0 200 OK\r\n");
send(client, buf, strlen(buf), 0);

if (pipe(cgi_output) < 0) {
    cannot_execute(client);
    return;
}
if (pipe(cgi_input) < 0) {
    cannot_execute(client);
    return;
}

```

```

if ((pid = fork()) < 0) {
    cannot_execute(client);
    return;
}
if (pid == 0) /* child: CGI script */
{
    char meth_env[255];
    char query_env[255];
    char length_env[255];

    dup2(cgi_output[1], 1);
    dup2(cgi_input[0], 0);
    close(cgi_output[0]);
    close(cgi_input[1]);
    sprintf(meth_env, "REQUEST_METHOD=%s", method);
    putenv(meth_env);
    if (strcasecmp(method, "GET") == 0) {
        sprintf(query_env, "QUERY_STRING=%s", query_string);
    }
}

```

```

        putenv(query_env);
    }
    else {    /* POST */
        sprintf(length_env, "CONTENT_LENGTH=%d",
content_length);
        putenv(length_env);
    }
    execl(path, path, NULL);
    exit(0);
}
else {    /* parent */
    close(cgi_output[1]);
    close(cgi_input[0]);
    if (strcasecmp(method, "POST") == 0)
        for (i = 0; i < content_length; i++) {
            recv(client, &c, 1, 0);
            write(cgi_input[1], &c, 1);
        }
}

```

```

while (read(cgi_output[0], &c, 1) > 0)
    send(client, &c, 1, 0);

close(cgi_output[0]);
close(cgi_input[1]);
waitpid(pid, &status, 0);
}
}

/*****
/* Get a line from a socket, whether the line ends in a newline,
* carriage return, or a CRLF combination. Terminates the string read
* with a null character. If no newline indicator is found before the
* end of the buffer, the string is terminated with a null. If any of
* the above three line terminators is read, the last character of the
* string will be a linefeed and the string will be terminated with a
* null character.
* Parameters: the socket descriptor
*             the buffer to save the data in
*             the size of the buffer
* Returns: the number of bytes stored (excluding null) */
*****/

```

```

int get_line(int sock, char *buf, int size)
{
    int i = 0;
    char c = '\0';
    int n;

    while ((i < size - 1) && (c != '\n'))
    {
        n = recv(sock, &c, 1, 0);
        /* DEBUG printf("%02X\n", c); */
        if (n > 0)
        {
            if (c == '\r')
            {
                n = recv(sock, &c, 1, MSG_PEEK);
                /* DEBUG printf("%02X\n", c); */
                if ((n > 0) && (c == '\n'))
                    recv(sock, &c, 1, 0);
            }
        }
    }
}

```

```

        else
            c = '\n';
        }
        buf[i] = c;
        i++;
    }
    else
        c = '\n';
    }
    buf[i] = '\0';

    return(i);
}

/*****
/* Return the informational HTTP headers about a file. */
/* Parameters: the socket to print the headers on
*               the name of the file */
*****/

```

```

void headers(int client, const char *filename)
{
    char buf[1024];
    (void)filename; /* could use filename to determine file type */

    strcpy(buf, "HTTP/1.0 200 OK\r\n");
    send(client, buf, strlen(buf), 0);
    strcpy(buf, SERVER_STRING);
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "Content-Type: text/html\r\n");
    send(client, buf, strlen(buf), 0);
    strcpy(buf, "\r\n");
    send(client, buf, strlen(buf), 0);
}

/*****
/* Give a client a 404 not found status message. */
*****/

```



```

void not_found(int client)
{
    char buf[1024];

    sprintf(buf, "HTTP/1.0 404 NOT FOUND\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, SERVER_STRING);
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "Content-Type: text/html\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "<HTML><TITLE>Not Found</TITLE>\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "<BODY><P>The server could not fulfill\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "your request because the resource
specified\r\n");
}

```

```

send(client, buf, strlen(buf), 0);
sprintf(buf, "is unavailable or nonexistent.\r\n");
send(client, buf, strlen(buf), 0);
sprintf(buf, "</BODY></HTML>\r\n");
send(client, buf, strlen(buf), 0);
}

/*****
/* Send a regular file to the client. Use headers, and report
* errors to client if they occur.
* Parameters: a pointer to a file structure produced from the socket
*             file descriptor
*             the name of the file to serve */
*****/
void serve_file(int client, const char *filename)
{
    FILE *resource = NULL;
    int numchars = 1;
    char buf[1024];

```

```

    buf[0] = 'A'; buf[1] = '\0';
    while ((numchars > 0) && strcmp("\n", buf)) /* read &
discard headers */
        numchars = get_line(client, buf, sizeof(buf));

resource = fopen(filename, "r");
if (resource == NULL)
    not_found(client);
else
{
    headers(client, filename);
    cat(client, resource);
}
fclose(resource);
}

```

```

/*****
/* This function starts the process of listening for web connections
* on a specified port. If the port is 0, then dynamically allocate a
* port and modify the original port variable to reflect the actual
* port.
* Parameters: pointer to variable containing the port to connect on
* Returns: the socket */
*****/

int startup(u_short *port)
{
    int httpd = 0;
    struct sockaddr_in name;

    httpd = socket(PF_INET, SOCK_STREAM, 0);
    if (httpd == -1)
        error_die("socket");
    memset(&name, 0, sizeof(name));
    name.sin_family = AF_INET;
    name.sin_port = htons(*port);
    name.sin_addr.s_addr = htonl(INADDR_ANY);

```

```

if (bind(httpd, (struct sockaddr *)&name, sizeof(name)) < 0)
    error_die("bind");
if (*port == 0) /* if dynamically allocating a port */
{
    int namelen = sizeof(name);
    if (getsockname(httpd, (struct sockaddr *)&name,
&namelen) == -1)
        error_die("getsockname");
    *port = ntohs(name.sin_port);
}
if (listen(httpd, 5) < 0)
    error_die("listen");

return(httpd);
}

```

```

/*****
/* Inform the client that the requested web method has not been
* implemented.
* Parameter: the client socket */
*****/
void unimplemented(int client)
{
    char buf[1024];

    sprintf(buf, "HTTP/1.0 501 Method Not Implemented\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, SERVER_STRING);
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "Content-Type: text/html\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "\r\n");
    send(client, buf, strlen(buf), 0);
    sprintf(buf, "<HTML><HEAD><TITLE>Method Not
Implemented\r\n");

```

```

send(client, buf, strlen(buf), 0);
sprintf(buf, "</TITLE></HEAD>\r\n");
send(client, buf, strlen(buf), 0);
sprintf(buf, "<BODY><P>HTTP request method not supported.\r\n");
send(client, buf, strlen(buf), 0);
sprintf(buf, "</BODY></HTML>\r\n");
send(client, buf, strlen(buf), 0);
}
/*****
int main(void)
{
    int server_sock = -1;
    u_short port = 8080;
    int client_sock = -1;
    struct sockaddr_in client_name;
    int client_name_len = sizeof(client_name);
    pthread_t newthread;
    server_sock = startup(&port);

```

```

printf("httpd running on port %d\n", port);

while (1)
{
    client_sock = accept(server_sock,
        (struct sockaddr *)&client_name,
        &client_name_len);
    if (client_sock == -1)
        error_die("accept");
    /* accept_request(client_sock); */
    if (pthread_create(&newthread, NULL, accept_request,
&client_sock) != 0)
        perror("pthread_create");
}
close(server_sock);

return(0);
}

```


A3

代码阅读

TINYHTTPD 0.1.0

附加课程



廈門大學
XIAMEN UNIVERSITY



信息学院
(国家示范性软件学院)
School of Informatics

黃 煒
博士, 副教授
Dr. Wei Huang