

Module 3: Heritability and Reliability Estimations in R

Fundamentals of Genomic Prediction and Data-Drive Crop Breeding

(August 4-8, 2025)



Waseem Hussain

Senior Scientist-I

International Rice Research Institute

Rice Breeding Innovations Platform

waseem.hussain@cgiar.org

whussain2.github.io

Mahender Anumalla

Scientist-I

International Rice Research Institute

South-Asian Hub, Hyderabad

m.anumalla@cgiar.org

August 5, 2025

Contents

Load the Libraries	1
Upload the Phenotypic Data Sets	1
Run the Model to Estimate Heritability	2
Heritability Based on Single Environment	2
Run the mixed model	2
Extract Results and Variance Components	3
Extract variance components	3
ANOVA for fixed effects	4
Extract the Fixed effects	4
Extract the Random effects	4
Heritability	4
Heritability Based on Variance Components	4
Reliability based on Cullis et al.	5
Heritability Based on MET Analysis	5
Combined ANOVA	5
Combined Analysis in lme4	6
Summary of MET results	6
Plot of model	7
Reliability Using Mean Difference	7
Additional Resources	8

Load the Libraries

```
> # Load the Required Libraries
> rm(list=ls()) # Remove previous work
> library(easypackages)
> libraries("dplyr", "reshape2", "readxl", "lme4", "arm")
```

Upload the Phenotypic Data Sets

Here we will use the Rainfed Rice Breeding Trial data of IRRI which has 192 entries, 2 replications and 5 blocks and experimental design is Alpha lattice.

```
> # Read the saved csv file, if working directly
> demo.data.filtered<-read.csv(file="demo.data.filtered2.csv",
+                             header = TRUE)
> str(demo.data.filtered)
```

```
'data.frame':  1600 obs. of  11 variables:
 $ Environment: chr  "Env1" "Env1" "Env1" "Env1" ...
 $ Plot       : int  59 19 27 127 132 92 106 82 199 57 ...
 $ Genotype   : int  1 2 3 4 5 6 7 8 9 10 ...
 $ Rep        : int  1 1 1 1 1 1 1 1 1 1 ...
 $ Block      : int  2 1 1 4 4 3 3 3 5 2 ...
 $ Row        : int  2 1 1 4 4 3 3 3 5 2 ...
 $ Column     : int  19 19 27 7 12 12 26 2 39 17 ...
 $ Line.type  : chr  "Entry" "Entry" "Entry" "Entry" ...
 $ DTF        : int  94 78 87 87 94 94 82 87 82 85 ...
```

```

$ HT          : num  118 116 108 116 134 ...
$ Yield       : num  5873 5844 5777 6284 5703 ...

> # factor conversion if below are not in factors
> columns<-c("Environment", "Genotype", "Rep", "Block",
+           "Row", "Column", "Line.type")
> demo.data.filtered[, columns]<-lapply(columns, function(x) as.factor(demo.data.filtered[[x]]))
> demo.data.filtered$Yield<-as.numeric(demo.data.filtered$Yield)
> demo.data.filtered$HT<-as.numeric(demo.data.filtered$HT)
> demo.data.filtered$DTF<-as.numeric(demo.data.filtered$DTF)
> # Subset the required columns
> demo.data.filtered<-demo.data.filtered[, c("Environment", "Genotype",
+           "Rep", "Block", "Row", "Column",
+           "Line.type", "Yield", "HT", "DTF")]
> # First we will arrange the rows and columns for spatial analysis.
> # Now we will subset the environments and Yields for analysis
> demo.data.filtered<-data.frame(demo.data.filtered%>% group_by(Environment)%>% arrange(Row, Column))
> demo.data.filtered<-data.frame(demo.data.filtered%>% arrange(Environment)) # Arrange by environment

```

Run the Model to Estimate Heritability

- Here in this section we will use open source R package called **lme4** to run the mixed-model and extract variance components
- More on this R package can be found here [lme4 Tutorial 1](#), and [lme4 Tutorial 2](#).

Heritability Based on Single Environment

- First let us subset the data for on environment to show how to perform the analysis for one trial or environment in lme4 R package
- We will run models which are feasible in lme4 R package.
- We will use basic models and show how to extract the results
- Subset the data for one environment first.

```

> # Subset the environment 1
> sub.data<-subset(demo.data.filtered, Environment=="Env1")
> sub.data<-droplevels.data.frame(sub.data)

```

Run the mixed model

Model 1.lme4

- The model described below is:

$$y_{ijk} = \mu + g_i + r_j + b_{jk} + \epsilon_{ijk}$$

y_{ijk} = is the effect of i th genotype in j th replication and k th block within the j th replication

μ = overall mean

g_i = random effect of the i th genotype

r_j = fixed effect of the j th replication

b_{jk} = random effect of k th block nested within j replication

ε_{ijk} = residual error

here we assume errors are independent and identically distributed $\epsilon \sim iidN(0, \sigma_\epsilon^2)$

```
> # Now apply model
> model1<-lmer(Yield~Rep+(1|Genotype)+(1|Rep:Block), data =sub.data)
```

Extract Results and Variance Components

- Here we will summarize the results using *summary()* function.
- The first few lines of output indicate that the model was fitted by REML as well as the value of the REML criterion.
- The second piece of the summary output provides information regarding the random-effects and residual variation.
- The third piece of the summary output provides information regarding the fixed-effects and the fourth piece of summary output provides information regarding the correlation of fixed effects.

```
> # Summarise the results
> summary(model1)
```

```
Linear mixed model fit by REML ['lmerMod']
Formula: Yield ~ Rep + (1 | Genotype) + (1 | Rep:Block)
Data: sub.data
```

REML criterion at convergence: 6239.3

Scaled residuals:

Min	1Q	Median	3Q	Max
-1.90048	-0.59387	0.03899	0.60311	1.71001

Random effects:

Groups	Name	Variance	Std.Dev.
Genotype	(Intercept)	431861	657.2
Rep:Block	(Intercept)	28499	168.8
Residual		193255	439.6

Number of obs: 394, groups: Genotype, 197; Rep:Block, 10

Fixed effects:

	Estimate	Std. Error	t value
(Intercept)	5233.19	94.20	55.552
Rep2	60.38	115.60	0.522

Correlation of Fixed Effects:

	(Intr)
Rep2	-0.614

Extract variance components

- Here we will extract variance components

```
> Ve<- VarCorr(model1)
> Ve
```

Groups	Name	Std.Dev.
Genotype	(Intercept)	657.16

```
Rep:Block (Intercept) 168.82
Residual              439.61
```

ANOVA for fixed effects

```
> # ANOVA
> anova(model1)
```

	npar	Sum Sq	Mean Sq	F value
Rep	1	52724.26	52724.26	0.2728223

Extract the Fixed effects

- Here will show how to extract the BLUEs.

```
> BLUEs<-fixef(model1)
> BLUEs
```

```
(Intercept)      Rep2
5233.1856      60.3794
```

Extract the Random effects

- Here will show how to extract the BLUPs.

```
> # Extract the Random effects
> BLUPs<-data.frame(Blups.yield=ranef(model1)$Genotype)
> GV<-data.frame(BLUPs.GY=coef(model1)$Genotype[,1]) #Genotype values (Blups +Intercept)
```

Heritability

- Here will show how to calculate the heritability. Two approaches will be show how to estimate heritability: 1) Based on Variance components and 2) Based on Cullis et al. 2006 is also $1 - \frac{\bar{V}_{BLUP}}{2\sigma^2_g}$. Where \bar{V}_{BLUP} is mean variance difference of two genotypes based on BLUPs and σ^2_g is variance of genotypes.

Heritability Based on Varaince Components

```
> # Extract the variance components
> Ve<- data.frame (VarCorr(model1))
> Ve
```

grp	var1	var2	vcov	sdcor
Genotype	(Intercept)	NA	431860.94	657.1613
Rep:Block	(Intercept)	NA	28498.55	168.8151
Residual	NA	NA	193254.94	439.6077

```
> # Now calculate heritability using variance components
> genotype.var=Ve[1,4]
> error.var=Ve[2,4]
> # Now heritability
> h2=genotype.var/(genotype.var+error.var)*100
> h2
```

```
[1] 93.8095
```

Reliability based on Cullis et al.

```
> # Reliability
> std.err<-se.ranef(model1)$Genotype
> v_BLUP<- mean(std.err)
> # Heritability/Reliability
> h2<- (1-((v_BLUP)^2/(Ve[1,4]*2)))*100
> h2
```

```
[1] 90.55036
```

Heritability Based on MET Analysis

Model 2.lme4

- Here we will analyze all the environments jointly and extract the single BLUPs for each genotype.
- We will use mixed model analysis in lme4 r package model.
- We will treat genotypes as random and environment as fixed effect.

Combined ANOVA

- Here ANOVA will be generated for all the factor levels.
- Replications are nested with environments and Blocks are within Replications which are nested within environment.

```
> # Linear model to get ANOVA
> demo.data.filtered$Environment<-as.factor(demo.data.filtered$Environment)
> model.anova<-lm(formula = Yield~Genotype+Environment+Genotype*Environment+Environment:Rep+ Environment:Block,
+ data=demo.data.filtered)
> # Get ANOVA
> anova(model.anova)
```

	Df	Sum Sq	Mean Sq	F value	Pr(>F)
Genotype	199	547177221	2749634	5.577295	0.00e+00
Environment	3	2081940510	693980170	1407.653397	0.00e+00
Genotype:Environment	588	1002589262	1705084	3.458553	0.00e+00
Environment:Rep	4	22794162	5698541	11.558788	0.00e+00
Environment:Rep:Block	32	37568681	1174021	2.381358	3.54e-05
Residuals	754	371725774	493005	NA	NA

Significant differences are observed for all factors and genotype by environment interactions are significant

Combined Analysis in lme4

- The model we will use is give below:

$$y_{ijkl} = \mu + g_i + e_j + (ge)_{ij} + r_{jk} + b_{jkl} + \epsilon_{ijklm}$$

μ = overall mean

g_i = random effect of the i th genotype

e_j = random effect of the j th environment

$(ge)_{ij}$ = is the interaction effect of i th genotypes with the j th environment

r_{jk} = fixed effect of the k th replication nested within j th environment

b_{jkl} = random effect of l th block nested with j environment and k th replication

ϵ_{ijkl} = residual error

here we assume residuals are independent and identically distributed

- Mixed models are powerful tools to handle assumptions of linear model Read this one
- We will extract variance components and also calculate heritability.

```
> demo.data.filtered$Environment<-as.factor(demo.data.filtered$Environment)
> Model3.lme4<-lmer(Yield~Rep+(1|Genotype)+(1|Environment)+
+ (1|Block), data=demo.data.filtered)
```

Summary of MET results

- In summary we will get following summarized results: 1) Description of model we used, 2) Random effects and variances, 3) Fixed effects, 4) Correlation of fixed effects

```
> summary(Model3.lme4)
```

Linear mixed model fit by REML ['lmerMod']

Formula: Yield ~ Rep + (1 | Genotype) + (1 | Environment) + (1 | Block)

Data: demo.data.filtered

REML criterion at convergence: 26571.7

Scaled residuals:

	Min	1Q	Median	3Q	Max
	-3.7537	-0.5702	-0.0115	0.4669	5.3187

Random effects:

Groups	Name	Variance	Std.Dev.
Genotype	(Intercept)	205131	452.9
Block	(Intercept)	7224	85.0
Environment	(Intercept)	1789049	1337.6
Residual		1033082	1016.4

Number of obs: 1581, groups: Genotype, 200; Block, 5; Environment, 4

Fixed effects:

	Estimate	Std. Error	t value
(Intercept)	4740.65	671.60	7.059

```
Rep2          -151.88      51.13  -2.971
```

Correlation of Fixed Effects:


(Intr)

```
Rep2 -0.038
```

Plot of model

- With the plot function model we will get the residuals vs fitted values

```
> plot(Model13.lme4)
```



Reliability Using Mean Difference

- Based on Cullis et al.2006

```
> # Extract the variance components
> Ve<- data.frame (VarCorr(Model13.lme4))
> Ve
```

grp	var1	var2	vcov	sdcov
Genotype	(Intercept)	NA	205131.050	452.91395
Block	(Intercept)	NA	7224.397	84.99645
Environment	(Intercept)	NA	1789048.808	1337.55329
Residual	NA	NA	1033082.471	1016.40665

```
> std.err<-se.ranef(Model13.lme4)$Genotype
> v_BLUP<- mean(std.err)
> # Heritability/Reliability
```



```
> h2<- (1-((v_BLUP)^2/(Ve[1,4]*2)))*100
> h2
```

```
[1] 80.29987
```

Additional Resources

- Here In this section we have provided additional R resources where similar analysis and mixed models can be run:
- Fitting linear mixed-effects models using lme4
- Linear Mixed-Effects Models Using R
- sommer: Solving Mixed Model Equations in R
- robustlmm
- Introduction to Linear Mixed Models
- Computing Heritability and Selection Response From Unbalanced Plant Breeding Trials
- Estimating Broad-Sense Heritability with Unbalanced Data from Agricultural Cultivar Trials

Note: For questions specific to data analysis shown here contact waseem.hussain@irri.org

If your experiment needs a statistician, you need a better experiment - Ernest Rutherford