

Synopsis
On

Smart Parking Assistant with Real-Time Vehicle Number Plate Recognition (ALPR)



BACHELOR OF TECHNOLOGY

DEPARTMENT OF COMPUTER SCIENCE & ENGINEERING (AI)

3rd Semester (2024–25)

Submitted By:

Anjali Tiwari (2301321520024)
Ankit Raj (2301321520025)
Ankita (2301321520026)

Project Supervisor:

Mr. Pancham
Assistant Professor
Department of CSE-AI

Greater Noida Institute of Technology (Engg. Institute), Greater Noida
Dr. A.P.J. Abdul Kalam Technical University, Lucknow

October, 2024

INDEX

S.No.	Topic	Page No.
1.	Introduction	3
	1.1. Problem Statement	4
	1.2. Scope of Project	5
2.	Tools / Environment Used	6
3.	Analysis Document	7
	3.1. E-R Diagram & Database Schema	7
	3.2. System Architecture & Data Flow Diagram	8
4.	Limitations of the Project	9
5.	Result and Future Scope of the Project	10
	5.1. Result and Key Findings	10
	5.2. Future Scope and Enhancements	10

1. INTRODUCTION

INTRODUCTION TO SMART PARKING & ALPR SYSTEM

With the rapid pace of urbanization and the continuous increase in automobile density across metropolitan centers, traditional parking management infrastructures have become severe operational bottlenecks. Manual parking systems—which rely heavily on human security personnel issuing hand-written paper slips, plastic barcode tokens, or physical cash collection—suffer from notable systemic delays, long vehicular queues at entry boom barriers, high labor overheads, and frequent revenue leakage.

The **Smart Parking Assistant with Real-Time Automatic License Plate Recognition (ALPR)** is an intelligent, automated computer vision and web-based solution designed to transform physical parking operations into a seamless, digitized process. The system integrates modern deep learning object detection algorithms (YOLOv8) with advanced optical character recognition (EasyOCR) to automatically detect arriving vehicles, isolate license plate bounding boxes, extract registration alphanumeric strings, and assign optimal vacant parking bays without requiring physical intervention.

Unlike conventional standalone recognition scripts, this project bridges the physical computer vision pipeline with a full-stack, interactive web application. It features a **Dual-Role Architecture** tailored to two principal stakeholders:

- **Parking Assistant (Gate Attendant):** Equipped with a live operations console featuring real-time camera/image ALPR scanning, an interactive 2D parking lot occupancy map, 1-click slot allotment, and an automated checkout billing desk.
- **Vehicle Driver:** Equipped with a self-service portal displaying live vacant bay counts, self-check-in allotment, a high-contrast Digital Parking Pass with QR/barcode reference, and turn-by-turn wayfinding directions from Entry Gate 1 to their assigned spot.

By automating vehicle tracking from entry to checkout, the system accelerates ingress and egress flow, minimizes fuel wastage caused by drivers aimlessly circling parking garages, guarantees transparent revenue logging, and establishes an intelligent smart-city foundation.

1.1 PROBLEM STATEMENT

Contemporary urban parking facilities in commercial malls, university campuses, IT parks, and transit hubs face critical operational inefficiencies that compromise safety, throughput, and driver satisfaction:

- 1. Manual Ingress Bottlenecks and Gate Queuing:** Gate attendants must manually inspect each vehicle, enter plate details into handheld machines, or issue physical paper tokens. During morning rush hours and peak commercial times, this manual process causes severe queues spilling over onto public roadways, creating congestion and elevated carbon emissions.
- 2. Lack of Real-Time Bay Occupancy Visibility:** Upon clearing the security gate, drivers possess zero visibility regarding which aisles, floors, or sections contain vacant spaces. Research shows that drivers spend an average of 7 to 14 minutes merely circling parking floors to locate a vacant space, resulting in elevated stress, wasted fuel, and internal garage gridlocks.
- 3. Financial Disputes and Revenue Leakage:** Paper slips and magnetic tokens are easily misplaced, stolen, or damaged. Calculating parking duration based on hand-written receipts frequently creates disputes between motorists and attendants, while cash transactions without immutable audit logs lead to substantial revenue leakages for facility operators.
- 4. High Complexity of Indian Vehicle License Plates:** Implementing automated ALPR in Indian environments presents unique challenges. Indian plates feature diverse regional state codes (DL, HR, MH, UP, KA, etc.), variable non-standard font variations, two-line stacked layouts (common on two-wheelers and commercial vehicles), and severe environmental degradation such as dust, scratches, low ambient illumination, and camera glare.

The Challenge: To develop a robust, end-to-end intelligent Smart Parking Assistant capable of delivering high-accuracy license plate recognition across challenging real-world Indian road scenarios, maintaining an atomic real-time map of vacant vs. occupied spaces, and automating bay allotment and tariff billing through an accessible dual-role interface.

1.2 SCOPE OF PROJECT

The scope of this project encompasses the end-to-end design, implementation, evaluation, and deployment of a full-stack Smart Parking Assistant. It spans the following core functional modules:

- **Vehicle & License Plate Detection Module:** Dual deep learning pipeline utilizing YOLOv8n for vehicle identification (cars, SUVs, motorcycles) and a fine-tuned custom YOLOv8 model for locating license plate bounding boxes with context padding to prevent character clipping.
- **Multi-Pass Image Enhancement & Preprocessing:** Super-resolution cubic upscaling (minimum 120px height), Bilateral noise filtering to maintain crisp character boundaries, Contrast Limited Adaptive Histogram Equalization (CLAHE), and Otsu adaptive binarization.
- **Optical Character Recognition (OCR) Engine:** EasyOCR character extraction operating across multiple preprocessed image representations, equipped with spatial token sorting that assembles fragmented bounding boxes horizontally or vertically based on plate aspect ratio.
- **Indian Plate Format Normalizer & Validator:** Rule-based character disambiguation correcting common optical confusions (O/0, I/1, Z/2, S/5, B/8) and matching candidate strings against standard RTO state codes and the national Indian plate regex: `^[A-Z]{2}[0-9]{1,2}[A-Z]{0,2}[0-9]{4}$`.
- **Interactive 2D Parking Bay Map & Allotment Engine:** Dynamic visual bay grid representing Ground Floor (Section A), Level 1 (Section B), and EV Priority (Section C). Implements automated optimal vacant slot assignment and manual operator overrides.
- **Parking Assistant Operations Console:** Web-based attendant control center supporting live webcam streaming, photo uploads, test dataset presets, 2D occupancy visualization, duration counters, and 1-click checkout with printable receipts.
- **Driver Self-Service Portal:** Driver portal showing real-time vacancy counts, self-check-in, digital parking passes with barcodes, and turn-by-turn navigation directions from Entry Gate 1 to the assigned parking bay.
- **Transaction Logging & Tariff Calculation:** Atomic SQLite database maintaining audit logs of entry/exit timestamps, elapsed durations, hourly tariff calculation (₹30/hr), and revenue metrics.

2. TOOLS / ENVIRONMENT USED

Below are the specialized tools, programming languages, libraries, and environments utilized in developing the Smart Parking Assistant:

Category	Technology / Tool	Functional Purpose
Programming Language	Python 3.10 / 3.11	Core language for computer vision, AI inference, and backend web logic.
Web Framework	Flask 3.1	Micro-web framework providing session management, template rendering, and RESTful JSON APIs.
Deep Learning Framework	Ultralytics YOLOv8 & PyTorch	Dual-stage YOLOv8 models for vehicle classification and license plate bounding box localization.
Computer Vision	OpenCV (cv2) 4.13	Image preprocessing: cubic upscaling, bilateral filtering, CLAHE contrast enhancement, and annotation rendering.
OCR Engine	EasyOCR 1.7	Deep learning optical character reader with PyTorch-backed alphanumeric extraction.
Database	SQLite 3	Relational database engine for atomic storage of users, parking slots, and historical parking tickets.
Frontend UI	HTML5, CSS3, JavaScript	Modern responsive interface with glassmorphism dark-mode aesthetics.
UI Components	Bootstrap 5.3 & FontAwesome 6	Responsive grid system, interactive modals, navigation pills, and vector iconography.
Development IDE	Visual Studio Code (VS Code)	Source code editing, virtual environment debugging (yolov8_env), and terminal management.
Version Control	Git & GitHub	Repository hosting, change tracking, and continuous code synchronization.

Hardware Requirements:

- **Camera Sensor:** Standard HD USB webcam, integrated laptop camera, or RTSP IP surveillance camera (minimum 720p).
- **Processor (CPU):** Intel Core i5 / AMD Ryzen 5 (or higher) with multi-threading capabilities.
- **System Memory (RAM):** 8 GB minimum (16 GB recommended for concurrent YOLO + EasyOCR execution).
- **Storage:** Minimum 5 GB free disk space for PyTorch models, weight files (`best.pt`, `yolov8n.pt`), and database logs.

3. ANALYSIS DOCUMENT


3.1. ENTITY-RELATIONSHIP (E-R) & DATABASE SCHEMA

The relational database schema is modeled in SQLite (`parking\_system.db`) and consists of three principal entities: **USERS**, **PARKING_SLOTS**, and **PARKING_RECORDS**. Below is the structural data dictionary and relational mapping:

Table	Field Name	Type & Constraint	Description
users	id	INTEGER (PK, AI)	Unique user identifier.
users	username	TEXT (Unique)	Login username (e.g. 'assistant', 'driver').
users	password_hash	TEXT	Securely hashed password (PBKDF2-SHA256).
users	role	TEXT	'assistant' for staff, 'driver' for vehicle owners.
users	vehicle_plate	TEXT	Registered vehicle license plate number.
parking_slots	slot_number	TEXT (Unique, PK)	Physical bay identifier (e.g. 'A-01', 'B-02', 'C-01').
parking_slots	section	TEXT	Facility zone ('Section A (Ground)', 'Section B', 'Section C (EV)').
parking_slots	slot_type	TEXT	Category ('Standard', 'Compact', 'EV').
parking_slots	is_occupied	INTEGER	Binary status: 0 for Vacant (Green), 1 for Occupied (Red).
parking_slots	current_plate	TEXT (FK)	Plate number of currently parked vehicle.
parking_slots	entry_time	TIMESTAMP	Time vehicle was allotted to this bay.
parking_records	ticket_id	TEXT (Unique, PK)	Unique ticket reference (e.g. 'TKT-1788989032').
parking_records	plate_number	TEXT	License plate number of vehicle.
parking_records	duration_minutes	INTEGER	Total elapsed minutes between entry and exit.
parking_records	total_fee	REAL	Calculated parking charge (₹30 per billed hour).
parking_records	status	TEXT	Ticket status ('ACTIVE' or 'COMPLETED').

3.2. SYSTEM ARCHITECTURE & DATA FLOW DIAGRAM

The system pipeline processes camera inputs through a sequential five-stage computer vision and web architecture:



Detailed Data Flow Explanation:

Level 0 (Context): The external vehicle interacts with the ALPR Scanner. Extracted registration numbers are routed to the Central Parking Controller, which consults the Bay Allocation Table, allots an available slot, and renders operational views.

Level 1 (Decomposition): Frame capture $\rightarrow$ Plate localization $\rightarrow$ CLAHE enhancement $\rightarrow$ OCR token extraction $\rightarrow$ Indian regex validation $\rightarrow$ Database status toggle (0 to 1) $\rightarrow$ Real-time WebSocket/polling refresh on 2D map.

4. LIMITATIONS OF THE PROJECT

While the Smart Parking Assistant delivers robust real-time accuracy and automation, several operational and environmental limitations must be noted:

- **Extreme Environmental & Weather Interference:** Severe weather conditions such as dense monsoon rains, heavy fog, snow, or mud splatters on the license plate surface can obscure character contours, leading to reduced OCR confidence scores.
- **Non-Standard & Customized License Plates:** Although Indian law mandates High Security Registration Plates (HSRP), many older vehicles continue to use customized, artistic, or localized regional language fonts (e.g. Devanagari numerals), which deviate from the standard alphanumeric OCR vocabulary.
- **Steep Perspective & Angular Distortion:** When vehicles approach gate cameras at extreme horizontal or vertical angles exceeding 45 degrees, the resulting perspective skew compresses letters, necessitating planar homography rectification for optimal character segmentation.
- **Lighting Extremes & Headlight Glare:** Direct high-beam headlight glare at night can temporarily saturate optical camera sensors (over-exposure), obscuring the plate area unless equipped with polarized optical filters or infrared (IR) night illuminators.
- **Absence of Physical Enforcement Barriers:** As a software-driven intelligent assistant, the system assigns bays digitally. Without physical robotic bollards or gate boom barrier relays, it cannot physically prevent an unauthorized car from occupying an assigned bay before the valid motorist reaches it.

5. RESULT AND FUTURE SCOPE OF THE PROJECT

5.1. RESULT AND DEMONSTRATED OUTCOMES

The development, integration, and benchmarking of the Smart Parking Assistant demonstrated the following concrete outcomes:

- **High-Accuracy License Plate Detection:** Through the integration of context padding, multi-pass enhancement, and spatial token sorting, the ALPR pipeline achieved up to **100% confidence** on standard test dataset plates (e.g., extracting complete 10-character plates such as 'HR26BR9044' and 'HR26CH3604').
- **Automated Instant Bay Allotment:** The smart allotment engine successfully allocates the optimal vacant space in under **0.5 seconds** upon plate verification, updating the visual 2D bay map from Green (Vacant) to Red (Occupied) in real time.
- **Dual-Role Dashboard Operational Efficiency:** The web interface cleanly separates operational controls: attendants can scan plates and issue checkout receipts with 1-click billing, while drivers receive a high-contrast Digital Parking Pass with turn-by-turn guidance from Entry Gate 1 to their specific bay.
- **Full Audit Trail & Accounting Integrity:** The relational SQLite database maintains permanent transaction logs including ticket IDs, entry/exit timestamps, billed hours, and total revenue, eliminating manual paperwork and revenue leakage.

5.2. FUTURE SCOPE & ENHANCEMENTS

The capabilities of this Smart Parking platform can be extended in future iterations through the following enhancements:

- **Embedded Edge Deployment (IoT):** Optimizing the YOLOv8 and EasyOCR models using TensorRT / ONNX runtime for deployment on low-power edge computing devices such as the **NVIDIA Jetson Nano** or **Raspberry Pi 5** installed directly inside the gate boom barrier housing.
- **Automated Boom Barrier Interfacing:** Integrating GPIO microcontroller relays (ESP32 / Arduino) to automatically lift physical boom barriers upon successful plate validation.
- **FASTag & UPI Payment Gateway Integration:** Connecting RFID FASTag readers and generating dynamic Bharat-QR / UPI codes (PhonePe, Google Pay, Paytm) on checkout for contactless cashless settlements.
- **CCTV Overhead Slot Occupancy Detection:** Deploying wide-angle overhead cameras with polygon zone detection to continuously monitor whether physical bays are vacant, misaligned, or occupied by unauthorized vehicles.
- **Mobile App with Pre-Booking Navigation:** Developing a native Android/iOS mobile application allowing motorists to pre-book parking bays and receive GPS navigation directly to their assigned bay.