Tables (15)

Name	Type	Schema
cache		CREATE TABLE "cache" ("key" varchar not null, "value" text not null, "expiration" integer not null, primary key ("key"))
key	varchar	"key" varchar NOT NULL
value	text	"value" text NOT NULL
expiration	integer	"expiration" integer NOT NULL
cache_locks		CREATE TABLE "cache_locks" ("key" varchar not null, "owner" varchar not null, "expiration" integer not null, primary key ("key"))
key	varchar	"key" varchar NOT NULL
owner	varchar	"owner" varchar NOT NULL
expiration	integer	"expiration" integer NOT NULL
carts		CREATE TABLE "carts" ("id" integer primary key autoincrement not null, "user_id" integer, "session_id" varchar, "product_id" integer not null, "quantity" integer not null, "created_at" datetime, "updated_at" datetime, foreign key("user_id") references "users"("id") on delete cascade, foreign key("product_id") references "products"("id") on delete cascade)
id	integer	"id" integer NOT NULL
user_id	integer	"user_id" integer
session_id	varchar	"session_id" varchar
product_id	integer	"product_id" integer NOT NULL
quantity	integer	"quantity" integer NOT NULL
created_at	datetime	"created_at" datetime
updated_at	datetime	"updated_at" datetime
categories		CREATE TABLE "categories" ("id" integer primary key autoincrement not null, "name" varchar not null, "slug" varchar not null, "description" text, "image" varchar, "is_active" tinyint(1) not null default '1', "sort_order" integer not null default '0', "created_at" datetime, "updated_at" datetime)
id	integer	"id" integer NOT NULL
name	varchar	"name" varchar NOT NULL
slug	varchar	"slug" varchar NOT NULL
description	text	"description" text
image	varchar	"image" varchar
is_active	tinyint(1)	"is_active" tinyint(1) NOT NULL DEFAULT '1'
sort_order	integer	"sort_order" integer NOT NULL DEFAULT '0'
created_at	datetime	"created_at" datetime
updated_at	datetime	"updated_at" datetime
failed_jobs		CREATE TABLE "failed_jobs" ("id" integer primary key autoincrement not null, "uuid" varchar not null, "connection" text not null, "queue" text not null, "payload" text not null, "exception" text not null, "failed_at" datetime not null default CURRENT_TIMESTAMP)
id	integer	"id" integer NOT NULL
uuid	varchar	"uuid" varchar NOT NULL

Name	Type	Schema
connection	text	"connection" text NOT NULL
queue	text	"queue" text NOT NULL
payload	text	"payload" text NOT NULL
exception	text	"exception" text NOT NULL
failed_at	datetime	"failed_at" datetime NOT NULL DEFAULT CURRENT_TIMESTAMP
job_batches		CREATE TABLE "job_batches" ("id" varchar not null, "name" varchar not null, "total_jobs" integer not null, "pending_jobs" integer not null, "failed_jobs" integer not null, "failed_job_ids" text not null, "options" text, "cancelled_at" integer, "created_at" integer not null, "finished_at" integer, primary key ("id"))
id	varchar	"id" varchar NOT NULL
name	varchar	"name" varchar NOT NULL
total_jobs	integer	"total_jobs" integer NOT NULL
pending_jobs	integer	"pending_jobs" integer NOT NULL
failed_jobs	integer	"failed_jobs" integer NOT NULL
failed_job_ids	text	"failed_job_ids" text NOT NULL
options	text	"options" text
cancelled_at	integer	"cancelled_at" integer
created_at	integer	"created_at" integer NOT NULL
finished_at	integer	"finished_at" integer
jobs		CREATE TABLE "jobs" ("id" integer primary key autoincrement not null, "queue" varchar not null, "payload" text not null, "attempts" integer not null, "reserved_at" integer, "available_at" integer not null, "created_at" integer not null)
id	integer	"id" integer NOT NULL
queue	varchar	"queue" varchar NOT NULL
payload	text	"payload" text NOT NULL
attempts	integer	"attempts" integer NOT NULL
reserved_at	integer	"reserved_at" integer
available_at	integer	"available_at" integer NOT NULL
created_at	integer	"created_at" integer NOT NULL
migrations		CREATE TABLE "migrations" ("id" integer primary key autoincrement not null, "migration" varchar not null, "batch" integer not null)
id	integer	"id" integer NOT NULL
migration	varchar	"migration" varchar NOT NULL
batch	integer	"batch" integer NOT NULL
order_items		CREATE TABLE "order_items" ("id" integer primary key autoincrement not null, "order_id" integer not null, "product_id" integer not null, "product_name" varchar not null, "product_sku" varchar not null, "quantity" integer not null, "unit_price" numeric not null, "total_price" numeric not null, "created_at" datetime, "updated_at" datetime, foreign key("order_id") references "orders"("id") on delete cascade, foreign key("product_id") references "products"("id") on delete cascade)
id	integer	"id" integer NOT NULL

Name	Type	Schema
order_id	integer	"order_id" integer NOT NULL
product_id	integer	"product_id" integer NOT NULL
product_name	varchar	"product_name" varchar NOT NULL
product_sku	varchar	"product_sku" varchar NOT NULL
quantity	integer	"quantity" integer NOT NULL
unit_price	numeric	"unit_price" numeric NOT NULL
total_price	numeric	"total_price" numeric NOT NULL
created_at	datetime	"created_at" datetime
updated_at	datetime	"updated_at" datetime
orders		CREATE TABLE "orders" ("id" integer primary key autoincrement not null, "order_number" varchar not null, "user_id" integer not null, "status" varchar not null default 'pending', "subtotal" numeric not null, "tax_amount" numeric not null default '0', "shipping_amount" numeric not null default '0', "discount_amount" numeric not null default '0', "total_amount" numeric not null, "currency" varchar not null default 'IDR', "payment_status" varchar not null default 'pending', "payment_method" varchar, "billing_address" text not null, "shipping_address" text not null, "notes" text, "shipped_at" datetime, "delivered_at" datetime, "created_at" datetime, "updated_at" datetime, foreign key("user_id") references "users"("id") on delete cascade)
id	integer	"id" integer NOT NULL
order_number	varchar	"order_number" varchar NOT NULL
user_id	integer	"user_id" integer NOT NULL
status	varchar	"status" varchar NOT NULL DEFAULT 'pending'
subtotal	numeric	"subtotal" numeric NOT NULL
tax_amount	numeric	"tax_amount" numeric NOT NULL DEFAULT '0'
shipping_amount	numeric	"shipping_amount" numeric NOT NULL DEFAULT '0'
discount_amount	numeric	"discount_amount" numeric NOT NULL DEFAULT '0'
total_amount	numeric	"total_amount" numeric NOT NULL
currency	varchar	"currency" varchar NOT NULL DEFAULT 'IDR'
payment_status	varchar	"payment_status" varchar NOT NULL DEFAULT 'pending'
payment_method	varchar	"payment_method" varchar
billing_address	text	"billing_address" text NOT NULL
shipping_address	text	"shipping_address" text NOT NULL
notes	text	"notes" text
shipped_at	datetime	"shipped_at" datetime
delivered_at	datetime	"delivered_at" datetime
created_at	datetime	"created_at" datetime
updated_at	datetime	"updated_at" datetime
password_reset_tokens		CREATE TABLE "password_reset_tokens" ("email" varchar not null, "token" varchar not null, "created_at" datetime, primary key ("email"))
email	varchar	"email" varchar NOT NULL
token	varchar	"token" varchar NOT NULL
created_at	datetime	"created_at" datetime

Name	Type	Schema
products		CREATE TABLE "products" ("id" integer primary key autoincrement not null, "category_id" integer not null, "name" varchar not null, "slug" varchar not null, "description" text, "short_description" text, "sku" varchar not null, "price" numeric not null, "sale_price" numeric, "stock_quantity" integer not null default '0', "manage_stock" tinyint(1) not null default '1', "status" varchar not null default 'active', "images" text, "brand" varchar, "manufacturer" varchar, "expiry_date" date, "batch_number" varchar, "prescription_required" tinyint(1) not null default '0', "dosage_instructions" text, "side_effects" text, "contraindications" text, "weight" numeric, "unit" varchar, "is_featured" tinyint(1) not null default '0', "sort_order" integer not null default '0', "created_at" datetime, "updated_at" datetime, foreign key("category_id") references "categories"("id") on delete cascade)
id	integer	"id" integer NOT NULL
category_id	integer	"category_id" integer NOT NULL
name	varchar	"name" varchar NOT NULL
slug	varchar	"slug" varchar NOT NULL
description	text	"description" text
short_description	text	"short_description" text
sku	varchar	"sku" varchar NOT NULL
price	numeric	"price" numeric NOT NULL
sale_price	numeric	"sale_price" numeric
stock_quantity	integer	"stock_quantity" integer NOT NULL DEFAULT '0'
manage_stock	tinyint(1)	"manage_stock" tinyint(1) NOT NULL DEFAULT '1'
status	varchar	"status" varchar NOT NULL DEFAULT 'active'
images	text	"images" text
brand	varchar	"brand" varchar
manufacturer	varchar	"manufacturer" varchar
expiry_date	date	"expiry_date" date
batch_number	varchar	"batch_number" varchar
prescription_required	tinyint(1)	"prescription_required" tinyint(1) NOT NULL DEFAULT '0'
dosage_instructions	text	"dosage_instructions" text
side_effects	text	"side_effects" text
contraindications	text	"contraindications" text
weight	numeric	"weight" numeric
unit	varchar	"unit" varchar
is_featured	tinyint(1)	"is_featured" tinyint(1) NOT NULL DEFAULT '0'
sort_order	integer	"sort_order" integer NOT NULL DEFAULT '0'
created_at	datetime	"created_at" datetime
updated_at	datetime	"updated_at" datetime
sessions		CREATE TABLE "sessions" ("id" varchar not null, "user_id" integer, "ip_address" varchar, "user_agent" text, "payload" text not null, "last_activity" integer not null, primary key ("id"))
id	varchar	"id" varchar NOT NULL
user_id	integer	"user_id" integer

Name	Type	Schema
ip_address	varchar	"ip_address" varchar
user_agent	text	"user_agent" text
payload	text	"payload" text NOT NULL
last_activity	integer	"last_activity" integer NOT NULL
sqlite_sequence		CREATE TABLE sqlite_sequence(name,seq)
name		"name"
seq		"seq"
users		CREATE TABLE "users" ("id" integer primary key autoincrement not null, "name" varchar not null, "email" varchar not null, "email_verified_at" datetime, "password" varchar not null, "remember_token" varchar, "created_at" datetime, "updated_at" datetime, "is_admin" tinyint(1) not null default '0')
id	integer	"id" integer NOT NULL
name	varchar	"name" varchar NOT NULL
email	varchar	"email" varchar NOT NULL
email_verified_at	datetime	"email_verified_at" datetime
password	varchar	"password" varchar NOT NULL
remember_token	varchar	"remember_token" varchar
created_at	datetime	"created_at" datetime
updated_at	datetime	"updated_at" datetime
is_admin	tinyint(1)	"is_admin" tinyint(1) NOT NULL DEFAULT '0'

Indices (11)

Name	Type	Schema
carts_session_id_product_id_index		CREATE INDEX "carts_session_id_product_id_index" on "carts" ("session_id", "product_id")
session_id		"session_id"
product_id		"product_id"
carts_user_id_product_id_index		CREATE INDEX "carts_user_id_product_id_index" on "carts" ("user_id", "product_id")
user_id		"user_id"
product_id		"product_id"
categories_slug_unique		CREATE UNIQUE INDEX "categories_slug_unique" on "categories" ("slug")
slug		"slug"
failed_jobs_uuid_unique		CREATE UNIQUE INDEX "failed_jobs_uuid_unique" on "failed_jobs" ("uuid")
uuid		"uuid"
jobs_queue_index		CREATE INDEX "jobs_queue_index" on "jobs" ("queue")
queue		"queue"
orders_order_number_unique		CREATE UNIQUE INDEX "orders_order_number_unique" on "orders" ("order_number")
order_number		"order_number"
products_sku_unique		CREATE UNIQUE INDEX "products_sku_unique" on "products"

Name	Type	Schema
		`("sku")`
sku		"sku"
products_slug_unique		`CREATE UNIQUE INDEX "products_slug_unique" on "products" ("slug")`
slug		"slug"
sessions_last_activity_index		`CREATE INDEX "sessions_last_activity_index" on "sessions" ("last_activity")`
last_activity		"last_activity"
sessions_user_id_index		`CREATE INDEX "sessions_user_id_index" on "sessions" ("user_id")`
user_id		"user_id"
users_email_unique		`CREATE UNIQUE INDEX "users_email_unique" on "users" ("email")`
email		"email"

Views (0)

Name	Type	Schema

Triggers (0)

Name	Type	Schema