



AF140V

Pharmacy refrigerators

+2° +12° C from 100 to 1400 lt. > Capacity 1400 lt



AF140V Model

Capacity 1400 LT

Structure

External structure in hot-dip galvanized steel, anti-corrosion treated and PVC film coated.
Scotch-brite stainless steel internal structure.

Insulation

60 mm of insulation obtained by injection of high density polyurethane CFC-free foam for excellent product preservation and best energy saving

Door

Two self-closing glass doors (double insulating - low emissivity glass) with folding magnetic gasket on four sides for perfect closing. Lock with key.

Light

LED light (energy saving up to 70%) with automatic switch at door opening. Manual switch on control panel.

Internal fittings

8 scotch-brite stainless steel shelves, removable and adjustable in height.

Temperature range

Setting between 2°C and 12°C. Factory preset to 4°C. Digital adjustable with an increment of 0.1°C.

Refrigeration system

Completely sealed, silent and highly efficient hermetic compressor and ventilated air condenser (suitable also for tropical countries). Internal ventilated evaporator. Forced-air cooling system conceived to achieve maximum temperature uniformity and stability inside the refrigerator even in case of frequent door openings. Evaporator fan shuts off during door openings. CFC/HCFC-free R290 refrigerant gas.

Defrosting

Fully automatic defrosting cycle and auto-evaporation of condensed water.

Capacity

1400 liters

Voltage

230V/50 Hz (on request 230V/60 Hz, 115V/60 Hz)

Absorption

230 Watt

Gas

CFC/HCFC-free R290 refrigerant gas.

Control panel and alarms

TP-1 full touch control panel

<https://www.frimed.it/en/control-panel.html#tp-1>

Data logger

To record temperatures and alarms. Download data on USB pen drive.

Standard

- 8 shelves
- Four one way wheels with stabilizing adjustable feet
- Lock with key
- Power cord with Schuko type plug (or British plug on request)
- Protection fuses (on power switch and electronic mainboard)
- RFI filter
- Password protected power switch and settings
- Electronic control panel with alarm system
- Remote contact (dry, volt-free) for alarm
- Data logger with USB port to download records and data
- Memory of latest alarms visible on screen

Optional accessories

- 7" full touch screen
- Sliding drawers (up to 14) in scotch-brite stainless steel, with see-through frontal side and telescopic ball-bearings slides
- Internal dividers for drawers
- Additional shelf
- Castors with two frontal brakes
- Weekly temperature chart recorder working with 1,5 V battery, equipped with 52 disks and a pen
- Back-up battery supplying energy to control panel in order to display temperature and generate alarms in case of power failure
- Independent safety thermostat
- Cloud system
- Electric digital key lock
- Power supply 115V/60Hz

External dimensions and unit net weight

1400x800x1990 (wxdxh-mm)-kg. 226

Dimensions of packaging and shipping weight

- carton box on pallet: 1500x900x2170 (wxdxh-mm)-kg. 249
- wooden crate (option on request): 1600x960x2210 (wxdxh-mm)-kg. 348

Equipment in accordance with:

Low voltage Directive 2014/35/UE, Electromagnetic Compatibility Directive 2014/30/UE

The picture doesn't necessarily show the product in its standard version.

©Copyright FRI.MED. S.r.l.

Strada Fontaneto 44 10023 Chieri (TO) - Italy

p.IVA /C.F. 07356760012