



FP30V/2

Combined refrigerators

+2° +15°/+2 + 15°C from 150/150 to 700/700 LT > Capacity 300 lt



FP30V/2 Model

Upper compartment capacity 150 LT - lower compartment 150 LT.

Structure

External structure in hot-dip galvanized steel, anti-corrosion treated and PVC film coated.
Scotch-brite stainless steel internal structure.

Insulation

60 mm of insulation obtained by injection of high density polyurethane CFC-free foam for excellent product preservation and best energy saving

Door

Two self-closing glass doors (double insulating - low emissivity glass) for both refrigerator compartments. Folding magnetic gasket on four sides for perfect closing. Right hand opening or left hand on request. Locks with key.

Light

LED light (energy saving up to 70%) with automatic switch at door opening. Manual switch on control panel.

Internal fittings

Two separate and independent compartments equipped with 3 scotch-brite stainless steel shelves, removable and adjustable in height.

Temperature range

Upper compartment: between +2°C and +15°C. Factory preset to +4°C.

Lower compartment: between +2°C and +15°C. Factory preset to +4°C.

Digital adjustable setting with an increment of 0.1°C.

Refrigeration system

Two completely sealed, silent and highly efficient hermetic compressors and ventilated air condensers (suitable also for tropical countries). Forced-air cooling system in both compartments conceived to achieve maximum temperature uniformity and stability even in case of frequent door openings. Evaporator fan shuts off during door openings. Static evaporator in freezer compartment. CFC/HCFC-free R290 refrigerant gas.

Defrosting

Fully automatic defrosting cycle and auto-evaporation of condensed water in both compartments.

Capacity

Upper compartment: 150LT

Lower compartment: 150LT

Voltage

230V/50 Hz (on request 230V/60 Hz, 115V/60 Hz)

Absorption

Upper compartment: 150 Watt

Lower compartment: 150 Watt

Gas

CFC/HCFC-free R290 refrigerant gas.

Control panel and alarms

Available:

LGK-2 digital control panel

<https://www.frimed.it/en/control-panel.html#lk-2>

TP-1 full touch control panel

<https://www.frimed.it/en/control-panel.html#tp-1>

Data logger

To record temperatures and alarms in refrigerator and freezer compartments. Download data on USB pen drive.

Standard

- 3 shelves in each compartment
- Four one-way wheels with stabilizing adjustable feet
- 2 locks with key
- Power cord with Schuko type plug (or British plug on request)
- Protection fuses (on power switch and electronic mainboard)
- RFI filter
- Password protected power switch and settings
- Electronic control panel with alarm system
- Remote contact (dry, volt-free) for alarm
- Data logger with USB port to download readings and data
- Memory of latest alarms visible on screen

Optional accessories

- Standard sliding drawers (up to 3) in scotch-brite stainless steel, with see-through frontal side and telescopic ball-bearings slides in each compartment
- Up to 5 pharmacy drawers (height 7 cm) in scotch-brite stainless steel, with see-through frontal side and telescopic ball-bearings slides in each compartment
- Internal dividers for both types of drawers
- Additional shelf
- Smooth shelf with borders
- Castors with two frontal brakes
- Weekly temperature chart recorder working with 1,5 V battery, equipped with 52 disks and a pen
- 12V back-up battery (LGK-2) or rechargeable batteries (TP-1 full touch) supplying energy to control panel in order to display temperature and generate alarms in case of power failure
- GSM module to send SMS alarm messages to mobile phones, showing date, time, cabinet temperature and type of alarm (LGK-2)
- LAN Port to connect the appliance via ethernet on PC to monitor correct functioning (LGK-2)
- Cloud system (TP-1 full touch)

- Independent safety thermostat (DIN 13277 conformity)
- Test hole (Ø 25 mm) for external user sensor
- Electric digital key lock (TP-1 full touch)
- Power supply 115V/60Hz

External dimensions and unit net weight

600x700x2030 (wxdxh-mm)-kg. 125

Dimensions of packaging and shipping weight

- carton box on pallet: 720x720x2200 (wxdxh-mm)-kg. 139
- wooden crate (option on request): 960x840x2260 (wxdxh-mm)-kg. 204

Equipment in accordance with:

Low voltage Directive 2014/35/UE, Electromagnetic Compatibility Directive 2014/30/UE

The picture doesn't necessarily show the product in its standard version.

©Copyright FRI.MED. S.r.l.

Strada Fontaneto 44 10023 Chieri (TO) - Italy

p.IVA /C.F. 07356760012