



FS20V

Pharmacy refrigerators

+2° +12° C from 100 to 1400 lt. > Capacity 200 lt



FS20V Model

Capacity 200 LT

Structure

External structure in hot-dip galvanized steel, anti-corrosion treated and PVC film coated.
Scotch-brite stainless steel internal structure.

Insulation

60 mm of insulation obtained by injection of high density polyurethane CFC-free foam for excellent product preservation and best energy saving

Door

Self-closing glass door (double insulating - low emissivity glass) with folding magnetic gasket on four sides for perfect closing. Right hand opening or left hand on request. Lock with key.

Light

LED light (energy saving up to 70%) with automatic switch at door opening. Manual switch on control panel.

Internal fittings

3 scotch-brite stainless steel shelves, removable and adjustable in height.

Temperature range

Setting between 2°C and 12°C. Factory preset to 4°C. Digital adjustable with an increment of 0.1°C.

Refrigeration system

Completely sealed, silent and highly efficient hermetic compressor and ventilated air condenser (suitable also for tropical countries). Internal ventilated evaporator. Forced-air cooling system conceived to achieve maximum temperature uniformity and stability inside the refrigerator even in case of frequent door openings. Evaporator fan shuts off during door openings. CFC/HCFC-free R290 refrigerant gas.

Defrosting

Fully automatic defrosting cycle and auto-evaporation of condensed water.

Capacity

200 litres

Voltage

230V/50 Hz (on request 230V/60 Hz, 115V/60 Hz)

Absorption

155 Watt

Gas

CFC/HCFC-free R290 refrigerant gas.

Control panel and alarms

TP-1 full touch control panel

<https://www.frimed.it/en/control-panel.html#tp-1>

Data logger

To record temperatures and alarms. Download data on USB pen drive.

Standard

- 3 shelves Four one way wheels with stabilizing adjustable feet
- Lock with key
- Power cord with Schuko type plug (or British plug on request)
- Protection fuses (on power switch and electronic mainboard)
- RFI filter
- Password protected power switch and settings
- Electronic control panel with alarm system
- Remote contact (dry, volt-free) for alarm
- Data logger with USB port to download records and data
- Memory of latest alarms visible on screen

Optional accessories

- 7" full touch screen
- Sliding drawers (up to 4) in scotch-brite stainless steel, with see-through frontal side and telescopic ball-bearings slides
- Internal dividers for drawers
- Additional shelf
- Castors with two frontal brakes
- Weekly temperature chart recorder working with 1,5 V battery, equipped with 52 disks and a pen
- Back-up battery supplying energy to control panel in order to display temperature and generate alarms in case of power failure
- Cloud system
- Independent Safety thermostat
- Electric digital key lock
- Power supply 115V/60Hz

External dimensions and unit net weight

600x600x1560 (wxdxh-mm)-kg. 86

Dimensions of packaging and shipping weight

- carton box on pallet: 700x700x1770 (wxdxh-mm)-kg. 93
- wooden crate (option on request): 790x740x1960 (wxdxh-mm)-kg. 138

Equipment in accordance with:

Low voltage Directive 2014/35/UE, Electromagnetic Compatibility Directive 2014/30/UE

The picture doesn't necessarily show the product in its standard version.

©Copyright FRI.MED. S.r.l.

Strada Fontaneto 44 10023 Chieri (TO) - Italy

p.IVA /C.F. 07356760012