D2Mini

Microbial Identification & Antimicrobial Susceptibility Testing System (ID/AST)



Features

- Running bacteria ID and AST at the same time, and reporting the ID and S.I.R result with True MIC value
- Identification range covering the vast majority of routine organisms (over 500 microorganisms), such as Enterobacteriaceae, non-Fermentative bacteria, bacteria of Vibrionaceae, Staphylococcus/Micrococcus, Yeast like fungi, Streptococcus, Enterococcus, Vibrionaceae, etc.
- Advanced expert system presents testing results with high accuracy and instructive interpretation for over 200 kinds of antibiotics.
- According to CLSI regulation, antibiotics are divided into A/B/C/U group to report MIC results, which help doctors to choose the appropriate antibiotics.
- Multiple drug resistant monitoring: MRSA, BETA-lac, VRE, VRSA, HLAR, ESBLs
- Customized report format
- Robust statistic function
- Benchtop

Technical Specifications

✸ Test Principles

Identification: Colorimetry

Susceptibility testing: Turbidimetry

✸ Reading Throughput

≥50 pcs/hr,

✸ Optional Configuration

Automated sampling device, sampling 50 plates per hour

✸ Working environment

Environmental temperature: 5-30℃;

Relative humidity: ≤80% ;

Placed on a steady and plane table, away from direct strong sun light and electromagnetic interference, and well grounded

✸ Atmospheric pressure

76kPa--106kPa;

✸ Power supply

AC 100-240V, 50/60 HZ

✸ Dimension & Weigh

D2Mini

(Size of closing LCD)： 215mmX 258mm X215mm

(Size of opening LCD)： 215mmX 258mm X378mm

Weight：4.4KG (N.W)

Auto Sampling instrument

Dimension : 496×365×443mm Weight: 14KG

DL-ZD3

Dimension : 190×95×70mm Weight: 0.5KG