#	IMAGE	MODEL	DESCRIPTION	PRICE
DAHUA VIDEO INTERCOM				
1		**DHI-VTH2621G-WP**	IP & Wi-Fi Indoor Monitor	**SAR 330**
GENERAL				
2		**DH-HAC-HFW1519SMN-IL-A-PRO**	Max 25 fps@5 MP (16:9 video output).	**SAR 165**
3		**DH-HAC-HDW1519SMN-IL-A-PRO**	Max 25 fps@5 MP (16:9 video output).	**SAR 165**
4		**DH-HAC-HDW1519SLN-IL-A-PRO**	Max 25 fps@5 MP (16:9 video output).	**SAR 158**
5		**DH-HAC-HFW1519SLN-IL-A-PRO**	Max 25 fps@5 MP (16:9 video output).	**SAR 158**
6		**DH-IPC-HFW2849S-S-IL-S2**	Super AI Coding , 8-MP 1/2.7" CMOS image sensor, low illuminance, and high definition image.	**SAR 489**
7		**DH-IPC-HFW2849T-AS-IL-S2**	Super AI Coding , 8-MP 1/2.7" CMOS image sensor, low illuminance, and high definition image.	**SAR 516**
8		**DH-IPC-HDBW2849E-S-IL-S2**	Super AI Coding , 8-MP 1/2.7" CMOS image sensor, low illuminance, and high definition image.	**SAR 492**
9		**DH-IPC-HFW2849T-ZAS-IL-S2**	Super AI Coding , 8-MP 1/2.7" CMOS image sensor, low illuminance, and high definition image.	**SAR 829**
10		**DH-IPC-HDBW2849R-ZAS-IL**	Super AI Coding ,8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 829**
11		**DH-IPC-HDBW2649R-ZAS-IL**	Super AI Coding ,6-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 750**
12		**DH-IPC-HFW1639TC-A-IL-S7**	Super AI Coding,6-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 262**
13		**DH-IPC-HDBW1639E1-A-IL-S7**	Super AI Coding, 6-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 262**
14		**DH-IPC-HFW1839TC-A-IL-S7**	Super AI Coding,8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 441**
15		**DH-IPC-HDBW1839E1-A-IL-S7**	Super AI Coding,8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 433**
16		**DH-SD5A425MB-HNR**	1/2.8" 4Megapixel CMOS.	**SAR 2,020**
17		**DH-SD5A432MB-HNR**	1/2.8" 4Megapixel CMOS.	**SAR 2,700**
18		**DH-SD5A825MA-HNR**	1/1.8" 8Megapixel CMOS.	**SAR 3,636**
19		**DH-SD5A425MA-HNR**	1/1.8" 4Megapixel STARVIS™ CMOS	**SAR 2,714**
20		**DH-SD5A825MA-HNR**	1/1.8" 8Megapixel CMOS.	**SAR 3,636**

21		**DH-SD6E825MA-HNR-A-PV1**	1/1.8" 8Megapixel CMOS	**SAR 3,215**
22		**DH-SD4F420DA-HNY**	1/1.8" 4Megapixel CMOS.	**SAR 1,756**
23		**DH-SD4E825MB-HNR-A-PV1**	1/2.8" 8Megapixel STARVIS™ CMOS.	**SAR 2,217**
24		**DH-SD4E425MB-HNR-A-PV1**	1/2.8" 4Megapixel CMOS	**SAR 1,695**
25		**DH-SD4E225MB-HNR-A-PV1**	1/2.8" 2Megapixel CMOS	**SAR 1,293**
26		**DHI-NVR4104HS-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 402**
27		**DHI-NVR4104HS-P-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 466**
28		**DHI-NVR4108HS-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 431**
29		**DHI-NVR4108HS-P-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 593**
30		**DHI-NVR4108HS-8P-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 672**
31		**DHI-NVR4116HS-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 490**
32		**DHI-NVR4116HS-8P-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 837**
33		**DHI-NVR4208-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 542**
34		**DHI-NVR4208-8P-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 847**
35		**DHI-NVR4216-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 627**
36		**DHI-NVR4216-16P-4KS3-L**	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	**SAR 1,107**
37		**DHI-ASI7213G-PW**	Features a 7-inch LCD screen with a resolution of 600 (H) x 1024 (V) .	**SAR 1,747**
38		**DHI-ASI7213G-WG2**	Features a 7-inch LCD screen with a resolution of 600 (H) x 1024 (V) .	**SAR 2,016**
39		**ASF7G-MEK**	Made from PC+ABS plastic and glass materials.	**SAR 235**
40		**ASF7G-MEKF**	Made from PC+ABS plastic and glass materials.	**SAR 302**
41		**ASF7G-MEFQ**	Made from PC+ABS plastic and glass materials.	**SAR 370**
42		**DH-ASF6S-ZY**	Rain Cover for ASI6S series	**SAR 59**
43		**DHI-ASI3103F-MEPW**	Includes a 2-megapixel CMOS dual-lens camera that supports IR illumination and WDR.	**SAR 703**

44		**DHI-ASI3103F-MEW**	Includes a 2-megapixel CMOS dual-lens camera that supports IR illumination and WDR.	**SAR 669**
45		**DHI-ASI3103F-W**	Includes a 2-megapixel CMOS dual-lens camera that supports IR illumination and WDR.	**SAR 625**
46		**DHI-ASI1201M-ME**	Use zinc alloy material, vandal-proof design with IK08 level; Built-in webpage and can be accessed by PC or mo	**SAR 321**
47		**D H I - A S I 1 2 0 1 M - M E P**	The front part of the case is made of zinc alloy and the back part is made of plastic.	**SAR 380**
48		**DHI-ASI2201H-DW**	Access Standalone	**SAR 504**
49		**DHI-ASI2212J-PW**	Dahua Single Door IC Card, Password, Fingerprint, Bluetooth Access Standalone	**SAR 467**
50		**DHI-ASR2101A-D**	Access Reader-ID	**SAR 148**
51		**DHI-ASR2115A**	1. PC material, acrylic panel and IP66, suitable for indoor and outdoor use.	**SAR 296**
52		**DHI-ASC2202B-D**	1. Support TCP/IP communication	**SAR 370**
53		**DHI-ASC2202C-D**	1. TCP/IP communication.	**SAR 747**
54		**DHI-ASC2202C-S**	1. TCP/IP communication.	**SAR 622**
55		**DHI-ASF908-V1**	Professional circuit design, no mechanical failure	**SAR 34**
56		**DHI-ART-ARC3000H-03-W2(868)**	Alarm KIT	**SAR 666**
57		**DHI-ART-ARC3000H-03-FW2(868)**	Alarm KIT-4G	**SAR 931**
58		**DH-CS4010-8ET2GT-110**	8 × RJ-45 10/100 Mbps PoE ports, 2 × RJ-45 Gigabit ports.	**SAR 216**
59		**DH-CS4010-8ET2GT-60**	8 × RJ-45 10/100 Mbps PoE ports, 2 × RJ-45 Gigabit ports.	**SAR 195**
60		**DH-PFM922I-6UN-C-100**	CAT6, 100m	**SAR 77**
61		**DH-PFM320D-BS**	Desktop power adapter	**SAR 19**
62		**DHI-DAE-HC1301W- M1PRO**	"1920P × 1080P ultra high resolution image	**SAR 148**
63		**S100**	S100 is a 4G dash camera with front 2K and rear 1080P, one-click capture,	**SAR 672**
64		**DHI-DAE-HC3500WVR-M3**	4MP dash camera	**SAR 182**
65		**DHI-DAE-HC5710WVI-H10**	4K dash camera	**SAR 363**
66		**DHI-DAE-HC5711GW-T5**	4K dual lens dash camera	**SAR 437**

67		DH-DAE-CDL-V9H	Parking Surveillance Cable for S3 S5 M1 M3 M7 M6 S6 S8 Hardwire Kit for 24H Parking Monitor in Car	SAR 32
68		DHI-LM43-F200N	43 inch, 60Hzÿ VGA+HDMI+USB+speaker*2, 1080p	SAR 1,206
69		DHI-LM50-F400N	50 inch, 60Hzÿ VGA+HDMI*3+USB_+Audio in	SAR 2,085
70		DHI-LM55-F400N	55 inch, 60Hzÿ VGA+HDMI*2+USB_+Audio in+RS232	SAR 2,354
71		DHI-LM65-F400N	65 inch, 60Hzÿ VGA+HDMI*3+USB_+Audio in	SAR 3,632
72		DHI-NKB1000-E	Keyboard	SAR 809
73		DHI-NVD0105DH-4K	Decoder	SAR 2,241
74		DHI-LPH65-SC410-S2	65 inch Intelligent Interactive Tablet	SAR 4,571
75		DHI-LPH75-SC410-S2	75 inch Intelligent Interactive Tablet	SAR 6,723
76		DHI-LPH86-SC410-S2	86 inch Intelligent Interactive Tablet	SAR 8,379
77		DHI-VTH5123H-W	7” inch 2 wire Hybrid VTH	SAR 494
78		DHI-KTP01 PLUS	VTH changed to DHI-VTH5721A-WP	SAR 975
79		DHI-KTP04 PLUS	VTH changed to DHI-VTH5721A-WP	SAR 937
80		DHI-VTH5721A-WP	7" inch IP VTH with elegant design, ISP screen	SAR 460
81		DHI-VTH5741A-WP	10" inch IP VTH with elegant design, ISP screen	SAR 617
82		DHI-VTH2621G-W	7" TFT capacitive touch screen, 1024 × 600.	SAR 330
83		DHI-SCP3022B-CBZ-S	Adopts the Android 14 system, 4 GB RAM + 16 GB ROM, offering advanced performance and a user-friendly experien	SAR 1,454
84		DHI-SCP3022B-IBZ	Adopts the Android 14 system, 4 GB RAM + 16 GB ROM, offering advanced performance and a user-friendly experien	SAR 1,394
85		DHI-SCP3024B-CBZ	Adopts the Android 14 system, 4 GB RAM + 16 GB ROM, offering advanced performance and a user-friendly experien	SAR 1,394
86		DHI-SCP3022A-B	Adopts the Android 14 system, 4 GB RAM + 16 GB ROM, offering advanced performance and a user-friendly experien	SAR 1,297
87		DHI-SCP3024A-B	Adopts the Android 14 system, 4 GB RAM + 16 GB ROM, offering advanced performance and a user-friendly experien	SAR 1,236
88		DHI-SCP3044A-BZ	Adopts the Android 14 system, 4 GB RAM + 16 GB ROM, offering advanced performance and a user-friendly experien	SAR 1,576
89		DHI-VTO4201F-P1	Modular video door station with one button	SAR 435

90		**DHI-VTO4201FB-P1**	Modular video door station with one button	**SAR 435**
91		**DHI-VTO4202F-MK**	Modular video door keypad	**SAR 255**
92		**DHI-VTO4202FB-MK**	Modular video door keypad	**SAR 255**
93		**DHI-VTO4202F-MR**	Modular video door card modular, IC card	**SAR 158**
94		**DHI-VTO4202FB-MR**	Modular video door card modular, IC card	**SAR 158**
95		**DHI-VTO4202F-MR1**	Modular video door card modular, ID card	**SAR 158**
96		**DHI-VTO4202FB-MR1**	Modular video door card modular, ID card	**SAR 158**
97		**DHI-VTO4202F-MB2**	Modular video door 2 buttons	**SAR 141**
98		**DHI-VTO4202FB-MB2**	Modular video door 2 buttons	**SAR 127**
99		**DHI-VTO4202F-MB5**	Modular video door 5 buttons	**SAR 119**
100		**DHI-VTO4202FB-MB5**	Modular video door 5 buttons	**SAR 119**
101		**DHI-VTO4202F-MDB10**	Modular video door 10 buttons	**SAR 219**
102		**DHI-VTO4202FB-MDB10**	Modular video door 10 buttons	**SAR 226**
103		**DHI-VTO4202F-MS**	Modular video door screen	**SAR 121**
104		**DHI-VTO4202FB-MS**	Modular video door screen	**SAR 121**
105		**DHI-VTO4202F-ML**	Touchless 0-ch IP55 IK07 Indicator Module	**SAR 102**
106		**DHI-VTO4202FB-ML**	Touchless 0-ch IP55 IK07 Indicator Module	**SAR 102**
107		**DHI-VTO4202FB-MF**	Fingerprint Touchless 0-ch IP55 IK07 Fingerprint Module	**SAR 318**
108		**VTM130**	Surface Mounting Plate for VTO65/75 Series Door Station	**SAR 133**
109		**VTM121**	Flush Mount Plate for VTO65/75 Series Door Station	**SAR 100**
110		**VTM75**	Silver surface rain cover, single modualr	**SAR 80**
111		**VTM76**	Black surface rain cover; single modualr	**SAR 80**
112		**VTM77**	Silver pannel, single modualr	**SAR 107**

113		**VTM78**	Black pannel, single modualr	**SAR 120**
114		**VTM79**	Flush mount box, single modualr	**SAR 53**
115		**VTM126**	silver pannel, 3 modular	**SAR 173**
116		**VTM128**	Silver surface braket, 3 modular	**SAR 173**
117		**VTM125**	silver pannel, 2 modular	**SAR 133**
118		**VTM127**	Silver surface braket, 2 modular	**SAR 153**
119		**DH-H3AS**	High-performance image sensor, low luminance, and high definition image. Supports 3 MP (2304 × 1296)@15 fps.	**SAR 97**
120		**DH-H5AS**	High-performance image sensor, low luminance, and high definition image. Supports 5 MP (2880 × 1620)@15 fps.	**SAR 117**
121		**DH-H3JE**	High-performance image sensor, low luminance, and high definition image. Supports 3 MP (2304 × 1296)@15 fps.	**SAR 109**
122		**DH-H5JE**	High-performance image sensor, low luminance, and high definition image. Supports 5 MP (2880 × 1620)@15 fps.	**SAR 131**
123		**DH-P3AS**	3-MP 1/3.2" CMOS image sensor, low luminance, and high definition image.	**SAR 167**
124		**DH-P5AS**	5-MP 1/3.2" CMOS image sensor, low luminance, and high definition image.	**SAR 187**
125		**DH-P5X**	5-MP 1/3" CMOS image sensor, low luminance, and high definition image.	**SAR 197**
126		**DH-P3D**	2 × 3-MP 1/3.2" CMOS image sensor, low luminance, and high definition image. Outputs max. 6 MP (2304 × 1296)@1	**SAR 258**
127		**DH-P5D**	2 × 5-MP 1/3.2" CMOS image sensor, low luminance, and high definition image. Outputs max. 10 MP (2880 × 1620)@	**SAR 301**
128		**DH-BP3E**	3-MP image sensor, low illuminance, and high definition image.	**SAR 343**
129		**DH-BP5E**	5-MP image sensor, low illuminance, and high definition image.	**SAR 362**
130		**DH-BP5E-4G**	5-MP image sensor, low illuminance, and high definition image.	**SAR 381**

DAHUA ACCESS CONTROL & ATTENDANCE

131		**DHI-ASI3204E-DW**	Dahua Single Door Face Recognition Access Controller	**SAR 340**
132		**DHI-ASI3214A-W**	Face Recognition Access Controller > Multiple unlock methods: fingerprint, face, IC card and pass word. You ca	**SAR 608**
133		**DHI-ASI1212F-D**	Access Standalone	**SAR 481**
134		**DHI-ASI2212J-DPW**	Dahua Single Door Password, ID Card, Fingerprint, Bluetooth Access Standalone > 2.4" TFT display screen with a	**SAR 430**

135		**DHI-ASI2212H-DW**	Access Standalone	**SAR 591**
136		**DHI-ASI6213D-W**	Dahua Face Recognition Access Controller (Multiple unlock methods including face, card, password and QR code)	**SAR 595**
137		**DHI-ASI6214S-D**	Face Recognition Access Controller-ID > 4.3 inch glass touch screen with a resolution of 272 × 480. > 2-MP wid	**SAR 811**
138		**DHI-ASI6214J-MFW**	FACT Access Control Terminal > 4.3-inch LCD touch screen; resolution 480 × 272 > 2MP wide-angle dual lens came	**SAR 1,184**
139		**DHI-ASI6214S-PW**	Face Recognition Access Controller-Wi-Fi	**SAR 1,008**
140		**DHI-ASI7213S-W**	Dahua Face Recognition,Card Swiping,Password Face Recognition Access Controller > 7" LCD with a resolution of	**SAR 1,080**
141		**DHI-ASI6214D-W**	• Visible Light Facial Recognition and Liveness Detection	**SAR 662**
142		**DHI-ASI6214S**	Face Recognition Access Controller-IC	**SAR 811**
143		**DHI-ASI1201M-MEP**	The front part of the case is made of zinc alloy and the back part is made of plastic.	**SAR 380**
144		**DHI-ASI1201M-MEW**	The front part of the case is made of zinc alloy and the back part is made of plastic.	**SAR 380**
145		**DHI-ASI1201M-MEW (WIFI)**	Card Swiping, Password Access Standalone (WIFI)	**SAR 380**
146		**ASI1202M/ASI1202M-D**	Access Control Standalone Terminal > Material: Zinc alloy plate > Support card unlock, fingerprint unlock, and	**SAR 481**
147		**DHI-ASI1201A-D**	RFID Standalone > Touch keyboard and LCD display > Support 30,000 valid cards & 150,000 records > Support m	**SAR 269**
148		**ASI1201E/ASI1201E-D**	> Support 30,000 valid cards & 150,000 records > Support multiple cards(default IC card) (“-D” means ID EM car	**SAR 222**
149		**DHI-ASR2200A-B**	Dahua Card Swiping, Bluetooth card Reader > PC material, tempered glass panel and IP66, suitable for indoor an	**SAR 185**
150		**DHI-ASR1200E-D**	Water-proof RFID Reader	**SAR 52**
151		**DHI-ASR1200E**	Water-proof RFID Reader	**SAR 52**
152		**DHI-ASR1102A-D(V3)**	Fingerprint RFID Reader-ID	**SAR 281**
153		**DHI-ASR2101A**	Access Reader-IC	**SAR 163**
154		**DHI-ASC2204B-S**	1. Support TCP/IP communication	**SAR 407**
155		**DHI-ASC2208C-S**	Access Controller	**SAR 1,036**
156		**DHI-ASM100-D**	Card Enrollment Reader	**SAR 155**
157		**DHI-ASM202**	Fingerprint Enrollment Reader	**SAR 370**

158		**DHI-ASF180A-V1**	Built of aluminum alloy and treated with surface oxidation, making it suitable for indoor scenes.	**SAR 84**
159		**DHI-ASF180B-V1**	Built of aluminum alloy and treated with surface oxidation, making it suitable for indoor scenes.	**SAR 161**
160		**DHI-ASF280A-V1**	Built of aluminum alloy and treated with surface oxidation, making it suitable for indoor scenes.	**SAR 105**
161		**DHI-ASF280B-V1**	Built of aluminum alloy and treated with surface oxidation, making it suitable for indoor scenes.	**SAR 202**
162		**DHI-ASF280ZL-V1**	The bracket is used to install and secure the magnetic lock.	**SAR 42**
163		**DHI-ASF280L-V1**	The bracket is used to install and secure the magnetic lock.	**SAR 21**
164		**DHI-ASF280U-V1**	The bracket is used to install and secure the magnetic lock.	**SAR 21**
165		**ASF908**	Professional circuit design, no mechanical failure	**SAR 69**
166		**ASF921**	Photoelectric control technology to prevent the mechanical failure	**SAR 45**
167		**ASF900**	Professional circuit design, no mechanical failure	**SAR 7**
168		**ASF905**	Professional circuit design, no mechanical failure	**SAR 42**
169		**IC-S50**	Mifare 1, 13.56MHz;	**SAR 5**
170		**IC-SM**	Compatible with ISO 14443-A protocol.	**SAR 3**
171		**IC-M1**	Mifare 1, 13.56MHz	**SAR 1**
172		**IC-S70**	Supports ISO/IEC 14443-A protocol.	**SAR 7**
173		**IC-M1B**	Compatible with ISO/IEC 14443-A protocols.	**SAR 3**
174		**ID-EM**	Compatible with ISO 7815 protocol.	**SAR 3**
175		**ID-SM**	Compatible with ISO 7815 protocol.	**SAR 3**

DAHUA VIDEO INTERCOM

176		**DHI-VTO2311R-WP**	Wi-Fi Villa Door Station,IK07/IP65	**SAR 416**
177		**DHI-VTO6541H-S2**	4.3" inch screen Face VTO terminal with fingerptint	**SAR 1,900**
178		**DHI-VTH5321GB-W**	7" inch IP Android VTH	**SAR 793**
179		**DHI-VTO6531H-S2**	4.3" inch screen Face VTO terminal	**SAR 1,427**

180		**DHI-KTA02**	> VTK-VTO2010D + VTK-VTH2020DW +Mounting box + Adapter + Cable, 4-Wire indoor monitor KIT 2MP CMOS camera,	**SAR 315**
181		**DHI-VTH5341G-W**	10" inch IP Android VTH	**SAR 918**
182		**DHI-VTO2201F-P-S2**	Villa door station with one button,IK07/IP65	**SAR 487**
183		**DHI-KTH01**	7” inch monitor Analog VDP KIT with mobile function	**SAR 429**
184		**DHI-KTP02**	•IP KIT •VTO VT2111D-P-S2+VTH2421FW-P+4 ports POE switch PFS3005-4ET-36 in one package •VTO come with a 2MP fi	**SAR 837**
185		**DHI-KTP03PRO**	IP Video Intercom KIT IP Villa Door Station > Megapixel image sensor > Supports IR illumination and night visi	**SAR 741**
186		**DHI-KTP04 PRO**	Video Intercom KIT	**SAR 937**
187		**DHI-KTP01L(S) (F)**	DHI-VTO2202F+DHI-VTH2421FW-P+PFS3005-4ET-60+Mounting box+Adapter	**SAR 874**
188		**DHI-KTP01(S) (F)**	> DHI-VTO2202F+DHI-VTH2421FW-P+PFS3005-4ET-60+Mounting box+Adapter	**SAR 874**
189		**DHI-KTP01 PRO**	Dahua 2Mp Touch 6-ch IP65 Video Intercom KIT DHI-VTO2201F-P,DHI-VTH8621KMS-WP,DH-PFS3006-4ET-36	**SAR 975**
190		**DHI-KTX01(S)**	7” inch monitor 2 wire Analog VDP KIT with mobile function	**SAR 915**
191		**DHI-VTH2421FB-P**	7" TFT Capacitive touch screen, 1024x600	**SAR 387**
192		**DHI-VTH8621KMS-WP**	7" inch IP VTH with elegant design	**SAR 445**
193		**DHI-VTO3311Q-WP**	IP & Wi-Fi Villa Door Station > Full metal casing design. > Customizable Number of Buttons. > Wi-Fi connection	**SAR 544**
194		**VTO6222E-P**	2-wire IP Apartment Door Station > Highly durable and elegant, it is made of aluminum panelÿ and has a mechanic	**SAR 807**
195		**DHI-VTO2111D-P-S3**	IP Villa Door Station > High definition camera; WDR > Operating temperature -30°C–60°C > IP65(Silicone seal	**SAR 381**
196		**DHI-VTO2202F-P-S3**	> 2MP CMOS camera > Mechanical button , > Night vision & voice indicator > 140° angle of view > Compatible wit	**SAR 567**
197		**VTM114**	Flush Mounted Box for VTO2202F-P, > Material: ADC12 > Dimensions(Front) : 128.9mm×162.9mm×34.5mm (5.08"×6.42"×	**SAR 67**
198		**VTM115**	Surface mounted Box for VTO2202F-P, > Material:AL5052 t=2.0mm > Dimensions: 129.0mm×95.0mm×28.5mm (5.08"×3.74"	**SAR 67**
199		**DHI-KTW02**	Wi-Fi Villa Door Station& IP Indoor Monitor > Ultra slim design > PC and ABS material make it ideal for indo	**SAR 741**
200		**DHI-KTD01L(S)**	7” inch monitor 2-wire IP Villa Door Station	**SAR 1,129**
201		**DHI-VTO1000J**	· 1.3mp, Video intercom function: Unlock, voice call, video call and volume	**SAR 141**
202		**DHI-VTO1000JM**	1.3mp	**SAR 153**

203		**DHI-VTH1020J**	7” inch Analog VTH	**SAR 181**
204		**DHI-DS1AG**	Dahua Indoor Doorbell Wireless Chime,	**SAR 99**
205		**DH-DB41AB**	4MP WiFi Video Doorbell	**SAR 219**
206		**DHI-VTH2624GW-WP**	7” inch 4 wire Hybrid VTH	**SAR 326**
207		**DHI-KTX01(F)**	7” inch monitor 2 wire Analog VDP KIT with mobile function	**SAR 915**

DAHUA NETWORK VIDEO RECORDER

208		**DHI-NVR1104HS-S3/H**	•H.265+ •1HDD •4CH •4ch@1080P Decode	**SAR 236**
209		**DHI-NVR1104HS-P-S3/H**	•H.265+ •1HDD •4CH POE •4ch@1080P Decode	**SAR 298**
210		**DHI-NVR1108HS-S3/H**	•H.265+ •1HDD •8CH •4ch@1080P Decode	**SAR 286**
211		**DHI-NVR1108HS-8P-S3/H**	•H.265+ •1HDD •8CH POE •4ch@1080P Decode	**SAR 445**
212		**NVR4104HS-4KS2/L**	80Mbps input, 4ch 1080P decoding, max 4 IPC input, H.265+&H.264+ 1HDD, 1 VGA&1 HDMI, 1 RJ45(100M), 2 USB2.0 S	**SAR 310**
213		**DHI-NVR4104HS-P-4KS2/L**	80Mbps input, 8ch 1080P decoding, max 4 IPC input, H.265+&H.264+	**SAR 410**
214		**DHI-NVR4104HS-P-4KS3**	80Mbps input, 8ch 1080P decoding, max 4 IPC input, H.265+&H.264+	**SAR 466**
215		**DHI-NVR4108HS-4KS3**	80Mbps input, 8ch 1080P decoding, max 8 IPC input, H.265+&H.264+ 1HDD, 1 VGA&1 HDMI, 1 RJ45(100M), 2 USB2.0 S	**SAR 431**
216		**DHI-NVR4108HS-8P-4KS3**	160Mbps input, 8ch 1080P decoding, max 8 IPC input, H.265+&H.264+ 1HDD, 1 VGA&1 HDMI, 1 RJ45(100M), 8PoE, 2 U	**SAR 672**
217		**DHI-NVR4116HS-8P-4KS3**	160Mbps input, 8ch 1080P decoding, max 16 IPC input, H.265+&H.264+ 1HDD, 1 VGA&1 HDMI, 1 RJ45(1000M), 8PoE, 2	**SAR 837**
218		**DHI-NVR4208-4KS3**	128Mbps input, 8ch 1080P decoding, max 8 IPC input, H.265+&H.264+	**SAR 542**
219		**DHI-NVR4208-8P-4KS3**	160Mbps input, 8ch 1080P decoding, max 8 IPC input, H.265+&H.264+ 2HDD, 1 VGA&1 HDMI, 1 RJ45(1000M), 8PoE, 2 U	**SAR 847**
220		**DHI-NVR4208-XI**	8CH Compact 1U 2Bay WizMind Network Video Recorder (AcuPick Camera Supports Each HDD up to 20 TB.)	**SAR 783**
221		**DHI-NVR4208-8P-XI**	8CH 8 PoE Compact 1U 2Bay WizMind Network Video Recorder (AcuPick Camera Supports Each HDD up to 20 TB.)	**SAR 1,143**
222		**DHI-NVR5208-EI**	8 Channels 1U 2HDDs WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding for	**SAR 1,022**
223		**DHI-NVR5208-8P-EI**	8 Channels 1U 8PoE 2HDDs WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decodin	**SAR 1,430**
224		**DHI-NVR5216-EI**	16 Channels 1U 2HDDs WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding fo	**SAR 1,227**

225		**DHI-NVR5216-16P-EI**	16 Channels 1U 16PoE 2HDDs WizSense Network Video Recorder	**SAR 2,011**
226		**DHI-NVR4216-4KS3**	160Mbps input, 8ch 1080P decoding, max 16 IPC input, H.265+&H.264+ 2HDD, 1 VGA&1 HDMI, 1 RJ45(1000M), 2 USB2.	**SAR 627**
227		**DHI-NVR4216-16P-4KS3**	160Mbps input, 8ch 1080P decoding, max 16 IPC input, H.265+&H.264+ 2HDD, 1 VGA&1 HDMI, 1 RJ45(1000M), 16PoE, 2	**SAR 1,107**
228		**DHI-NVR4216-16P-EI**	16CH 1U 16PoE 2HDDs WizSense Network Video Recorder	**SAR 1,499**
229		**DHI-NVR4232-4KS3**	160Mbps input, 8ch 1080P decoding, max 32 IPC input, H.265+&H.264+ 2HDD, 1 VGA&1 HDMI, 2 RJ45(1000M), 2 USB(1	**SAR 842**
230		**DHI-NVR4232-EI**	32CH 1U 2HDDs WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format >	**SAR 1,039**
231		**DHI-NVR4432-4KS3**	32 CHANNEL NVR - 4K 256Mbps input, 32ch 1080P decoding, max 32 IPC input, H.265+&H.264+ 4HDD, 1 VGA&1 HDMI, 2	**SAR 1,225**
232		**DHI-NVR4432-EI**	32CH 1.5U 4HDDs WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding format	**SAR 1,768**
233		**DHI-NVR4432-16P-EI**	32 CHANNEL NVR WITH -16 POE	**SAR 2,447**
234		**DHI-NVR5232-EI**	32 Channels 1U 2HDDs WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decoding fo	**SAR 1,441**
235		**DHI-NVR5232-16P-EI**	32 Channels 1U 16PoE 2HDDs WizSense Network Video Recorder > Smart H.265+/H.265/Smart H.264+/H.264/MJPEG decod	**SAR 2,421**
236		**DHI-NVR5232-EI2**	32 Channels 1U 2HDDs WizSense Network Video Recorder	**SAR 1,513**
237		**DHI-NVR5416-16P-EI**	16 Channels 2U - 4HDD WizSense Network Video Recorder	**SAR 2,865**
238		**DHI-NVR5432-EI**	Dahua 32CH 4HDD 1.5U NETWORK VIDEO RECORDER > Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG deco	**SAR 2,178**
239		**DHI-NVR5432-16P-EI**	32 Channels 1.5U 16PoE 4HDDs WizSense NVR	**SAR 3,049**
240		**NVR2108HS-8P-4KS2**	8 Channel Compact 1U 8PoE Lite 4K H.265 Network Video Recorder, > Smart H.265+/Smart H.264+/H.265/H.264	**SAR 512**
241		**DHI-NVR4104HS-4KS3**	80Mbps input, 8ch 1080P decoding, max 4 IPC input, H.265+&H.264+	**SAR 402**
242		**DHI-NVR4108HS-P-4KS3**	80Mbps input, 8ch 1080P decoding, max 8 IPC input, H.265+&H.264+	**SAR 593**
243		**DHI-NVR4116HS-4KS3**	160Mbps input, 8ch 1080P decoding, max 16 IPC input, H.265+&H.264+	**SAR 490**
244		**DHI-NVR4232-16P-4KS3**	160Mbps input, 8ch 1080P decoding, max 32 IPC input, H.265+&H.264+	**SAR 1,454**
245		**DHI-NVR4104HS-XI**	• Max. Decoding Capability: 24 × 1080p@30 fps or 6 × 8 MP@30 fps	**SAR 592**
246		**DHI-NVR4104HS-P-XI**	• Max. Decoding Capability: 24 × 1080p@30 fps or 6 × 8 MP@30 fps	**SAR 762**
247		**DHI-NVR4416-EI**	16CH 1.5U 4HDDs WizSense Network Video Recorder	**SAR 1,483**

248		DHI-NVR4416-16P-EI	16CH 1.5U 16PoE 4HDDs WizSense Network Video Recorder	SAR 2,154
249		DHI-NVR5416-EI	16 Channels 1.5U 4HDDs WizSense Network Video Recorder	SAR 2,028
250		DHI-NVR5832-EI	32 Channels 2U 8HDD WizSense Network Video Recorder	SAR 3,937
251		DHI-NVR5832-16P-EI	32 Channels 2U 16PoE 8HDDs WizSense Network Video Recorder	SAR 5,028
252		DHI-NVR5864-EI	64 Channels 2U 8HDDs WizSense Network Video Recorder	SAR 3,961
253		DHI-NVR5864-16P-EI	64 Channels 2U 16PoE 8HDDs WizSense Network Video Recorder	SAR 5,446
254		DHI-NVR5208-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 1,073
255		DHI-NVR5208-8P-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 1,584
256		DHI-NVR5216-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 1,386
257		DHI-NVR5216-16P-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 2,088
258		DHI-NVR5232-16P-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 2,542
259		DHI-NVR5416-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 2,129
260		DHI-NVR5432-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 2,287
261		DHI-NVR5832-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 4,562
262		DHI-NVR5832-16P-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 5,279
263		DHI-NVR5864-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 4,985
264		DHI-NVR5864-16P-EI2	Supports Smart H.265+, H.265, Smart H.264+, H.264 and MJPEG decoding formats.	SAR 5,718
IP CAMERA-LIGHT 2MP 6MP 8MP				
265		DH-IPC-HDW1239T1-A-IL	2MP Full-color 2.8mm Fixed-focal Eyeball Netwok Camera	SAR 118
266		DH-IPC-HFW1239S1-A-IL	2 MP IPC FULL COLOR IR BULLET CAMERA	SAR 115
267		DH-IPC-HDW1639T-A-IL	6MP Entry Smart Dual Light Fixed-focal Eyeball Network Camera	SAR 249
268		DH-IPC-HDBW1639E1-A-IL	6MP Entry Smart Dual Light Fixed-focal Dome Network Camera >6MP (3200 × 1800) @20/30 fps >IR 30m, Warm light 3	SAR 249
269		DH-IPC-HFW1639TC-A-IL	6MP Entry Smart Dual Light Fixed-focal Bullet Network Camera >6MP (3200 × 1800) @20/30 fps >IR 30m, Warm light	SAR 249

270		**DH-IPC-HFW1839TC-A-IL**	8MP Entry Smart Dual Light Fixed-focal Bullet Network Camera	**SAR 420**
271		**DH-IPC-HDBW1839E1-A-IL**	8MP Entry Smart Dual Light Fixed-focal Network Dome Camera	**SAR 412**
272		**DH-IPC-HDW1839T-A-IL**	8MP Entry Smart Dual Light Fixed Network Camera	**SAR 412**
273		**DH-IPC-HFW1239TL1-A-IL**	2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image.	**SAR 139**
274		**DH-IPC-HDBW1239E1-A-IL**	2-MP 1/2.8" CMOS image sensor, low luminance, and high definition image.	**SAR 143**
IPC-2MP DAHUA IP CAMERA				
275		**IPC-HFW1230T1-ZS-S4**	2MP Entry IR Motorized/Vari-focal Bullet Netwok Camera,	**SAR 325**
276		**IPC-HDW2231T-ZS-S2** **SPECIAL PRICE WHILE STOCKS LAST**	> 2MP (1920 × 1080)@25/30 fps, IR 60m > motorized vari-focal 2.7mm–13.5mm > H.265 > max. 256 GB Micro SD card	**SAR 360**
277		**IPC-HFW2231T-ZS-S2 SPECIAL PRICE WHILE STOCKS LAST**	> 2MP (1920 × 1080)@25/30 fps, IR 60 m > motorized vari-focal 2.7mm–13.5mm > H.265 > Supports max. 256 GB Micr	**SAR 375**
IPC-5MP DAHUA IP CAMERA				
278		**IPC-HDBW2541E-S**	5MP IR Fixed-focal Dome WizSense Network Camera	**SAR 315**
279		**IPC-HFW2541S-S**	> 5MP (2592×1944)@25/30fps > IR 30 m > H.264/H.265 > max. 256 GB Micro SD card > POE >metal housing	**SAR 313**
280		**DH-IPC-HFW2541E-S**	5-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.> Outputs max. 5 MP (2592 × 1944) @20	**SAR 341**
281		**IPC-HFW2541T-AS**	· 5MP, 1/2.7" CMOS image sensor, low illuminance, high image definition · Outputs max. 5MP (2592 × 1944) @20 f	**SAR 333**
282		**IPC-HDW2541T-S**	5MP IR Fixed-focal Eyeball WizSense Network Camera	**SAR 328**
283		**IPC-HFW2541T-ZS**	> 5MP Lite IR Vari-focal Bullet Network Camera, 5MP(2592×1944)@25/30fps, > motorized vari-focal 2.7mm–13.5m	**SAR 537**
284		**IPC-HDW2541T-ZS**	>5MP IR Vari-focal Eyeball WizSense Network Camera > motorized vari-focal 2.7mm–13.5mm > IR 40m > H.264/	**SAR 549**
285		**DH-IPC-HDBW2541R-ZS**	5MP IR Vari-focal Dome WizSense Network Camera > 5-MP 1/2.7" CMOS image sensor, low luminance, and high defini	**SAR 528**
286		**DH-IPC-HDBW2541R-ZAS**	5MP IR Vari-focal Dome WizSense Network Camera > 5-MP 1/2.7" CMOS image sensor, low luminance, and high defini	**SAR 533**
287		**DH-IPC-HFW2541T-ZAS**	5MP IR Vari-focal Bullet WizSense Network Camera > 5-MP 1/2.7" CMOS image sensor, low luminance, and high defi	**SAR 547**
288		**IPC-EW5541-AS**	>5MP(1~20fps) >H.265+/H.265/H.264+/H.264 >1.4mm fisheye lens >IR 10m >Micro SD, >Bulit-in Mic >PoE	**SAR 739**
IPC-8MP DAHUA IP CAMERA				
289		**IPC-HFW2841S-S**	> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 8 MP (3840 × 2160) @	**SAR 435**

290		**IPC-HDW2841T-S**	> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 8 MP (3840 × 2160) @	**SAR 400**
291		**DH-IPC-HFW2841T-AS**	> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 8 MP (3840 × 2160) @	**SAR 468**
292		**IPC-HDW2841T-AS**	> 8MP@15FPS, 4MP@30FPS > H.265ÿ IR 30 mÿ POE > SD c Housing	**SAR 366**
293		**DH-IPC-HDBW2841E-S**	> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 8 MP (3840 × 2160) @	**SAR 425**
294		**DH-IPC-HFW2841T-ZS**	> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 8 MP (3840 × 2160) @	**SAR 730**
295		**DH-IPC-HDBW2841R-ZS**	8MP IR Vari-focal Dome WizSense Network Camera	**SAR 730**
296		**DH-IPC-HDW2841T-ZS**	> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 8 MP (3840 × 2160)@2	**SAR 604**
297		**IPC-HDBW2841R-ZAS**	> 8MP@15FPS, 4MP@30FPS > H.265, IR 40 m, POE > SD card, Audio 1 in 1 out Moterized lens Vandalproof	**SAR 738**
298		**DH-IPC-HFW2841T-ZAS**	> 8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image. > Outputs max. 8 MP (3840 × 2160) @	**SAR 738**
299		**IPC-HDW2831T-ZS-S2**	> 8MP Lite IR Vari-focal Eyeball Nework Camera > 8MP@15FPS, 4MP@30FPS > H.2	**SAR 571**
DAHUA IP CAMERA 12MP				
300		**DH-IPC-HDW21249T-S-IL**	12-MP 1/2.5" CMOS image sensor, low luminance, and high definition image.	**SAR 469**
301		**DH-IPC-HFW21249T-AS-IL**	12-MP 1/2.5" CMOS image sensor, low luminance, and high definition image.	**SAR 480**
IP CAMERA - SMART DUAL ILLUMINATIONÿ IR+LEDÿ				
302		**DH-IPC-HFW2549S-S-IL**	5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera > 5-MP 1/2.7" CMOS image sensor, low luminance	**SAR 329**
303		**DH-IPC-HDW2549T-S-IL**	5MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera > 5-MP 1/2.7" CMOS image sensor, low luminanc	**SAR 331**
304		**DH-IPC-HFW2549T-AS-IL**	5MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera > 5-MP 1/2.7" CMOS image sensor, low luminance	**SAR 371**
305		**DH-IPC-HDBW2649E-S-IL**	6MP Smart Dual Light Fixed-focal Dome WizSense Network Camera	**SAR 396**
306		**DH-IPC-HFW2649S-S-IL**	6MP NETWORK BULLET CAMERA-Smart Dual Light Fixed-focal WizSense	**SAR 430**
307		**DH-IPC-HDW2849T-S-IL**	8MP Smart Dual Light Fixed-focal Eyeball WizSense Network Camera	**SAR 455**
308		**DH-IPC-HFW2849S-S-IL**	8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera	**SAR 466**
309		**DH-IPC-HFW2849T-AS-IL**	8MP Smart Dual Light Fixed-focal Bullet WizSense Network Camera > 8-MP 1/2.7" CMOS image sensor, low luminance	**SAR 495**
310		**DH-IPC-HFW2849T-ZAS-IL**	8MP Smart Dual Light Vari-focal Bullet WizSense Network Camera	**SAR 785**

Metal

311		DH-IPC-HFW2649T-ZAS-IL	1. Built-in IR and LED light, freely switch illumination mode;	SAR 750
312		DH-IPC-HDW2649T-ZS-IL	1. Built-in IR and LED light, freely switch illumination mode;	SAR 687
313		DH-IPC-HFW2649T-AS-IL	1. Built-in IR and LED light, freely switch illumination mode;	SAR 436
314		DH-IPC-HDBW2849E-S-IL	8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.	SAR 485
IPC-WIZCOLOR				
315		DH-IPC-HDW2549T-S-PRO	5MP 1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 5MP (2960×1668)@20 fps,	SAR 368
316		DH-IPC-HFW2549TL-S-PRO	5MP 1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 5MP (2960×1668) @20 fps,	SAR 368
317		DH-IPC-HFW2549M-S-B-PRO	5MP 1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 5MP (2960×1668) @20 fps,	SAR 388
318		DH-IPC-HDW2649T-S-PRO	1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 6MP (3288 ×1850) @20 fps, an	SAR 486
319		DH-IPC-HFW2649TL-S-PRO	1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 6 MP (3288 ×1850) @20 fps, a	SAR 486
320		DH-IPC-HFW2649M-S-B-PRO	1/1.8" CMOS image sensor, low luminance, and high definition image.	SAR 500
321		DH-IPC-HDW2849T-S-PRO	8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 8 MP (3840 × 2160)@20 f	SAR 507
322		DH-IPC-HFW2849TL-S-PRO	8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image. Outputs max. 8 MP (3840 × 2160)@20 f	SAR 507
323		DH-IPC-HFW2849M-S-B-PRO	8-MP 1/1.8" CMOS image sensor, low luminance, and high definition image.	SAR 525
DAHUA TIOC IP CAMERAÿ FULL COLOR0 AI0 ACTIVE DETERRENCEÿ				
324		DH-IPC-HFW3849T1-AS-PV	8MP Smart Dual Light Active Deterrence Fixed-focal Bullet WizSense Network Camera	SAR 767
325		DH-IPC-PFW2849S-A180-S-PV	2x4MP Duo Splicing Fixed-focal Bullet WizSense Network Camera	SAR 585
326		DH-IPC-PDW2849-A180-S-PV	2x4MP Duo Splicing Fixed-focal Eyeball WizSense Network Camera	SAR 585
327		IPC-HFW3849T1-AS-PV-PRO	> 8MP @20 fps, 25fps,30fps > Smart H.265+, POEÿ WDR, Full color > Sound and light LEDÿ 40 m > Intelligent	SAR 1,158
328		DH-IPC-PFW3849S-A180-AS-PV	2x4MP TiOC Duo Splicing Fixed-focal Bullet WizSense Network Camera > Outputs 180° wide angle splicing image. >	SAR 1,000
329		DH-IPC-HFW2849TL-S-T-PV	8MP Smart Dual Light Fixed-focal WizSense Network Bullet Camera	SAR 469
330		DH-IPC-PDW3849-A180-AS-PV	2x4MP TiOC Duo Splicing Fixed-focal Eyeball WizSense Network Camera > Outputs 180° wide angle splicing image.	SAR 1,000
331		IPC-HDW3849H-AS-PV	> 8MP @20 fps, 25fps,30fps > Smart H.265+, POEÿ WDR, Full color > Sound and light LEDÿ 30 m > Intelligent	SAR 672

332		**IPC-HDW3549H-AS-PV**	> 5MP (2592 × 1944) @20 fps > Smart H.265+, POEÿ WDR, I alarm, LEDÿ 30 m > Intelligen	**SAR 662**
333		**DH-IPC-HFW3849T1-ZAS-PV**	8MP Smart Dual Light Active Deterrence Vari-focal Bullet WizSense Network Camera > 8-MP 1/2.8" CMOS image sens	**SAR 1,091**
334		**IPC-HFW3549T1-AS-PV**	> 5MP (2592 × 1944) @20 fps > Smart H.265+, POEÿ WDR, I alarm, LEDÿ 40 m > Intelligen	**SAR 732**
335		**DH-IPC-HFW2649TL-S-T-PV**	1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 441**
336		**DH-IPC-HDW2649TM-S-T-PV**	1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 425**
337		**DH-IPC-HDW2849TM-S-T-PV**	8-MP 1/2.7" CMOS image sensor, low luminance, and high definition image.	**SAR 476**
338		**DH-IPC-HFW3649T1-AS-PV-PRO**	6-MP 1/1.8" CMOS image sensor, low luminance, and high definition image.	**SAR 1,010**
339		**DH-IPC-HDW3849H-AS-PV-PRO**	8MP @20 fps, 25fps,30fps	**SAR 969**
340		**DH-IPC-HFW3849T1-ZAS-PV-PRO**	8MP Smart Dual Light Active Deterrence Vari-focal Bullet WizSense Network Camera	**SAR 1,447**
IP CAMERA - FULL COLOR				
341		**DH-IPC-HDW2439T-AS-LED-S2**	•4MP FULL COLOR •H.265+ •WDR •LED Up to m •IP67 •Metal	**SAR 344**
342		**DH-IPC-HFW2439S-SA-LED-S2**	•4MP FULL COLOR •H.265+ •WDR •LED Up to m •IP67 •Metal	**SAR 342**
343		**DH-IPC-HDW2239T-AS-LED-S2**	•2MP FULL COLOR •H.265+ •WDR •LED Up to m •IP67 •Metal	**SAR 296**
344		**DH-IPC-HDW1239T1-LED-S5**	•2MP FULL COLOR •H.265+ •DWDR •LED Up to 10m •IP67 •Metal+Plastic	**SAR 195**
345		**DH-IPC-HFW1239S1-LED-S5**	•2MP FULL COLOR •H.265+ •DWDR •LED Up to 10m •IP67 •Metal+Plastic	**SAR 195**
DAHUA PTZ IP CAMERA 2MP				
346		**DH-SD49216DB-HNY**	2MP 16X IR Network PTZ Camera	**SAR 1,011**
347		**DH-SD4D225DB-HNY**	1/2.8" 2Megapixel STARVIS™ CMOS.	**SAR 1,231**
348		**DH-SD5A225GB-HNR**	2MP 25x Starlight IR WizSense Network PTZ Camera	**SAR 2,221**
349		**DH-SD6E232MB-HNR-A-PV1**	1/2.8" 2Megapixel STARVIS™ CMOS	**SAR 3,080**
350		**DH-SD6E245MB-HNR-A-PV1**	1/2.8" 2Megapixel STARVIS™ CMOS	**SAR 3,505**
351		**DH-SD2A300NB-GNY-A-PV**	3MP Smart Dual Light Network PT Camera	**SAR 260**
352		**DH-SD3E205DB-GNY-A-PV1**	1/2.8" 2Megapixel CMOS	**SAR 699**

353		**DH-SD49225DB-HNY**	> 2MP 25x Starlight IR PTZ Network Camera > 25x optical zoom > Max.25/30fps@1080P > PoE+,IR 100m,	**SAR 1,127**
354		**DH-SD60230UN-HNI**	> 2MP Starlight >30x optical zoom, >H.265, Auto-tracking, IR 200m, > vandaproof, POE+,	**SAR 2,685**
355		**DH-SD6CE245GB-HNR**	> 2MP Starlight > 45x optical zoom, >H.265, Auto-tracking, IR 250m, > vandaproof, POE+	**SAR 2,823**
356		**DH-SD5A232GB-HNR**	>2MP Starlight >32x optical zoom >H.265, Auto-tracking, >IR 150m, POE+	**SAR 1,979**
357		**SD5A225XAN-HNR**	> 2MP 25x Starlight IR PTZ Network Camera > 25x optical zoom > Max. 50/60fps@1080P > Auto-tracking , PoE+,IR	**SAR 1,678**
358		**SD49216UE-HN**	> 2MP 16x Starlight IR PTZ Network Camera > 16x optical zoom > ,Max.25/30fps@1080P > PoE+,IR 100m,	**SAR 1,190**
359		**SD42C212T-HN-S2**	> 2MP 12x Starlight PTZ Network Camera > 12x optical zoom > Max. 25/30fps@1080P > PoE+, vandaproof	**SAR 1,082**

DAHUA PTZ IP CAMERA 4MP AND 8MP

360		**DH-SD2C400NA-B-PV-PRO**	1/1.8" 4Megapixel CMOS.	**SAR 444**
361		**DH-SD3E410DB-GNY-A-PV1**	4MP 5x Smart Dual Light WizSense PTZ	**SAR 894**
362		**DH-SD2A500NB-GNY-A-PV**	5MP Smart Dual Light Network PT Camera	**SAR 283**
363		**DH-SD4D825MB-HNR**	1/2.8" 8Megapixel STARVIS™ CMOS	**SAR 2,188**
364		**DH-IPC-PTS2449C-4E3Z-S-PV-PRO**	Displays videos in two channels at the same time	**SAR 726**
365		**DH-SD3E405DB-GNY-A-PV1**	1/2.8" 4Megapixel STARVIS™ CMOS	**SAR 766**
366		**DH-SD4D425MB-HNR**	1/2.8" 4Megapixel STARVIS™ CMOS	**SAR 1,672**
367		**DH-SD49425DB-HNY**	4MP 25x Starlight IR Network PTZ Camera	**SAR 1,496**
368		**DH-SDT4E425-8P-GB-APV1**	8+4MP 25x TiOC Network Panoramic PTZ Camera	**SAR 2,430**
369		**DH-SDT3E410-8P-MB-A-PV1**	Panoramaÿ Outputs 180° wide angle splicing image	**SAR 1,435**
370		**DH-SD6E425MB-HNR-A-PV1**	1/2.8" 4Megapixel STARVIS™ CMOS	**SAR 2,369**
371		**DH-SD6E445MB-HNR-A-PV1**	1/2.8" 4Megapixel STARVIS™ CMOS	**SAR 3,758**
372		**DH-SDT6C432-4P-GB-APV-0280**	4MP 32X Smart Dual Light Network Panoramic PTZ Camera > 1/2.8" 4Megapixel STARVIS™ CMOS > 32× optical zoom. >	**SAR 2,531**
373		**DH-SD49825GB-HNR**	1/2.8" 8MP STARVIS™ CMOS, 4K 25× optical zoom Starlight technology Max. 25/30 fps@8 MP IR distance up to 100 m	**SAR 2,202**
374		**DH-SDT4E425-4F-GB-A-PV1**	X-Spans 4MP+4MP 25x TiOC WizSense Network PTZ Camera	**SAR 1,894**

375		DH-SD1C432-4P-GB-APV-0280	4MP 32X Dual Light Network Panoramic PTZ Camera	SAR 2,531
376		DH-SD5A432GB-HNR	4MP 32x optical zoom	SAR 2,567
377		DH-SD49425GB-HNR	4MP 25x Starlight IR Network PTZ Camera > 1/2.8" STARVIS™ CMOS. > 25x optical zoom. > Starlight technology. >	SAR 1,462
378		DH-SD49425XB-HNR-S3	>4MP Starlight 25x optical zoom >Pro AI performance:,Perimeter protection, Video Structuralization, SMD >H.265	SAR 1,307
DAHUA IP PTZ-ACTVE DETERRENCE				
379		SD3A400-GNP-B-PV	4MP Full-color Active Deterrence WizSense Network PTZ Camera > 1/2.8" 4MP, Fixed lens > Starlight technology	SAR 667
380		SD3A205-GNP-PV	2MP Starlight IR AI WizSense Network PTZ Camera > 1/2.8" 2MP, 5X Optical Zoom > Starlight technology > IR dist	SAR 667
381		SD3A200-GNP-PV	2MP Starlight IR AI WizSense Network PTZ Camera > 1/2.8" 2MP, Fixed lens > Starlight technology > IR distance	SAR 578
382		SD3A200-GNP-W-PV	2MP Starlight IR Active Deterrence Wizsense Network PTZ Camera > 1/2.8" 2MP,Fixed lens > Starlight technology	SAR 578
DAHUA IP PTZ - SPECIAL SENARIO				
383		SD1A203T-GN-S2	> 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 3x optical zoom > Starlight, WDR > Max. 25/30fps@1080P > IVS > I	SAR 639
384		SD1A203T-GN-W-S2	> 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 3x optical zoom > Starlight, WDR > Max. 25/30fps@1080P > IVS	SAR 666
385		IPC-PDBW5831-B360	> Four 1/2.8" 2Megapixel progressive scan STARVISTM CMOS > H.265&H.264 dual-stream encoding > 25/30fps@2M(1920	SAR 4,657
4G SOLAR POWER NETWORK CAMERA				
386		DH-IPC-PTS2649C-3E3Z-4GB20	3+3MP WizColor Hybrid-zoom PT 4G Solar Power Network Camera > Displays videos in two channels at the same time	SAR 1,018
387		DH-IPC-HFW2441DG-4G-SP-B-MAX -	4MP Smart Dual Light Fixed-focal Bullet 4G Solar Power Network Camera	SAR 912
DAHUA HDVCI RECORDER SUPPORT 2MP				
388		DH-XVR1B04-I	4 CHANNEL XVR UP TO 2MP 1080N/720P realtime > H.265+/H.265 dual-stream video compression > Supports Full cha	SAR 159
389		DH-XVR1B04-I/T	4-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and rec	SAR 205
390		DH-XVR1B08-I	8 CHANNEL XVR UP TO 2MP 1080N/720P realtime > H.265+/H.265 dual-stream video compression, Supports Full chan	SAR 203
391		DH-XVR1B08-I/T	8-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and rec	SAR 258
392		DH-XVR1B16-I	16 CHANNEL XVR (UP TO 2MP) 1080N/720P realtime > H.265+/H.265 dual-stream video compression, Supports Full-c	SAR 375
393		DH-XVR1B16-I/T	• 16-ch Analog Video Input, Max. 1080N/720p@15fps Encoding Capability	SAR 502

HDVCI-2MP,4MP

394		**DH-HAC-T1A21N-U**	2MP IR HDCVI Fixed-focal Eyeball Camera . > Max. 30 fps@1080p > Smart IR Illumination > 25 m illumination dist	**SAR 51**
395		**DH-HAC-B1A21N-U**	2MP IR HDCVI Fixed-focal Bullet Camera . Max. 30 fps@1080p.	**SAR 52**
396		**HAC-B2A21**	> Max. 30fps@1080P > 3.6mm fixed lens (6mm optional) > IR 20m > Metal Housing	**SAR 64**
397		**DH-HAC-B2A21N-U**	Max. 30fps@1080P	**SAR 67**
398		**DH-HAC-HDW1200TRQN**	Max 30fps@1080P	**SAR 66**
399		**DH-HAC-HFW1200CMN**	Max 30fps@1080P	**SAR 77**
400		**DH-HAC-HFW1200CMN-A**	Max 30fps@1080P	**SAR 91**
401		**HAC-HDW1200TL-A**	> Max 30fps@1080P > Built-in mic > 3.6mm fixed lens (2.8mm optional) > IR 30m	**SAR 86**
402		**HAC-HDW1200TLMQ-A**	> Max 30fps@1080P, > Built-in mic	**SAR 93**
403		**DH-HAC-HDW1200TRQN-A**	Max 30fps@1080P	**SAR 83**
404		**HAC-HFW1200CM**	> Max 30fps@1080P > CVI/CVBS/AHD/TVI switchable > 3.6mm fixed lens > Max. IR length 30m, Smart IR	**SAR 68**
405		**HAC-HFW1200CM-A**	> Max 30fps@1080P > CVI/CVBS/AHD/TVI switchable > 3.6mm fixed lens > Built-in mic(-A) > Max. IR length 30m, S	**SAR 83**
406		**HAC-HDW1200EMN (POC)**	2MP HDCVI PoC IR Eyeball Camera, > Max 30fps@1080P, > HD and SD output switchable > 3.6mm	**SAR 80**
407		**HAC-HFW1200TN**	> Max 30fps@1080P > 3.6mm fixed lens (2.8mm, 6mm optional) > IR 30m > Metal Housing	**SAR 93**
408		**DH-HAC-HFW1200THN-I4**	Max 30fps@1080P	**SAR 101**
409		**DH-HAC-HFW1200THN-I4-A**	Max 30fps@1080P	**SAR 111**
410		**DH-HAC-HFW1200THN-I8**	> Max 30fps@1080P > 3.6mm fixed lens (6mm, 8mm optional) > IR 80m	**SAR 121**
411		**DH-HAC-HFW1200THN-I8-A**	Max 30fps@1080P	**SAR 133**
412		**DH-HAC-HFW1200RN-Z-IRE6**	Max 30fps@1080P	**SAR 165**
413		**HAC-HFW2231RN-Z-IRE6**	2MP Starlight HDCVI IR Bullet Camera,> Starlight, 120dB true WDR, 3DNR > Max 30fps@1080P, > HD and SD output s	**SAR 200**
414		**HAC-HDW1400EMN-POC**	>4MP HDCVI POC IR Eyeball Camera, > Max. 30fps@4MP, > HD and SD output switchable > 3.6mm fixed lens (2.8mm op	**SAR 115**
415		**HAC-HDBW1400RN-VF**	> 4MP HDCVI IR Dome Camera, Max 30fps@4MP > HD and SD output switchable, > 2.7-13.5mm vari-focal lens > Max. I	**SAR 200**

416		**HAC-HDW2401-EMN**	>4MP HDCVI WDR IR Eyeball Camera, 120dB True WDR, 3DNR, Max 4MP real-time, HD and SD dual-output, 3.6mm fixed	**SAR 170**
417		**HAC-HFW2401TN-Z-A**	4MP Starlight HDCVI IR Motorized Bullet Camera,· Starlight, 120dB true WDR, 3DNR, Max. 30fps@4MP, HD/SD output	**SAR 255**
418		**HAC-HDW2401R-Z**	> 4MP WDR HDCVI IR Eyeball Camera, > 120dB True WDR, 3DNR > Max 4MP real-time, > HD and SD dual-output > 2.7-1	**SAR 177**
419		**HAC-HFW3231EN-Z**	2MP Starlight HDCVI IR Bullet Camera, > Starlight, 120dB true WDR, 3DNR > Max 30fps@1080P > HD and SD dual-out	**SAR 465**
420		**HAC-LC1220TN-TH**	2MP HDCVI Temperature & Humidity Camera, > Max 30fps@1080P > 3.6mm fixed le	**SAR 140**

DAHUA HDVCI RECORDER SUPPORT 5MP

421		**DH-XVR5104HS-I3/T**	4-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and rec	**SAR 245**
422		**DH-XVR5108HS-I3/T**	8-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and rec	**SAR 387**
423		**DH-XVR5116HS-I3/T**	16-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and re	**SAR 769**
424		**DH-XVR5216AN-I3/T**	16-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and re	**SAR 982**
425		**DH-XVR5232AN-I3/T**	32-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and re	**SAR 1,635**
426		**DH-XVR1B04H-I**	4 CHANNEL XVR (UP TO 5MP) 4 Channels Penta-brid 5M-N/1080p Cooper 1U 1SSD 1TB WizSense Digital Video Recorde	**SAR 200**
427		**DH-XVR1B04H-I-T**	4 CHANNEL XVR (UP TO 5MP) 4CH Penta-brid 5MP Value/1080P Cooper 1U 1HDD WizSense Digital Video Recorder Doly	**SAR 226**
428		**DH-XVR1B08H-I/T**	8-channel two-way talk over coaxial cable allows for seamless communication between the camera, client and rec	**SAR 360**
429		**DH-XVR1B08H-I**	8 CHANNEL XVR (UP TO 5MP) 8CH Penta-brid 5MP Value/1080P Cooper 1U 1HDD WizSense Digital Video Recorder Dolynk	**SAR 315**
430		**XVR5104HS-I3**	> H.265+/H.265 dual-stream video compression > Supports HDCVI/AHD/TVI/CVBS/IP video inputs> Max 6 channels IP	**SAR 209**
431		**XVR5108HS-I3**	> H.265+/H.265 dual-stream video compression > Max 12 channels IP camera inputs, each channel up to 6MP; Max 6	**SAR 320**
432		**XVR5116HS-I3**	Supports HDCVI/AHD/TVI/CVBS/IP video inputs Max 24 channels IP camera inputs, each channel up to 4 MP Max 96 M	**SAR 660**
433		**DH-XVR5216AN-I3**	· Support HDCVI/AHD/TVI/CVBS/IP video inputs · Max 24 channels IP camera inputs, each channel up to 5MP; Max	**SAR 847**
434		**DH-XVR5232AN-I3**	> Embedded processor > Support HDCVI/AHD/TVI/CVBS/IP video inputs > Max 32 channels IP camera inputs; Max 128M	**SAR 1,397**

DAHUA HDVCI-5MP 16:9 CAMERA

435		**DH-HAC-HFW1500THN-I8-A**	5MP IR HDCVI Fixed-focal Bullet Camera	**SAR 129**
436		**DH-HAC-B1A51N-U**	Max. 20fps@5MP (16:9 video output with - S2)	**SAR 84**

437		DH-HAC-HDBW1500RN-Z-POC	• High-Quality Imaging with 5MP 16:9 Resolution	SAR 261
438		DH-HAC-T1A51N-U	5MP IR HDCVI Fixed-focal Eyeball Camera. In order to use the 5MP 16:9 HDCVI camera, the firmware of XVR must b	SAR 71
439		HAC-B1A51	> Max. 20fps@5MP (16:9 video output with - S2) > 3.6mm fixed lens (2.8mm,6mm optional) > IR 20m > IP67, DC12V	SAR 80
440		HAC-B2A51	> Max. 20fps@5MP (16:9 video output with - S2) > 3.6mm fixed lens (2.8mm,6mm optional) > IR 20m Metal housing	SAR 85
441		HAC-HFW1500C	> Max 25 fps@5MP (16:9 video output - S2) > 3.6 mm fixed lens (2.8 mm optional) > Max. IR length 30 m, Smart I	SAR 84
442		HAC-HFW1500CN-A	> Max 25 fps@5MP (16:9 video output - S2) > 3.6 mm fixed lens (2.8 mm optional) > Max. IR length 30 m, Smart I	SAR 97
443		HAC-HFW1500CM	> Max 25 fps@5MP (16:9 video output with - S2) > 3.6 mm fixed lens (2.8 mm optional) > Max. IR length 30m, Sma	SAR 110
444		DH-HAC-HDW1500TRQN-A	Max 25 fps@5MP (16:9 video output with -S2)	SAR 89
445		HAC-HDW1500TLMQ-A	> Max 25 fps@5MP (16:9 video output with -S2) > Quick-to-install eyeball saves installation time > 3.6 mm fixe	SAR 123
446		HAC-HDW1500TLQ-A-S2	> Max. 20fps@5MP (16:9 video output with -S2) > Built-in mic (-A) > 3.6mm fixed lens (2.8mm optional) >IR 30m	SAR 117
447		HAC-HFW1500CM-A	> Max 25 fps@5MP (16:9 video output with - S2) > 3.6 mm fixed lens (2.8 mm optional) > Max. IR length 30m, Sma	SAR 95
448		HAC-HFW1500T	> Max. 20fps@5MP > 3.6mm fixed lens (2.8mm, 6mm optional) > IR 30m Metal housing	SAR 108
449		DH-HAC-HFW1500TLN	Max 25 fps@5MP (16:9 video output)	SAR 98
450		DH-HAC-HFW1500THN-I4	Max. 20fps@5MP (16:9 video output with - S2)	SAR 110
451		DH-HAC-HFW1500THN-I8	Max. 20fps@5MP (16:9 video output with - S2)	SAR 129
452		HAC-HDW1500T-Z-A	> Max. 20fps@5MP (16:9 video output with -S2) > Built-in mic > 2.7-12mm motorized lens > IR 60m	SAR 225
453		DH-HAC-HDBW1500RN-Z	· Max 25 fps@5MP (16:9 video output) · CVI/CVBS/AHD/TVI switchable · 2.7-12 mm motorized lens · Max. IR len	SAR 171
454		DH-HAC-HFW1500RN-Z-IRE6-A	20fps@5MP, 25/30fps@4MP, 25/30fps@1080P (16:9 video output with - S2)	SAR 273
455		DH-HAC-HFW1500RN-Z-IRE6	20fps@5MP, 25/30fps@4MP, 25/30fps@1080P (16:9 video output with - S2)	SAR 218
456		HAC-HFW1500D	> Max. 20fps@5MP > 3.6mm fixed lens (6mm, 8mm optional) > IR 80m	SAR 146
457		DH-HAC-EW2501N	5MP HDCVI IR-Fisheye Camera	SAR 323

DAHUA HDCVI RECORDERÿ LIVE VIEW 8MPÿ RECORDING 8MPÿ -REAL 4K

458		DH-XVR5216AN-4KL-I3/T	• 16-ch Analog Video Input, Max. 4K@15fps/5MP@25fps Encoding Capability	SAR 1,287

459		DH-XVR5116H-4KL-I3/T	• 16-ch Analog Video Input, Max. 4K@15fps/5MP@25fps Encoding Capability	SAR 1,207
460		DH-XVR5232AN-4KL-I3	32 Channels Penta-brid 4K-N/5MP 1U 2HDDs WizSense Digital Video Recorder	SAR 2,544
461		DH-XVR5232AN-4KL-I3/T	• 32-ch Analog Video Input, Max. 4K@15fps/5MP@25fps Encoding Capability	SAR 2,939
462		DH-XVR5104HS-4KL-I3	> H.265+/H.265 dual-stream video compression > Max 8 channels IP camera inputs, each channel up to 8MP; Max 64	SAR 325
463		DH-XVR5104HS-4KL-I3/T	4CH Penta-brid 4K Value/5MP Compact 1U 1HDD WizSense Digital Video Recorder > *Dolynk cloud version: DMSS 2.3.	SAR 402
464		XVR5116H-4KL-I3	4K/4MP non-realtime, 1080P realtime 1 HDMI/1 VGA, 16ch Video in, 1 Audio in/1 Audio out,1 RJ45(1000M), 2 USB	SAR 1,036
465		XVR5216AN-4KL-I3	16 Channel Penta-brid 4K-N/1U 2HDDs WizSense Digital Video Recorder,> H.265+/H.265 dual-stream video compressi	SAR 1,067
466		DH-XVR7104H-4K-I3	4 Channels Penta-brid 4K 1U 1HDD WizSense Digital Video Recorder > H.265+/H.265 dual-stream video compression	SAR 549
467		DH-XVR7108H-4K-I3	8 Channels Penta-brid 4K 1U 1HDD WizSense Digital Video Recorder > H.265+/H.265 dual-stream video compression	SAR 917
468		DH-XVR7208A-4K-I3	2-channel QuickPick 2.0 for analog channels which improves the efficiency of target retrieval. 1-channel Priv	SAR 981
469		DH-XVR7216AN-4K-I3	16 Channels Penta-brid 4K 1U 2HDDs WizSense Digital Video Recorder > H.265+/H.265 dual-stream video compressi	SAR 2,441
470		DH-XVR7416L-4K-I3	16 Channels Penta-brid 4K 1.5U 4HDDs WizSense Digital Video Recorder > H.265+/H.265 dual-stream video compres	SAR 2,795
471		XVR5108HS-4KL-I3	>4K/4MP non-realtime, 1080P realtime >1 HDMI/1 VGA, 8ch Video in, 1 Audio in/1 Audio out,1 RJ45(1000M), 2 >US	SAR 521
472		XVR5108HS-4KL-I3/T	8CH Penta-brid 4K Value/5MP Compact 1U 1HDD WizSense Digital Video Recorder > *Dolynk cloud version: DMSS 2.3.	SAR 638

HDVCI-8MP 4K REAL TIME WDR

473		DH-HAC-HFW1801THN-I8-A	· Max. 15 fps@4K	SAR 183
474		DH-HAC-HDW1801TLQN-A	15fps@4K, 20fps@5MP, 25/30fps@4MP	SAR 139
475		DH-HAC-HFW1801CN	Max. 15 fps@4K.	SAR 132
476		DH-HAC-HFW1801TLN	15fps@4K, 20fps@5MP, 25/30fps@4MP	SAR 175
477		DH-HAC-HFW1801TN	15fps@4K, 20fps@5MP, 25/30fps@4MP	SAR 150
478		DH-HAC-HFW1801TN-A	15fps@4K, 20fps@5MP, 25/30fps@4MP	SAR 175
479		DH-HAC-HFW1801THN-I4	15fps@4K, 20fps@5MP, 25/30fps@4MP	SAR 161
480		DH-HAC-HFW1801THN-I8	15fps@4K, 20fps@5MP, 25/30fps@4MP	SAR 175

481		DH-HAC-HDW1801TN-Z-A	15fps@4K, 20fps@5MP, 25/30fps@4MP	SAR 336
482		DH-HAC-HFW1801RN-Z-IRE6	4K HDCVI IR Bullet Camera, > 120dB true WDR, 3D NR > Max. 4K resolution > CVI/CVBS/AHD/TVI switchable > Au	SAR 269
483		HAC-HFW1801D	> 15fps@4K, 20fps@5MP, 25/30fps@4MP > 3.6mm fixed lens(6mm optional) > IR 80m > metal	SAR 210
484		DH-HAC-HFW1801THN-I8-A	Max. 15 fps@4K	SAR 183
485		DH-HAC-HFW1801RN-Z-A	Max. 15 fps@4K.	SAR 298
486		DH-HAC-HDW1801TLQN	Max. 15 fps@4K.	SAR 126
487		DH-HAC-HDBW1801EAN-A	Max. 15 fps@4K.	SAR 208
488		DH-HAC-HDBW1801RAN-Z-A	Max. 15 fps@4K.	SAR 310
HDCVI-SMART DUAL LIGHT, TWO-WAY TALK				
489		DH-HAC-HFW1200TLMN-IL-T	Max. 30 fps@1080p	SAR 102
490		DH-HAC-HFW1200RLN-IL-T	Max. 30 fps@1080p	SAR 84
491		DH-HAC-HDW1200TQN-IL-T	Max. 30 fps@1080p	SAR 90
492		DH-HAC-HFW1500TLMN-IL-T	Max. 25 fps@5MP	SAR 149
493		DH-HAC-HFW1500RLN-IL-T	· Max. 25 fps@5MP	SAR 112
494		DH-HAC-HDW1500TQN-IL-T	Max. 25 fps@5MP	SAR 129
495		DH-HAC-HFW1801RLN-IL-T	Max. 15 fps@4K.	SAR 179
496		DH-HAC-HFW1801RMN-IL-T	· Max. 15 fps@4K.	SAR 195
497		DH-HAC-HDW1801TQN-IL-T	· Max. 15 fps@4K.	SAR 212
498		DH-HAC-HFW1801TLMN-IL-T	Max. 15 fps@4K.	SAR 242
HDCVI SMART DUAL ILLUMINATIONÿ IR+LEDÿ				
499		DH-HAC-T1A51N-U-IL-A	5MP Smart Dual Light HDCVI Fixed-focal Eyeball Camera	SAR 77
500		DH-HAC-HFW1500RLN-IL-A	5MP Smart Dual Light Bullet Camera	SAR 88
501		DH-HAC-HFW1500RMN-IL-A	5MP Smart Dual Light Bullet Camera	SAR 98

502		**DH-HAC-HFW1801RLN-IL-A**	4K Smart Dual Light Bullet Camera Max. 15 fps@4K.	**SAR 139**
503		**DH-HAC-HFW1801RMN-IL-A**	4K Smart Dual Light Bullet Camera · Max. 15 fps@4K.	**SAR 151**
504		**DH-HAC-HDW1801CLQN-IL-A**	4K Smart Dual Light Bullet Camera Max. 15 fps@4K.	**SAR 141**
505		**DH-HAC-B1A51N-U-IL-A**	• High-Quality Imaging with 5MP 16:9 Resolution	**SAR 90**
506		**DH-HAC-HFW1500RLN-IL-A**	* In order to use the 5MP 16:9 and the Smart Dual Light HDCVI camera, the firmware of XVR must be upgraded to	**SAR 92**
507		**DH-HAC-HFW1500CLN-IL-A**	5MP Smart Dual Light Bullet Camera > Max 25 fps@5MP (16:9 video output). > Smart Dual Light. > Built-in MIC. >	**SAR 84**
508		**DH-HAC-HDW1500CLQN-IL-A**	5MP Smart Dual Light Eyeball Camera > Max 25 fps@5MP (16:9 video output). > Smart Dual Light. > Built-in MIC.	**SAR 77**
509		**DH-HAC-HFW1500CMN-IL-A**	5MP Smart Dual Light Bullet Camera > Max 25 fps@5MP (16:9 video output) > CVI/CVBS/AHD/TVI switchable > Built-	**SAR 88**
510		**DH-HAC-HDW1500TN-IL-A**	5MP Smart Dual Light Eyeball Camera > Max 25 fps@5MP (16:9 video output). > Smart Dual Light. > Built-in MIC.	**SAR 126**
511		**DH-HAC-HFW1500TLMN-IL-A**	5MP Smart Dual Light Bullet Camera > Max 25 fps@5MP (16:9 video output). > Smart Dual Light. > Built-in MIC. >	**SAR 126**
512		**DH-HAC-HDW1500TLMN-IL-A**	5MP Smart Dual Light Eyeball Camera > Max 25 fps@5MP (16:9 video output). > Smart Dual Light. > Built-in MIC.	**SAR 126**
513		**DH-HAC-HFW1509TLMN-IL-A**	5MP Smart Dual Illuminators Bullet Camera > Max 25 fps@5MP (16:9 video output). > 120 dB true WDR, 3D NR. > Sm	**SAR 173**
514		**DH-HAC-HFW1801CMN-IL-A**	4K Smart Dual Light Bullet Camera > Max. 15 fps@4K. > 120 dB true WDR, 3D NR. > Built-in MIC. > Smart Dual Lig	**SAR 172**
515		**DH-HAC-HDW1801TN-IL-A**	4K Smart Dual Illuminators Eyeball Camera > Max. 15 fps@4K. > 120 dB true WDR, 3D NR. > Smart Dual Illuminator	**SAR 185**
516		**DH-HAC-HFW1801TLMN-IL-A**	4K Smart Dual Light Bullet Camera > Max. 15 fps@4K. > 120 dB true WDR, 3D NR. > Super Adapt. > Built-in MIC. >	**SAR 211**
517		**DH-HAC-HDW1801TLMN-IL-A**	4K Smart Dual Light Eyeball Camera > Max. 15 fps@4K. > 120 dB true WDR, 3D NR. > Smart Dual Light. > Built-in	**SAR 170**

HDVCI- 6MP & 8MP 4K REAL TIME

518		**HAC-HFW1800T**	> 15fps@4K, 20fps@5MP, 25/30fps@4MP > 3.6mm fixed lens(2.8mm, 6mm optional) > IR 30m > metal	**SAR 137**
519		**HAC-HDW1800R**	30fps@4K, 20fps@5MP, 25/30fps@4MP 3.6mm fixed lens IR 30m	**SAR 136**
520		**HAC-HFW1800TL**	> Max. 4K resolution, real-time video transmission > Fixed lens (2.8mm; 3.6mm;6mm optional) > Max. IR length 8	**SAR 151**
521		**HAC-HDW1800TL-A**	> Max. 4K resolution, real-time video transmission > Built-in mic (-A) > Fixed lens > Max. IR length 30m, Smar	**SAR 160**
522		**HAC-HFW1800TH-I4**	> Max. 4K resolution, real-time video transmission > Fixed lens > Max. IR length 40m, Smart IR > Big Case	**SAR 167**
523		**HAC-HFW1800TH-I8**	> Max. 4K resolution, real-time video transmission > Fixed lens > Max. IR length 80m, Smart IR > Big Case	**SAR 177**

524		HAC-HFW2601EN-A	6MP WDR HDCVI IR Bullet Camera,> 120dB True WDR, 3DNR > Max. 6MP resolution > HD/SD switchable > Audio in inte	SAR 240
525		HAC-HDW2601TN-ZA	6MP WDR HDCVI IR Eyeball Camera,> 120dB True WDR, 3DNR > Max. 6MP resolution > HD/SD switchable,> Audio in int	SAR 351
HDCVI - WIZCOLOR				
526		DH-HAC-HFW1549XP-A-PRO	24/7 color imaging, Max. 25 fps@5MP (16:9 video output)	SAR 237
527		DH-HAC-HFW1549XP-IL-A-PRO	Max. 25 fps@5MP (16:9 video output)	SAR 241
528		DH-HAC-HDW1549XP-IL-A-PRO	Max. 25 fps@5MP (16:9 video output)	SAR 223
529		DH-HAC-HDW1549XP-A-PRO	· 24/7 color imaging, Max. 25 fps@5MP (16:9 video output)	SAR 219
HDCVI-TIOC CAMERAÿ FULL COLOR0 AI0 ACTIVE DETERRENCEÿ				
530		HAC-ME1809HN-A-PV	4K HDCVI Full-Color Active Deterrence Fixed Eyeball Camera, > 24/7 color imaging > Active deterrence with red	SAR 334
531		HAC-ME1509THN-A-PV	5MP HDCVI Full-Color Active Deterrence Fixed Bullet Camera, > 24/7 color imaging > Active deterrence with red	SAR 245
532		HAC-ME1509HN-A-PV	5MP HDCVI Full-Color Active Deterrence Fixed Eyeball Camera,> 24/7 color imaging > Active deterrence with red	SAR 274
533		DH-HAC-ME1809THN-A-PV	· 24/7 color imaging · Active deterrence with red blue light,siren and alarm out interface · Built-in mic ·	SAR 296
HDVCI-2MP PIR				
534		HAC-ME1200E-LED	>MotionEye 2mp >ICR, OSD, 3.6mm fixed lens(2.8mm optional) >IR 20m, bulit-in PIR Dual-tect, Built-in white l	SAR 88
535		HAC-ME1200B-LED	>MotionEye 2mp >ICR, OSD, 3.6mm fixed lens(2.8mm optional) >IR 20m >bulit-in PIR Dual-tect, Built-in white l	SAR 88
536		HAC-ME1200D	>2mp >ICR, OSD, 3.6mm fixed lens(2.8mm optional) >IR 20m >Built-in PIR Dual-tect, Built-in white light and sp	SAR 123
HDVCI-5MP PIR				
537		HAC-ME1500E-LED	>20fps@5MPÿ 25/30fps@4MP, 25/30fps@1080P >3.6mm fixe 20m >bulit-in PIR Dual-tect, Bu	SAR 110 onal) >
538		HAC-ME1500D	>20fps@5MP 25/30fps@4MP, 25/30fps@1080P >3.6mm fixed lens (2.8mm optional) >IR 20m >Built-in PIR Dual-tect, Bu	SAR 134
539		HAC-ME1500B-LED	>20fps@5MPÿ 25/30fps@4MP, 25/30fps@1080P >3.6mm fixe 20m > bulit-in PIR Dual-tect,Bu	SAR 110 onal) >
HDVCI - FULL COLOR				
540		HFW1209C-LED	2MP Full-color HDCVI Bullet Camera,	SAR 97
541		HDW1209TLQ-LED	2MP Full-color HDCVI Quick-to-install Eyeball Camera, > 24/7 color imaging > 20 m illumination distance> Max.	SAR 97
542		HAC-HDW1239TLQ-LED-S2	>Full-color starlight >20m LED distance >3.6mm fixed lens(2.8mm Optional)	SAR 119

543		**HAC-HFW1239T-LED**	> Full-color starlight > 20m LED distance > 3.6mm fixed lens	**SAR 124**
544		**HAC-HDW1239TLQ-A-LED-S2**	>Full-color starlight >20m LED distance >Built-in mic >3.6mm fixed lens(2.8mm Optional)	**SAR 130**
545		**HAC-HFW1239TLM-LED-S2**	> Full-color starlight > 40m LED distance > Max. 30fps@1080P > CVI/CVBS/AHD/TVI Switchable > 3.6mm fixed lens	**SAR 136**
546		**HAC-HDW1509TLQ-LED-S2**	•5MP •Full Color• LED •IP67 •Metal+Plastic	**SAR 122**
547		**HAC-HDW1509TLQ-A-LED-S2**	•5MP •Full Color• LED •Bulit-in Mic •IP67 •Metal+Plastic	**SAR 129**
548		**HAC-HFW1509T-LED-S2**	•5MP •Full Color• LED •IP67 •Metal	**SAR 123**
549		**HAC-HFW1509T-A-LED-S2**	•5MP •Full Color•Bulit-in Mic• LED •IP67 •Metal	**SAR 128**
HDVCI-2MP PTZ CAMERA				
550		**SD59225-HC-LA**	> 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 25x optical zoom > Starlight technology > 120 dB true WDR, 3D DNR	**SAR 1,639**
551		**DH-SD49225DBN-HC**	1/2.8" 2Megapixel STARVIS™ CMOS	**SAR 945**
552		**SD59232-HC-LA**	> 1/2.8" 2Megapixel STARVIS™ CMOS > Powerful 32X optical zoom > Starlight technology IR distance 150m > 120dB	**SAR 1,963**
ENTRANCE AND EXIT				
553		**DHI-ITC413-PW4D-IZ1**	Dahua Access ANPR Camera-IR light	**SAR 2,046**
554		**DHI-ITC413-PW4D-IZ3**	Dahua Access ANPR Camera-IR light	**SAR 2,222**
555		**PFA126**	Water-proof Junction Box	**SAR 222**
556		**DH-PFA150**	Pole mount for 3-10kg device	**SAR 70**
557		**ITC-BRACKET-1200**	Entrance and exit camera mounting bracket-1.2m	**SAR 272**
558		**ITSZJ-1101-15**	Entrance and exit camera mounting bracket-1.5m	**SAR 314**
559		**DHI-ITSJC-2303-DC12**	Dahua Anti Smashing Radar	**SAR 565**
560		**DHI-ITSXS-1201-44**	Entrance and Exit LED Display	**SAR 2,010**
561		**IPM-AE7-0020A**	Converter	**SAR 114**
WIRELESS ALARM SYSTEMS				
562		**DHI-ART-ARC3000H-03-GW2(868)**	Alarm KIT-2G	**SAR 710**

563		DHI-ART-ARC3800H-03-FW2 (868)	1. Supports connecting up to 8 IPCs in the same LAN	SAR 1,126
564		DHI-ARM310-W2(868)	Wireless input expander	SAR 104
565		DHI-ARD912-W2(868)	Wireless Water Leak Detector	SAR 121
566		DHI-ARD912-W2(868D)	Wireless Water Leak Detector	SAR 131
567		DHI-ARM7011-W2(868)	Dahua Wireless Relay	SAR 74
568		DHI-ARM7012-W2(868)	Dahua Wireless WallSwitch	SAR 91
569		DHI-ARC3000H-03-FW2(868)	Alarm KIT	SAR 931
570		DHI-ARC3000H-FW2(868)	Alarm hub > Supports 150 wireless peripherals (6 sirens, 64 wireless keyfobs). > Peripherals status display (s	SAR 571
571		DHI-ARD1731-W2(868)	Wireless PIR detector camera > Supports IR detection and video review. > Maximum resolution 1600 × 1200. > One	SAR 288
572		DHI-ARD1233-W2(868)	Wireless PIR detector > Pet immunity function. > Auto temperature compensation. > 3-level sensitivity adjustme	SAR 121
573		DHI-ARD323-W2(868)	Wireless door detector > Signal strength detection. > Low battery alarm. > Temperature measurement. > Frequenc	SAR 91
574		DHI-ARD323-W2(868S)	Wireless door detector > Signal strength detection. > Low battery alarm. > Temperature measurement. > Frequenc	SAR 83
575		DHI-ARA43-W2(868)	Alarm Repeater > Connects up to 32 peripherals. > Two-way RF communication. > LED indicator displays device st	SAR 253
576		DHI-ARD822-W2(868)	Wireless Panic Button > Two-way RF communication. > Provides multiple LED colors to indicate different statuse	SAR 60
577		DHI-ARK30T-W2(868)	Wireless Keypad > Supports 3 shortcut alarms: Medical, fire, emergency. > Arm/Disarm with password or IC card.	SAR 186
578		DHI-ARA24-W2(868)	Wireless keyfob > SOS emergency alarm. > Frequency hopping function and two-way communication technology > Clo	SAR 63
579		DHI-ARA13-W2(868)	Wireless outdoor siren > IP65 rated. > Outdoor product (–25 °C to +60 °C). > 12 VDC and battery power supply.	SAR 207
580		DHI-ARA12-W2(868)	Wireless siren > Signal strength detection. > Low battery alarm. > Temperature measurement. > Frequency hoppin	SAR 138
581		DHI-HY-SA21A-W2(868)	Wireless Smoke Alarm > Split-spectrum sensor technology > Test and silence features in one single button > Lou	SAR 167
582		DHI-HY-SAV849HAN-E	5MP IR AI-fire Smoke Sensing Network Camera	SAR 514
CLOUD MANAGED SWITCH				
583		DH-CS4006-4GT-60	6-Port Cloud Managed Desktop Gigabit Switch with 4-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3u,	SAR 140
584		DH-CS4228-24GT-375	28-Port Cloud Managed Desktop Gigabit Switch with 24-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3	SAR 1,010

585		**DH-CS4220-16GT-135**	20-Port Cloud Managed Desktop Gigabit Switch with 16-Port PoE	**SAR 684**
586		**DH-CS4226-24ET-375**	26-Port Cloud Managed Desktop Switch with 24-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3u,IEEE80	**SAR 798**
587		**DH-CS4226-24ET-240**	26-Port Cloud Managed Desktop Switch with 24-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3u,IEEE80	**SAR 730**
588		**DH-CS4218-16ET-240**	18-Port Cloud Managed Desktop Switch with 16-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3u,IEEE80	**SAR 598**
589		**DH-CS4218-16ET-190**	18-Port Cloud Managed Desktop Switch with 16-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3u,IEEE80	**SAR 588**
590		**DH-CS4218-16ET-135**	18-Port Cloud Managed Desktop Switch with 16-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3u,IEEE80	**SAR 546**
591		**DH-CS4228-24GT-240**	28-Port Cloud Managed Desktop Gigabit Switch with 24-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3	**SAR 924**
592		**DH-CS4220-16GT-240**	20-Port Cloud Managed Desktop Gigabit Switch with 16-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3	**SAR 735**
593		**DH-CS4010-8GT-110**	10-Port Cloud Managed Desktop Gigabit Switch with 8-Port PoE	**SAR 289**
594		**DH-CS4010-8GT-60**	10-Port Cloud Managed Desktop Gigabit Switch with 8-Port PoE	**SAR 248**
595		**DH-CS4006-4ET-60**	6-Port Cloud Managed Desktop Switch with 4-Port PoE > Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.	**SAR 125**

DAHUA SWITCHES

596		**DH-S5428-24GT4XF-360**	• 24 × RJ-45 10/100/1000 Mbps (PoE) Ports, 4 × SFP+ 1/10 Gbps (Uplink) Ports	**SAR 1,333**
597		**DH-S5452-48GT4XF-400**	• 48 × RJ-45 10/100/1000 Mbps (PoE) Ports, 4 × SFP+ 1/10 Gbps (Uplink) Ports	**SAR 2,056**
598		**DH-S5452-48GT4XF-750**	• 48 × RJ-45 10/100/1000 Mbps (PoE) Ports, 4 × SFP+ 1/10 Gbps (Uplink) Ports	**SAR 2,222**
599		**DH-S5428-12GF12GT4XF**	• 12 × RJ-45 10/100/1000 Mbps Ports, 12 × SFP 100/1000 Mbps Ports, 4 × SFP+ 1/10 Gbps (Uplink) Ports	**SAR 1,868**
600		**DH-S5436-24GF8GT4XF**	• 24 × SFP 100/1000 Mbps Ports, 8 × RJ-45 10/100/1000 Mbps Ports, 4 × SFP+ 1/10 Gbps (Uplink) Ports	**SAR 2,490**
601		**DH-CHS4106-4ET-60**	• 4 × RJ-45 10/100 Mbps PoE Ports, 1 × RJ-45 10/100/1000 Mbps Port, 1 × Gigabit SFP Port	**SAR 283**
602		**DH-CHS4206-4ET-90**	• 4 × RJ-45 10/100 Mbps PoE Ports, 2 × Gigabit SFP Ports	**SAR 336**
603		**DH-CHS4206-4ET-60**	• 4 × RJ-45 10/100 Mbps PoE Ports, 2 × Gigabit SFP Ports	**SAR 283**
604		**DH-CHS4110-8ET-90-F**	• 8 × RJ-45 10/100 Mbps PoE Ports, 1 × RJ-45 10/100/1000 Mbps Port, 1 × Gigabit SFP Port	**SAR 404**
605		**DH-CHS4212-8GT-110**	• 8 × RJ-45 10/100/1000 Mbps PoE Ports, 2 × RJ-45 10/100/1000 Mbps Ports, 2 × Gigabit SFP Ports	**SAR 572**
606		**DH-CHS4210-8GT-110**	• 8 × RJ-45 10/100/1000 Mbps PoE Ports, 2 × Gigabit SFP Ports	**SAR 538**

607		**DH-CHS4206-4GT-60**	• 4 × RJ-45 10/100/1000 Mbps PoE Ports, 2 × Gigabit SFP Ports	**SAR 336**
608		**DH-CHS4206-4GT-90**	• 4 × RJ-45 10/100/1000 Mbps PoE Ports, 2 × Gigabit SFP Ports	**SAR 404**
609		**DH-IS4204-2GT-120**	· All-gigabit port design	**SAR 716**
610		**DH-PFWB5-30AC**	Wireless Range: "e3km	**SAR 404**
611		**DH-CS4006-4ET2GT-36**	Meets the requirements of IEEE802.3,IEEE802.3u,IEEE802.3x,IEEE802.3ab standards.	**SAR 102**
612		**DH-CS4006-4ET2ET-60**	1.Supports cloud managed via DoLynk care	**SAR 109**
613		**DH-CS4006-4ET2GT-60**	6-Port Cloud Managed Desktop Switch with 4-Port PoE	**SAR 125**
614		**DH-CS4006-4GT-36**	4 × RJ45 Gigabit PoE ports, 2 × RJ45 Gigabit ports.	**SAR 126**
615		**DH-CS4010-8ET-60**	10-Port Cloud Managed Desktop Switch with 8-Port PoE	**SAR 192**
616		**DH-CS4010-8ET-110**	10-Port Cloud Managed Desktop Switch with 8-Port PoE	**SAR 216**
617		**DH-CS4220-16GT-190**	20-Port Cloud Managed Desktop Gigabit Switch with 16-Port PoE	**SAR 709**
618		**DH-PFS4210-8GT-DP**	10-port Gigabit Industrial Switch with 8-port PoE (Managed) > All-gigabit port design > Supports IEEE802.3af	**SAR 990**
619		**DH-PFS4226-24GT-370**	26-Port Managed Gigabit Switch with 24-Port PoE > Intelligent PoE. > Red port supports 90W IEEE802.3bt. > W	**SAR 880**
620		**DH-LR1002-1EC**	Single-Port Long Reach Ethernet over Coax Extender > Supports IEEE802.3, IEEE802.3u standards > Supports IEE	**SAR 94**
621		**DH-LR1002-1ET**	Single-Port Long Reach Ethernet over Coax Extender > Supports IEEE802.3, IEEE802.3u standards > Supports IEE	**SAR 94**
622		**DH-PFWB5-90AC**	Wireless Standard: IEEE802.11 a/n/ac Frequency: 5GHz Wireless Range: 5km recommended (max"e7km) Wireless Spe	**SAR 672**
623		**DH-PFWB5-10AC**	Wireless Standard: IEEE802.11 a/n/ac Frequency: 5GHz Wireless Range: 5km recommended (max"e7km) Wireless Spe	**SAR 605**
624		**DH-PFM880E**	Wireless Standard: IEEE802.11 a/n/ac Frequency: 5GHz Wireless Range: "d3km W Speed: 867Mbps Antenna	**SAR 2,017**
625		**DH-PFM881E**	Wireless Standard: IEEE802.11 a/n/ac Frequency: 5GHz W 3km Wi Speed:867Mbps Antenna An	**SAR 1,076**
626		**DH-PFM885-I**	Wireless Standard: IEEE802.11 b/g/n Frequency: 2.4GHz Wireless Range: "d500m Speed: 300Mbps Antenn	**SAR 592**
627		**DH-IS4207-4GT-120**	7-Port Gigabit Industrial Swicth with 4-Port Gigabit PoE (Managed) > All-gigabit port design. > Supports IE	**SAR 974**
628		**DH-LR2218-16ET-240**	18-Port Managed Switch with 8-Port ePoE & 8-Port PoE > Layer-two web managed ePoE switch. > Three self-adapt	**SAR 1,076**
629		**DH-IS4210-8GT-120**	10-Port Managed Industrial Gigabit Switch with 8-Port PoE (Managed) > All-gigabit port design. > Supports IE	**SAR 1,405**

630		**DH-LR2110-8ET-120**	8-Port ePoE Switch > Supports long distance PoE transmission up to 800m with ePoE technology > Layer-two ePo	**SAR 639**
631		**DH-PFS4207-4GT-DP**	7-Port Gigabit Industrial Swicth with 4-Port Gigabit PoE (Managed) > All-gigabit port design. > Supports IE	**SAR 1,210**
632		**DH-PFS3117-16ET-135**	16-Port FE PoE+ 1-Port Gigabit Combo PoE Switch > Compliant IEEE 802.3, IEEE 802.3u, IEEE802.3ab, IEEE802.3x	**SAR 565**
633		**DH-PFS4204-2GT-DP**	4-Port Gigabit Industrial Swicth with 2-Port Gigabit PoE (Managed) > All-gigabit port design > Supports IEEE	**SAR 773**
634		**DH-PFS4226-24ET-240**	24-port 100 Mbps + 2-port Gigabit Managed PoE Switch > * The parameters and datasheets below can only be appl	**SAR 1,015**
635		**DH-PFS4226-24GT-360**	> 24x10/100/1000 Base-T0 2x1000 Base-Xÿ > IEEE 802.3af "d60Wÿ Port 3-24 "d30W > Tota	**SAR 1,358** > Port 1
636		**DH-PFS4218-16GT-230**	18-Port Managed Gigabit Switch with 16-Port PoE > Intelligent PoE. > Red port supports 90W IEEE802.3bt. > W	**SAR 1,096**
637		**DH-PFS4226-24ET-360**	24-port 100 Mbps + 2-port Gigabit Managed PoE Switch > Intelligent PoE · Red port supports 90W IEEE802.3bt >	**SAR 1,143**
638		**DH-PFS4218-16ET-190**	16-port 100 Mbps + 2-port Gigabit Managed PoE Switch > * The parameters and datasheets below can only be appl	**SAR 847**
639		**DH-PFS4218-16GT-240**	> 16x10/100/1000 Base-T 2x1000 Base-Xÿ > IEEE 802.3af/ "d60Wÿ Port 3-16 "d30W > Tota	**SAR 1,096** > Port 1
640		**DH-PFS3006-4GT-60**	6-Port Unmanaged Desktop Switch with 4-Port PoE > Intelligent PoE > Hi-PoE 60W (orange port) > Long distanc	**SAR 198**
641		**DH-PFS4212-8GT-96**	> 8 xRJ45 10/100/1000M (Hi-PoE/PoE+/PoE); > 2 xRJ45 10/100/1000M; > 2 xSFP 1000M > Power supply: DC48~57V	**SAR 645**
642		**DH-PFS3009-8ET-65**	>1x10/100 Base-T >x10/100 Base-T (PoE power supply) >Port1"d36W Port2-8"d10W Total"d36W	**SAR 161**
643		**DH-PFS3010-8GT-96**	10-Port Gigabit Unmanaged Desktop Switch with 8-Port PoE > Intelligent PoE > 8-pin assignment PoE power supp	**SAR 403**
644		**DH-PFS3008-8GT-60**	8-Port Unmanaged Desktop Switch with 4 Port PoE > Intelligent PoE > 8-pin assignment PoE power supply > Lon	**SAR 222**
645		**DH-PFS3006-4ET-60**	6-Port 10/100Mbps Unmanaged Desktop Switch with 4 PoE Ports > Layer two commercial switch > Supports IEEE80	**SAR 150**
646		**DH-PFS3010-8ET-65**	10-Port Fast Ethernet Switch with 8-Port PoE > Support eight 10/100M PoE power supply ports, and two 10/100M	**SAR 184**
647		**DH-PFS3006-4ET-36**	> 1x10/100 Base-T > 4x10/100 Base-T (PoE power supply) Total"d36W	**SAR 109** ort2-4"d
648		**DH-PFS3008-8GT**	8-Port Desktop Metal Gigabit Ethernet Switch > Plug and play: No configuration required > Robust design: 24/	**SAR 112**
649		**DH-PFS3005-4ET-36**	4-Port PoE Switch (Unmanaged) > Two-layer PoE Ethernet switch > MAC auto study and aging, MAC address list c	**SAR 99**
650		**DH-PFS3005-5GT**	5-Port Desktop Metal Gigabit Ethernet Switch > Plug and play: No configuration required. > Robust design: 24	**SAR 56**
651		**DH-PFS3008-8ET**	8-Port Desktop Metal Fast Ethernet Switch > Plug and play: No configuration required > Robust design: 24/7 s	**SAR 45**
652		**DH-PFS3005-5ET**	5-Port Desktop Metal Fast Ethernet Switch > Plug and play: No configuration required. > Robust design: 24/7	**SAR 37**

653		DH-PFS3008-8GT-L	8-Port Desktop Plastic Gigabit Ethernet Switch > Compact design: Miniature size and light weight make it easy	SAR 73
654		DH-PFS3005-5GT-L	5-Port Desktop Plastic Gigabit Ethernet Switch > Compact design: Miniature size and light weight make it easy	SAR 42
655		DH-PFS3008-8ET-L	8-Port Desktop Plastic Fast Ethernet Switch > Compact design: Miniature size and light weight make it easy to	SAR 29
656		DH-PFS3005-5ET-L	5-Port Desktop Plastic Fast Ethernet Switch > Compact design: Miniature size and light weight make it easy to	SAR 18
WIFI CAMERA				
657		KIT/BP4A-4G/M0508	4-MP 1/3" CMOS image sensor, low luminance, and high definition image.	SAR 616
658		DH-BF4CP-XL/M0508	4-MP 1/3" CMOS image sensor, low luminance, and high definition image.	SAR 311
659		DH-IPC-HFW2441DGP-4G-SP-EAU-B-0360B-MAX	1. All-in-one Design. Self-powered and Networked, No Extra Wiring Needed	SAR 912
660		DH-BF5H	5-MP 1/3" CMOS image sensor, low luminance, and high definition image.	SAR 324
661		DH-BF8H	8-MP 1/3" CMOS image sensor, low luminance, and high definition image.	SAR 381
662		DH-XA3	3MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera AI Human Detection,Pet Detection, Auto Tracking, SD Ca	SAR 97
DAHUA UTP CABLES				
663		DH-PFM922I-6UN-C	305m UTP CAT6 Cable	SAR 276
664		DH-PFM920I-6UN-CN	UTP CAT6 Cable > 305 m (1000 ft)/carton UTP CAT6, power over Ethernet, compatible with one cable > High-p	SAR 620
WIRELESS SERIES				
665		DH-XB3	3MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera One call button,AI Human Detection,Pet Detection, Auto	SAR 109
666		DH-XB5	5MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera	SAR 131
667		DH-XA5	5MP Indoor Fixed-focal Wi-Fi Pan & Tilt Network Camera	SAR 117
668		DH-Y3D-3F	3+3MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera	SAR 237
669		DH-Y5D-5F	5+5MP Outdoor Wi-Fi Dual-Lens Pan & Tilt Camera	SAR 277
670		DH-X3D-3F	3+3MP Indoor Wi-Fi Dual-Lens Pan & Tilt Camera	SAR 163
671		DH-X5D-5F	5+5MP Indoor Wi-Fi Dual-Lens Pan & Tilt Camera	SAR 196
672		DH-YB3-PV	3MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera Smart Dual Light,AI Human Detection,Pet Detection, Au	SAR 167
673		DH-YB5-PV	5MP Outdoor Fixed-focal Wi-Fi Pan & Tilt Network Camera Smart Dual Light,AI Human	SAR 187

674		DH-H2C	2MP Indoor Fixed-focal Wi-Fi Network PT Camera > 1/2.8" 2Megapixel CMOS. > Max. 25/30fps@1080p. > H.265 enc	SAR 87
675		DH-H4C	4MP Indoor Fixed-focal Wi-Fi Network PT Camera > 1/2.8" 4Megapixel CMOS. > Max. 25/30fps@4M. > H.265 encodi	SAR 109
676		DH-BP3EW-4G	Dahua APOLLO / WITHS 4G -3MP Solar Security Camera System	SAR 381
677		DH-P3F-PV	3MP Wizcolor Outdoor Wi-Fi Pan & Tilt Network Camera	SAR 286
678		DH-P5F-PV	5MP Wizcolor Outdoor Wi-Fi Pan & Tilt Network Camera	SAR 317
679		DH-P8F-PV	8MP Wizcolor Outdoor Wi-Fi Pan & Tilt Network Camera	SAR 349
680		DH-SDT2A200-2F-NB-A-PV	> Fixed lens: 2 MP; PT Lens: 2 MP > Classified human/vehicle detection > smart dual light+ > Two-way talk	SAR 356
681		DH-SD2A200HB-GN-AW-PV-S2	2MP Full-color Network PT Camera > 1/2.8" 2Megapixel CMOS. > Max. 25/30 fps@1080p. > Human detection. > Tripwi	SAR 199
682		DH-SD2A500HB-GN-AW-PV-S2	5MP Full-color Network PT Camera > 1/2.8" 5Megapixel STARVIS™ CMOS. > Max. 20 fps@5MP. > Human detection. > Tr	SAR 239
683		DH-P3D-3F-PV-P	3+3MP Outdoor WizColor Wi-Fi Dual-Lens Pan & Tilt Camera	SAR 457

DAHUA DISPLAY & CONTROL

684		DHI-LTV32-LN100-C	32 inch HD ATV	SAR 413
685		DHI-LM22-F200	22 inch, 60Hzÿ VGA+HDMI, 1080p	SAR 380
686		DHI-LM22-H200	22 inch, 100Hzÿ VGA+HDMI+AUDIO IN+ speakrer*2, 1080p	SAR 368
687		DHI-LM24-H200	24 inch, 100Hzÿ VGA+HDMI+AUDIO IN+ speakrer*2, 1080p	SAR 480
688		DHI-LM24-F200	24 inch, 60Hzÿ VGA+HDMI+AUDIO OUT, 1080p	SAR 538
689		DHI-LM32-F200	32 inch, 60Hzÿ VGA+HDMI+USB+speaker*2, 1080p	SAR 848
690		DHI-LM43-F200	43 inch, 60Hzÿ VGA+HDMI+USB+speaker*2, 1080p	SAR 1,206
691		DHI-LM43-F400	43 inch, 60Hzÿ input: VGA+HDMI*2+USB*2_+Audio+Lan, out	SAR 1,968 +speake
692		DHI-LM55-F400	55 inch, 60Hzÿ VGA+HDMI*3+USB_+Audio in	SAR 2,413
693		NVD0105DH-4K	Decoder Video output: HDMI/VGA Decoding:1CH@8K/3CH@12MP(25fps)/4CH@4K(30fps)/16CH@1080P(30fps)/8CH@1080P(60fps	SAR 2,017
694		NKB1000	Keyboard >Direct mode, Network mode, USB mode >1 RJ-45 port (100/1000M), RS232, RS485, RS422(reserved), USB	SAR 874

DASH CAMERA & USB CAMERA

695		**HTI-UC320**	USB Camera > Max.25/30fps@1080P > Built-in microphone, 3 meters pickup distance > USB connection & easy operat	**SAR 121**
696		**DHI-DAE-HC1311GW-S6**	2MP dash camera Two side view, Front:2MP,Rear:720P,Mini USB,3inch Screen,Voice control, -20°C to 70°C(-4°F to	**SAR 323**
697		**DHI-DAE-HC3511GW-S8**	8MP dash camera 4K,Mini USB,3inch Screen,Voice control,H.265, -20°C to 70°C(-4°F to 158°F) 3840P × 2160P ult	**SAR 403**
698		**DHI-DAE-HC3300WV-S3**	4MP dash camera Mini USB,3inch Screen,Voice control,H.265, -20°C to 70°C(-4°F to 158°F)	**SAR 289**
699		**DHI-DAE-HC2301WV-M6**	3MP dash camera Mini USB,Voice control,H.265, -20°C to 70°C(-4°F to 158°F)	**SAR 182**
700		**DHI-DAE-HC1300WVR-M1**	2MP dash camera Mini USB,Voice control,H.265, -20°C to 70°C(-4°F to 158°F)	**SAR 148**