

Package Reference

Package Reference · docs/latest · generated 2026-08-02

The platform ships **seven packages**, one per architecture bucket. Every package is an ordinary npm package — external consumers install them under their real names with no aliases and no build glue.

PACKAGE	BUCKET PATH	ROLE
@wellsfargo-starui/types	packages/types	foundation contracts
@wellsfargo-starui/design-system	packages/design-system	tokens, themes, icons
@wellsfargo-starui/core	packages/core	vanilla-TS runtime
@wellsfargo-starui/data	packages/data	SharedWorker data services
@wellsfargo-starui/openfin	packages/openfin	OpenFin workspace shell
@wellsfargo-starui/react	packages/react-core	React primitives + SDK
@wellsfargo-starui/grid	packages/react-grid	MarketsGrid product surface

Layering and allowed imports are covered in [Architecture](#) →.

@wellsfargo-starui/types

Foundation types — host-port identity/theme/surface contracts plus the shared widget-framework types. Depends on nothing.

SUBPATH	CONTENTS
.	host-port and widget contracts
./shared	shared framework types
./shared/configuration	configuration shapes
./shared/dataProvider	data-provider contracts
./shared/fieldSelector	field-selector contracts

@wellsfargo-starui/design-system

The design system: primitives, semantic tokens, themes, framework adapters and framework-agnostic SVG icons. Every visual property in the platform resolves through its `--bn-*` / `--fi-*` CSS variables; themes switch by flipping `data-theme="dark" | "light"` on `<html>`.

SUBPATH	CONTENTS
<code>.</code>	<code>applyTheme</code> , <code>getTheme</code> , JS token access
<code>./css</code> , <code>./styles.css</code> , <code>./reset.css</code>	built theme CSS
<code>./tokens</code> , <code>./tokens/primitives</code> , <code>./tokens/semantic</code> , <code>./tokens/components</code> , <code>./tokens/controls</code>	token tree, by tier
<code>./tailwind</code>	Tailwind preset wired to the tokens
<code>./shadcn</code>	shadcn/ui theme layer
<code>./primeng</code>	PrimeNG (Angular) theme
<code>./adapters/ag-grid</code>	AG Grid theme adapter
<code>./cell-renderers</code> , <code>./cell-renderers-registry</code>	token-driven cell renderers
<code>./icons</code> , <code>./icons/react</code> , <code>./icons/angular</code> , <code>./icons/all-icons</code> , <code>./icons/svg/*</code>	icon set, per framework and raw SVG

Peers: `react` (icon adapter), `tailwindcss`, `ag-grid-community`.

@wellsfargo-starui/core

Framework-agnostic core runtime: the vanilla-TS grid engine, host ports with a browser adapter and a Dexie (IndexedDB) config store, and the widget framework.

SUBPATH	CONTENTS
<code>.</code>	grid engine + shared runtime
<code>./host</code>	host port contracts
<code>./host/browser</code>	browser host adapter
<code>./host/config</code>	Dexie-backed config store
<code>./widget</code>	widget framework
<code>./widget/browser</code>	browser widget adapter

Deps: `dexie`, `ssf`, `zustand`. Peer: `ag-grid-community`.

@wellsfargo-starui/data

SharedWorker-backed data services: one upstream STOMP connection fanned out to every grid in every window, with snapshot + thin-delta frames. See [Architecture § data services](#) →.

SUBPATH	CONTENTS
.	data-services API
./runtime	runtime shared pieces
./runtime/sharedWorker	SharedWorker bootstrap
./runtime/client	per-window client
./runtime/worker/defaultEntry	worker entry for custom bundling
./assets/data-services-worker.mjs	prebuilt worker bundle (build-generated)

Deps: `@stomp/stompjs`.

@wellsfargo-starui/openfin

OpenFin RuntimePort plugin plus the workspace shell — dock, home, notifications, child windows, and config import/export. **The only package allowed to import** `@openfin/core`.

SUBPATH	CONTENTS
.	public API
./host	workspace shell host
./config	config import/export
./plugin	RuntimePort plugin
./dock-editor	dock layout editor
./test-bridge	e2e test bridge

Peers: `@openfin/core`, `@openfin/workspace`, `@openfin/workspace-platform`.

@wellsfargo-starui/react

The React layer: shadcn/Radix UI primitives, the widget SDK, the React host wrapper, workspace setup, and React data bindings.

SUBPATH	CONTENTS
.	UI primitives (Button, Dialog, Select, ...)
./chart	chart components (Recharts-based)
./tailwind-config	app-side Tailwind wiring
./widget-sdk	React widget SDK
./host, ./host/test-bridge	React host wrapper
./workspace-setup	workspace bootstrap for React apps
./data, ./data/runtime	React bindings for the data services

Peers: `react`, `react-dom`, `tailwindcss`, `@tanstack/react-query`.

@wellsfargo-starui/grid

The product surface: **MarketsGrid** (an opinionated, profile-persistent AG Grid host), the grid customizer, the config browser, and the widget catalog.

SUBPATH	CONTENTS
.	<code>MarketsGrid</code> , toolbars, storage helpers, types
./customizer	grid customizer (column settings, formatting, alerts, ...)
./styles.css, ./styles/core.css, ./styles/chrome.css	grid chrome CSS layers
./runtime/openfin	OpenFin glue for grid widgets
./config-browser, ./config-browser/icons	configuration browser
./widgets, ./widgets/*	packaged widgets (markets-grid-container, provider-editor, data-provider-selector, hosted)

Peers: `react`, `react-dom`, `ag-grid-community`, `ag-grid-enterprise`, `ag-grid-react`, `@tanstack/react-query`.

The excluded package

`packages/data/host-data-angular` is the one remaining Angular package. It is **excluded from the pipeline** — not in the root workspaces, skipped by packing and consumer-tsconfig generation. It stays kebab-cased per the Angular Style Guide and is recoverable history, not an active surface.

Versioning & dependency policy

- Pins follow the **stable line** per major (React 19.2.x, `@openfin/core` 43.101.x) — not latest-patch drift.
- Framework libraries are **peer dependencies**: the consuming app owns React, AG Grid, OpenFin and Tailwind versions.
- Lockfiles are **not committed** — environments behind different registries regenerate their own; reproducibility rests on the version pins.