

Package Reference

Package Reference · docs/latest · generated 2026-08-15

The platform ships **seven packages**, one per architecture bucket. Every package is an ordinary npm package — external consumers install them under their real names with no aliases and no build glue.

PACKAGE	BUCKET PATH	ROLE
@wellsfargo-starui/types	packages/types	foundation contracts
@wellsfargo-starui/design-system	packages/design-system	tokens, themes, icons
@wellsfargo-starui/core	packages/core	vanilla-TS runtime
@wellsfargo-starui/data	packages/data	SharedWorker data services
@wellsfargo-starui/openfin	packages/openfin	OpenFin workspace shell
@wellsfargo-starui/react	packages/react-core	React primitives + SDK
@wellsfargo-starui/grid	packages/react-grid	MarketsGrid product surface

Layering and allowed imports are covered in [Architecture](#) →.

@wellsfargo-starui/types

Foundation types — host-port identity/theme/surface contracts and the shared data-provider/config contracts. Depends on nothing.

SUBPATH	CONTENTS
.	host-port contracts (re-exports the shared set)
./shared	shared framework types — the single source of truth
./shared/configuration	configuration shapes
./shared/dataProvider	data-provider contracts
./shared/fieldSelector	field-selector contracts

@wellsfargo-starui/design-system

The design system: primitives, semantic tokens, themes, framework adapters and framework-agnostic SVG icons. Every visual property in the platform resolves through its `--bn-*` / `--fi-*` CSS variables; themes switch by flipping `data-theme="dark" | "light"` on `<html>`.

SUBPATH	CONTENTS
<code>.</code>	JS token access + theme helpers (root barrel)
<code>./apply-theme</code>	<code>applyTheme</code> / <code>getTheme</code> — THE theme writer, dependency-light for plain- <code>tsc</code> consumers
<code>./css</code> , <code>./styles.css</code> , <code>./reset.css</code>	built theme CSS (<code>./styles.css</code> is the one-import stylesheet for external apps; <code>./reset.css</code> is opt-in preflight)
<code>./tokens</code> , <code>./tokens/primitives</code> , <code>./tokens/semantic</code> , <code>./tokens/components</code> , <code>./tokens/controls</code>	token tree, by tier
<code>./tailwind</code>	Tailwind preset wired to the tokens
<code>./adapters/ag-grid</code>	AG Grid theme adapter (<code>staruiGridTheme</code> , mode-switched by <code>data-ag-theme-mode</code>)
<code>./cell-renderers</code> , <code>./cell-renderers-registry</code>	token-driven cell renderers
<code>./icons</code> , <code>./icons/react</code> , <code>./icons/all-icons</code> , <code>./icons/svg/*</code>	icon set (curated Lucide re-exports + <code>DynamicIcon</code> + raw SVG)

Peers: `react` (icon adapter), `tailwindcss`, `ag-grid-community`.

@wellsfargo-starui/core

Framework-agnostic core runtime: the vanilla-TS grid engine (GridPlatform, modules, expression engine, profiles) and host ports with a browser adapter and a Dexie (IndexedDB) config store.

SUBPATH	CONTENTS
<code>.</code>	grid engine + shared runtime (curated barrel — every export has an external consumer)
<code>./host</code>	host port contracts (<code>RuntimePort</code> , <code>toolSurfaces</code>)
<code>./host/browser</code>	browser host adapter (<code>BrowserRuntime</code>)
<code>./host/config</code>	Dexie-backed config store (<code>ConfigManager</code> , seed/deploy export)

Deps: `@wellsfargo-starui/design-system`, `@wellsfargo-starui/types`, `dexie`, `ssf`, `zustand`.

Peer: `ag-grid-community`.

@wellsfargo-starui/data

SharedWorker-backed data services: one upstream STOMP connection fanned out to every grid in every window, with snapshot + thin-delta frames. See [Architecture § data services](#) →.

SUBPATH	CONTENTS
.	data-services API
./runtime	runtime shared pieces (hub client, providers, AppData mirror)
./runtime/client	per-window client
./ssrm-engine	transport-agnostic SSRM query/aggregation engine (see SSRM Engine →)
./assets/data-services-worker.mjs	prebuilt worker bundle (build-generated)

Deps: `@stomp/stompjs`.

@wellsfargo-starui/openfin

The OpenFin workspace shell — dock, notifications, child tool windows, config import/export — plus the contained OpenFin seams every other package uses. **The only package allowed to import `@openfin/core`.**

SUBPATH	CONTENTS
.	workspace shell (<code>initWorkspace</code> + its callable pieces, registry config)
./host	the OpenFin seams: <code>isOpenFin</code> , IAB/interop/identity helpers, <code>OpenFinRuntime</code> (RuntimePort), <code>openOpenFinPopout</code>
./config	side-effect-free config entry (safe in a plain browser; ConfigManager wiring, IAB topics, action ids)
./dock-editor	dock layout editor helpers
./test-bridge	e2e test bridge (IAB channel, dev-only)

Peers: `@openfin/core`, `@openfin/workspace`, `@openfin/workspace-platform`.

@wellsfargo-starui/react

The React layer: shadcn/Radix UI primitives, workspace setup, and the React data bindings (including `createStarui`, the one-call bootstrap).

SUBPATH	CONTENTS
.	UI primitives (Button, Dialog, Select, ...)
./chart	chart components (Recharts-based)
./tailwind-config	app-side Tailwind wiring
./workspace-setup	workspace bootstrap for React apps
./data/runtime	React bindings for the data services — <code>createStarui</code> , <code>StaruiIdentityProvider</code> , <code>useAppData</code> , provider hooks

Peers: `react`, `react-dom`, `tailwindcss`, `@tanstack/react-query`.

@wellsfargo-starui/grid

The product surface: **StarGrid** (the one consumer-facing grid) over **MarketsGrid** (the internal opinionated, profile-persistent AG Grid host), the grid customizer, the config browser, and the provider editor.

SUBPATH	CONTENTS
.	<code>MarketsGrid</code> , toolbars, storage helpers, <code>ensureAgGridModules</code> , types
./customizer	curated customizer surface (14 names; <code>ExpressionEditor</code> , state types)
./styles.css	grid chrome CSS
./config-browser	configuration browser panel
./widgets	<code>StarGrid</code> + container widgets
./widgets/ssrm-markets-grid-container	SSRM container
./widgets/provider-editor	data-provider editor
./widgets/hosted	hosted-integration hooks (<code>useHostedStarui</code> , workspace-save flush, grid linking)

Peers: `react`, `react-dom`, `ag-grid-community`, `ag-grid-enterprise`, `ag-grid-react`, `@tanstack/react-query`.

Versioning & dependency policy

- Pins follow the **stable line** per major (React 19.2.x, `@openfin/core` 43.101.x) — not latest-patch drift.

- Framework libraries are **peer dependencies**: the consuming app owns React, AG Grid, OpenFin and Tailwind versions.
- Lockfiles are **not committed** — environments behind different registries regenerate their own; reproducibility rests on the version pins.