

# Five Architectural Rules

The dependencies you have to internalise. Full package list — see Figure 1.

① runtime-port is the seam

runtime-port (interface)  
↑ implements ↑ implements  
runtime-browser runtime-openfin

Every host wrapper / app shell / hosted-view hook  
talks to the interface — never to fin.\* directly.

② @openfin/core is firewalled

Only runtime-openfin and openfin-platform  
may import @openfin/core.

Every other package that needs OpenFin lifecycle  
goes through the RuntimePort interface.  
(Rationale: keep the platform browser-runnable.)

③ core is vanilla TS

@starui/core never imports a framework adapter.

grid-react → core (React side)  
widgets-angular → core (Angular side)

Both consume the same GridPlatform / ProfileManager  
/ ExpressionEngine. No React in core.

④ providers wrap services

config-service-react —  
config-service-angular —|— wrap —→ config-service  
data-services-react —|  
data-services-angular —|

Hosts get framework-shaped API; services stay vanilla.

⑤ apps consume packages — never the reverse

apps/demo-react · apps/demo-angular · apps/demo-configservice-react  
apps/markets-ui-react-reference · apps/demo-apps/basic-starui-app · apps/stomp-view-server

No package may import from apps/. Apps are the leaves of the dependency tree.  
When in doubt about where new code belongs, ask: "is this a leaf, or is it reusable?"