

Order No (v4)	883.DS.17		
PL order No.			first version:28-11-2017, 15:28 this version:29-11-2017, 11:55
Client	STOCK		
Delivery address to client	TOCCO		
VIN	ZB3M300010Y066813		
Production slot (week)	6th week		
Units	1		
Brand	Viberti		
Category	NS3K/KB/KO M2-IT (107mm neck)		
Typ	NS3KBM3-IT		

axle producer	SAF Disc	accessory, other, 1	none
Calliper	Knorr	accessory 3	ADR:extinguisher; extinguisher toolbox on landing leg (W983059); ADR plate; grounding strap (m07050305); assembly wedges on mail beam (2x W100067) because of extinguisher box
options	Knorr callipers, for paletbox 32 long, Curtainsider with dropsides	Break pad wear sensors	Knorr break pad wear sensors K025586 (Knorr sensors+WABCO wire 449 816 030 0)
upper structure type	Curtainsider with dropsides	rear buffer	roll stop- W184261
hinges for dropsides	YES	mudguards	full mudguards with rainflaps only on rear axle (W973391)
pocket for hestall pillars	YES	ferry rings	YES
long palletbox	YES	lashing rings for fixing goods inside semi.	YES
pockets for 80x80 pillars	none	1st axle lifted (steering from the cabin)	YES
KTL	YES	Lights	Aspock Europoint III (with bulbs)
Nominal5 wheel	1150	tire from Poland	YES
(real 5 wheel)	1145	rims from Poland	YES
wheel size	385/65/R22,5	Electric socket	2x 7pin + 1x 15 pin
wheels*	6x BRIDGESTONE R168, 6x steel rims	Frame	KTL + 7021- gray
steering axle	NO YES	Rear bumper profile, light fixing profile	Standard RAL 9003
axle type	BI9-22S01 IU30/2505 33 2040-1300 (Integral, Knorr brake callipers/zaciski hamulcowe)	Wheel hub	Original
Chassis PDM drawing	P211-K030400	Side protection color	Standard (aluminum)
QAD NR	K234237	Front pillar	Standard RAL9006
dropside	K031360- H800-L3185-bolted with eyelets fixed to 2nd plank from bottom	Rear pillar	Standard RAL9006
front wall	Aluminium front wall	Front wall color	Standard RAL9006
upper structure	M3 (aluminium rear pillars and doors, all elements from PL)	Rear door	Original
roof type	lift to load	Hestall	Original
double plywood on front wall	NO	tarpaulin No.	none
internal heights	2700	tarpaulin color	default
upper structure planks	3 rows of alu planks 100mm	tarpaulin with graphic	NO
planks holder	none	back doors with graphic	NO
landing legs/shaft length/foot/position/ground dis.	L500S750/1450/S/up/215	information about standard configuration	brake system is Wabco, steel air tanks (120 litre total, 2x K034285)
accessory, boxes and wheel holders, 1	toolbox Jbz700 (W191948)		
accessory, boxes and wheel holders, 2	wheel basket (W015165 for ET-120 or W185514 for ET-0)		
Non standard description	M3 Wielton's upperstructure but Viberti brand: front wall aluminum , rear portal aluminum completely assembled in Wieluń, after disassembled and delivered to Tocco without central pump- pumps in side pillars		

#### For logistics/Indeksy magazynowe

axle type	BI9-22S01 IU30/2505 33 2040-1300 (Integral, Knorr brake callipers/zaciski hamulcowe)	M010100010112, 2x M010100010113
roof type	lift to load	oil pump with tubes and fitting kit for chassis only M09090103_01, M09090104